

BOB-060 â€” Degenerate-input crash guards for public-tracker plugins

Revision: 1 **Last modified:** 2026-06-09T00:00:00Z **Type:** Bug **Severity:** Low **Status:** Fixed **Mandate:** Â§11.4.43 TDD (REDâ†’GREEN), Â§11.4.115 RED-on-broken-artifact, Â§11.4.118 discovery-pressure, Â§11.4.135 permanent regression guard, Â§11.4.83 QA transcript.

Four public-tracker plugins raised **unhandled exceptions** on degenerate / empty / malformed upstream responses. Each was reproduced (RED) on the pre-fix code, fixed with a minimal guard mirroring sibling-plugin patterns, and re-verified (GREEN). All inputs that did *not* crash were added as passing regression guards rather than fabricated as fixes (anti-bluff Â§11.4.6). One gap (piratebay) was found by a Â§11.4.118 discovery audit, not by the original report.

tokyotoshokan â€” `re.search(None)` **TypeError** on `retrieve_url` â†’ `None`

Root cause: `search()` / `handle_more_pages()` call `re.search(data)` on the `retrieve_url` result; a network/SSL failure yielding `None` raised `TypeError: expected string or bytes-like object` before the `if not match` guard ran. Fix: `if not data: early-return/break` before the regex.

RED â†’ `TypeError: expected string or bytes-like object` (plugins/tokyoto
GREENâ†’ 4 passed in 0.06s

Files: `plugins/tokyotoshokan.py`, `tests/unit/test_plugin_tokyotoshokan_guards.py` (new).

kickass â€” `None.startswith` **AttributeError** in `download_torrent`

Root cause: `download_torrent(url)` called `url.startswith("magnet:")` before any guard; `download_torrent(None)` raised `AttributeError: 'NoneType' object has no attribute 'startswith'`. Fix: falsy/non-str guard emitting the qBittorrent fallback `<url> <engine_url>` shape. (A separate while `True` pagination/loop concern was honestly noted as out-of-scope.)

RED â†’ `AttributeError: 'NoneType' object has no attribute 'startswith'`
GREENâ†’ 21 passed in 0.40s

Files: `plugins/kickass.py`, `tests/unit/test_plugin_kickass_guards.py` (+8 tests).

yts â€” `AttributeError` on non-dict / null-data JSON

Root cause: `j.get("data", {}).get("movie_count")` assumed `j` was a dict and data non-null; non-dict array, bare null, `{"data": null}`, and error-shaped JSON raised

AttributeError: 'list'/'NoneType' object has no attribute 'get'.
Fix: validate j is a dict, coerce data to {} when not a dict. Positive control proves well-formed responses still yield rows.

RED 4 failed (AttributeError, plugins/yts.py:41)
GREEN 9 passed in 0.24s (incl. positive control)

Files: plugins/yts.py, tests/unit/test_plugin_yts_guards.py (new).

TypeError: string indices must be integers on {"data": null}

Found by the 11.4.118 discovery audit (docs/research/bob015_plugin_degenerate_input_audit/REPORT.md). Root cause: json.loads('{"data": null}') dict {"data": None} (len 1, so the empty check never fires); for result in response_json: iterates dict keys and result["info_hash"] indexes a str with a str. Fix: mirror anilibra if not isinstance(response_json, list): return before the len-check, plus a per-element if not isinstance(result, dict): continue. Positive control proves well-formed arrays still yield rows.

RED 3 failed (TypeError: string indices must be integers, plugins/pir
GREEN 7 passed in 0.18s (incl. positive control)

Files: plugins/piratebay.py, tests/unit/
test_plugin_piratebay_guards.py (new).

Consolidated regression-guard run (11.4.132 risk-ordered, 11.4.135)

```
.venv/bin/python -m pytest \
  tests/unit/test_plugin_tokyotoshokan_guards.py \
  tests/unit/test_plugin_kickass_guards.py \
  tests/unit/test_plugin_yts_guards.py \
  tests/unit/test_plugin_piratebay_guards.py \
  tests/unit/test_plugin_crash_guards.py \
  tests/unit/test_plugin_parser_guards.py -q --import-mode=importlib
4 55 passed in 0.91s
```

These guard tests are the permanent regression suite for this defect class (11.4.135): each RED_MODE-equivalent reproduced the crash on the pre-fix code and now asserts its absence.