

A “ Backend Contract (Extension “ Boba)

Revision: 1 **Last modified:** 2026-06-10T00:00:00Z **Authority:** Real source code (cited file:line). The browser-extension research docs (Dim01/Dim09) are NOT authoritative and were both partly wrong “ see “Conflict resolution“ below.

Verdict on the conflicting research claims (11.4.123 “ evidence only)

Claim	Source	Verdict	Evidence
Port 8080, JWT auth, /api/v1/torrents	Dim09	FALSE “ no such port, no JWT, no /torrents route anywhere	No 8080 in docker-compose.yml; no JWT/bearer-app-auth in routes.py/ __init__.py/auth.py; the only “torrents“ path is qBittorrent’s own /api/v2/torrents/add called server-side (routes.py:819)
Ports 7186/7187/7189 + /api/v1/search download magnet	Dim01	CORRECT	docker-compose.yml port env; routes.py route decorators; __init__.py:250 prefix

Dim01 is the accurate one. Dim09 should be discarded.

Live probe (Task 5)

Services were **DOWN** at probe time (2026-06-10):

```
$ curl -s -m4 http://localhost:7187/health “ (no response, connection
$ curl -s -m4 http://localhost:7187/openapi.json “ (no response)
$ curl -s -m4 -o/dev/null -w '%{http_code}' http://localhost:7186/ “ 000
$ curl -s -m4 -o/dev/null -w '%{http_code}' http://localhost:7189/ “ 000
```

Services not running “ endpoints derived from source (source is authoritative).

Port map (Task 4 “ from docker-compose.yml)

Port	Service	container	docker-compose evidence	Extension uses?
7185	qBittorrent WebUI (container-internal)	qbittorrent	:9 WEBUI_PORT=7185; health :25	No “ answers 401 without proxy
7186	Download proxy “ qBittorrent WebUI (reverse proxy, injects auth)	qbittorrent-proxy	:121 PROXY_PORT=7186; health :158 curls :7186/	Optional (raw WebUI mirror)
7187	Merge Search Service (FastAPI default, or Go/Gin)	qbittorrent-proxy / qbittorrent-proxy-go	:122/:67 MERGE_SERVICE_PORT=7187; health :104/:158	YES “ primary
7188	webui-bridge (host process / Go binary)	host / webui-bridge	:70 BRIDGE_PORT=7188	No (private-tracker download helper)
7189	boba-jackett (Go) “ Jackett creds/ overrides/ autoconfig	boba-jackett	:179 PORT=7189; health :195 /healthz	No (admin UI backend)
9117	Jackett indexer	jackett	:48 health :9117/health	No

Both the Python download-proxy container AND the Go qbittorrent-proxy-go container bind 7186 (proxy) + 7187 (merge) “ they are mutually exclusive (Go is opt-in via --profile go). main.py:88-95 runs the original proxy (7186) and FastAPI merge service (7187) as **two threads in one container**.

Direct-qBittorrent vs Boba routing (Task 3 “ the key answer)

The extension talks to Boba“™s merge service on 7187, NOT to qBittorrent directly.

- Boba“™s POST /api/v1/download is the actual add-torrent path. Server-side it logs into qBittorrent ({qbit_url}/api/v2/auth/login, routes.py:778-789) using **admin/admin** (_get_qbit_username/_password, routes.py:707-718, default QBITTORRENT_URL=http://localhost:7185), then POSTs to qBittorrent“™s /api/v2/torrents/add (routes.py:819 for tracker-fetched .torrent, routes.py:847 for plain URLs/magnets via data={"urls": url}).

- So qBittorrent auth (admin/admin) is **handled by Boba on the server side** – the extension never sends qBittorrent credentials and never calls 7185//api/v2.
- Port **7186** is a separate raw reverse-proxy of the qBittorrent WebUI (the `download_proxy.run_server()` thread, `main.py:36-38`). The extension does NOT need it for adding torrents; it exists for humans/tools wanting the WebUI.

What /api/v1/download actually accepts

Body model `DownloadRequest` (`routes.py:170-172`):

```
{ "result_id": "<string>", "download_urls": ["<url-or-magnet>", ...] }
```

`result_id` is **just a label** (used for the `download_id/event` payload, NOT a DB lookup) – there is **no requirement that the URLs came from a prior search**. The handler iterates `download_urls[:5]` (`routes.py:791`) and for each: - **Private-tracker page URL** (`rutracker/kinozal/nmclub/iptorrents` host, `TRACKER_DOMAINS` `routes.py:721-731`) – fetches the real .torrent with auth cookies via `orch.fetch_torrent(...)`, uploads as a file (`routes.py:806-844`). - **Anything else** – including an arbitrary magnet: link or a direct .torrent URL – forwarded straight to qBittorrent as `data={"urls": url}` (`routes.py:846-861`).

=> **An ad-hoc magnet IS accepted** by `POST /api/v1/download` with `{"result_id":"anything","download_urls":["magnet:?xt=..."]}`. No search needed.

❖ **Go-profile gap:** the `GoDownloadHandler` (`internal/api/download.go:17-39`) is a **STUB** – it echoes `{"status":"added"}` for every URL **without ever contacting qBittorrent**. If the deployment runs `--profile go`, downloads silently no-op. The extension's real backend **MUST** be the **Python** merge service. (Flag this to the team; treat Go download path as not-implemented.)

Definitive endpoint enumeration (Task 1 – Python FastAPI, the source of truth)

Base: `http://<host>:7187`. Routers mounted in `__init__.py`: `api_router @ /api/v1(:250)`, `auth_router @ /api/v1(:252)`, `hooks_router @ /api/v1/hooks(:251)`, `scheduler_router @ /api/v1/schedules(:253)`. **No app-level auth / JWT on any route**. CORS allowlist defaults to `localhost:4200 + localhost:7187` (`__init__.py:101-131`); extensions send `Origin: chrome-extension://` – so the team must add that origin to `ALLOWED_ORIGINS` (see Gaps).

Method	Full path	Request	Response (key fields)
GET	/health	–	{status:"health"}
GET	/api/v1/config	–	{qbittorrent_proxy},qbittorrent
GET	/api/v1/stats	–	{active_searches}
GET	/api/v1/bridge/health	–	{healthy,status}

Method	Full path	Request	Response (key fields)
POST	/api/v1/search	SearchRequest (query,category,limit,sort_by,sort_order,â€¦)	SearchResponse (returns immediately)
POST	/api/v1/search/sync	SearchRequest	SearchResponse
GET	/api/v1/search/stream/{search_id}	?token= or Authorization: Bearer (only if SSE_REQUIRE_TOKEN)	SSE event: them
GET	/api/v1/search/{search_id}	â€”	SearchResponse
POST	/api/v1/search/{search_id}/abort	â€”	{search_id,sta
GET	/api/v1/downloads/active	â€”	{downloads:[{n (queries qBittorrent)
POST	/api/v1/download	DownloadRequest {result_id,download_urls[]}	{download_id,s
POST	/api/v1/download/file	DownloadRequest	streams .torrent
POST	/api/v1/magnet	{result_id,download_urls[]}	{magnet:"magne from btih)
POST	/api/v1/auth/qbittorrent	{username,password,save} (defaults admin/admin)	{status:"authe
GET	/api/v1/auth/status	â€”	{trackers:{rut
GET	/api/v1/auth/rutracker/status	â€”	{authenticated
GET	/api/v1/auth/rutracker/captcha	â€”	{captcha_requi
POST	/api/v1/auth/rutracker/login	CaptchaLoginRequest	{authenticated
POST	/api/v1/auth/rutracker/cookie-login	{cookie_string}	{authenticated
GET	/api/v1/auth/	â€”	{authenticated

Method	Full path	Request	Response (key fields)
POST	nmclub/ status /api/v1/ auth/ nmclub/ login	â€” (env creds)	{authenticated
POST	/api/v1/ auth/ qbittorrent/ logout	â€”	{status:"logge
GET	/api/v1/ theme, PUT / api/v1/ theme, GET / api/v1/ theme/stream	theme dashboard state	â€”
GET/ POST/ DELETE	/api/v1/ hooks, /api/ v1/hooks/ {id}	webhook CRUD	â€”
GET/ POST/ DELETE	/api/v1/ schedules, / api/v1/ schedules/ {id}	scheduled-search CRUD	â€”
GET	/, / dashboard, / {path}	Angular SPA	index.html

SearchRequest fields (routes.py:110-117)

query (req, min 1), category (def "all"), limit (1â€”100, def 50), enable_metadata (def true), validate_trackers (def true), sort_by (def "seeds"), sort_order (def "desc").

Go equivalent (Task 2 â€” qBitTorrent-go/, opt-in -- profile go)

Same ports (7186 proxy / 7187 merge / 7188 bridge), routes registered in cmd/qbittorrent-proxy/main.go:48-94. Endpoint set â€” Python (search, search/sync, search/stream/:id, search/:id, search/:id/abort, download, download/file, magnet, downloads/active, auth/qbittorrent, theme, hooks, schedules, config, stats, bridge/health, health). **Differences vs Python (material):** - DownloadHandler is a **no-op stub** (internal/api/download.go:17-39) â€” does NOT add to qBittorrent. **Do not rely on the Go backend for downloads.** - ActiveDownloadsHandler returns empty {downloads:[], count:0} stub (download.go:138). - No /api/v1/auth/rutracker/, /nmclub/, /auth/status routes (the Go proxy lacks the tracker-auth/CAPTCHA surface). - Go also has **no JWT / no 8080** â€” confirms Dim09 wrong on both backends.

DEFINITIVE extension â†’ Boba integration contract (Task 6)

Base URL: `http://<host>:7187` (the merge service). Use the **Python** backend. No auth header required by Boba itself (no JWT).

Extension capability	Call	Body / params	Notes
(a) Add an ad-hoc magnet	POST <code>http://<host>:7187/api/v1/download</code>	<code>{"result_id":"ext-<id>","download_urls":["magnet:?xt=urn:btih:..."]}</code>	<code>result_id</code> is a free label; magnet forwarded to qBittorrent <code>urls=(routes.py:84)</code> . Success = <code>added_count>0 / status:"initiated"</code> .
(b) Add a .torrent file	POST <code>http://<host>:7187/api/v1/download</code>	<code>{"result_id":"ext-<id>","download_urls":["https://â€¦/x.torrent"]}</code>	Direct .torrent URL forwarded as URL too. GAP: no multipart raw-file-bytes upload endpoint â€” see Gaps.
(c) Health / auth check	GET <code>http://<host>:7187/health</code> (liveness) + GET <code>/api/v1/auth/status</code> (qBittorrent + tracker session state)	â€”	<code>/health</code> proves merge service up; <code>/api/v1/auth/status</code> â†’ <code>trackers.qbittorrent.has_session</code>
(d) Search (optional)	POST <code>/api/v1/search/sync</code> (blocking, simplest) OR GET <code>/api/v1/search/stream/{search_id}</code> (live SSE)	<code>{"query":"...", "limit":50}</code>	<code>sync</code> returns <code>full_results[]</code> with <code>download_urls[]</code> to feed into (a)/(b)
Active downloads (status panel)	GET <code>/api/v1/downloads/active</code>	â€”	live qBittorrent torrent list.

Backend gaps the extension needs filled (Task 6 flag)

- CORS for the extension origin.** `ALLOWED_ORIGINS` default (`__init__.py:101-106`, `docker-compose:85/:137`) lists only `localhost:4200` + `localhost:7187`. A browser extension sends `Origin: chrome-extension://<id>` (or `moz-extension://â€¦`). Either the extension must call `via background fetch` exempt from CORS (MV3 with host permissions can), OR the team adds the extension origin to `ALLOWED_ORIGINS`.

`allow_credentials=False` is fine (no cookies needed). **Action: confirm the extension uses host-permission background fetch, else add the origin.**

2. **Raw .torrent file-bytes upload.** `/api/v1/download` only accepts URLs (`download_urls[]`). There is **no endpoint to POST raw .torrent file bytes** (multipart). `/api/v1/download/file` returns a torrent, it doesn't accept one. If the extension must add a user-picked local .torrent file (bytes, not a URL), Boba needs a new `POST /api/v1/download/upload` (multipart) qBittorrent `/api/v2/torrents/add` with a `torrents` form field, mirroring the server-side code already at `routes.py:811-822`. **Backend addition required.**
3. **Go-profile download is a stub.** If any deployment runs `--profile go`, `/api/v1/download` no-ops (`download.go:17-39`). Either implement the Go handler to mirror Python, or document that the extension requires the Python backend. **Backend addition required if Go is to be supported.**
4. **No JWT/token on Boba endpoints** – the extension does NOT need to obtain or send a bearer token to Boba (only the SSE stream has an optional per-search `stream_token`, off by default). Dim's JWT requirement is fictional.