

BOB-141 â€” CLAUDE.md vs the Go Dockerfile: doc corrected, provisioning question OPEN

Revision: 1 Last modified: 2026-08-20T17:05:00Z

What was wrong

CLAUDE.md stated the Go profile â€œreplaces the Python proxy on **7186**, **7187**, **7188**â€. The container cannot deliver that. Read from source, not prose:

qBittorrent-go/Dockerfile:16	CMD ["/app/qbittorrent-proxy"]	(ONE
qBittorrent-go/Dockerfile:15	EXPOSE 7187 7188	(dec
cmd/qbittorrent-proxy/main.go	r.Run(fmt.Sprintf(":%d", cfg.ServerPort))	
internal/config/config.go:58	ServerPort = MERGE_SERVICE_PORT (default 7	

webui-bridge is a separate binary (cmd/webui-bridge, /bridge/health, cfg.BridgePort) that this container never starts. Nothing in it binds 7186 either, though the compose service sets PROXY_PORT=7186 and BRIDGE_PORT=7188 in its environment, which reinforces the wrong impression.

Why it mattered

This prose was used as the source of truth when authoring config/served_ports.yaml, producing serves: [7186, 7187, 7188] for that service. The healthcheck gate built on it then FAILED a service whose healthcheck was already correct â€” a Â§11.4.201(1) false-positive refusal caused directly by trusting the doc over the Dockerfile. The manifest was corrected against source at the time; the doc was not, and would have misled the next reader identically.

Done in this pass

- CLAUDE.md line 110 now states the container serves **7187 only**, with the source citations inline so the next reader can re-derive it rather than trust another sentence.
- The Port Map row for 7188 now says explicitly that the qbittorrent-proxy-go container does NOT start webui-bridge.

Verified by re-deriving from source after the edit (Dockerfile CMD, r.Run(addr), ServerPort resolution all re-read and quoted above).

STILL OPEN â€” an operator decision, deliberately not made here

Whether the doc was wrong, or the CONTAINER is under-provisioned relative to the original intent (it should also run webui-bridge and a 7186 listener), is not determinable from the code â€” both readings are consistent with what exists. The doc now describes REALITY, which is the safe reversible state (Â§11.4.101); if the intent was a three-port container, the fix is to provision it and re-widen the doc, not to leave a doc describing something that does not run.

Whichever way it resolves, these should agree with reality afterwards: - the compose serviceâ€™s PROXY_PORT / BRIDGE_PORT env vars, which no process in that container consumes; - the Dockerfileâ€™s EXPOSE 7187 7188, which declares a port nothing binds; - config/served_ports.yaml, which currently declares serves: [7187].

BOB-141 therefore stays OPEN.