

scripts/pre_build/ check_cm_killpg_pgid_guard.sh â€” CM-KILLPG-PGID-GUARD static pre-build gate

Revision: 2 **Last modified:** 2026-08-19T00:00:00Z **Status:** active **Item:** BOB-126 follow-up (Â§11.4.238 discovery-channel-escape closure â€” a new automated check for a defect class first found out-of-band)

Purpose

scripts/pre_build/check_cm_killpg_pgid_guard.sh statically detects calls that send a signal to a **negative pid** or an entire **process group** (Python `os.killpg(pgid, sig)`, `os.kill(-pid, sig)`; bash `killpg`, an explicit `kill -SIG` invocation) that are **not** preceded, within the 10 lines above the call, by a guard proving the target identifier is a real, positive process id:

```
isinstance(<ident>, int) and <ident> > 1
```

on the **same** identifier that reaches the dangerous call.

The defect class this closes (BOB-126)

`os.killpg(1, SIGKILL)` is, under glibc, **identical** to `kill(-1, SIGKILL)` â€” a broadcast kill of every process the callerâ€™s UID owns. A test double whose `.pid` attribute is an unconfigured mock object (`MagicMock.__int__` defaults to 1) silently reaches that call. This was the root cause traced across 7 forced logouts (BOB-116/120/123/124/125/126): a `pytest runâ€™s kill(os.getpgid(proc.pid), SIGKILL)` resolved `proc.pid` to a `MagicMock`, `os.getpgid()` (or the mock itself) yielded 1, and the kill call became a broadcast kill of the operatorâ€™s own session.

The fix landed as a guard requiring the id to be a real int greater than 1 immediately before the dangerous call (download-proxy/src/merge_service/search.py:1200-1240, two identical guards on `_pid` and `_pgid`). This gate makes that shape a **mechanically enforced invariant** instead of tribal knowledge living only in a comment â€” per Â§11.4.226 (evidence-class-at-closure), a source-only fix with no standing guard is exactly the class of closure that silently reopens the next time someone touches the cleanup path.

Usage

```
# Default scope: download-proxy/src/, plugins/, scripts/ (relative to the
# repo root this script resolves from its own location).
scripts/pre_build/check_cm_killpg_pgid_guard.sh

# Explicit-path mode " scan exactly the given file(s)/directory(ies)
# instead of the default scope (directories are still walked with the
# same excludes). Used by the meta-test to run against hermetic fixtures.
scripts/pre_build/check_cm_killpg_pgid_guard.sh /path/to/file.py
scripts/pre_build/check_cm_killpg_pgid_guard.sh /path/to/fixture/dir

# Verbose (prints every hit that WAS correctly guarded, not just findings)
scripts/pre_build/check_cm_killpg_pgid_guard.sh -v

scripts/pre_build/check_cm_killpg_pgid_guard.sh --help
```

Inputs

- **Positional arguments** (optional): zero or more file/directory paths.
 - Zero arguments " default scope: download-proxy/src/, plugins/, scripts/ under the repository root, walked recursively.
 - One or more arguments " scan exactly those paths instead (single files must end in .py or .sh to be considered; directories are walked with the same directory-name excludes as the default scope).
- **-v / --verbose**: also print each hit that passed the guard check.
- **-h / --help**: print the in-source documentation header and exit 0.
- No environment variables are read.

Outputs

- **stdout**: a run header (scope, window size, file count) and either PASS: CM-KILLPG-PGID-GUARD clean across N file(s) or (on -v) a guarded: <path>:<line> [identifier=...] line per correctly-guarded hit.
- **stderr** (only on failure): a === FINDINGS === block, one FAIL: <path>:<line>: unguarded <call kind> " <trimmed source> [identifier=<ident-or-none>] line per unguarded hit, followed by a FAIL: <N> unguarded killpg/kill-group hit(s) ... summary line.
- **Exit codes**:
 - 0 " zero unguarded hits (or, in explicit-path mode, zero matching files " an empty scope is not itself a finding).
 - 1 " one or more unguarded hits; see stderr for the per-hit report.
 - 2 " usage/environment error (unknown flag, or an explicit PATH argument that does not exist). Distinct from finding-level FAIL, per Â§11.4.201(4) "œconservative-safe default on an unresolvable signal"❖.

Detection patterns

Language Patterns

Python (*.py) os\killpg\(\ Â· os\kill\(\s*-

Bash (*.sh) killpg\s Â· kill\s+-[1-9][0-9]*\b

Two deliberate scoping decisions, both evidence-based (Â§11.4.6), not guesses:

1. **Comment-only lines are never hit candidates.** A line that is entirely a comment (starts with #, after optional leading whitespace) is skipped before pattern matching. `search.py` itself contains two comment lines that quote the dangerous call syntax while *documenting* the BOB-126 fix (`# \os.killpg(1, sig)` == `kill(-1, sig)` under glibc`)` “those are text, not code, and flagging them would be a false-positive refusal on the very comment explaining the fix (§11.4.201).
2. **The bash signal-kill pattern excludes signal 0** (requires [1-9] [0-9]*, not the brief™s literal \d). `kill -0 PID` delivers no signal at all (see `kill(2)`) “it is the standard POSIX liveness-probe idiom (“œis this process still alive?œ), used unguarded twice in this repo today (`scripts/system-slice-watchdog/user1000-watchdog.sh`, `scripts/tunnel-keepalive.sh`) and structurally incapable of ever becoming the BOB-126 broadcast-kill defect, since it never delivers a real signal regardless of what pid/pgid it targets. Including -0 would make the gate FAIL against the real tree on two known-safe call sites “itself a §11.4.201 FAIL-bluff (a false-positive refusal is exactly as forbidden as a false-negative pass).

Guard recognition

For each real (non-comment) hit, the target identifier is extracted from the call itself “ the first argument to `killpg()`, the name after the leading `-` in `kill(-`, or the token following `killpg /` the signal-kill call in `bash`. The identifier may be a **simple bare name** OR a **dotted-attribute chain** (e.g. `self._pgid`) “ both are captured in full and matched literally (any . inside the identifier is regex-escaped before use, so it never behaves as an “any character” wildcard). The 10 lines immediately preceding the hit are then checked for **both**, on the same identifier, anywhere in that window (same line or split across lines):

- `isinstance(<ident>, int)`
- `<ident> > 1` “the literal digit 1; `> 0`, `> 10`, `> 100` do **not** satisfy this (a pgid/pid of 1 is precisely the broadcast-kill value “the whole point of the guard is excluding it).

When no identifier can be extracted (literal/numeric targets)

The fallback path fires exactly when the call[™]s target does **not start with an identifier character** a **literal or numeric target**, which is

precisely the BOB-126 defect shape itself: `os.killpg(1, ...)` in Python, or `kill -9 -1` in bash. In that case no identifier can be extracted at all, and the hit is **ALWAYS treated as UNGUARDED** — there is **no** non-identifier-scoped fallback scan of the window.

An earlier revision of this gate fell back, in that identifier-less case, to a looser check: *any* `isinstance(..., int)` **and** *any* `> 1` **anywhere** in the 10-line window, for *any unrelated variable* (including inside a comment). That was a false-negative PASS-bluff (Â§11.4.201): a literal broadcast-kill target sitting near ANY unrelated int-bounds guard for a totally different variable — a common surrounding idiom (retry-count / timeout bounds checks) — was misreported as “œguarded.” Refusing to guess when no identifier can be isolated is the conservative-safe default (Â§11.4.101/Â§11.4.201); the paired meta-test™s golden-bad-3 fixture reproduces this exact scenario as a permanent regression guard.

Note that a **nested call expression**, e.g. `os.killpg(get_pgid(), sig)`, does **not** hit this identifier-less path: its target *does* start with an identifier character, so the function name `get_pgid` is captured and used (mis-scoped to that name, but non-empty) as the identifier — the identifier-scoped check above applies to it, not the always-unguarded fallback. Only a genuinely identifier-less (literal/numeric) target reaches the always-unguarded path.

Self-exclusion (anti-carrier guard)

This gate™s own source necessarily quotes the very patterns it detects (the pattern strings themselves, the report label text, the doc comments describing the bash `kill -SIG` idiom). Its own file is therefore **structurally excluded from its own scan** — resolved by absolute path, not by careful wording — closing the Â§11.4.196(D)/Â§12.12 —œinstrument matches its own carrier text — footgun class. Verified in-session: without the exclusion, the gate™s own comments trigger `killpg`s four times (the word “œkillpg” followed by a space occurs in prose describing the tool).

Side-effects

None. The gate is read-only: it never modifies any scanned file. It creates one `mktemp` findings file for its own run and removes it on exit via `trap ... EXIT`.

Dependencies

- bash (uses `[[ ]]`, `<<<` here-strings, process substitution).
- `grep -E`, `sed -E`, `find` — all standard on the project™s supported hosts; no GNU-specific extension is required beyond `\s/d`-style shorthand support in `grep -E` (present on both GNU `grep` and the `ugrep-as-grep` compatibility layer this host ships).
- No Python, no network access, no repository write access.

Cross-references

- **BOB-126** “ the forced-logout incident chain (BOB-116/120/123/124/125/126) this gate’s real-tree pattern was extracted from.
- **Â§11.4.238** “ QA-discovery-channel mandate: this gate is the “œnew or strengthened automated check” a coverage-escape audit requires for a defect first found out-of-band.
- **Â§11.4.226** “ evidence-class-at-closure: a standing guard, not merely a source-side comment, is what keeps a fix from silently reopening.
- **Â§11.4.115 / Â§11.4.135** “ RED-first meta-test discipline / permanent regression-guard suite: tests/pre_build/test_check_cm_killpg_pgid_guard.sh is this gate’s paired Â§1.1 mutation harness.
- **Â§11.4.196(D) / Â§12.12** “ the “œinstrument matches its own carrier text” footgun class this gate’s self-exclusion closes.
- **Â§11.4.201** “ every guard/gate asserts the real condition; a false-positive refusal is a FAIL-bluff exactly as forbidden as a false-negative pass (the rationale for excluding comment-only lines and the kill -0 liveness-probe idiom).
- download-proxy/src/merge_service/search.py:1200-1240 “ the real, currently-guarded call sites this gate verifies stay guarded.

Companion files

- scripts/pre_build/check_cm_killpg_pgid_guard.sh “ the gate itself.
- tests/pre_build/test_check_cm_killpg_pgid_guard.sh “ the Â§1.1 paired meta-test: five hermetic fixtures “ golden-good (properly guarded, bare identifier), golden-good-2 (properly guarded, dotted-attribute identifier self._pgid), golden-bad-1 (brief-literal os.killpg(1, SIGKILL), no guard at all), golden-bad-2 (guard present but checks > 0 instead of > 1), golden-bad-3 (literal, identifier-less target near an UNRELATED int-bounds guard for a different variable “ the Critical-1 false-negative regression case) “ plus a real-tree smoke run against the current checkout.

Last verified

2026-08-19 “ bash tests/pre_build/test_check_cm_killpg_pgid_guard.sh ran GREEN (6/6: golden-good rc=0, golden-good-2 rc=0, golden-bad-1 rc=1, golden-bad-2 rc=1, golden-bad-3 rc=1, real-tree default scope rc=0); shellcheck -x clean on both scripts with zero findings. Independently re-reproduced the reviewer’s two live false-negative repro cases (os.killpg(1, signal.SIGKILL) near an unrelated int guard; bash kill -9 -1 near a comment quoting isinstance(x, int) and x > 1) and confirmed both now correctly FAIL (rc=1) against the fixed gate.