

Fixed “ Closed Workable Items

Revision: 1 **Last modified:** 2026-06-06T12:20:00Z **Ticket prefix:** BOB (operator-mandated, 2026-06-06) **Scope:** Closed items only. Open items live in [Issues.md](#).

Closure statuses per Â§11.4.33: Bug “ Fixed, Feature “ Implemented, Task “ Completed. Each carries captured-evidence (anti-bluff Â§11.4).

Â§1. [BOB-001] start.sh BSD-sed incompatibility aborted the boot

Status: Fixed (“ Fixed.md) **Type:** Bug **Closed:** 2026-06-06 Â· **Commit:** c5cbd40

GNU sed -i SCRIPT calls (6 sites) aborted start.sh on macOS/BSD sed with “invalid command code”, before compose up “ the stack never started. Added a portable sed_inplace() (-i .bak then drop backup; works GNU+BSD) and converted all 6 sites (Â§11.4.67/Â§11.4.81). **Evidence:** tests/unit/test_sed_inplace_portable.sh “ 4 passed (RED before fix); boot #2 then progressed past the config step.

Â§2. [BOB-002] start.sh podman unshare incompatible with macOS remote podman

Status: Fixed (“ Fixed.md) **Type:** Bug **Closed:** 2026-06-06 Â· **Commit:** c5cbd40

podman unshare cp/chmod (rootless-Linux-only) aborted plugin install on the macOS remote podman client. Added _podman_unshare_works() self-detection; falls back to plain cp/chmod on macOS (Â§11.4.81). **Evidence:** boot #3 reached compose up and brought all 4 containers up.

Â§3. [BOB-003] macOS tunnel port detection broken (ports never forwarded)

Status: Fixed (“ Fixed.md) **Type:** Bug **Closed:** 2026-06-06 Â· **Commit:** c5cbd40

ensure-macos-tunnel.sh parsed the connection NAME, not the SSH port (“Bad port “podman-machine-default”), so container ports were never forwarded to macOS localhost. Now uses podman machine inspect {{.SSHConfig.Port}} with a URI-parse fallback. **Evidence:** tunnel established (port 51347); curl localhost 7186 “200, 7187 “200, 7189 “404, 9117 “301 after the fix.

Â§4. [BOB-004] Private-tracker credentials stored securely + verified working

Status: Completed (“ Fixed.md) **Type:** Task **Closed:** 2026-06-06

Stored RuTracker / IPTorrents / RuTor / NNMClub credentials in the gitignored .env (mode 0600). A pre-store leak audit ran clean (no value in tree or git history). Credentials never committed and never logged. **Evidence:** - Security suite: test_credential_scrubbing + test_credential_file_safety + test_jackett_autoconfig_secrets + test_log_filter 22 passed, 1 skip. - Wiring: orchestrator reports rutracker + iptorrents creds-available=True. - **End-to-end live proof:** POST /api/v1/search/sync query ubuntu IPTorrents status=success, results=49, auth=True with real result names (e.g. Ubuntu Linux Toolbox 1000+ Commands). RuTracker login attempted (auth=True, CAPTCHA-blocked tracked as BOB-008).

5. [BOB-013] torrentkitty _parse_size reported 0 for every KB/MB/GB/TB size

Status: Fixed (Fixed.md) **Type:** Bug **Closed:** 2026-06-06 **Commit:** 14bc5c4

"B" substring-matched inside KB/MB/GB/TB so all realistic sizes parsed to 0. Fixed to match on the suffix, longest unit first. **Evidence:** tests/unit/test_plugin_search_engines.py torrentkitty size tests assert correct byte values; 18 passed.

6. [BOB-014] Go generateID() collided under burst (UnixNano-only)

Status: Fixed (Fixed.md) **Type:** Bug **Closed:** 2026-06-06 **Commit:** d46ea57

time.Now().UnixNano() is not unique under rapid StartSearch calls dropped searches + broke MAX_CONCURRENT_SEARCHES. Fixed with an atomic counter. **Evidence:** TestGenerateID_UniqueUnderBurst (10k IDs unique) + queue-full test via real StartSearch; go test -race green, deterministic.