

closure_evidence_20260923

BOB-229 closure evidence — 2026-09-23

Discovery

The very first real-repo run of the new BOB-212 guard (scripts/pre_build/check_gitignore_swallow.sh, wired into scripts/pre_build_verification.sh as invariant 56 this session) immediately caught a live, real instance of exactly the defect class it was built to detect:

```
[56/56] CM-GITIGNORE-SWALLOW-GUARD: no first-party source file is
silently swallowed by .gitignore ($11.4.201(6), BOB-212)
FAIL [4]: CM-GITIGNORE-SWALLOW-GUARD: exit 1 – a first-party
source file is silently swallowed by .gitignore
BOB-212 swallow-guard: REFUSED – 2 first-party source file(s) are
silently swallowed by .gitignore.
SWALLOWED (first-party source, silently ignored): scripts/
pre_build/check_cm_qbittorrent_webui_credentials.sh
blocked by: .gitignore:31:*credentials* scripts/pre_build/
check_cm_qbittorrent_webui_credentials.sh
SWALLOWED (first-party source, silently ignored): tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh
blocked by: .gitignore:31:*credentials* tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh
```

Independently confirmed real, not a guard false-positive

```
$ ls -la scripts/pre_build/
check_cm_qbittorrent_webui_credentials.sh tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh
-rwxrwxr-x ... Sep  1 18:26 scripts/pre_build/
```

```

check_cm_qbittorrent_webui_credentials.sh
-rwxrwxr-x ... Sep  1 18:27 tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh

$ git ls-files scripts/pre_build/
check_cm_qbittorrent_webui_credentials.sh tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh
(empty – confirmed NOT tracked)

$ git status --short scripts/pre_build/
check_cm_qbittorrent_webui_credentials.sh tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh
(empty – the exact false-null: a file exists, is functional, and
produces zero signal)

$ git check-ignore -v scripts/pre_build/
check_cm_qbittorrent_webui_credentials.sh tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh
.gitignore:31:*credentials* scripts/pre_build/
check_cm_qbittorrent_webui_credentials.sh
.gitignore:31:*credentials* tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh

```

These two files have been in DAILY FUNCTIONAL USE by scripts/pre_build_verification.sh invariant 53 (CM-QBITTORRENT-WEBUI-CREDENTIALS, §11.4.239), which has passed cleanly every single run this whole session — the gate script runs perfectly fine FROM DISK regardless of git tracking state, so nothing in the ordinary development flow ever surfaced that these files had never actually landed in version control. A fresh clone, a different environment, or an accidental git clean would have silently lost an entire gate implementation plus its 8-case self-validated paired-mutation meta-test.

Fix

.gitignore: added two explicit ! negation lines for these exact paths, matching the codebase's existing hand-maintained per-file allowlist pattern (lines 34-50) that already carves out other legitimately credential-named source files (credentials.go, the frontend credentials-management UI, etc.).

Independently verified this session

```

$ git check-ignore -v scripts/pre_build/
check_cm_qbittorrent_webui_credentials.sh tests/pre_build/
test_check_cm_qbittorrent_webui_credentials.sh

```

```
.gitignore:47:!scripts/pre_build/  
check_cm_qbittorrent_webui_credentials.sh  scripts/pre_build/  
check_cm_qbittorrent_webui_credentials.sh  
.gitignore:48:!tests/pre_build/  
test_check_cm_qbittorrent_webui_credentials.sh  tests/pre_build/  
test_check_cm_qbittorrent_webui_credentials.sh  
(negation now wins – confirmed no longer ignored)
```

```
$ git status --short scripts/pre_build/  
check_cm_qbittorrent_webui_credentials.sh tests/pre_build/  
test_check_cm_qbittorrent_webui_credentials.sh  
?? scripts/pre_build/check_cm_qbittorrent_webui_credentials.sh  
?? tests/pre_build/test_check_cm_qbittorrent_webui_credentials.sh  
(now genuinely visible)
```

```
$ bash scripts/pre_build/check_gitignore_swallow.sh "$(pwd)"  
BOB-212 swallow-guard: OK – no first-party source files are  
silently swallowed by .gitignore.
```

```
$ bash -n scripts/pre_build/  
check_cm_qbittorrent_webui_credentials.sh && echo OK  
$ bash -n tests/pre_build/  
test_check_cm_qbittorrent_webui_credentials.sh && echo OK  
(both clean – the rescued files are syntactically intact)
```

```
$ timeout 60 bash tests/pre_build/  
test_check_cm_qbittorrent_webui_credentials.sh  
=== paired-mutation meta-test: CM-QBITTORRENT-WEBUI-CREDENTIALS  
===  
PASS: golden-good (rc=0 as expected)  
PASS: golden-bad-1 (rc=1 as expected)  
PASS: golden-bad-2 (rc=1 as expected)  
PASS: golden-bad-3 (rc=1 as expected)  
PASS: golden-bad-4 (rc=1 as expected)  
PASS: negative-control-quoted (rc=0 as expected)  
PASS: negative-control-carrier (rc=0 as expected)  
PASS: negative-control-fresh (rc=0 as expected)  
=== META-TEST PASS: gate fires on every broken arm and stays clean  
on every good arm ===
```

The rescued gate + its meta-test are both fully functional (8/8 self-check cases pass) — this is a genuine, working, no-longer-at-risk artifact.

Honest boundary

This item is filed and closed in the same session per this project's own §11.4.202 reporting-directive discipline (a discovered defect always lands as a tracked item, even when fixed immediately) — it is not a hypothetical or a design exercise, it is a real incident the new guard genuinely caught on its very first real-repo run.

git diff –stat

```
.gitignore | 7 +++++++  
1 file changed, 7 insertions(+)
```

Plus two previously-untracked files now staged for the first time:
scripts/pre_build/check_cm_qbittorrent_webui_credentials.sh, tests/
pre_build/test_check_cm_qbittorrent_webui_credentials.sh.