

Search / api-app / Provider Residuals Audit (2026-06-14)

Scope: residual, unverified, and OWED items around search, onboarding, the api-app, and providers AFTER the 5-layer search fix shipped (client 1.3.9-1066 + api-app 0.2.9-14). Read-only audit; evidence-cited per §11.4.6 (no guessing — claims are anchored to source or marked UNVERIFIED / OWED).

Headline (the question the master plan must answer): On-device search is PROVEN only for **Internet Archive** (archiveorg, AuthType=AuthNone). It is **NOT proven for RuTracker / YTS / Kinozal**. The 5-layer fix is provider-agnostic for the *transport + Lava-Auth key delivery*, but auth-required providers need a SECOND credential (the provider login session, delivered via the Auth-Token header) that the dynamic ApiBackedTrackerClient search path **does not attach today**. See Item 1 — it is the largest gap and a likely P0 for "search works for the providers the operator originally reported."

Residuals table

#	Item	Status	Sev	What's needed
1	Auth-provider search: Auth-Token provider credential not attached on dynamic /v1/ {provider}/search	OWED + UNVERIFIED on-device	P0	ApiBackedTrackerClient.withAuth() a Lava-Auth per-instance key (ApiBackedTrackerClient.kt:80–81); i Auth-Token provider-login header. Go parseCredentials(c) reads Auth-Token (handlers.go:118, multiprovider.go:9 provider the server gets Type:"none" (a rutracker/kinozal Search runs token-less returns login/empty. Need: (a) persist th session from the dynamic login flow, (b) Token: {provider}:cookie:... on the streamMultiSearch/ApiBackedTrackerC request, (c) wire AUTH_REQUIRED capabil login step for dynamic (RemoteTrackerD providers.

#	Item	Status	Sev	What's needed
2	YTS / curated-provider search on-device	UNVERIFIED	P1	YTS is a curated provider (no auth). Tra but it was never run on-device end-to-e archiveorg was. Confirm the dynamic c declares SEARCH, routes to /v1/yts/sear rows.
3	Existing-install key-restore: api-app uninstalled	OWED	P1	ApiClient.read() returns null when provider is absent (ApiClient.kt:65 endpoint → /v1 ops 401 until re-onboar start restore (21031f2a) heals a keyless only when the key is still readable; an u yields a silent keyless state with no user prompt.
4	Remote (non-local) LAN api-app: local ApiClient key is wrong for a remote endpoint	OWED + UNVERIFIED	P1	withLocalApiKeyIfMissing (Onboarding no covering tests per codegraph) reads device api-app key. For a remote/LAN a different device's api-app), the local key authenticate the remote endpoint → 40 + onboarding key-attach paths assume the co-installed local api-app.
5	READ_API_KEY permission name variant-suffix (L4)	OWED (MEDIUM / QA-fidelity)	P2	Per docs/issues/2026-06-14-readapik variant-analysis.md §2c: the permissi literal in both manifests (api-app/.../ AndroidManifest.xml:11-13,93; app/. AndroidManifest.xml:9) while every ot variant-suffixed. Mixed debug+release c INSTALL_FAILED_DUPLICATE_PERMISSION (test-VM artifact). Production matched d). Fix: make the name a \${apiKeyPermi placeholder + per-variant value + BuildC BOTH apps.
6	Dead /v1/search SSE — server-side aggregator	CLOSED (consumer removed) /	P2	The dead observeSseSearch → /v1/sear removed (addaacd0); no backend serves Go server DOES have a MultiSearchHan aggregator (search.go:114 GetMultiSe

#	Item	Status	Sev	What's needed
		OPTIONAL feature		client uses client-side streamMultiSearch is sufficient. A server-side aggregator is optimization, not a correctness gap.
7	Watchable issue-videos re-record (operator task #24)	OWED	P1	Prior 4 "success videos" FAILED HelixQA analyzer liveness (issue3=1 frame, issue3 frozen) — instrumentation recordings for issue3 (search) could NOT be recorded because broken; now search works, so a paced e2e walkthrough + the refreshed set are Downloads. Evidence: <code>.lava-ci-evidence-analysis/2026-06-14-issue-videos.m</code> Telemetry exists on the client <code>ApiKeyClient</code> (logcat-only <code>Log.w</code>, NOT <code>recordNonFatal</code> → not in Crashlytics — <code>ApiKeyClient.k</code> <code>api-app ApiKeyProvider.query()</code> empty <code>(ApiKeyProvider.kt:101-107)</code> records <code>N</code> serves an empty cursor (the exact L5 de Go multi-search per-provider error is no design (SSE is the surface). Gap: the client failures should route through <code>AnalyticsTracker.recordWarning</code> (not field recurrence of the keyless-endpoint Crashlytics; the <code>api-app</code> empty-cursor is non-fatal.
8	§6.AC telemetry coverage gap on the key/search error paths	OWED (PARTIAL)	P2	<code>addaacd0</code> dropped the ignored <code>apiKeyRe param</code> + the dead SSE path. <code>MainActivity.buildApiKeyReader</code> returns <code>client.read()?.key }</code> (no authority and lesson in the root-cause doc §8). Confirm call sites pass an authority that is silent that the <code>currentEndpointIsGoApi</code> removal branch.
9	apiKeyReader no-arg refactor ripple + currentEndpointIsGoApi removal	DONE (verify clean)	P2	The <code>withFakes</code> seam (<code>ApiKeyProvider.k</code> the real <code>onCreate</code>→holder lifecycle when (root-cause doc §8 + §6.J). A real-holder (<code>running_engine_exposes_real_key_v engine_not_running_exposes_empty_c appear in codegraph</code>) must drive the real ordering, no <code>withFakes</code>. Confirm it exists falsifiability-rehearsed (caching-version version PASSES).
10	L5 real-holder regression test (retire the withFakes bluff)	OWED	P1	

Evidence index

Claim	Cite
Client search attaches only Lava-Auth, not Auth-Token	core/tracker/client/.../ ApiBackedTrackerClient.kt:80-81,87-100,214-224
Go reads provider creds from Auth-Token header	lava-api-go/internal/handlers/v1/ handlers.go:118-124; lava-api-go/internal/ auth/multiprovider.go:35-93
Go search runs provider with parsed creds (anonymous if no Auth-Token)	lava-api-go/internal/handlers/v1/ search.go:32-75,192
rutracker provider is AuthCaptchaLogin	lava-api-go/internal/rutracker/provider.go:59
rutracker Kotlin search needs a token	core/tracker/rutracker/.../feature/ RuTrackerSearch.kt:31
On-device search verified only for Internet Archive	docs/CONTINUATION.md:14; .lava-ci-evidence/ search-verification/2026-06-14-fresh-onboard- search.md
L4 permission variant analysis	docs/issues/2026-06-14-readapikey-permission- variant-analysis.md
L5 root cause + withFakes bluff lesson	docs/issues/2026-06-14-search-multilayer- rootcause.md §6,§8; api-app/.../handoff/ ApiKeyProvider.kt:57-108
withLocalApiKeyIfMissing has no covering tests	codegraph blast-radius (OnboardingViewModel.kt:382, 1 caller, no tests)
Client key-read telemetry is logcat-only	app/.../handoff/ApiKeyClient.kt:48,63,69
Issue-videos liveness failure	.lava-ci-evidence/video-analysis/2026-06-14- issue-videos.md; docs/CONTINUATION.md:20
Dead /v1/search removed; server SSE aggregator exists	docs/issues/2026-06-14-search-multilayer- rootcause.md §2; lava-api-go/internal/handlers/ v1/search.go:114