

Defect B — api-app Crashlytics telemetry misattribution (findings)

Date: 2026-06-14 Scope: investigation + prepared remediation (no build change applied, no rebuild, no secret committed) Classification: project-specific (Lava api-app Firebase wiring)

Symptom

Crashlytics crashes and non-fatals originating from the standalone **api-app** (`digital.vasic.lava.api / .api.dev`) report under the **client** Firebase app in the Firebase console instead of the api-app's own Firebase app.

Root cause — CONFIRMED

`api-app/google-services.json` (tracked, on disk) maps the api-app package names to the **client app's** `mobilesdk_app_id` values. The `google-services` Gradle plugin selects the `client[]` entry by matching `package_name`, then bakes that entry's `mobilesdk_app_id` into the APK. Because the api-app's `package_name` entry carries the client app's app id, the api-app registers with Firebase as the client app, and all its Crashlytics/Analytics telemetry lands under the client app id. This is the misattribution.

Evidence (current on-disk file vs. Firebase authoritative truth)

api-app `applicationId` is confirmed in `api-app/build.gradle.kts`:
`digital.vasic.lava.api` (release), + `".dev"` suffix →
`digital.vasic.lava.api.dev` (debug).

Firebase project `lava-vasic-digital` registered Android apps (via Firebase MCP `firebase_list_apps / firebase_get_sdk_config`):

mobilesdk_app_id (suffix)	Firebase displayName	real package_name
...456475e2ef4039d8cfd20a	Lava Android	<code>digital.vasic.lava.client</code>
...54ca2ca31e6c4f42cfd20a		<code>digital.vasic.lava.client.dev</code>

mobilesdk_app_id (suffix)	Firebase displayName	real package_name
	Lava Android (Debug)	
...d57b960e955645f6cfd20a	Lava API (release)	digital.vasic.lava.api
...2932451e07ca80a7cfd20a	Lava API (debug)	digital.vasic.lava.api.dev

Current on-disk api-app/google-services.json contains:

package_name in file	mobilesdk_app_id in file	what that app id ACTUALLY is
digital.vasic.lava.api	...456475e2ef4039d8cfd20a	client release app (WRONG)
digital.vasic.lava.api.dev	...54ca2ca31e6c4f42cfd20a	client debug app (WRONG)

The correct app ids for the api-app are ...d57b960e955645f6cfd20a (release) and ...2932451e07ca80a7cfd20a (debug) — i.e. the "Lava API (release)" / "Lava API (debug)" Firebase apps. These match the app ids recorded in the session notes.

The two real api-app Firebase apps **exist** in the project (no firebase_create_app needed).

Remediation (prepared, not yet applied)

A corrected google-services.json has been generated to a non-committed staging path so it cannot be accidentally committed:

/tmp/api-app-google-services.corrected.json

It contains exactly two client[] entries:

- digital.vasic.lava.api →
1:815513478335:android:d57b960e955645f6cfd20a
- digital.vasic.lava.api.dev →
1:815513478335:android:2932451e07ca80a7cfd20a

(Same `project_info`, same shared Android API key already present in the tracked file — `apiKeyId 56cefd24-...`, shared across all four apps in this project; no new secret introduced.)

Steps to apply

1. Copy the staged file over the tracked one: `cp /tmp/api-app-google-services.corrected.json api-app/google-services.json` (NOTE: `api-app/google-services.json` is gitignored per §6.H — it is replaced on disk only, never committed.)
2. Rebuild the `api-app` (debug first per §6.AA): the `google-services` plugin will bake `...d57b960e955645f6cfd20a / ...2932451e07ca80a7cfd20a` into the APK.
3. Verify on device: trigger a non-fatal from the `api-app` and confirm it lands under "Lava API (release/debug)" in the Firebase console, not "Lava Android".

GO / NO-GO

GO. Both correct `api-app` Firebase apps already exist; the corrected config is staged at `/tmp/api-app-google-services.corrected.json` and is ready to drop in + rebuild. No operator Firebase action (no `firebase_create_app`) is required.