

# T7 Fast Storage — relocation map (operator-designated main fast storage)

**Operator directive (2026-05-31):** "Use for any storage-demanding work T7 drive and update paths references to it since this is our main fast storage."

T7 = Samsung T7 external SSD mounted at `/Volumes/T7` (1.8 TiB, ~1.2 TiB free). It is the project's designated **main fast storage** for all storage-demanding work (container image builds, emulator system-images/AVDs, build caches).

## Relocations in effect

| Concern                                     | Host path                                                   | Target on T7                         | Mechanism                       |
|---------------------------------------------|-------------------------------------------------------------|--------------------------------------|---------------------------------|
| Podman VM + image storage                   | <code>~/.local/share/containers</code>                      | <code>/Volumes/T7/containers</code>  | symlink                         |
| Gradle home                                 | <code>~/.gradle</code> (via <code>GRADLE_USER_HOME</code> ) | <code>/Volumes/T7/Gradle</code>      | env var ( <code>.zshrc</code> ) |
| XDG cache                                   | <code>~/.cache</code>                                       | <code>/Volumes/T7/cache</code>       | symlink                         |
| Android <code>.android</code> (AVDs, 24 GB) | <code>~/.android</code>                                     | <code>/Volumes/T7/dot-android</code> | symlink                         |

## Podman VM (the \$6.M Class-II disk-pressure fix, 2026-05-31)

The podman applehv machine stores its whole VM as one fixed-size `.raw` disk image under the graphroot. Originally 50 GB and living on the host data-volume (which had dropped to 16 GiB free / 97%); the lava-api-go OCI image build filled it and `build_and_release.sh` exited 125 "no space left on device" (incident `.lava-ci-evidence/sixth-law-incidents/2026-05-31-disk-pressure-podman-vm-image-build.json`).

Fix:

1. `podman machine stop`
2. `mv ~/.local/share/containers /Volumes/T7/containers`
3. `ln -s /Volumes/T7/containers ~/.local/share/containers`
4. `podman machine start`

**Verified result:** host data-volume freed ~50 GB (16 GiB → 66 GiB free). After the move + restart, the live VM reported `/dev/vda4 50G total / 41G free` (the move to a clean graphroot on T7 plus a `podman system prune` is what reclaimed the working room) — and `build_and_release.sh` then completed `EXIT 0` including the lava-api-go OCI image build that previously failed at `COPY . .`.

**UNCONFIRMED:** `podman machine set --disk-size 150` was issued and returned 0, but the running VM still reported a 50 GB root afterward — on `applehv` the disk-size change does not appear to apply to the already-provisioned `.raw` without a machine recreate. The 50 GB → 41 GB-free headroom on T7 was sufficient for this build; if a future build needs more, recreate the machine (`podman machine rm + podman machine init --disk-size N`) so the larger raw is provisioned fresh on T7.

## Caveat (§6.M)

These relocations make T7 a hard dependency for container + emulator work: if T7 is unmounted, `podman` + the AVD matrix break until it is remounted. This is the operator's deliberate choice (T7 is the designated main fast storage). The pre-push hook + `scripts/run-challenge-matrix.sh` continue to work host-side; only the container/emulator runtime needs T7 present.

Classification: project-specific (Lava's host storage layout).