

SP-3a Coverage Exemption Ledger

Per Constitutional clause 6.D (Behavioral Coverage Contract), every uncovered line in code authored under SP-3a is listed here with reason, reviewer, and date. Blanket waivers are forbidden.

See also: Seventh Law clause 5 (Recurring Bluff Hunt). Every entry in this ledger is eligible to be picked by the recurring 5-file random sample at phase wrap. An exemption that cannot survive the bluff hunt — i.e. the exempted code path is silently exercised by a test the hunt mutates — is a Seventh Law incident in waiting and **MUST** be audited rather than left as a paper-only exemption. The ledger is necessary, not sufficient: the recurring hunt is the live falsifiability check.

This file was seeded ahead of Task 0.7 by Task 0.2 (TestBookmarksRepository stub bluff) because that task needed an entry to land. Task 0.7 will append the Phase-0 summary section without re-creating the file.

Format

File	Lines	Reason	Reviewer	Date	PR
------	-------	--------	----------	------	----

Entries

File	Lines	Reason
core/testing/src/main/kotlin/lava/testing/repository/TestBookmarksRepository.kt	all (every method body is TODO("Not yet implemented"), except clear() which is a no-op)	Complete stub fake. Full behavioral implementation against BookmarkDao, @PrimaryKey on createdAt, JSONArray-encoded newTopics covered by SP-3a consumer of BookmarksRepository. SP-3a Phase 4 (tracker_setting) is locked in place by the inverted test. TestBookmarksRepositoryStubB is replaced with a real fake, those tests failing and force the maintainer to (b) replace the inverted test with

File	Lines	Reason
core/testing/src/main/kotlin/lava/testing/service/TestAuthService.kt	all	patterned after TestEndpointsRepository. The current MenuViewModelTest.ClearBookmarksUseCase(TestBookmarksRepository) but never triggers a code path through MenuAction.ClearBookmarks (no MenuAction.ClearBookmarks.latent rather than actively broken violation acknowledged; falsifiable). lava-ci-evidence/sp3a-bluff-bookmarks-repository.json. Fake has zero test consumers in 2026-04-30 (verified via <code>grep -r include='*.kt' core/</code> feature, declaration site — empty result). Phase 0 audit, equivalence audit consumer (anticipated SP-3a Phase tests using the Authenticatable). When the first consumer is added, TestAuthServiceEquivalenceTest, TestEndpointsRepositoryEquivalence, AuthServiceImpl token persistence, storage, login/logout state transition observation). Anti-Bluff Pact This cannot mislead any test; the bluff consumer materialises. Evidence: evidence/sp3a-bluff-audit/0.1. Equivalence already verified by tests in core/domain: (a) core/domain/lava/testing/contract/TestInfrastructureContractTest, TestLocalNetworkDiscoveryService (emit contract section) covers the surface — non-suspending emit, scheduler rendezvous — i.e. the 5 fake's previous rendezvous-Channels and (b) core/domain/src/test/kotlin/contract/LocalNetworkDiscoveryService.kt (lines, 8 @Test methods) covers the <code>_lava._tcp.local. / _lava-api.</code> logic via matchesServiceType, with match regression guard. The fake suffix scoping by design — it is a that consumers feed pre-resolved instances into; suffix-scoping has resolution boundary that the fake
core/testing/src/main/kotlin/lava/testing/service/TestLocalNetworkDiscoveryService.kt	n/a — fake is a post-resolution injection point	

File	Lines	Reason
		(the LocalNetworkDiscoveryService.emit DiscoveredEndpoints", not new test required for SP-3a; this resolution. Evidence recorded in bluff-audit/0.4-test-local-n

Latent findings

The following are NOT coverage exemptions — they are known-risk observations surfaced during the Phase 0 audit. They do NOT block Phase 1 (Foundation), but each is a future-facing tripwire that MUST be revisited before its respective trigger condition materialises.

LF-1 — MenuViewModelTest holds TestBookmarksRepository without exercising it (linked: Task 0.2)

Location: feature/menu/src/test/kotlin/lava/menu/MenuViewModelTest.kt:115–118

Observation: the test constructs TestBookmarksRepository() and wires it into ClearBookmarksUseCase, which is then injected into MenuViewModel. As of 2026-04-30 no @Test method in this file dispatches a MenuAction whose handler invokes a stubbed method on the repository — i.e. the bookmarks fake is held but never touched. The instant a test is added that drives, for example, a MenuAction.ClearBookmarks flow, the stub will throw NotImplementedError at the first stubbed call site (getBookmarks(), saveBookmark(...), etc.) and the test will fail at runtime, not at compile time.

Mitigation trigger: when the first MenuViewModel test path that exercises bookmarks is added (anticipated during SP-3a Phase 4 tracker settings work or earlier feature work), the author MUST either:

1. Implement TestBookmarksRepository against the TestEndpointsRepositoryEquivalenceTest pattern (full behavioural equivalence to BookmarksRepositoryImpl), and remove the corresponding ledger entry above; or
2. Document why the new test path does not need a real fake (e.g. it uses a purpose-built local fake), and leave the ledger entry intact.

Audit linkage: Task 0.2 evidence at .lava-ci-evidence/sp3a-bluff-audit/0.2-test-bookmarks-repository.json.

LF-2 — TestHealthcheckContract is currently a future-facing tripwire (linked: Task 0.6)

Location: `lava-api-go/tests/contract/healthcheck_contract_test.go::TestHealthcheckContract`

Observation: Constitutional clause 6.A (real-binary contract tests) was authored in response to the `lava-api-go --http3 healthcheck` regression of 2026-04-29, where `docker-compose.yml` invoked `healthprobe --http3 https://localhost:8443/health` against a binary that only registered `-url/-insecure/-timeout`. The contract test extracts the `healthcheck` command from `docker-compose.yml`, recovers the registered flag set from the binary's Usage output, and asserts strict subset. As of 2026-04-30 the `lava-api-go` service block in `docker-compose.yml` has no `healthcheck:` block at all (the bug was triaged by removing the broken `healthcheck` rather than fixing the flag). Consequently the contract test's "extract command" step finds an empty command and the subset check is trivially satisfied — the test passes vacuously.

The test is still load-bearing as a tripwire: the moment a `healthcheck:` block is re-introduced for `lava-api-go`, this contract test will validate it against the actual flag set of the `healthprobe` binary at the pinned hash. The falsifiability rehearsal recorded in Task 0.6 confirmed the test fails when a bogus `--http2` flag is added to the compose `healthcheck`.

Mitigation trigger: before re-introducing any `healthcheck:` block on the `lava-api-go` service in `docker-compose.yml`, the author MUST:

1. Run `go test ./tests/contract/... -run TestHealthcheckContract` against the new compose file and confirm the test now exercises the subset check non-vacuously (i.e. the extracted command is non-empty).
2. Add a falsifiability rehearsal sub-test asserting that an unregistered flag in the new `healthcheck` command causes the contract checker to fail.
3. Record the rehearsal in a new evidence file under `.lava-ci-evidence/` with the same Test/Mutation/Observed/Reverted protocol used by Task 0.6.

Audit linkage: Task 0.6 evidence at `.lava-ci-evidence/sp3a-bluff-audit/0.6-healthprobe-contract.json`.

LF-3 — Tracker chain compiles to JVM 21 while Android targets JVM 17 (linked: Phase 2 Section A) — RESOLVED in Phase 2 Section E wrap-up

Resolution (2026-04-30): mitigation trigger #1 applied. Tracker-SDK submodule commit `b779fda` adds `subprojects { ... jvmTarget = JVM_17 }` to `submodules/tracker_sdk/build.gradle.kts`, pinning every

SDK subproject to JVM 17. Lava's three JVM 17→21 overrides reverted (KotlinTrackerModuleConventionPlugin, core/tracker/api/build.gradle.kts, core/tracker/testing/build.gradle.kts). Submodule pin updated in Lava to b779fda. Build verified GREEN end-to-end:
:core:tracker:api, :core:tracker:testing, :core:tracker:rutracker:test
all compile and test against JVM 17 toolchain.

Submodule commit landed locally on branch sp3a-jvm17-target; mirror push to GitHub + GitLab is a separate operator action (per Decoupled Reusable Architecture rule "Submodule fetch/pull is an EXPLICIT operator action").

The original observation below is preserved for forensic context.

Locations:

- buildSrc/src/main/kotlin/KotlinTrackerModuleConventionPlugin.kt
- core/tracker/api/build.gradle.kts
- core/tracker/testing/build.gradle.kts

Observation: Phase 2 Section A (Task 2.5) required the new :core:tracker:rutracker module to compile via lava.kotlin.tracker.module. At HEAD the Tracker-SDK composite-build's :api/:mirror/:registry/:testing projects default to the JDK 21 toolchain and emit JVM 21 class files. The Lava-side tracker convention plugin previously targeted JVM 17, which produced "class file has wrong version 65.0, should be 61.0" failures the moment any Lava module on the JVM-17 chain (e.g. :core:tracker:api, :core:tracker:testing) tried to consume an SDK type. To unblock Section A's required BUILD SUCCESSFUL acceptance gate, the implementer bumped JVM target to 21 in three places: the new tracker convention plugin, and the two pure-Kotlin Lava-side tracker modules that were previously on JVM_17 via lava.kotlin.library. The rest of the codebase (Android modules via KotlinAndroid.kt, regular Kotlin libraries via KotlinLibraryConventionPlugin.kt) remains JVM_17 — the APK still targets JVM 17 bytecode.

Why this is a latent finding rather than a fix: The plan does not authorize a JVM-target bump and the cleaner resolution is upstream — set kotlin { jvmToolchain(17) } on each Tracker-SDK Gradle module. That requires a new Tracker-SDK pin and a fresh 4-upstream mirror push. Deferred so the rename can land cleanly in Phase 2 Section A.

Mitigation trigger: before Section F (Tasks 2.28-2.31, Hilt + LavaTrackerSdk wiring) lands the tracker chain into the Android :app Hilt module, the author MUST verify one of:

1. The Tracker-SDK pin has been updated upstream to target JVM 17 in its convention/module Gradle scripts, the new pin recorded in submodules/tracker_sdk/, and the three JVM_21 overrides reverted to JVM_17 in KotlinTrackerModuleConventionPlugin.kt, core/tracker/api/build.gradle.kts, core/tracker/testing/build.gradle.kts.
2. The Android build (AGP/D8) is configured to accept JVM 21 input bytecode, and the rest of the codebase is bumped to JVM 21 for consistency. (Larger blast radius — only choose this path if upstream Tracker-SDK is sticky on JVM 21.)

If neither condition is met before Section F, :app:assembleDebug will fail at D8 dexing the moment the tracker registry lands on the dependency graph.

Audit linkage: Phase 2 Section A spec compliance review (commit landing the LF-3 entry).

LF-5 — RuTrackerDescriptor declares UPLOAD + USER_PROFILE without feature interfaces (linked: Phase 2 Section C) — RESOLVED 2026-04-30

Status: RESOLVED by commit lf-5-resolved on 2026-04-30. Resolution chose mitigation option 2 (drop the two capabilities) rather than option 1 (add the feature interfaces) because the legacy UploadTorrentUseCase and GetCurrentProfileUseCase plumbing is not consumed by any SP-3a feature ViewModel — adding the interfaces would be scope creep beyond the SP-3a foundation. Re-introducing either capability is appropriately scheduled for a future SP (SP-3a-bridge or later) where a feature ViewModel actually needs it.

Location: core/tracker/rutacker/src/main/kotlin/lava/tracker/rutacker/RuTrackerDescriptor.kt

Observation (historic): Phase 2 Section B (Task 2.6) populated RuTrackerDescriptor.capabilities with the full 12-capability set including TrackerCapability.UPLOAD and TrackerCapability.USER_PROFILE. As of Phase 2 Section C end-of-task, the new :core:tracker:api package did NOT define UploadableTracker or ProfileTracker feature interfaces. Consequently RuTrackerClient.getFeature<T>() could not return a non-null impl for those two capabilities — the KClass<T> for the missing interfaces did not exist as a dispatch key in the when switch.

Constitutional clause 6.E literal: "capability declared in descriptor $\Rightarrow$ this returns non-null". The original code SATISFIED this letter-of-the-law because no caller could construct `getFeature(UploadableTracker::class)` — the type didn't exist. But the descriptor was making a forward-looking claim that no impl backed. Treated as a latent finding rather than an immediate violation.

Resolution (2026-04-30):

- `RuTrackerDescriptor.capabilities` reduced from 12 to 10 entries.
- `UPLOAD` and `USER_PROFILE` removed.
- `RuTrackerDescriptorTest` assertion updated from 12 capabilities to 10 capabilities and a new test `LF-5 RESOLVED – UPLOAD and USER_PROFILE are NOT declared (no feature interface)` added.
- `core/tracker/rutracker/README.md` capability matrix updated.
- The dormant scrapers (`RuTrackerInnerApi.uploadTorrent`, `getProfile`) and their wrapping `UseCases` continue to ship as legacy plumbing in this module but are no longer advertised through the SDK.

Audit linkage: Phase 2 Section C spec + code-quality review (commit landing the LF-5 entry); Phase 5 wrap follow-up (commit `lf-5-resolved`).

LF-6 — `TorrentItem.sizeBytes` permanently null for `rutracker` (linked: Phase 2 Section D) — RESOLVED 2026-04-30

Status: RESOLVED by commit `lf-6-resolved` on 2026-04-30. Resolution chose mitigation option 2 (parse the formatted display string in the forward mapper). A new internal helper `RuTrackerSizeParser` lives next to the forward mappers in `core/tracker/rutracker/src/main/kotlin/lava/tracker/rutracker/mapper/` and handles GB/MB/KB/B/TB suffixes with optional decimal (period or comma) at binary multipliers ($1\text{ GB} = 2^{30}$) — matching what the legacy `rutracker` scraper's `formatSize` helper renders, so a render-then-parse round-trip is bitwise correct (modulo Long truncation of the truncated Double value, which is the same precision the formatted display string carries).

Locations:

- `core/tracker/rutracker/src/main/kotlin/lava/tracker/rutracker/mapper/SearchPageMapper.kt`
- `core/tracker/rutracker/src/main/kotlin/lava/tracker/rutracker/mapper/CategoryPageMapper.kt`
- `core/tracker/rutracker/src/main/kotlin/lava/tracker/rutracker/mapper/TopicMapper.kt`

Observation (historic): The new tracker-api model `TorrentItem` exposes `sizeBytes: Long?`. The legacy rutracker scraper delivers torrent size as a pre-formatted display string (e.g. "4.7 GB"), and the raw byte count is discarded before the DTO reaches the forward mapper. Consequently every `TorrentItem` produced by the rutracker forward mappers HAD `sizeBytes = null`. The display string was preserved in `metadata["rutracker.size_text"]` so UI could render it, but any consumer of `Searchable/Browsable/Topic` features that relied on `sizeBytes` for filtering, sorting, or comparison against a threshold silently received `null` for every rutracker row.

Resolution (2026-04-30):

- New `RuTrackerSizeParser` (internal object) in `core/tracker/rutracker/src/main/kotlin/lava/tracker/rutracker/mapper/RuTrackerSizeParser.kt`. Tolerates null/blank input by returning null; tolerates `U+00A0` between number and unit; supports B/KB/MB/GB/TB (case-insensitive); accepts comma-decimal as well as period-decimal.
- `SearchPageMapper.toTorrentItem` (the `TorrentDto` extension) now calls the parser; `TopicMapper.toTorrentItem` (the `TopicPageDto` extension) does the same. `CategoryPageMapper`'s `TopicDto` branch is intentionally unchanged — `TopicDto` has no size field upstream.
- Tests: `RuTrackerSizeParserTest` (15 cases covering integer GB, decimal GB period+comma, MB, KB, B, integer TB, decimal TB Double-precision truncation, case-insensitive, null, blank, garbage, no-whitespace, non-breaking-space). `SearchPageMapperTest` and `TopicMapperTest` now positively assert non-null `sizeBytes` on the fixtures with a size field.

Audit linkage: Phase 2 Section D combined review (commit landing the LF-6 entry); Phase 5 wrap follow-up (commit `lf-6-resolved`).