

scripts/distribute.sh — User Guide

Last verified: 2026-05-15 (1.2.23 closure-cycle, §6.AD-debt task #61 backfill)

Inheritance: HelixConstitution §11.4.18 (script documentation mandate)

Overview

Stub doc generated from the script's in-source header comment. See `scripts/distribute.sh` for canonical behavior. This stub exists so the CM-SCRIPT-DOCS-SYNC pre-push gate (`.github/hooks/pre-push Check 9`) starts gating modifications to this script.

The script's own header documentation (verbatim):

`scripts/distribute.sh` – operator's single-command distribute flow.

Rebuilds every artifact (Android debug + release APKs, Ktor proxy fat

JAR, lava-api-go static binary, lava-api-go OCI image), then:

- * Uploads Android APKs to Firebase App Distribution + invites testers.

- * Distributes the Go API to the configured remote host (default: `thinker.local`) via the Containers-submodule-driven remote pipeline

- and tears down the local API stack so the workstation no longer

- runs Postgres + the Go API.

Usage:

<code>./scripts/distribute.sh</code>	<code># rebuild + distribute everything</code>
<code>./scripts/distribute.sh --android-only</code>	<code># rebuild + distribute Android only</code>
<code>./scripts/distribute.sh --api-only</code>	<code># rebuild + distribute Go API only</code>
<code>./scripts/distribute.sh --no-rebuild</code>	<code># skip rebuild, distribute existing artifacts</code>
<code>./scripts/distribute.sh --release-only</code>	<code># only release APK (skip debug)</code>
<code>./scripts/distribute.sh --debug-only</code>	<code># only debug APK</code>
<code>./scripts/distribute.sh --no-teardown</code>	<code># leave local API containers running</code>

Architecture (per Decoupled Reusable Architecture rule):

* Generic remote-host SSH + container-orchestration primitives live in

``submodules/containers/pkg/remote/`` (the vasic-digital/Containers

submodule). Lava's distribute scripts are thin glue that:

1. Build artifacts via `build_and_release.sh` (which itself routes through the Containers build path).
2. Invoke ``scripts/distribute-api-remote.sh`` for the SSH+scp+podman-load+boot dance on the remote.
3. Drive Firebase App Distribution for the Android side.

* The Containers submodule's ``bin/boot`` CLI is built on demand (so

pinned hash failures show up early, before any remote operation).

Constitutional bindings:

§6.J Anti-Bluff – propagates failures via `set -euo pipefail`

§6.K Builds-Inside-Containers – `build_and_release.sh` routes through

the container path for release-tagged builds

§6.H Credential Security – all Firebase tokens + remote SSH config

loaded from `.env` (gitignored)

§6.P Distribution Versioning + Changelog Mandate – both the Firebase

and the remote-distribute scripts gate on §6.P.

Usage

See the script's in-source comment block (above) for canonical usage examples.

Maintenance

When this script is modified, update this document in the same commit (CM-SCRIPT-DOCS-SYNC requires it). Per §11.4.18, the documentation MUST stay in sync with the codebase — no doc may be out of sync with its script.

Cross-references

- `scripts/distribute.sh` — the script itself
- `docs/helix-constitution-gates.md` — gate inventory
- `HelixConstitution Constitution.md` §11.4.18 (the mandate)
- `Lava CLAUDE.md` §6.AD (HelixConstitution Inheritance)