

sync-markdown-exports.sh

Constitution: §11.4.65 / CONST-066 — Universal Markdown Export Sync **Closes:** §6.AF-debt (§11.4.65 item)

Purpose

Generator + checker for the universal-markdown-export rule: every in-scope committed markdown document **MUST** have synchronized `.html` and `.pdf` sibling exports kept current with the markdown source.

- **HTML:** `pandoc "$md" --from gfm -o "$html" --standalone`
- **PDF:** `pandoc "$md" --from gfm -o "$pdf" --pdf-engine=weasyprint`

(`--from gfm` reads sources as GitHub-Flavored Markdown so a leading `----`-fenced block is **NOT** misparsed as a YAML metadata block — the `CHANGELOG.md` failure class.)

The gate `scripts/check-markdown-export-sync.sh` (CM-UNIVERSAL-MARKDOWN-EXPORT-SYNC) wraps this script's `--check-only` mode.

Scope

Authority: `docs/chaos-stress/EXPORT-AUDIT.md`.

INCLUDED

- Project-root `*.md` (depth 1)
- `docs/**/*.*md`
- `scripts/**/*.*md` (companion docs per §11.4.18)

EXCLUDED (each syncs its own / not source-export domain)

- `external/`, `prebuilts/`
- `submodules/**` (own-org + third-party — they sync their own)
- `constitution/**` (the HelixConstitution submodule syncs its own)
- `lava-api-go/**` source trees
- `build/`, `out/`, `.git/`, `node_modules/`
- `app/`, `core/`, `feature/` Kotlin source-code trees

Usage

```
scripts/sync-markdown-exports.sh --check-only      # default;  
gate mode  
scripts/sync-markdown-exports.sh --regenerate-all  # backfill/  
refresh all  
scripts/sync-markdown-exports.sh --regenerate <file> # one .md's  
siblings  
scripts/sync-markdown-exports.sh --help
```

Modes

- **--check-only** — exit 1 if any in-scope .md lacks a sibling OR a sibling is older than its .md (mtime). This is the gate's mode.
- **--regenerate-all** — generate/refresh every in-scope sibling.
- **--regenerate** — regenerate one specific .md's siblings.

Resource discipline (§6.T.2)

Each pandoc conversion is sub-second. Per-file timeout 60 (GNU timeout or gtimeout, when present) caps any runaway. The candidate set is capped at 500; the script refuses to silently truncate (§6.J) and exits 2 if exceeded.

Exit codes

- 0 — siblings present + current (check-only); all generated (regenerate)
- 1 — check-only found missing/stale siblings; or a generation failed
- 2 — tooling missing, scope/arg error, or candidate cap exceeded

Generated artifacts are TRACKED

The produced .html / .pdf siblings ARE the synced artifacts mandated by §11.4.65. They are committed (not gitignored). 224 in-scope .md files → 448 sibling files at backfill time.