

Firestore scripts — quick reference

Script	Purpose	Typical use
scripts/ firebase- env.sh	Sourced by other scripts to load Firestore keys from .env.	source scripts/ firebase-env.sh
scripts/ firebase- setup.sh	One-time Firestore project bootstrap; refreshes app/google-services.json + lava-api-go/firebase-web-config.json; invites testers.	First clone after firebase login:ci
scripts/ firebase- distribute.sh	Uploads built APKs to Firestore App Distribution + invites testers from .env.	After ./ build_and_release.sh
scripts/ firebase- stats.sh	Prints dashboard URLs + machine-readable summary of Firestore services.	Operator inspection
scripts/ distribute.sh	Umbrella: rebuilds artifacts + distributes via Firestore + prints stats.	One-command operator distribute

Examples

First-time setup on a fresh clone

```
# 1. Authenticate Firestore CLI
firebase login:ci          # copy the token into .env as
                           LAVA_FIREBASE_TOKEN
```

```
# 2. Copy template + fill in real values
cp .env.example .env
$EDITOR .env
```

```
# 3. Refresh Firestore config files + invite testers
./scripts/firebase-setup.sh
```

Distribute a new build to testers

```
# Rebuild + upload + invite — one command
./scripts/distribute.sh
```

```
# Skip rebuild (use the artifacts already in releases/<version>/)
./scripts/distribute.sh --no-rebuild

# Distribute only the release-signed APK
./scripts/distribute.sh --release-only

# Provide custom release notes
./scripts/firebase-distribute.sh --release-notes "Hotfix:
    API_VERSION drift caught + fixed"
```

Inspect Firebase health / stats

```
./scripts/firebase-stats.sh                # human-readable,
    last 7 days
./scripts/firebase-stats.sh --days 30     # last 30 days
./scripts/firebase-stats.sh --json        # machine-readable
```

Refresh config files without re-inviting testers

```
./scripts/firebase-setup.sh --refresh
```

Re-invite testers without touching config files

```
./scripts/firebase-setup.sh --invite-only
```

Constitutional bindings (per CLAUDE.md)

- **§6.H Credential Security** — LAVA_FIREBASE_TOKEN and firebase-admin-key.json are gitignored; pre-push hooks reject pushes that introduce them.
- **§6.J Anti-Bluff** — every script uses set -euo pipefail; there is no WARN-swallow pattern; failures propagate.
- **§6.K Builds-Inside-Containers** — build_and_release.sh invocations from distribute.sh route through the container path for release builds.

See docs/FIREBASE.md for the full integration architecture.