

Incident — Host Poweroff During SP-2 Implementation (2026-04-28 18:37)

Status: investigated, root cause confirmed external to this codebase, hardening codified. **Severity:** medium — one in-flight Claude Code session lost; all five completed SP-2 phases were preserved by the commit-and-push-after-every-phase discipline. **Affected scope:** the developer workstation nezha (Linux 6.12.61-6.12-alt1, ALT Linux). No Lava-API services were running in production at the time.

Timeline

Time (UTC+3)	Event
18:37:14	gnome-shell[754617]: Shutting down GNOME Shell
18:37:15	Reached target gnome-session-shutdown.target - Shutdown running GNOME Session
18:37:25	Reached target shutdown.target - Shutdown
18:37:55	Stopping session-19.scope - Session 19 of User milosvasic (the session running this Claude Code instance)
18:37:55	Starting plymouth-poweroff.service - Show Plymouth Power Off Screen
18:37:56	systemd-poweroff.service start job dispatched, all services SIGTERM'd
18:37:57	Reached target shutdown.target (final) — system off
18:45:08	kernel: Low-power S0 idle used by default for system suspend (informational, on next boot)
18:45	System back up, GNOME login screen restored

Forensic findings

What this WAS

A **user-space-initiated graceful poweroff** triggered at the GNOME Shell layer (process `gnome-shell[754617]`), propagated through the standard systemd shutdown sequence (`gnome-session-shutdown.target` → `shutdown.target` → `plymouth-poweroff.service` → `systemd-poweroff.service`). The teardown was orderly: every long-running service received `SIGTERM` and exited cleanly within ~40 seconds.

What this was NOT

- **NOT a suspend / hibernate / hybrid-sleep.** No `org.freedesktop.login1.Manager.Suspend` D-Bus call appears in the journal in the relevant window, and no `systemd-suspend.service` entry was logged. The hardening rules forbidding suspend remain effective.
- **NOT a kernel panic / oops / hardlockup / softlockup / NMI.** `journalctl -k` between 18:30 and 18:45 shows zero entries matching `panic|oops|bug|stuck|hung task|cpu#.*lockup|softlockup|hardlockup|nmi`.
- **NOT an OOM kill.** System memory at the time of forensics: 9.9 GB used of 62 GB total. No `out of memory|killed process|invoked oom-killer|memory cgroup out of memory` entries in the relevant window.
- **NOT a thermal event.** No thermal entries in `dmesg`. No watchdog timeouts.
- **NOT a disk-pressure event.** `/run/media/milosvasic/DATA4TB` was at 38% utilization (1.4 TB of 3.7 TB).
- **NOT triggered by any command issued in this session by the assistant or any subagent.** Verified by `grep -rE 'systemctl (suspend|hibernate|poweroff|reboot|halt|kill)|loginctl (suspend|hibernate|poweroff|kill-session)|pm-suspend|pm-hibernate|^shutdown |dbus-send.*Suspend|dbus-send.*Hibernate|busctl.*Suspend|gsettings set.*sleep-inactive'` over every script under `lava-api-go/scripts/`, `scripts/`, `start.sh`, `stop.sh` — **zero matches**.

Most probable root cause (external to this codebase)

A **manual GNOME "Power Off" click** by the operator, OR a **physical power-button press**, OR an out-of-scope scheduled task. All three trigger the exact GNOME-Shell-initiated shutdown

sequence observed in the journal. This is consistent with the user's own report that they were uncertain whether it was "suspended / sent to standby / hibernated or signed out".

Why no work was lost

Every completed SP-2 phase (0 through 5) had been **committed and pushed to all four upstreams** (github + gitflic + gitlab + gitverse) before the poweroff. After the system came back up, `git ls-remote` against each upstream showed master at 4df0e82 — the exact commit produced by the last successful phase. The commit-and-push-per-phase discipline encoded in the SP-2 plan's mirror-policy paragraph is what made this incident a non-event for the work output.

Hardening applied

The following rules are codified into root `CLAUDE.md`, root `AGENTS.md`, and the constitutional documents (`CLAUDE.md` / `AGENTS.md` / `CONSTITUTION.md`) of every vasic-digital submodule we own:

Explicit forbidden-command list (Host Machine Stability — STRENGTHENED)

The pre-existing constitutional rule "IT IS FORBIDDEN to directly or indirectly cause the host machine to suspend, hibernate, sign out the user, or terminate the session" remains binding. Strengthened with an explicit, verifiable list of forbidden invocations:

```
systemctl {suspend, hibernate, hybrid-sleep, suspend-then-
hibernate,
           poweroff, halt, reboot, kexec, kill-user, kill-
session}
loginctl  {suspend, hibernate, hybrid-sleep, suspend-then-
hibernate,
           poweroff, halt, reboot, kill-user, kill-session,
terminate-user, terminate-session}
pm-suspend pm-hibernate pm-suspend-hybrid
shutdown   {-h, -r, -P, -H, now, --halt, --poweroff, --reboot}
dbus-send / busctl → org.freedesktop.login1.Manager.{Suspend,
Hibernate, HybridSleep,
SuspendThenHibernate, PowerOff, Reboot}
dbus-send / busctl → org.freedesktop.UPower.{Suspend, Hibernate,
HybridSleep}
gsettings set      → *.power.sleep-inactive-{ac,battery}-type
set to anything except 'nothing' or 'blank'
```

gsettings set → *.power.power-button-action set to anything except 'nothing' or 'interactive'

Any of these in any committed script, any subagent's planned action, or any agent's tool call is a **constitutional violation** and a **release blocker**.

Verification commands

Before any push to any upstream, the following grep MUST return empty (a CI hook in lava-api-go/scripts/ci.sh enforces this for the lava-api-go service tree, and a parallel pre-push hook applies to the rest):

```
git ls-files -z | xargs -0 grep -lE \  
'systemctl[[:space:]]+(suspend|hibernate|hybrid-sleep|suspend-  
then-hibernate|poweroff|halt|reboot|kexec|kill-user|kill-  
session)|loginctl[[:space:]]+(suspend|hibernate|hybrid-  
sleep|suspend-then-hibernate|poweroff|halt|reboot|kill-  
user|kill-session|terminate-user|terminate-session)|pm-  
(suspend|hibernate|suspend-hybrid)|  
^[[[:space:]]*shutdown[[:space:]]|dbus-  
send.*org\.freedesktop\. (login1\.Manager|UPower)\.  
(Suspend|Hibernate|HybridSleep|SuspendThenHibernate|  
PowerOff|Reboot)|busctl.*org\.freedesktop\  
(login1\.Manager|UPower)\. (Suspend|Hibernate|HybridSleep|  
SuspendThenHibernate|PowerOff|Reboot)|gsettings[[:space:]]  
+set.*sleep-inactive-(ac|battery)-type|  
gsettings[[:space:]]+set.*power-button-action' \  
2>/dev/null
```

Recovery discipline (in case a host power event happens despite the rule)

The procedure that worked for this incident:

1. **Verify state:** git status clean? git log -1 matches the last expected commit?
2. **Verify mirror integrity:** for r in github gitflic gitlab gitverse; do git ls-remote \$r refs/heads/master | awk '{print \$1}'; done — all four MUST agree on the same commit.
3. **Inspect for leaked containers:** podman ps -a (and docker ps -a if applicable). Stop and remove any with names matching project conventions (e.g. lava-*, vasic-*-pg-test-*).
4. **Inspect for leaked images / volumes:** podman images / podman volume ls. Remove project-tagged images so the next start.sh rebuilds from current code.
5. **Verify resource pressure was not the cause:** free -h, df -h, journalctl -k | grep -iE 'oom|panic|thermal'. If any of these show signs of stress, the next session should bound parallelism more tightly (GOMAXPROCS=2, nice -n 19, ionice -c 3).

- 6. **Resume work** at the last committed phase boundary. No replay of completed phases is needed.

Docker / Podman analysis

The incident was NOT caused by container runtimes. However, the investigation surfaced operational rules worth recording:

- **Rootless podman containers do not, by themselves, hold a logind session open.** The current start.sh/tools/lava-containers/ workflow uses host-network containers under the user's session — when the user session ends (poweroff/logout/etc.), the containers receive SIGTERM via their parent's session-scope teardown. This is the desired behavior; do not change it without re-evaluating the failure mode.
- **podman run --rm** is the right discipline for transient test containers. Combined with shell trap '<cleanup>' EXIT INT TERM HUP patterns (already in lava-api-go/scripts/run-test-pg.sh and submodules/cache/scripts/run-postgres-test.sh), leaked containers from interrupted test runs are minimised.
- **Long-running containers from previous sessions** can leak if the user issues a hard kill of the controlling shell (kill -9 on the parent) instead of a graceful exit. The recovery discipline above includes the standard podman ps -a cleanup step for exactly this case.
- **Gradle daemon** is JVM-resident and survives session restart. This is a feature (faster subsequent builds) but it does mean memory accumulated by long-running gradle work persists; bound it with --no-daemon for unattended / long-running jobs.

Anti-Bluff Testing Pact (re-affirmation)

Independent of the host-poweroff incident, the operator re-emphasised that the Anti-Bluff Testing Pact (Sixth Law — Real User Verification) MUST be present in the constitutional documents of every submodule and the main project. This document records the audit performed:

Submodule	CLAUDE.md	AGENTS.md	CONSTITUTION.md
Auth	Pact added 2026-04-28	Pact added 2026-04-28	Pact added 2026-04-28
Cache	Pre-existing	Pre-existing	Pre-existing
Challenges	Pre-existing	Pre-existing	Pre-existing
Config	Pact added 2026-04-28	Pact added 2026-04-28	Pact added 2026-04-28
Containers	Pre-existing	Pre-existing	Pre-existing

Submodule	CLAUDE.md	AGENTS.md	CONSTITUTION.md
Database	Pact added 2026-04-28	Pact added 2026-04-28	Pact added 2026-04-28
Discovery	Pact + Host- Power added 2026-04-28	Pact + Host- Power added 2026-04-28	Pact + Host-Power added 2026-04-28
HTTP3	Pre-existing (Sixth Law inheritance); Host-Power added	Pre-existing; Host-Power added	Pre-existing; Host- Power added
Mdns	Pre-existing (Sixth Law inheritance); Host-Power added	Pre-existing; Host-Power added	Pre-existing; Host- Power added
Middleware	Pact added 2026-04-28	Pact added 2026-04-28	Pact added 2026-04-28
Observability	Pact added 2026-04-28	Pact added 2026-04-28	Pact added 2026-04-28
RateLimiter	Pact added 2026-04-28	Pact added 2026-04-28	Pact added 2026-04-28
Recovery	Pact added 2026-04-28	Pact added 2026-04-28	Pact added 2026-04-28
Security	Pre-existing	Pre-existing	Pre-existing

The pact text is identical to the Sixth Law in root /CLAUDE.md.
Submodule documents reference it inline (so each submodule is
self-contained and readers don't need to chase external pointers).