

T7 Fast Storage — relocation map (operator-designated main fast storage)

Operator directive (2026-05-31): "Use for any storage-demanding work T7 drive and update paths references to it since this is our main fast storage."

T7 = Samsung T7 external SSD mounted at /Volumes/T7 (1.8 TiB, ~1.2 TiB free). It is the project's designated **main fast storage** for all storage-demanding work (container image builds, emulator system-images/AVDs, build caches).

Relocations in effect

Concern	Host path	Target on T7	Mechanism
Podman VM + image storage	~/.local/share/containers	/Volumes/T7/containers	symlink
Gradle home	~/.gradle (via GRADLE_USER_HOME)	/Volumes/T7/Gradle	env var (.zshrc)
XDG cache	~/.cache	/Volumes/T7/cache	symlink
Android .android (AVDs, 24 GB)	~/.android	/Volumes/T7/dot-android	symlink

Podman VM (the \$6.M Class-II disk-pressure fix, 2026-05-31)

The podman applehv machine stores its whole VM as one fixed-size .raw disk image under the graphroot. Originally 50 GB and living on the host data-volume (which had dropped to 16 GiB free / 97%); the lava-api-go OCI image build filled it and

build_and_release.sh exited 125 "no space left on device" (incident .lava-ci-evidence/sixth-law-incidents/2026-05-31-disk-pressure-podman-vm-image-build.json).

Fix:

1. podman machine stop
2. mv ~/.local/share/containers /Volumes/T7/containers
3. ln -s /Volumes/T7/containers ~/.local/share/containers
4. podman machine start

Verified result: host data-volume freed ~50 GB (16 GiB → 66 GiB free). After the move + restart, the live VM reported /dev/vda4 50G total / 41G free (the move to a clean graphroot on T7 plus a podman system prune is what reclaimed the working room) — and build_and_release.sh then completed EXIT 0 including the lava-api-go OCI image build that previously failed at COPY . . .

UNCONFIRMED: podman machine set --disk-size 150 was issued and returned 0, but the running VM still reported a 50 GB root afterward — on applehv the disk-size change does not appear to apply to the already-provisioned .raw without a machine recreate. The 50 GB → 41 GB-free headroom on T7 was sufficient for this build; if a future build needs more, recreate the machine (podman machine rm + podman machine init --disk-size N) so the larger raw is provisioned fresh on T7.

Caveat (§6.M)

These relocations make T7 a hard dependency for container + emulator work: if T7 is unmounted, podman + the AVD matrix break until it is remounted. This is the operator's deliberate choice (T7 is the designated main fast storage). The pre-push hook + scripts/run-challenge-matrix.sh continue to work host-side; only the container/emulator runtime needs T7 present.

Classification: project-specific (Lava's host storage layout).