

HelixQA Wiring Plan — Lava Android app on the Genymotion VM

Revision	2
Created	2026-06-08
Last modified	2026-06-08
Status	active

Table of contents

- [1. Scope](#)
- [2. Claude Code as the LLM + Vision provider \(BridgedCLIPProvider\)](#)
- [3. Pointing an autonomous session at the Lava app on the Genymotion VM](#)
- [4. Test banks consumed by the session](#)
- [5. What is still MISSING \(concrete task list\)](#)
- [6. Constraints honoured](#)

1. Scope

This document specifies how to drive a real HelixQA autonomous QA session against the **Lava Android app** (`digital.vasic.lava.client.dev`) installed on the **Genymotion VM reachable at adb 127.0.0.1:6555**, using **Claude Code** as the LLM + Vision provider. It also enumerates the concrete gaps that must be closed before a fully autonomous, end-to-end provider-multiplexed run is possible.

The Lava-owned test banks this session consumes live at `lava-api-go/qa/banks/*.yaml` (seven banks; see §4).

The HelixQA submodule itself (`submodules/helixqa`) is **not modified** by any step here — all configuration is supplied via env vars, CLI flags, and the Lava-owned banks directory.

2. Claude Code as the LLM + Vision provider (BridgedCLIProvider)

HelixQA already ships the bridge: submodules/helixqa/pkg/llm/bridge_provider.go defines BridgedCLIProvider, which shells out to a CLI LLM tool with --json --print <prompt> (plus --model and --image when set) and parses the JSON result / content / text field of the response.

2.1 How discovery works (zero config)

The bridge discovery is **inside the cmdAutonomous function** (cmd/helixqa/main.go:404 func cmdAutonomous), in the "Bridged CLI model discovery" block at **cmd/helixqa/main.go:527-569** (verified against the real v0.2.0 binary). It iterates a fixed struct list — {claude, qwen-coder, opencode} (the claude entry is {"claude", "claude", ""} at **main.go:538**) — and for each runs osexec.LookPath(cli.bin) (**main.go:542**). If the binary is on \$PATH, it is wrapped via llm.NewBridgedCLIProvider(cliPath, cli.name, cli.model) (**main.go:546**) and appended to the chat pool (**main.go:553**); when bp.SupportsVision() is true it is also appended to the vision pool (**main.go:558**).

Confirmed: claude IS on this host's \$PATH at /Users/milosvasic/.local/bin/claude (command -v claude, verified this run).

Because the block lives in cmdAutonomous, the bridge is wired ONLY when running an autonomous QA session (helixqa autonomous). The helixqa list subcommand (cmdList) does NOT touch the bridge — it parses banks with no LLM, which is why listing the 7 Lava banks (§4) succeeds with zero env/credentials.

Consequences for Claude Code:

- **No env var or flag is required to enable the bridge.**
Putting the claude binary on \$PATH is sufficient — discovery is osexec.LookPath("claude") at main.go:542. If claude is not found, the loop continues (main.go:544) and the provider is simply absent; if NO API-key provider AND NO bridged CLI is found, cmdAutonomous exits 1 (main.go:571-578).
- **Vision is automatic for Claude.**
BridgedCLIProvider.SupportsVision() returns true only when cliName == "claude" (pkg/llm/bridge_provider.go:133-135), so the discovered claude provider is added to BOTH the chat pool and the vision pool. Vision() (bridge_provider.go:183) writes each screenshot to a temp PNG and passes it via --image <path> (buildArgs at bridge_provider.go:250-261). This is the screenshot-analysis path the autonomous VisionEngine needs.
- **Model** is left empty (" at main.go:538), so the --model flag is omitted (bridge_provider.go:254-256) and the claude CLI uses its

configured default. To pin a model, the discovery struct's model field must be non-empty — see the gap in §5 (the discovery list hardcodes "").

Env/config needed for an autonomous session to use Claude

1. `claude` on `$PATH` (confirmed present here). Nothing else enables the bridge.
2. `claude --json --print "<prompt>"` MUST emit JSON the bridge can parse (`parseResponse` at `bridge_provider.go:286` reads `result / content / text`; on non-JSON it falls back to treating `stdout` as plain text — `bridge_provider.go:327-331`).
3. Per-invocation timeout is `defaultBridgeTimeout = 120s` (`bridge_provider.go:20`); a single bridge call may not exceed it.
4. No `ANTHROPIC_API_KEY` is required — the bridge shells out to the CLI, which carries its own auth. (An API-key provider is an *alternative*, not a prerequisite, per the `main.go:571` "no providers" guard.)

2.2 Exact invocation the bridge issues

For a chat turn the bridge runs (`bridge_provider.go buildArgs`):

```
claude --json --print "<concatenated prompt>"
```

For a vision turn (screenshot analysis):

```
claude --json --print "<prompt>" --image /tmp/helixqa-vision-XXXX.png
```

Per-invocation timeout defaults to 120 s (`defaultBridgeTimeout`).

2.3 Pre-flight checklist

```
command -v claude          # MUST resolve – discovery is
                             LookPath("claude")
claude --json --print "ping" # MUST return JSON with a
                             result/content/text field
```

If `claude --json --print` does not emit a JSON object, the bridge falls back to treating `stdout` as plain text (`parseResponse`), which still works for chat but is lower-fidelity; prefer a `claude` build that honours `--json`.

3. Pointing an autonomous session at the Lava app on the Genymotion VM

3.1 Inputs

Input	Value	Supplied via
App package	digital.vasic.lava.client.dev	env HELIX_ANDROID_PACKAGE
Device serial	127.0.0.1:6555 (Genymotion)	env HELIX_ANDROID_DEVICE
Platforms	android	flag --platforms android
Project root	repo root (feature map from docs)	flag --project
Env file	.env (gitignored, real secrets)	flag --env
Output dir	qa-results/	flag --output
LLM + Vision	Claude Code on \$PATH	auto-discovery (\$2)

The env-var names are read directly in cmd/helixqa/main.go:
AndroidPackage: os.Getenv("HELIX_ANDROID_PACKAGE") (~line 662) and
AndroidDevice: os.Getenv("HELIX_ANDROID_DEVICE") (~line 660). The
autonomous flags (--project, --platforms, --env, --timeout, --
coverage-target, --output, --report, --curiosity, --curiosity-
timeout) are defined in the autonomous flagset (~line 404).

3.2 Connect adb to the Genymotion VM

Genymotion exposes adb over TCP. Connect the host's adb server to it first so the serial 127.0.0.1:6555 appears in adb devices:

```
adb connect 127.0.0.1:6555
adb devices                # MUST list 127.0.0.1:6555 as
                           'device' (not 'offline')
adb -s 127.0.0.1:6555 shell pm list packages | grep
                           digital.vasic.lava.client.dev
```

If the package is not installed, install the debug APK first:

```
adb -s 127.0.0.1:6555 install -r app/build/outputs/apk/debug/app-
debug.apk
```

3.3 The .env (real secrets — gitignored per §6.H / §11.4.10)

Create a .env at the location passed to --env. It MUST NOT be committed. Real tracker credentials are referenced BY NAME in the banks and read at runtime here:

```
# Device / app targeting
HELIX_ANDROID_DEVICE=127.0.0.1:6555
HELIX_ANDROID_PACKAGE=digital.vasic.lava.client.dev

# Tracker credentials consumed by the per-provider banks (NEVER
hardcoded in YAML)
RUTRACKER_USERNAME=...
RUTRACKER_PASSWORD=...
RUTOR_USERNAME=...
RUTOR_PASSWORD=...
KINOZAL_USERNAME=...
KINOZAL_PASSWORD=...
NNMCLUB_USERNAME=...
NNMCLUB_PASSWORD=...
# archiveorg + gutenbergl are auth_type NONE — no credentials.

# LLM + Vision: none required — Claude Code is auto-discovered on
$PATH (§2).
```

3.4 Launch command

```
cd /Volumes/T7/Projects/Lava
adb connect 127.0.0.1:6555
```

```
submodules/helixqa/bin/helixqa autonomous \
  --project . \
  --platforms android \
  --env ./env \
  --timeout 2h \
  --coverage-target 0.9 \
  --output qa-results/ \
  --report markdown,html,json
```

Outputs land under qa-results/ (report + tickets + videos), suitable as the docs/qa/<run-id>/ end-user evidence required by §11.4.83.

3.5 The session's 4 phases (what actually happens)

Per the HelixQA README, the autonomous session runs: (1) **Setup** — model selection + feature map from --project docs + spawn agents + init VisionEngine; (2) **Doc-Driven Verification** — workers verify documented features against the running app,

capturing screenshots/video; (3) **Curiosity-Driven Exploration**; (4) **Report & Cleanup**. The NavigationEngine's Android ActionExecutor drives the device over adb (taps/swipes/screencap); Claude (vision) interprets each screenshot to decide the next action and to verify the expected of each bank step.

4. Test banks consumed by the session

Seven Lava-owned banks, all platforms: [android]. **Verified against the real helixqa v0.2.0 binary** (built `go build -o /tmp/helixqa ./cmd/helixqa`, exit 0): all 7 banks load with ZERO YAML fixes required — the banks were already schema-correct for the real pkg/testbank loader (the earlier PyYAML-only check is now superseded by real-binary proof). 32 test cases total.

4.1 VERBATIM real-binary helixqa list output

```
$ /tmp/helixqa list --banks /Volumes/T7/Projects/Lava/lava-api-go/qa/banks
```

Test cases: 32

ID	NAME	CATEGORY
PRIORITY	PLATFORMS	

LAVA-ARCHIVEORG-001	Onboard and select the Internet Archi...	
functional	critical	android
LAVA-ARCHIVEORG-002	Continue anonymously without hanging ...	
functional	critical	android
LAVA-ARCHIVEORG-003	Search Internet Archive for a realist...	
functional	high	android
LAVA-ARCHIVEORG-004	Open an item and obtain a working HTT...	
functional	critical	android
LAVA-GUTENBERG-001	Onboard and select the Project Gutenb...	
functional	critical	android
LAVA-GUTENBERG-002	Continue anonymously without hanging ...	
functional	critical	android
LAVA-GUTENBERG-003	Search Project Gutenberg for a realis...	
functional	high	android
LAVA-GUTENBERG-004	Open an item and obtain a working dow...	
functional	critical	android
LAVA-KINOZAL-001	Onboard and select the Kinozal provider	
functional	critical	android
LAVA-KINOZAL-002	Authenticate to Kinozal with form-log...	
functional	critical	android
LAVA-KINOZAL-003	Search Kinozal for a realistic query ...	
functional	high	android
LAVA-KINOZAL-004	Open a result and obtain a working do...	
functional	critical	android
LAVA-NAV-001	Cold-start survival (no crash on firs...	functional
critical	android	

```

LAVA-NAV-002 Welcome brand mark renders in colour,... ux
high      android
LAVA-NAV-003 Full onboarding happy path reaches th... functional
critical  android
LAVA-NAV-004 Back-press on the first onboarding sc... functional
critical  android
LAVA-NAV-005 Configure multiple providers during o... functional
high      android
LAVA-NAV-006 Open Trackers from Settings without a... functional
high      android
LAVA-NAV-007 Theme switch and rotation preserve state ux
medium    android
LAVA-NAV-008 Primary in-app navigation reaches sea... functional
high      android
LAVA-NNMCLUB-001 Onboard and select the NNM-Club provider
functional critical  android
LAVA-NNMCLUB-002 Authenticate to NNM-Club with form-lo...
functional critical  android
LAVA-NNMCLUB-003 Search NNM-Club for a realistic query...
functional high      android
LAVA-NNMCLUB-004 Open a result and obtain a working do...
functional critical  android
LAVA-RUTOR-001 Onboard and select the RuTor provider
functional critical  android
LAVA-RUTOR-002 Authenticate to RuTor with form-login...
functional critical  android
LAVA-RUTOR-003 Search RuTor for a realistic query an...
functional high      android
LAVA-RUTOR-004 Open a result and obtain a working do...
functional critical  android
LAVA-RUTRACKER-001 Onboard and select the RuTracker prov...
functional critical  android
LAVA-RUTRACKER-002 Authenticate to RuTracker with captch...
functional critical  android
LAVA-RUTRACKER-003 Search RuTracker for a realistic quer...
functional high      android
LAVA-RUTRACKER-004 Open a result and obtain a working do...
functional critical  android

```

The --platform android variant (list --banks ... --platform android) emits the same 32 cases (all Lava cases declare platforms: [android]), in load order rather than sorted. Both invocations exit 0.

The 7 banks map to the table below:

Bank	Provider	auth_type	Download deliverable verified
lava-rutracker-journey.yaml	rutracker	CAPTCHA_LOGIN	torrent file / magnet

Bank	Provider	auth_type	Download deliverable verified
lava-rutor-journey.yaml	rutor	FORM_LOGIN	torrent file / magnet
lava-kinozal-journey.yaml	kinozal	FORM_LOGIN	torrent file / magnet
lava-nnmclub-journey.yaml	nnmclub	FORM_LOGIN	torrent file / magnet
lava-archiveorg-journey.yaml	archiveorg	NONE	HTTP file link (no torrent/magnet)
lava-gutenberg-journey.yaml	gutenberg	NONE	torrent file or HTTP file
lava-onboarding-navigation.yaml	(cross-cutting)	—	cold-start / gating / nav

Auth types and download capabilities are taken from the real descriptors under `core/tracker/<provider>/.../<Provider>Descriptor.kt`.

To reproduce the listing through the real binary:

```
cd /Volumes/T7/Projects/Lava/submodules/helixqa
go build -o /tmp/helixqa ./cmd/helixqa
/tmp/helixqa list --banks /Volumes/T7/Projects/Lava/lava-api-go/
qa/banks --platform android
```

5. What is still MISSING (concrete task list)

These are the concrete gaps between "banks exist + bridge exists" and "a fully autonomous provider-multiplexed run executes against the Genymotion VM". None of them are solved by this document; each is an actionable task.

- 1. RESOLVED — HelixQA binary now builds and lists the banks.** The earlier blocker (unresolved go.mod conflict markers + uninitialized own-org deps) is closed: 5 own-org dependency submodules were added, and `cd submodules/helixqa && go build -o /tmp/helixqa ./cmd/helixqa` now exits 0 and produces `helixqa v0.2.0`. `helixqa list` against `lava-api-go/qa/banks` loads all 7 banks / 32 cases (verbatim output in §4.1). No bank-YAML fix was needed — the banks already match the real `pkg/testbank` loader schema. `helixqa autonomous` is NOT

exercised here (it needs a booted device/emulator, which is not available this run — see §3.2/§5.4/§5.5 for the remaining wiring).

2. **Navigator adapter for Lava-specific screens (Q6).** The autonomous pkg/navigator Android ActionExecutor drives generic adb taps/swipes and relies on Vision to locate controls. Lava's Compose screens expose specific semantics (onboarding step controls, provider rows, the captcha field, the torrent vs magnet download affordances). **Task:** define a Lava navigator adapter / semantics map (resource-ids or Compose testTags for: provider list rows, login username/password/captcha fields, search input, result row, topic download + magnet controls) so the navigator can act deterministically instead of vision-guessing, with vision as the fallback. This is the open "Q6 navigator adapter" item.
3. **Session config for the bridge + device is not templated.** There is no committed .env.example enumerating HELIX_ANDROID_DEVICE, HELIX_ANDROID_PACKAGE, and the per-tracker credential VAR NAMES for a Lava autonomous run. **Task:** add a lava-api-go/qa/.env.example (placeholders only, no secrets — §6.R/§6.H) documenting every variable §3.3 lists, plus a --model pin decision for the bridge (the discovery block currently hardcodes model ""); pinning a Claude model requires either a small upstream change to the discovery list or an env-driven override — itself a HelixQA-side task).
4. **Per-provider multiplexing / orchestration is not wired.** A single helixqa autonomous invocation points at one app + one feature map; it does not iterate the six provider banks as distinct credentialed journeys, nor reset app state (pm clear) between providers. **Task:** add a Lava-side thin runner (e.g. lava-api-go/qa/run-provider-matrix.sh) that, per provider: adb connect 127.0.0.1:6555 → pm clear digital.vasic.lava.client.dev → export that provider's credential vars → invoke the session (or helixqa run) scoped to that provider's bank → collect qa-results/<provider>/. This is the multiplexing layer that turns seven banks into one matrix run.
5. **adb-over-TCP reachability gate.** The session assumes 127.0.0.1:6555 is in adb devices as device. **Task:** add a pre-flight step to the runner (#4) that runs adb connect + asserts the serial is online and the package is installed, failing loud (not silently testing nothing) per the anti-bluff posture.
6. **Download-payload verification is described, not yet asserted programmatically.** The banks specify "non-empty bencoded torrent" / "magnet:?xt=urn:btih:" / "HTTP 200 non-empty payload" as the expected. **Task:** ensure the navigator (or a post-step hook) actually captures the produced torrent

bytes / magnet URI / HTTP file and validates the shape — so a green step proves a real working download, not merely that a button was tappable (§6.G / §11.4.69 sink-side evidence).

6. Constraints honoured

- **§6.R / §6.H / §11.4.10** — no credentials in any tracked file. The banks and this doc reference credential VARIABLE NAMES only; real values live in the gitignored .env loaded at runtime.
- **submodules/helixqa unmodified** — all configuration is external (env, flags, Lava-owned banks). The build blocker in §5.1 is reported honestly, not worked around by editing the submodule.
- **CONST-046** — banks describe structure + intent prose; they do not hardcode the exact user-facing literal strings the app must display as assertion-equality values.

Sources verified

Real-binary evidence captured 2026-06-08 with helixqa v0.2.0 (go build -o /tmp/helixqa ./cmd/helixqa, exit 0):

- **helixqa list --banks lava-api-go/qa/banks [--platform android]** — exit 0, 32 cases across the 7 Lava banks (verbatim in §4.1). Supersedes the prior PyYAML-only validation.
- **submodules/helixqa/pkg/llm/bridge_provider.go** — bridge invocation (buildArgs :250, --model omit :254, --image :257), vision gating (SupportsVision :133), JSON/plain-text parse (parseResponse :286, fallback :327), defaultBridgeTimeout = 120s :20.
- **submodules/helixqa/cmd/helixqa/main.go** — bridge discovery inside cmdAutonomous (:404): block :527–:569, {"claude", "claude", ""} :538, osexec.LookPath(cli.bin) :542, NewBridgedCLIProvider(...) :546, chat-pool append :553, vision-pool append :558, no-provider exit guard :571–:578. Autonomous flags + HELIX_ANDROID_* env-var reads as noted in §3.1.
- **command -v claude** → /Users/milosvasic/.local/bin/claude (claude IS on \$PATH, so the bridge would self-discover in an autonomous session).
- **submodules/helixqa/README.md** — bank schema, autonomous 4-phase model, list/autonomous CLI.
- **core/tracker/<provider>/.../{<Provider>Descriptor}.kt** — per-provider id, displayName, authType, capabilities.