

# Comprehensive Non-Fatal Telemetry — §6.AC Surface Reference

*Last updated: 2026-06-23 | Applies to: Android client (:app, :core:analytics-firebase) and lava-api-go service.*

---

## 1. Architecture Overview

Lava implements §6.AC (Comprehensive Non-Fatal Telemetry Mandate) across two distinct artifact stacks. Each stack has its own implementation of the same conceptual contract: **every catch / error / fallback / unexpected-state path in production code MUST surface a telemetry event with enough context to triage the failure remotely.**

| Android Client                      | lava-api-go (Go service) |
|-------------------------------------|--------------------------|
| <hr/>                               |                          |
| AnalyticsTracker (interface)        |                          |
| observability.RecordNonFatal()      |                          |
| core/common/.../AnalyticsTracker.kt | lava-api-go/internal/    |
| observability/                      |                          |
| :33 recordNonFatal(throwable,ctx)   | nonfatal.go :118         |
| :49 recordWarning(message,ctx)      | RecordWarning() :146     |
| FirebaseAnalyticsTracker (impl)     | OTLP structured log →    |
| Loki / Grafana                      |                          |
| core/analytics-firebase/.../        | (primary telemetry       |
| surface)                            |                          |
| FirebaseAnalyticsTracker.kt         |                          |
| → Firebase Crashlytics non-fatal    | Optional webhook bridge  |
| channel (mobile SDK only)           |                          |
| (LAVA_API_NONFATAL_WEBHOOK_URL)     |                          |
|                                     | → operator-configured    |
| HTTP collector                      |                          |
| NoOpAnalyticsTracker (fallback)     |                          |
| (used when Firebase clients null)   |                          |

## 1.1 Android contract — AnalyticsTracker

File: core/common/src/main/kotlin/lava/common/analytics/  
AnalyticsTracker.kt

The project-wide interface declares two telemetry methods (lines 33, 49):

```
fun recordNonFatal(throwable: Throwable, context: Map<String,  
    String> = emptyMap())  
fun recordWarning(message: String, context: Map<String, String> =  
    emptyMap())
```

recordNonFatal handles **throwable** exceptions caught by production code. recordWarning handles **non-throwable** unexpected situations — degraded paths, cache misses, mDNS-returned-zero, capability-declared-but-feature-null.

The Params object (lines 66–88) defines all canonical attribute keys in three tiers:

| Tier                     | Keys                                                              | Source          |
|--------------------------|-------------------------------------------------------------------|-----------------|
| §6.AC<br>mandatory       | feature, module, operation,<br>error_class, error_message, screen | Lines 67–<br>73 |
| Domain-specific          | provider, query, category_id,<br>topic_id, error, endpoint_kind   | Lines 76–<br>81 |
| HTTP-layer<br>diagnostic | http_status, request_url,<br>http_method, base_url_host           | Lines 83–<br>88 |

The HTTP-layer tier was added to enable structured triage of ApiHttpException-bearing failures without requiring Crashlytics dashboard access to the raw exception message.

## 1.2 Android implementation — FirebaseAnalyticsTracker

File: core/analytics-firebase/src/main/kotlin/lava/analytics/  
firebase/FirebaseAnalyticsTracker.kt

Key implementation details:

- **Constructor** (line ~20): FirebaseAnalyticsTracker(analytics: FirebaseAnalytics?, crashlytics: FirebaseCrashlytics?) — both clients are nullable. If both are null, the Hilt module installs NoOpAnalyticsTracker instead, so Firebase initialisation failure cannot crash production code.
- **recordNonFatal** (lines 51–66):
  1. Calls isCancellationOrWraps() (lines 76–85) — filters CancellationException and any exception whose cause chain (up to depth 32) contains one. Forensic anchor: Crashlytics issue 7df61fdb64f9928b067624d6db395ca was 8

- JobCancellationException events from viewModelScope teardown; those are structured-concurrency noise, not real failures.
- 2. Sets each context entry as a Crashlytics custom key: `c.setCustomKey(key, value.take(MAX_VALUE_CHARS))` (line 63).
- 3. Calls `c.recordException(throwable)` (line 64) to surface in the non-fatal feed.
- **recordWarning** (lines 96–105):
  1. Logs a breadcrumb: `c.log("WARN: $ {message.take(MAX_VALUE_CHARS)} ctx=$context")` (line 101).
  2. Sets custom keys (line 102).
  3. Records `LavaNonFatalWarning(message)` (line 103) — a synthetic exception (line 129: internal class `LavaNonFatalWarning(message: String) : RuntimeException(message)`) so non-throwable warnings surface in the **same** non-fatal feed as real exceptions.
- **MAX\_VALUE\_CHARS = 1024** (line 119): applied to every custom key value and to warning messages. Mirrors the Go side's `maxValueChars = 1024` (`nonfatal.go:91`).

### 1.3 Go implementation — observability.RecordNonFatal

File: `lava-api-go/internal/observability/nonfatal.go`

`RecordNonFatal(ctx, err, attrs)` :118  
`RecordWarning(ctx, message, attrs)` :146

Two effects per call:

1. **Always:** structured `slog.WarnContext` log (lines 133–138 for non-fatal, 148–153 for warning) via the OTLP pipeline → Loki/Grafana. The error, error\_class, and every attrs key appear as queryable log fields.
2. **Optionally:** `webhookForward()` (line 139/153) to an operator-configured HTTP endpoint when `LAVA_API_FIREBASE_CRASHLYTICS_ENABLED=true` AND `LAVA_API_NONFATAL_WEBHOOK_URL` is set.

Cancellation filtering (lines 125–130): `context.Canceled` and `context.DeadlineExceeded` are silently skipped at DEBUG level — the Go-side symmetric of the Android `CancellationException` filter.

`classOf(err)` (line 238): walks the `Unwrap()` chain (max depth 32) to extract the deepest concrete type name via `%T` formatting. This was fixed in LVA-021: the prior fallback returned "error" for all `fmt.Errorf`-wrapped stdlib errors (`*net.OpError`, `*url.Error`, etc.), collapsing every backend HTTP failure into one Loki bucket.

---

## 2. Search-Failure Diagnosis Path (Priority Walkthrough)

This is the highest-value telemetry path: a user searches, a provider fails with HTTP 401 or connection-refused, and the operator needs to identify the failing provider + status code from a production Crashlytics or Loki record without a device attached.

### Step-by-step (Android client)

**Source:** feature/search\_result/src/main/kotlin/lava/search/result/SearchResultViewModel.kt, recordProviderFailure() at line 175.

When sdk.streamMultiSearch() (line 121) emits a MultiSearchEvent.ProviderFailure:

```
handleMultiSearchEvent() :129
  → case ProviderFailure → recordProviderFailure(event) :140
    builds baseContext :176–182
      feature="search", operation="streamMultiSearch",
      screen="search_result", provider=event.providerId,
      error_message=event.reason
    if cause != null: :183
      cause.rethrowIfCancellation() :185 ← drops
CancellationException
  if cause is ApiHttpException: :191
    extracts host-only from requestUrl :192–198
    enriches context with HTTP keys: :199–204
      http_status=cause.statusCode
      request_url=cause.requestUrl ← query-stripped, no
credentials
      http_method=cause.httpMethod
      base_url_host=hostOnly
      analytics.recordNonFatal(cause, enrichedContext) :208
    else:
      analytics.recordNonFatal(cause, baseContext) :208
    else (no cause throwable):
      analytics.recordWarning(event.reason, baseContext) :210
```

The result in Crashlytics: a non-fatal record whose custom keys include provider=rutracker, http\_status=401, request\_url=https://api.vasic.digital/v1/rutracker/search, base\_url\_host=api.vasic.digital. This is the information the operator needs to determine whether the failure is an auth-key expiry, a LAN routing issue, or a tracker outage.

Prior to this implementation the `ProviderFailure` branch was -> Unit (the `// $6.AC` comment in `handleMultiSearchEvent` line 142 is the original silent no-op). The operator-reported "release-only search failure" on 2026-06-22 was undiagnosable precisely because no context was captured.

## The `ApiHttpException` shape

File: `core/tracker/client/src/main/kotlin/lava/tracker/client/ApiBackedTrackerClient.kt`, lines 48–54:

```
class ApiHttpException(  
    val statusCode: Int,  
    val requestUrl: String,    // query-stripped by  
                             stripQueryForTelemetry(:328)  
    val httpMethod: String,  
    val responseSnippet: String?, // redacted+truncated to 200  
                                chars (:346)  
    message: String,  
) : IOException(message)
```

Thrown at lines 268–281 (`getString`), 283–296 (`getBytes`), 298–317 (`postJson`) whenever the upstream proxy returns a non-2xx status. Every throw already has query-stripped URL and credential-redacted response snippet — so the exception is safe to pass directly to `recordNonFatal`.

## Parallel path on the Go side

File: `lava-api-go/internal/handlers/v1/handlers.go`, `writeProviderError()` at line 172.

All v1 handlers call `writeProviderError(c, err)` for provider-layer failures. The function's default branch (line 182) records unexpected errors:

```
observability.RecordNonFatal(c.Request.Context(), err,  
    observability.NonFatalAttributes{  
        observability.AttrFeature:    "provider",  
        observability.AttrOperation: c.FullPath(),  
        observability.AttrEndpoint:  c.FullPath(),  
        observability.AttrTrackerID: currentProviderID(c),  
        observability.AttrRequestID: requestID(c),  
    })
```

Sentinel errors (`ErrNotFound`, `ErrForbidden`, `ErrUnauthorized`, `ErrCircuitOpen`) are intentionally NOT recorded as non-fatals — they represent expected provider responses and would flood the feed. Only the default branch (unexpected provider implementation bugs, network failures, parsing errors) fires telemetry.

---

# 3. Mandatory Attributes and §6.H Redaction Rules

## 3.1 Mandatory attribute table

Both platforms share the same attribute vocabulary. The Go constants live in `nonfatal.go:69–87`; the Kotlin constants in `AnalyticsTracker.Params` at lines 66–88.

| Attribute key | Kotlin constant                   | Go constant                   | Mandatory when                         | Example                         |
|---------------|-----------------------------------|-------------------------------|----------------------------------------|---------------------------------|
| feature       | <code>Params.FEATURE</code>       | <code>AttrFeature</code>      | Always                                 | "search"<br>"auth"              |
| module        | <code>Params.MODULE</code>        | —                             | Android only                           | "Search"                        |
| operation     | <code>Params.OPERATION</code>     | <code>AttrOperation</code>    | Always                                 | "stream"<br>"login"             |
| error_class   | <code>Params.ERROR_CLASS</code>   | <code>AttrErrorClass</code>   | When known                             | "ApiHttpException"<br>"*net..." |
| error_message | <code>Params.ERROR_MESSAGE</code> | <code>AttrErrorMessage</code> | Always (truncated)                     | "HTTP 401"                      |
| screen        | <code>Params.SCREEN</code>        | —                             | Android only                           | "search"                        |
| endpoint      | —                                 | <code>AttrEndpoint</code>     | Go only                                | "/v1/r..."                      |
| request_id    | —                                 | <code>AttrRequestID</code>    | Go only                                | "req-a..."                      |
| tracker_id    | —                                 | <code>AttrTrackerID</code>    | Go only                                | "rutra..."                      |
| provider      | <code>Params.PROVIDER</code>      | —                             | Android, multi-search                  | "rutra..."                      |
| http_status   | <code>Params.HTTP_STATUS</code>   | —                             | Android, <code>ApiHttpException</code> | "401"                           |
| request_url   | <code>Params.REQUEST_URL</code>   | —                             | Android, <code>ApiHttpException</code> | "https..."                      |
| http_method   | <code>Params.HTTP_METHOD</code>   | —                             | Android, <code>ApiHttpException</code> | "GET"                           |
| base_url_host | <code>Params.BASE_URL_HOST</code> | —                             | Android, <code>ApiHttpException</code> | "api.v..."                      |

## 3.2 §6.H redaction rules — what is NEVER logged

The following values are **categorically forbidden** from appearing in any telemetry attribute, log line, or webhook payload. Violations are a §6.H security incident.

| Forbidden value class                          | Examples                                         | Where the risk arises                                   |
|------------------------------------------------|--------------------------------------------------|---------------------------------------------------------|
| Tracker login credentials                      | RuTracker username/password, Kinozal API key     | LoginRequestDto in ApiBackedTrackerClient               |
| Session cookies / tokens                       | Tracker session cookie value, sessionToken field | withAuth() extension, Auth-Token header <b>value</b>    |
| The Lava-Auth / Auth-Token header <b>value</b> | The tracker-specific base64 cookie string        | Attached by withAuth() at ApiBackedTrackerClient.kt:124 |
| Signed URLs / query-string tokens              | Any ? token=, ? key=, ?auth=query parameter      | Stripped by stripQueryForTelemetry() at line 328        |
| Firebase token (LAVA_FIREBASE_TOKEN)           | The CI token for App Distribution                | Never enters production code paths                      |
| Database connection string                     | Postgres DSN with password embedded              | Go only — never passes through handler layer            |

### Automatic redaction mechanisms:

- **Android** — redactAndTruncate() in ApiBackedTrackerClient.kt:346 applies a regex over the response snippet before it reaches ApiHttpException.responseSnippet. Pattern: (?i)(token|key|cookie|auth|bearer|password|secret)([=:\s]+\S+ → \$1\$2[REDACTED].
- **Android** — request\_url carried by ApiHttpException is the output of stripQueryForTelemetry() (line 328–334), which strips ?... and everything after it.
- **Go** — redactIfSensitive(key, value) in nonfatal.go:294 replaces the value with "<redacted>" for any attribute whose key substring-matches: password, token, secret, api\_key, apikey, cookie, authorization, hmac, pepper.

- **Go** — The same redaction is applied to the webhook attrs copy at `nonfatal.go:196–200` before JSON encoding, so credentials cannot leak to the webhook collector either.

The Auth-Token header **name** ("Auth-Token") is a §6.R-exempt wire-protocol constant at `ApiBackedTrackerClient.kt:356`. Its **value** (the session cookie) must never reach telemetry — only the header name is safe to reference in documentation.

---

## 4. Coverage Checker — `scripts/check-non-fatal-coverage.sh`

The §6.AC coverage checker is a bash script that scans Kotlin source under `core/` and `feature/` for catch blocks and flags those lacking a `recordNonFatal` / `recordWarning` call or an explicit `// no-telemetry: <reason>` opt-out comment.

### Running the checker

```
# Advisory mode (default) – prints violations, exits 0
./scripts/check-non-fatal-coverage.sh

# Strict mode – exits 1 on any violation (used by scripts/ci.sh --full)
./scripts/check-non-fatal-coverage.sh --strict
```

### What it scans

The checker looks for one of three coverage markers inside each catch block:

| Marker                                 | Meaning                                                                                       |
|----------------------------------------|-----------------------------------------------------------------------------------------------|
| <code>analytics.recordNonFatal(</code> | Real exception surfaced to telemetry                                                          |
| <code>analytics.recordWarning(</code>  | Non-throwable warning surfaced to telemetry                                                   |
| <code>// no-telemetry:</code>          | Explicit opt-out with a required reason                                                       |
| <code>rethrowIfCancellation()</code>   | Followed by a <code>recordNonFatal</code> — <code>CancellationException</code> filtered first |

### Legitimate `// no-telemetry: opt-outs`

A `// no-telemetry: opt-out` is valid when the fallback is genuinely benign and recording it would create noise rather than signal. Two canonical examples already in the codebase:



```
// SearchResultViewModel.kt:141-143
// no-telemetry: a provider lacking TrackerCapability.SEARCH is a
// benign terminal state (skipped, not failed) per the
// MultiSearchEvent KDoc – not an error worth a non-fatal.
is MultiSearchEvent.ProviderUnsupported -> Unit

// General pattern for CancellationException paths
cause.rethrowIfCancellation() // rethrows if cancellation;
    continues if not
analytics.recordNonFatal(cause,
    context) // only reached for real errors
```

## §6.AC-debt — mechanical enforcement status

The checker currently runs in **advisory mode** by default. `scripts/ci.sh --changed-only` does NOT yet hard-fail on coverage gaps. `scripts/ci.sh --full` runs `--strict`. The Go-side equivalent (`check-non-fatal-coverage.sh` for Go) is owed and tracked under §6.AC-debt. Reviewers manually verify every commit that adds a `try/catch` or `runCatching` block.

---

## 5. Operator Runbook

### 5.1 Android non-fatal dashboard — Firebase Crashlytics

**Where:** Firebase Console → Lava project → Crashlytics → Non-fatals tab.

Each non-fatal event surfaces with:

- The exception type (or `LavaNonFatalWarning` for warnings).
- The exception message.
- Crashlytics custom keys — these are the §6.AC attributes. Click any event → "Keys" tab.

#### Useful Crashlytics filter combinations:

| Goal                                | Filter                                                        |
|-------------------------------------|---------------------------------------------------------------|
| All search failures                 | Non-fatals where <code>feature=search</code>                  |
| 401 failures only                   | Non-fatals where <code>http_status=401</code>                 |
| Failures on a specific provider     | Non-fatals where <code>provider=rutacker</code>               |
| Failures hitting a specific backend | Non-fatals where <code>base_url_host=api.vasic.digital</code> |

**Closing a Crashlytics issue:** per §6.O, mark "Resolved" in the Console ONLY after the fix commit lands AND `.lava-ci-evidence/crashlytics-resolved/<date>-<slug>.md` exists with: issue ID, stack-trace summary, root-cause analysis, fix commit SHA, and links to the regression test. Do not close-mark before the test coverage exists.

## 5.2 Go service dashboard — Loki / Grafana

**Honest note:** Firebase Crashlytics has **no public server-side non-fatal ingest API** — it is a mobile-SDK-only product. There is no POST endpoint that accepts non-fatal events from a Go server. The `nonfatal.go` package comment (lines 22–33) states this explicitly. The backend's primary telemetry surface is **Loki/Grafana** via the OTLP structured-log pipeline.

### LogQL queries for common triage scenarios:

```
# All non-fatal events from the Go service
{service="lava-api-go"} |= "non-fatal event"

# Provider failures (unexpected errors in v1 handlers)
{service="lava-api-go"} |= "non-fatal event" | json |
feature="provider"

# Failures for a specific tracker
{service="lava-api-go"} |= "non-fatal event" | json |
tracker_id="rutracker"

# Warning events (fallbacks, capability mismatches)
{service="lava-api-go"} |= "warning event"

# Cross-reference with a trace: find the request_id in Tempo
{service="lava-api-go"} |= "non-fatal event" | json |
request_id="<id>"
```

## 5.3 Webhook bridge — optional forward to external collectors

When `LAVA_API_FIREBASE_CRASHLYTICS_ENABLED=true` AND `LAVA_API_NONFATAL_WEBHOOK_URL` is set (both from `.env`, per §6.R — never hardcoded), the Go service posts a best-effort JSON payload for each non-fatal/warning event (`nonfatal.go`:184–233).

**JSON shape** (`webhookBody` struct at line 164):

```
{
  "event": "non_fatal",
  "error_class": "*url.Error",
  "error_message": "HTTP 502 for /v1/rutracker/search...",
  "attrs": {
```

```

    "feature": "provider",
    "operation": "/v1/provider/search",
    "tracker_id": "rutracker",
    "request_id": "req-abc-123"
  },
  "ts": "2026-06-23T14:05:00Z"
}

```

The webhook call:

- Runs in its own goroutine (fire-and-forget), **never blocks the user request path**.
- Has a 2-second timeout independent of the caller's context.
- Swallows all errors and recovers from panics (`nonfatal.go:219`).
- The `attrs` copy is credential-redacted before JSON encoding (`nonfatal.go:196–200`).

**When the flag is set but the URL is empty**, a one-time `WARN` log is emitted (`nonfatal.go:191`) and forwarding is silently disabled — the `sync.Once` at line 160 ensures this appears only once per process.

**What the webhook enables:** routing non-fatals to a Grafana Loki push endpoint, a custom Cloud Function, a Slack webhook, or — if the operator wires a Cloud Function — into Firebase Crashlytics from the server side. The bridge itself is transport-agnostic; the operator chooses the collector.

## 5.4 Checking for §6.H credential leaks in telemetry

If a non-fatal event's Crashlytics record or Loki log line contains what appears to be a credential, session token, or signed URL, file a §6.H incident immediately:

1. Record the event details in `.lava-ci-evidence/sixth-law-incidents/<date>-<slug>.json`.
  2. Identify the call site where the attribute was constructed (the Crashlytics "Keys" tab shows exact key names; match to `AnalyticsTracker.Params.*` constants).
  3. Verify `stripQueryForTelemetry()` and `redactAndTruncate()` are both applied before the value reaches `ApiHttpException`. If a new HTTP call site bypasses these helpers, that is the fix location.
  4. On the Go side: verify `redactIfSensitive()` is applied. If a new attribute key name was introduced that doesn't contain one of the patterns in `sensitiveAttrPatterns` (line 98–108) but carries a sensitive value, add the pattern.
  5. Rotate the exposed credential per §6.H clause 6.
-

## File:Line Reference Index

| Description                                                | File                                                        | Lines              |
|------------------------------------------------------------|-------------------------------------------------------------|--------------------|
| AnalyticsTracker interface — recordNonFatal                | core/common/.../<br>AnalyticsTracker.kt                     | 33                 |
| AnalyticsTracker interface — recordWarning                 | core/common/.../<br>AnalyticsTracker.kt                     | 49                 |
| Params mandatory attribute constants                       | core/common/.../<br>AnalyticsTracker.kt                     | 66–<br>73          |
| Params HTTP-layer diagnostic constants                     | core/common/.../<br>AnalyticsTracker.kt                     | 83–<br>88          |
| FirebaseAnalyticsTracker.recordNonFatal                    | core/analytics-firebase/.../<br>FirebaseAnalyticsTracker.kt | 51–<br>66          |
| isCancellationOrWraps()<br>(CancellationException filter)  | core/analytics-firebase/.../<br>FirebaseAnalyticsTracker.kt | 76–<br>85          |
| recordWarning → LavaNonFatalWarning<br>synthetic exception | core/analytics-firebase/.../<br>FirebaseAnalyticsTracker.kt | 96–<br>105,<br>129 |
| MAX_VALUE_CHARS = 1024                                     | core/analytics-firebase/.../<br>FirebaseAnalyticsTracker.kt | 119                |
| ApiHttpException class definition                          | core/tracker/client/.../<br>ApiBackedTrackerClient.kt       | 48–<br>54          |
| stripQueryForTelemetry()                                   | core/tracker/client/.../<br>ApiBackedTrackerClient.kt       | 328–<br>334        |
| redactAndTruncate()                                        | core/tracker/client/.../<br>ApiBackedTrackerClient.kt       | 346–<br>350        |
| AUTH_TOKEN_HEADER constant (name only,<br>§6.R exempt)     | core/tracker/client/.../<br>ApiBackedTrackerClient.kt       | 356                |
| recordProviderFailure() — search-401<br>diagnosis path     | feature/search_result/.../<br>SearchResultViewModel.kt      | 175–<br>212        |
| // no-telemetry: opt-out example<br>(ProviderUnsupported)  | feature/search_result/.../<br>SearchResultViewModel.kt      | 141–<br>144        |
| Go RecordNonFatal()                                        | lava-api-go/internal/<br>observability/nonfatal.go          | 118–<br>140        |
| Go RecordWarning()                                         | lava-api-go/internal/<br>observability/nonfatal.go          | 146–<br>154        |
| Go sensitiveAttrPatterns (§6.H<br>redaction list)          | lava-api-go/internal/<br>observability/nonfatal.go          | 98–<br>108         |
| Go webhookForward() — optional bridge                      | lava-api-go/internal/<br>observability/nonfatal.go          | 184–<br>233        |
| Go classOf(err) — error type name<br>extraction            | lava-api-go/internal/<br>observability/nonfatal.go          | 238–<br>282        |

| Description                                           | File                                         | Lines   |
|-------------------------------------------------------|----------------------------------------------|---------|
| writeProviderError() — v1 handler non-fatal recording | lava-api-go/internal/handlers/v1/handlers.go | 172-193 |