

Firebase scripts — quick reference

Script	Purpose	Typical use
scripts/firebase-env.sh	Sourced by other scripts to load Firebase keys from .env.	source scripts/firebase-env.sh
scripts/firebase-setup.sh	One-time Firebase project bootstrap; refreshes app/google-services.json + lava-api-go/firebase-web-config.json; invites testers.	First clone after firebase login:ci
scripts/firebase-distribute.sh	Uploads built APKs to Firebase App Distribution + invites testers from .env.	After ./build_and_release.sh
scripts/firebase-stats.sh	Prints dashboard URLs + machine-readable summary of Firebase services.	Operator inspection
scripts/distribute.sh	Umbrella: rebuilds artifacts + distributes via Firebase + prints stats.	One-command operator distribute

Examples

First-time setup on a fresh clone

```
# 1. Authenticate Firebase CLI
firebase login:ci          # copy the token into .env as
                           LAVA_FIREBASE_TOKEN

# 2. Copy template + fill in real values
cp .env.example .env
$EDITOR .env
```

```
# 3. Refresh Firebase config files + invite testers
./scripts/firebase-setup.sh
```

Distribute a new build to testers

```
# Rebuild + upload + invite – one command
./scripts/distribute.sh

# Skip rebuild (use the artifacts already in releases/<version>/)
./scripts/distribute.sh --no-rebuild

# Distribute only the release-signed APK
./scripts/distribute.sh --release-only

# Provide custom release notes
./scripts/firebase-distribute.sh --release-notes "Hotfix:
    API_VERSION drift caught + fixed"
```

Inspect Firebase health / stats

```
./scripts/firebase-stats.sh                # human-readable,
    last 7 days
./scripts/firebase-stats.sh --days 30     # last 30 days
./scripts/firebase-stats.sh --json        # machine-readable
```

Refresh config files without re-inviting testers

```
./scripts/firebase-setup.sh --refresh
```

Re-invite testers without touching config files

```
./scripts/firebase-setup.sh --invite-only
```

Constitutional bindings (per CLAUDE.md)

- **§6.H Credential Security** — LAVA_FIREBASE_TOKEN and firebase-admin-key.json are gitignored; pre-push hooks reject pushes that introduce them.
- **§6.J Anti-Bluff** — every script uses set -euo pipefail; there is no WARN-swallow pattern; failures propagate.
- **§6.K Builds-Inside-Containers** — build_and_release.sh invocations from distribute.sh route through the container path for release builds.

See docs/FIREBASE.md for the full integration architecture.