

scripts/check-cycle-coverage.sh

— User Guide

Last verified: 2026-07-01 (re-verified against the committed §6.AK implementation at HEAD — flags/exit-codes/file-formats below match scripts/check-cycle-coverage.sh; prior: 2026-06-26 gate landing) **Inheritance:** HelixConstitution §11.4.18 (script documentation mandate) · enforces Lava CLAUDE.md §6.AK clause 1 (Cycle-Coverage Device Gate)

Overview

check-cycle-coverage.sh is the mechanical implementation of the CM-CYCLE-COVERAGE-INTERSECTION gate (§6.AK / §6.AK-debt). It refuses to distribute unless **every CHANGELOG-claimed user-visible fix for the current version has an EXECUTED + PASSED covering device Challenge** in the matching §6.Z evidence file for the **same commit SHA**, recorded within the last 24 hours.

It exists to catch the class of bluff that shipped Lava-Android-1.3.12-1076 (commit 627a0d58): the §6.Z device gate executed ONLY Challenge00 (cold-start) while the CHANGELOG claimed fixes to search, provider-selection, and onboarding — a green gate that proved nothing about the shipped value.

The gate intersects two sets and requires $\text{claim-set} \subseteq \text{executed-pass set}$:

- **CLAIM-SET** — the covering Challenge declared for each CHANGELOG-claimed user-visible fix, read from a per-cycle cycle-coverage-map YAML.
- **EXECUTED-PASS SET** — Challenges that ran and PASSED on a gate-eligible device in the §6.Z evidence file (verdict PASS and runner != host-direct).

Any claim with no covering executed+passed Challenge → reject. It parses YAML and evidence line-by-line with grep/sed/bash (no yq dependency).

Usage

```
# Auto-detect everything (version from app/build.gradle.kts,
# evidence dir from channel,
# map next to the evidence file, HEAD from git, "now" from the
# system clock):
./scripts/check-cycle-coverage.sh --strict

# Explicit version + evidence dir (the form firebase-distribute.sh
# Gate 7 uses):
./scripts/check-cycle-coverage.sh --version="1.3.13-1077" \
  --evidence-dir=".lava-ci-evidence/distribute-changelog/firebase-
  app-distribution" --strict

# Fully pinned inputs (the form the hermetic tests use – no git,
# no clock, no gradle):
./scripts/check-cycle-coverage.sh --version="9.9.9-9999" \
  --evidence-dir "<dir>" --map="<map.yaml>" \
  --head="<sha40>" --now-epoch="<epoch>"
```

Flags

Flag	Default	Meaning
--version <name-code>	auto-detect from app/build.gradle.kts (versionName- versionCode)	Version under test, e.g. 1.3.12-1077.
--evidence-dir <path>	resolved from channel (see below)	Directory holding <version>- test-evidence.{md,json}.
--map <path>	auto-resolve (see below)	Path to the cycle-coverage- map YAML.
--head <sha>	git rev-parse HEAD	Commit under test. The evidence MUST declare a matching SHA; an absent or unknown SHA is a REFUSAL (exit 2), not a free pass. Overridable for hermetic tests.
--now-epoch <epoch>	date +%s	"Now" (Unix epoch) for the ≤24h freshness check. Overridable for determinism.
--strict	on by default (STRICT=1)	Reject on any uncovered claim. The flag is accepted but the behavior is the default.
-h, --help	—	Print usage to stderr and exit 0.

Environment overrides (read once at startup, lower precedence than the flags): LAVA_CYCLE_COVERAGE_HEAD (initial value for --head) and LAVA_CYCLE_COVERAGE_NOW_EPOCH (initial value for --now-epoch). An unknown argument prints usage and exits 3.

Path resolution

- **Evidence dir** (when --evidence-dir is omitted): channel release → .lava-ci-evidence/distribute-changelog/firebase-app-distribution; any other channel → .lava-ci-evidence/distribute-changelog/firebase-app-distribution-dev.
- **Evidence file**: the first of <EVIDENCE_DIR>/<version>-test-evidence.md then ...-test-evidence.json that exists (.md preferred). Missing → exit 2.
- **Map** (when --map is omitted): the first of <EVIDENCE_DIR>/<version>-cycle-coverage-map.yaml then .lava-ci-evidence/<version>/cycle-coverage-map.yaml. Missing → exit 2.

Exit codes

Code	Meaning
0	All claims covered by executed + PASSED, same-SHA, ≤24h device rows.
1	One or more claims lack a covering executed+PASSED Challenge (missing / FAIL / SKIP / host-direct), OR the evidence timestamp is older than 24h.
2	REFUSAL . Evidence file or map missing; map version: mismatch; the evidence declares no usable commit SHA (or only unknown); the declared SHA ≠ --head; the map declares zero claims; the evidence format yields no parseable verdict record at all ; or an unknown CLI argument (including the removed --channel).

There is no exit 3. Every "the gate cannot determine an answer" condition is an exit-2 REFUSAL, because a gate that cannot determine a verdict has not established a PASS.

Input file formats

1. cycle-coverage-map (<vname>-<code>-cycle-coverage-map.yaml)

A small YAML block. The gate reads it line-by-line and only consumes two keys:

```

version: "1.3.12-1077"
claims:
  - bullet: "Search now returns real results"
    covering_challenge: "Challenge58SearchReturnsResults"
  - bullet: "Search filters follow onboarded providers"
    covering_challenge: "Challenge59SearchUsesOnboardedProviders"

```

- Each covering_challenge: value is a **required claim**.
- The preceding bullet: (if any) is used only for human-readable FAIL messages.
- A claim whose covering_challenge is empty/absent is itself an uncovered claim (→ exit 1) — that is the "CHANGELOG claims a fix but no Challenge was written" case the 1076 incident is about.
- A map with **zero** claims is a vacuous pass and REFUSES (→ exit 2). A cycle with genuinely no user-visible change must say so explicitly as a claim with its re-verification Challenge, per §6.AK clause 6.
- Surrounding single/double quotes on values are stripped before matching.

(Other keys such as covers_issues: may appear per the spec but are NOT read by the gate; only covering_challenge: values are matched.)

2. §6.Z evidence file (<vname>-<code>-test-evidence.{md,json})

The gate PARSES VERDICTS. It does not match names. (LVA-149 — see the history note at the top of the script.) It scans the evidence for records that STATE a result, in any of six shapes, and refuses if it finds none:

#	Shape	Where it is used in practice
R1	challenge: fqN=<FQN> verdict=PASS runner=containers-submodule	autonomous-QA / structured evidence
R2	"<TestName>": "PASS" (also FAIL / SKIP / ERROR, with optional trailing prose)	JSON covering_challenges maps
R3	"test_class": "<FQN>" ... "test_passed": true	JSON per-AVD attestation rows
R4	<TestName> ... **PASS** ...	markdown device-gate tables (the production format)
R5	<TestName>: PASS	Go / colon-verdict blocks
R6	<TestName>: tests="7" failures="0" errors="0"	

#	Shape	Where it is used in practice
		JUnit summary lines (PASS iff tests>0, failures=0, errors=0)

A not run / – cell parses as SKIP, which is **not** a pass.

Coverage rule. A claim counts as covered only when a record whose name matches the map's covering name states PASS **and** the runner is not host-direct (host-direct is never gate-eligible per §6.AH/§6.AG).

Name matching is IDENTIFIER equality, not substring. Both sides are normalised to the last dot-segment with a single trailing Test stripped, so a map naming Challenge58SearchReturnsResults matches evidence naming lava.app.challenges.Challenge58SearchReturnsResultsTest. Substring matching is deliberately gone: it is how the pre-LVA-149 gate let a bare NAME anywhere in the file stand in for a verdict.

A name mentioned in prose is not a verdict. If the evidence names a Challenge but states no result for it, that claim is uncovered (exit 1), and the message says so explicitly.

An unrecognised format REFUSES (exit 2) and names the file. If the parser extracts zero verdict records, it prints the offending path and lists the six shapes above so the operator can fix their evidence rather than guess. It never falls back to assuming a pass.

3. Commit-SHA binding (F2)

The evidence must declare the commit it was produced against. Accepted fields, in both markdown and JSON:

```
cycle-coverage: ... commit=<sha>
"commit_sha": "<sha>"          "tested_code_sha": "<sha>"
"artifact_code_sha": "<sha>"
commit_sha: <sha>              **Commit SHA:** <sha>
**Tested code SHA:** <sha>
```

Values are matched against --head by prefix in either direction (short SHAs are fine). If **any** declared SHA matches, the binding holds. If SHAs are declared but none matches → exit 2. If **none** is declared, or the only value is the literal unknown → exit 2. "Unknown" is a refusal, not a free pass.

4. Freshness

A timestamp is read from cycle-coverage: ... timestamp=, "timestamp", "authored_utc", or markdown ****Evidence authored:**** <date>. If one is found and it is older than 24h relative to --now-epoch, the gate exits 1.

5. KNOWN CONSEQUENCE — pre-push Check 10 and the self-reference problem

Read this before the next distribute cycle. It is an open design question, not a defect in the parser.

scripts/firebase-distribute.sh Gate 7 runs with --head = the commit that carries the code and the evidence, so a correctly-authored evidence file binds cleanly. .github/hooks/pre-push Check 10 re-runs the same gate with --head set to the **pointer-advancing commit**, which by construction cannot contain its own SHA — so the evidence (committed earlier, naming the code commit) will not match, and the strict binding now REFUSES there.

Before LVA-149 this went unnoticed only because the binding was inert. Three resolutions exist, and the choice belongs to the operator:

1. Have Check 10 gate the code commit rather than the pointer-advance commit.
2. Accept a declared SHA that is an **ancestor** of --head when no production file differs between them (only .lava-ci-evidence/, docs/, CHANGELOG.md). This is code-identity, not leniency — any source change still refuses.
3. Leave it strict and author evidence at distribute time only.

Option 2 is NOT implemented here: it could not be proven with a hermetic positive case in this change, and shipping an untested acceptance path into a safety gate is the class of thing this gate exists to prevent.

How it is wired

- **scripts/firebase-distribute.sh — Phase 1 Gate 7 (§6.AK):** after the §6.P/§6.AA/§6.Z Phase-1 gates, the distribute script invokes this gate for the version+channel being distributed (--evidence-dir="\$CHANGELOG_DIR", --strict) and **refuses the distribute** on a non-zero exit (1 uncovered claim · 2 evidence/map missing/stale/wrong-SHA · 3 internal). It gates both the client and the api-app via the app-resolved changelog dir, with no bypass flag. See docs/scripts/firebase-distribute.sh.md for the Gate 7 detail.

- **.github/pre-push — Check 10 (per spec §5.4):** the spec defines a pre-push Check 10 that runs this gate (`--strict`) when a pushed commit advances a `.lava-ci-evidence/distribute-changelog/<channel>/last-version` pointer, so a version-advance (signalling "ready to distribute") cannot be pushed without the covering device evidence.

Constitutional binding (§6.AK clause 1)

No artifact may be distributed unless EVERY CHANGELOG-claimed user-visible fix for the current version has an EXECUTED + PASSED covering device Challenge in the matching §6.Z evidence file for the SAME commit SHA.

The CHANGELOG's user-visible bullets are the claim-set; the gate's executed-PASS Challenge set MUST be a superset of the claim-set's covering Challenges. A Challenge00-only (cold-start-only) evidence file NEVER satisfies this gate when the cycle claims flow/UI fixes — that is exactly the 1076 incident this gate exists to evict.

Maintenance

When this script is modified, update this document in the same commit (CM-SCRIPT-DOCS-SYNC / `.github/pre-push` Check 9 require it). Per §11.4.18 the documentation MUST stay in sync with the codebase. The gate's own hermetic test is `tests/cycle-coverage/test_cycle_coverage.sh` (spec §5.2 case matrix: positive + six negatives); keep its fixtures in lockstep with any change to the file formats or exit-code contract above.

Cross-references

- `scripts/check-cycle-coverage.sh` — the script itself
- `tests/cycle-coverage/test_cycle_coverage.sh` — hermetic falsifiability test
- `docs/superpowers/specs/2026-06-26-ak-cycle-coverage-spec.md` — the §6.AK spec (gate contract §5.1, test matrix §5.2, hook §5.4)
- `docs/scripts/firebase-distribute.sh.md` — Phase 1 Gate 7 wiring
- `docs/helix-constitution-gates.md` — gate inventory
- `Lava CLAUDE.md` §6.AK (Cycle-Coverage Device Gate) + §6.AK-debt
- `HelixConstitution Constitution.md` §11.4.18 (script documentation mandate)