

Tracker SDK — Provider Abstraction Architecture

Status: descriptive architecture reference. Every box, arrow, and symbol below corresponds to a real file in the working tree (cited inline). Anything not yet implemented is marked **NOT IMPLEMENTED**. Per HelixConstitution §11.4.6 (no-guessing vocabulary), nothing here is inferred — it is read from source.

Companion docs: [docs/ARCHITECTURE.md](#) (overview), [docs/sdk-developer-guide.md](#) (the 7-step recipe

- the magnet-cache + download-validator patterns), [docs/architecture/local-stack-topology.md](#) (server-side deployment).

1. The abstraction in one diagram

The Tracker SDK is a capability-gated plugin system. A feature ViewModel talks only to LavaTrackerSdk; the SDK routes the call through the active tracker's TrackerClient.getFeature<T>(), which returns a feature-interface implementation **only when the descriptor declares the matching capability** (constitutional clause 6.E, "Capability Honesty").

```
graph TD
    VM["feature:* ViewModels<br/>(search_result, topic, login,<br/>>provider_config, menu ...)"]
    SDK["LavaTrackerSdk @Singleton<br/>core/tracker/client/.../LavaTrackerSdk.kt"]
    REG["TrackerRegistry / DefaultTrackerRegistry<br/>core/tracker/registry/.../DefaultTrackerRegistry.kt"]
    FAC["TrackerClientFactory (per provider)<br/>core/tracker/registry/.../TrackerClientFactory.kt"]
    CLIENT["TrackerClient (active)<br/>core/tracker/api/.../TrackerClient.kt"]
    DESC["TrackerDescriptor<br/>core/tracker/api/.../TrackerDescriptor.kt"]
    CAP["TrackerCapability enum<br/>core/tracker/api/.../"]
```

```
TrackerCapability.kt"]
    GATE{"getFeature<T>(KClass<T>)<br/>capability E
descriptor.capabilities?"}
    FEAT["TrackerFeature impls<br/>core/tracker/api/.../feature/
*.kt"]

    VM -->|"inject @Singleton"| SDK
    SDK -->|"registry.get(id, config)"| REG
    REG -->|"create(config)"| FAC
    FAC -->|"returns"| CLIENT
    CLIENT -->|"val descriptor"| DESC
    DESC -->|"capabilities: Set"| CAP
    SDK -->|"client.getFeature(SearchableTracker::class) ..."| GATE
    GATE -->|"declared → impl"| FEAT
    GATE -->|"not declared → null<br/>(Failure outcome, never
throws)"| SDK
```

Grounding:

- LavaTrackerSdk — core/tracker/client/src/main/kotlin/lava/tracker/client/LavaTrackerSdk.kt
- TrackerClient.getFeature — core/tracker/api/src/main/kotlin/lava/tracker/api/TrackerClient.kt
- TrackerDescriptor — core/tracker/api/src/main/kotlin/lava/tracker/api/TrackerDescriptor.kt
- TrackerCapability — core/tracker/api/src/main/kotlin/lava/tracker/api/TrackerCapability.kt
- TrackerClientFactory / DefaultTrackerRegistry — core/tracker/registry/src/main/kotlin/lava/tracker/registry/

2. The contract surface (core:tracker:api)

2.1 TrackerDescriptor

A descriptor is the provider's identity + honesty contract. The fields below are verbatim from TrackerDescriptor.kt:

Field	Type	Meaning
trackerId (= id)	String	Stable id, e.g. "rutracker", "rutor", "kinozal", "nnmclub". Extends lava.sdk.api.HasId.
displayName	String	

Field	Type	Meaning
		Human-readable name shown in UI.
baseUrls	List<MirrorUrl>	Primary + mirror URLs; first isPrimary=true is canonical. MirrorUrl is a lava.sdk.api primitive from the Tracker-SDK submodule.
capabilities	Set<TrackerCapability>	What the tracker actually supports (clause 6.E — declarations of fact, not intent).
authType	AuthType	Auth mechanism (AuthType.kt).
encoding	String	e.g. "UTF-8", "Windows-1251".
expectedHealthMarker	String	Substring that must appear on the root page for a HEALTHY probe.
verified	Boolean (default false)	Clause 6.G gate — true only with a passing Challenge Test. Fail-closed: hidden from the provider list until earned.
supportsAnonymous	Boolean (default false)	Per-provider anonymous-browse capability (Phase 1.5, 2026-05-04).
apiSupported	Boolean (default false)	Whether lava-api-go routes /v1/{trackerId}/... for this provider today

Field	Type	Meaning
		(Phase 1 α -hotfix, 2026-05-06).

The three boolean flags (`verified`, `supportsAnonymous`, `apiSupported`) all default to `false` — a **fail-closed** posture so a half-wired provider never reaches users until each gate is explicitly satisfied.

2.2 TrackerCapability — the single source of truth

```
graph LR
    subgraph "TrackerCapability enum (13 values)"
        SEARCH; BROWSE; FORUM; TOPIC; COMMENTS; FAVORITES
        TORRENT_DOWNLOAD; MAGNET_LINK; AUTH_REQUIRED
        CAPTCHA_LOGIN; RSS; UPLOAD; USER_PROFILE
    end
```

Verbatim from `TrackerCapability.kt`: `SEARCH`, `BROWSE`, `FORUM`, `TOPIC`, `COMMENTS`, `FAVORITES`, `TORRENT_DOWNLOAD`, `MAGNET_LINK`, `AUTH_REQUIRED`, `CAPTCHA_LOGIN`, `RSS`, `UPLOAD`, `USER_PROFILE`.

The enum is the **single source of truth** that `TrackerDescriptor.capabilities` and `TrackerClient.getFeature<T>()` are gated on. Adding a feature interface without an enum entry makes the interface unreachable — a 6.E violation (see `core/CLAUDE.md` "Scoped clause for new feature interfaces").

Note on RSS, UPLOAD, USER_PROFILE: these enum values exist but have **no dedicated TrackerFeature interface** in `core/tracker/api/feature/` today — they are reserved capability slots, **NOT IMPLEMENTED** as feature interfaces. The seven implemented feature interfaces are listed in §2.3.

2.3 The seven feature interfaces

Each interface extends the `TrackerFeature` marker (`core/tracker/api/.../TrackerFeature.kt`). Method signatures are verbatim from `core/tracker/api/src/main/kotlin/lava/tracker/api/feature/`:

```
classDiagram
    class TrackerFeature {
        <<marker>>
    }
    class SearchableTracker {
        +search(request, page) SearchResult
    }
```

```

class BrowsableTracker {
    +browse(category, page) BrowseResult
    +getForumTree() ForumTree?
}
class TopicTracker {
    +getTopic(id) TopicDetail
    +getTopicPage(id, page) TopicPage
}
class CommentsTracker {
    +getComments(topicId, page) CommentsPage
    +addComment(topicId, message) Boolean
}
class FavoritesTracker {
    +list() List~TorrentItem~
    +add(id) Boolean
    +remove(id) Boolean
}
class AuthenticatableTracker {
    +login(req) LoginResult
    +logout()
    +checkAuth() AuthState
}
class DownloadableTracker {
    +downloadTorrentFile(id) ByteArray
    +getMagnetLink(id) String?
}
TrackerFeature <|-- SearchableTracker
TrackerFeature <|-- BrowsableTracker
TrackerFeature <|-- TopicTracker
TrackerFeature <|-- CommentsTracker
TrackerFeature <|-- FavoritesTracker
TrackerFeature <|-- AuthenticatableTracker
TrackerFeature <|-- DownloadableTracker

```

Interface	File	Capability it answers
SearchableTracker	feature/ SearchableTracker.kt	SEARCH
BrowsableTracker	feature/ BrowsableTracker.kt	BROWSE / FORUM
TopicTracker	feature/TopicTracker.kt	TOPIC
CommentsTracker	feature/ CommentsTracker.kt	COMMENTS
FavoritesTracker	feature/ FavoritesTracker.kt	FAVORITES
AuthenticatableTracker	feature/ AuthenticatableTracker.kt	AUTH_REQUIRED / CAPTCHA_LOGIN

Interface	File	Capability it answers
DownloadableTracker	feature/ DownloadableTracker.kt	TORRENT_DOWNLOAD / MAGNET_LINK

`DownloadableTracker.getMagnetLink(id)` is the **only non-suspend** method on any feature interface, and its contract ("Returns null if the magnet URI is not synchronously available without an HTTP fetch") is the reason the per-provider **magnet-cache pattern** exists — see §6 and the developer guide.

3. Capability gate — `getFeature<T>()`

`TrackerClient` (`core/tracker/api/.../TrackerClient.kt`) is the runtime enforcement point for clause 6.E:

```
interface TrackerClient : AutoCloseable {
    val descriptor: TrackerDescriptor
    suspend fun healthCheck(): Boolean
    fun <T : TrackerFeature> getFeature(featureClass: KClass<T>):
        T?
}
```

The contract, stated in the interface's KDoc: *"capability declared in descriptor ⇒ this returns non-null."* The inverse is the load-bearing honesty guarantee — a capability **not** declared returns `null`, and every SDK call site treats `null` as a typed failure outcome rather than throwing.

sequenceDiagram

```
participant SDK as LavaTrackerSdk
participant C as TrackerClient (active)
participant D as TrackerDescriptor
participant F as SearchableTracker impl
```

```
SDK->>C: getFeature(SearchableTracker::class)
```

```
C->>D: SEARCH in descriptor.capabilities?
```

```
alt declared
```

```
    D-->>C: true
```

```
    C-->>SDK: SearchableTracker impl
```

```
    SDK->>F: search(request, page)
```

```
    F-->>SDK: SearchResult
```

```
else not declared
```

```
    D-->>C: false
```

```
    C-->>SDK: null
```

```
    Note over SDK: SearchOutcome.Failure<br/>("tracker X does
```

```
not support SEARCH")<br/>- never throws  
end
```

This pattern repeats for every capability across LavaTrackerSdk (search, browse, getTopic, getCommentsPage, addComment, getFavorites, addFavorite, removeFavorite, login, checkAuth, logout, getMagnetLink, downloadTorrent) — each does a `getFeature(...)` null-check and returns a `Failure/null/false` outcome instead of throwing (`LavaTrackerSdk.kt`).

4. Registry + factory — how a provider gets wired

4.1 Registration topology (Hilt, `core:tracker:client`)

There is **one** Hilt module that builds the registry: `core/tracker/client/src/main/kotlin/lava/tracker/client/di/TrackerClientModule.kt`. Its `provideTrackerRegistry @Provides` function takes every provider's `TrackerClientFactory` as a constructor parameter and `register(...)`s each into a `DefaultTrackerRegistry`:

```
graph TD
    subgraph "TrackerClientModule.provideTrackerRegistry (Hilt @Provides)"
        RR["RuTrackerClientFactory"]
        RT["RuTorClientFactory"]
        NN["NnmclubClientFactory"]
        KZ["KinozalClientFactory"]
        AO["ArchiveOrgClientFactory"]
        GB["GutenbergClientFactory"]
    end
    REG["DefaultTrackerRegistry<br/>(register each factory)"]
    RR --> REG
    RT --> REG
    NN --> REG
    KZ --> REG
    AO --> REG
    GB --> REG
    REG -->|"exposes by descriptor.id"| SDK["LavaTrackerSdk"]
```

The six factories registered today (verbatim from `TrackerClientModule.kt provideTrackerRegistry`): `rutrackerFactory`, `rutorFactory`, `nmclubFactory`, `kinozalFactory`, `archiveOrgFactory`, `gutenbergFactory`.

Doc-drift note: docs/sdk-developer-guide.md §2 Step 5 still describes a @IntoSet-multibinding registration style and §5 lists only RuTracker + RuTor. The **actual** wiring in TrackerClientModule.kt is explicit constructor injection of six factories into provideTrackerRegistry (no @IntoSet). This diagram reflects the code. The guide's Step 5 is documentation that predates the additional providers.

4.2 TrackerClientFactory — clone-aware creation

TrackerClientFactory (core/tracker/registry/.../TrackerClientFactory.kt) extends the SDK primitive PluginFactory<TrackerDescriptor, TrackerClient> and exposes create(config: PluginConfig): TrackerClient.

The config carries an optional clone base-URL override (PluginConfig.cloneBaseUrlOverride, read via lava.tracker.registry.cloneBaseUrlOverride). When present (SP-4 Phase F.2), create returns a **per-call** client routed at the clone's primaryUrl; otherwise it returns the shared @Singleton client. See KinozalClientFactory.kt for the canonical implementation — note it shares ONE KinozalMagnetCache between the clone's topic + download features (§6).

5. Request flow: app → SDK → client → feature

End-to-end search flow through the production classes:

```
sequenceDiagram
    actor User
    participant VM as feature:search_result ViewModel
    participant SDK as LavaTrackerSdk
    participant REG as DefaultTrackerRegistry
    participant FAC as KinozalClientFactory
    participant C as KinozalClient
    participant S as KinozalSearch (SearchableTracker)
    participant MC as KinozalMagnetCache

    User->>VM: type query, tap Search
    VM->>SDK: multiSearch(request, providerIds)
    SDK->>REG: get("kinozal", config)
    REG->>FAC: create(config)
    FAC-->>SDK: KinozalClient
```

```
SDK->>C: getFeature(SearchableTracker::class)
C-->>SDK: KinozalSearch (capability declared)
SDK->>S: search(request, page)
S->>S: HTTP GET + parse rows
S->>MC: put(torrentId, magnetUri) per row
S-->>SDK: SearchResult
SDK->>SDK: DeduplicationEngine.deduplicate(...)
SDK-->>VM: UnifiedSearchResult
VM-->>User: render result rows
```

Grounding for the multi-provider path: `LavaTrackerSdk.multiSearch / streamMultiSearch` fan out across `providerIds` with `parallel async { ... }.awaitAll()` (SP-4 Phase D), roll up per-provider statuses, and deduplicate via `DeduplicationEngine` (`core/tracker/client/.../dedup/DeduplicationEngine.kt`). The magnet-cache write on each search row (`S->>MC: put`) is the real code in `NnmclubSearch.kt` (`result.items.forEach { magnetCache.put(it.torrentId, it.magnetUri) }`).

Cross-tracker / mirror fallback

The single-active-tracker path (search, browse) additionally runs through `runWithMirrorFallback`, which (when mirror collaborators are wired) executes via a per-tracker `MirrorManager` and, on total mirror exhaustion, proposes a `CrossTrackerFallbackProposed` outcome via `CrossTrackerFallbackPolicy` (`core/tracker/client/.../CrossTrackerFallbackPolicy.kt`). There is **no silent fallback** — the UI shows a modal and the user accepts or dismisses (see `docs/ARCHITECTURE.md` "Cross-tracker fallback flow").

The `switchTracker / activeTrackerId` single-active-tracker API is `@Deprecated` (SP-4 Phase D) in favor of `multiSearch / streamMultiSearch` with explicit provider lists (`LavaTrackerSdk.kt`).

6. The magnet-cache pattern (§6.E Capability Honesty)

`DownloadableTracker.getMagnetLink(id)` is **non-suspend**, so it cannot make an HTTP call. Its contract is to return the magnet **only if synchronously available**, else `null`. Three providers (kinozal,

nnmclub, rutor) declare the `MAGNET_LINK` capability and back `getMagnetLink` with a `@Singleton` magnet cache that the suspend topic/search path populates from genuinely-parsed magnets:

```
graph LR
    subgraph "write side (suspend, real fetch)"
        TOPIC["KinozalTopic.getTopic(id)<br/>parses topic page"]
        SEARCH["NnmclubSearch.search(...)<br/>parses result rows"]
    end
    end
    CACHE["@Singleton XxxMagnetCache<br/>ConcurrentHashMap<id, magnet>"]
    subgraph "read side (non-suspend)"
        DL["KinozalDownload.getMagnetLink(id)<br/>magnetCache.get(id)"]
    end
    end
    TOPIC -->|"put(id, magnetUri)"| CACHE
    SEARCH -->|"put(torrentId, magnetUri)"| CACHE
    CACHE -->|"get(id) → real magnet OR null"| DL
```

Real files implementing this pattern:

Provider	Cache	Writer(s)	Reader
Kinozal	kinozal/.../magnet/ KinozalMagnetCache.kt	KinozalTopic.getTopic	KinozalDownload.getMagne
NNM-Club	nnmclub/.../http/ NnmclubMagnetCache.kt	NnmclubTopic, NnmclubSearch	NnmclubDownload.getMagne
RuTor	rutor/.../magnet/ RuTorMagnetCache.kt	RuTor topic/search parsers	RuTor download feature

Why this is honest rather than a bluff: `get(id)` returns `null` when an id was never surfaced (an honest "not synchronously available" per the contract), and the cache is only ever populated with magnets that the **production parser** extracted from a real page — never fabricated. The cache is a `ConcurrentHashMap` (search + topic features may write from different coroutines while download reads). It is `@Singleton` so all features share one instance; the clone path passes an explicit shared instance (`KinozalClientFactory.create`, §4.2).

The full author-facing recipe — including the put-on-parse wiring and the clone-path shared-instance rule — is documented in [docs/sdk-developer-guide.md §8](#).

7. Proving a download is real — the torrent validators

core:common ships two validators (core/common/src/main/kotlin/lava/common/torrent/) that turn "we returned bytes / a string" into "we returned a genuinely-usable download". Both produce a `DownloadValidationResult { valid, infoHashHex, reason }` keyed on the **same** lowercase 40-char info-hash, so a .torrent file and a magnet for the same content cross-check.

```
graph TD
    BYTES[".torrent bytes (ByteArray)"]
    MAGNET["magnet: URI (String)"]
    TFV["TorrentFileValidator.validate(bytes)<br/>bencode → info dict → SHA-1(info)"]
    MLV["MagnetLinkValidator.validate(uri)<br/>xt=urn:btih:<hex|base32> → 40-hex"]
    RES["DownloadValidationResult<br/>{ valid, infoHashHex, reason }"]
    BYTES --> TFV
    TFV --> RES
    MAGNET --> MLV
    MLV --> RES
    RES -->|"same content ⇒ same infoHashHex"| RES
```

- **TorrentFileValidator** — parses the bytes as bencode (`Bencode.kt`), requires a top-level dict containing `info` with a non-empty name, a piece length > 0, and pieces whose length is a positive multiple of 20 (each piece SHA-1 is 20 bytes). The info-hash is SHA-1 over the **verbatim** bencoded info dict bytes (recovered via `valueRanges`), so it matches what a real BitTorrent client computes.
- **MagnetLinkValidator** — requires an `xt=urn:btih:<hash>` where `<hash>` is 40-char hex OR 32-char RFC-4648 base32; normalizes both to lowercase hex.

These are the canonical anti-bluff way to assert a download feature actually works (clause 6.E + the Anti-Bluff Pact's "primary assertion on user-visible state"). See [docs/sdk-developer-guide.md §9](#).

8. Module layout

```
graph TD
    API["core:tracker:api<br/>feature interfaces + capability enum + DTOs"]
    REG["core:tracker:registry<br/>TrackerRegistry over lava.sdk:registry"]
    CLIENT["core:tracker:client<br/>LavaTrackerSdk + Hilt module +"]
```

```

persistence"]
COMMON["core:common<br/>torrent validators + bencode"]
subgraph "per-provider plugins (core:tracker:*)"
    RUTRACKER["rutracker"]
    RUTOR["rutor"]
    KINOZAL["kinozal"]
    NNMCLUB["nnmclub"]
    ARCHIVEORG["archiveorg"]
    GUTENBERG["gutenberg"]
end
SUB["submodules/tracker_sdk<br/>(vasic-digital/Tracker-
SDK)<br/>MirrorUrl, PluginRegistry, PluginFactory"]

```

```

RUTRACKER --> API
RUTOR --> API
KINOZAL --> API
NNMCLUB --> API
ARCHIVEORG --> API
GUTENBERG --> API
KINOZAL --> COMMON
NNMCLUB --> COMMON
RUTOR --> COMMON
REG --> API
REG --> SUB
CLIENT --> REG
CLIENT --> RUTRACKER
CLIENT --> RUTOR
CLIENT --> KINOZAL
CLIENT --> NNMCLUB
CLIENT --> ARCHIVEORG
CLIENT --> GUTENBERG
API --> SUB

```

Generic primitives (MirrorUrl, PluginRegistry, PluginFactory, MapPluginConfig) live in the vasic-digital/Tracker-SDK submodule mounted at submodules/tracker_sdk/ per the Decoupled Reusable Architecture rule; the pin is frozen by default. DefaultTrackerRegistry composes the SDK's DefaultPluginRegistry via Kotlin interface delegation (the SDK class is final) and adds trackersWithCapability(...).

9. Where to go next

- **Add a provider:** [docs/sdk-developer-guide.md](#) (7-step recipe + §8 magnet cache + §9 validators).
- **Server-side deployment / Jaxet:** [docs/architecture/local-stack-topology.md](#).

- **mDNS discovery:** [docs/LOCAL_NETWORK_DISCOVERY.md](#).

Last updated: 2026-06-08. All symbols verified against the working tree.