

lava-api-go — Go coverage baseline — 2026-06-04

Completeness program Phase 2B. Captured via `make cover` (`GOMAXPROCS=2 go test ./... -coverprofile=coverage.out -covermode=atomic`).

Host: darwin/arm64, Go 1.26.2.

Scope of this rollup

This is the **default (no-external-deps) rollup**: unit + contract + e2e + parity tests that run against the host toolchain. The real-Postgres integration tests (tests/integration, gated behind `-Pintegration / podman`) are **excluded** from this number — they require a live Postgres container and are not part of the default `go test ./...` surface. The real coverage of DB-touching paths is higher than the headline once integration runs.

Headline

Overall: 44.5% of statements.

The overall number is dragged down by `cmd/*` and the generated `internal/gen/*` packages (0% — they are `oapi`-codegen output / thin main-package entrypoints exercised only by e2e binaries). The Lava-domain `internal/*` business packages sit substantially higher (see per-package below).

Per-package (statements)

Package	Coverage
internal/provider	100.0%
internal/config	93.9%

Package	Coverage
internal/auth	93.3%
internal/qa/ticket	93.2%
internal/handlers	93.1%
internal/qa/validator	92.5%
internal/ratelimit	90.0%
internal/server	90.1%
internal/qa/evidence	87.9%
internal/firebase	83.3%
internal/qa/detector	82.9%
internal/gutenberg	82.4%
internal/mobile	82.2%
internal/archiveorg	81.9%
internal/ observability	81.7%
internal/rutracker	76.8%
internal/cache	69.7%
internal/storage	65.7%
internal/discovery	57.1%
internal/handlers/v1	53.5%
internal/nnmclub	49.5%
internal/kinozal	48.9%
cmd/healthprobe	42.9%
internal/middleware	33.9%
cmd/lava-api-go	0.0% (entrypoint; covered via e2e binary, not unit)
internal/gen/client	0.0% (generated)
internal/gen/server	0.0% (generated)
internal/router	0.0% (wiring; exercised by e2e)

Notable lows worth raising in a later cycle

- internal/middleware (33.9%) and internal/handlers/v1 (53.5%) are Lava-domain request-path code; the lowest business-logic coverage in the module.

- `internal/kinozal` (48.9%) and `internal/nmclub` (49.5%) — tracker scrapers whose deeper paths need `real-tracker` (`-PrealTrackers`) runs.

Two pre-existing test failures during the rollup

The rollup completed and wrote `coverage.out`, but two packages were RED. Both reproduce on the clean baseline (verified by stashing the Phase 2B change) — they are pre-existing, not regressions:

- `tests/contract` → `TestAuthFieldName_NoLiteralInProductionGoSource` (a §6.R literal "Lava-Auth" in `internal/mobile/mobile.go`).
- `internal/qa/detector` → `TestCheckGoProcessByPID_Alive` (`fakeRunner` bypassed).

See `docs/security/2026-06-04-golangci-triage.md` for detail.

Evidence

- `.lava-ci-evidence/completeness-program/coverage/go-baseline-2026-06-04/coverage.out`
- `.lava-ci-evidence/completeness-program/coverage/go-baseline-2026-06-04/coverage-func.txt`
- `.lava-ci-evidence/completeness-program/coverage/go-baseline-2026-06-04/test-run.log`
- `.lava-ci-evidence/completeness-program/coverage/go-baseline-2026-06-04/staticcheck-baseline.txt`