

Video-QA Harness: record + validate Challenges on the Genymotion VM

Status: harness scaffolded (`scripts/record-challenge-video.sh`). NOT yet run end-to-end — the under-test fixes for the reported issues are still landing. Run the runbook in §4 once those fixes are in the working tree.

Classification: project-specific (Lava's Genymotion + \$HOME delivery flow; the underlying recorder + Challenge runner are inherited from §11.4.128 + §6.AG/§6.AH).

This note documents (1) what the HelixQA submodule REALLY provides for video QA, (2) the recording + validation flow this harness uses and why, and (3) the exact commands to record + validate the reported-issue Challenges with video.

1. HelixQA's REAL capabilities (with honest gaps)

The HelixQA submodule (`submodules/helixqa/`) has a far larger surface than its README's architecture diagram lists — 50 pkg/ dirs and 24 cmd/ binaries. All three concerns the operator named exist as real Go code:

(a) Autonomous test banks — EXISTS

- `submodules/helixqa/pkg/testbank/generator.go` — `TestGenerator` interface (`generator.go:36`): `GenerateTests(ctx, Feature) + GenerateEdgeCases(ctx, TestCase)`, LLM-backed (`generator.go:33`), degrades to nil without an agent. `GenerateFromFeatureMap` (`generator.go:53`) turns product Features into `[]TestCase`; `ExpandEdgeCases` (`generator.go:96`) adds edge variants.

- pkg/testbank/{loader,manager,schema,dispatch}.go — loads/manages/dispatches YAML test banks (the test_cases: schema documented in HelixQA's README).
- pkg/autonomous/ (46 files; pipeline.go, coordinator.go, structured_executor.go) — the 4-phase Setup → Doc-Driven Verification → Curiosity-Driven Exploration → Report autonomous session; pkg/planning/ generates platform-specific test plans (incl. an Android-TV-Channels framework).

(b) Video recording — EXISTS (real drivers, not stubs)

- pkg/video/scrcpy.go — ScrcpyRecorder with four real RecordMethods (scrcpy.go:26): MethodScrcpy, MethodADBScreenrecord (adb shell screenrecord), MethodScreenshotAssembly, MethodAuto. Carries a documented fix (scrcpy.go:48) that loops + ffmpeg-concats segments to beat Android screenrecord's 180 s hard limit. 16 Mbps (scrcpy.go:46).
- pkg/video/ffmpeg_recorder.go — FFmpegRecorder (ffmpeg_recorder.go:17), real x11grab 30fps/libx264/MP4 for web/desktop.
- pkg/capture/ (android/linux/macos/windows), pkg/screenshot/ (per-platform), pkg/gst/frame_extractor.go, pkg/video/frames.go.
- Note: pkg/session/video.go's VideoManager is state/timing tracking only ("does not execute ffmpeg/adb directly", video.go:11-15) — the real recorders are the video/ + capture/ drivers.

(c) Validate what's happening on the recorded video — EXISTS (CV + OCR + LLM-vision)

This is the strongest finding — HelixQA has purpose-built post-hoc video-frame validation, not just text/log verdicts:

- cmd/recording-analyzer/main.go — extracts frames via ffmpeg, OCRs each frame via Tesseract, optionally Whisper-transcribes audio, and emits PASS/FAIL/UNKNOWN per (frame, event) on whether the expected content appeared on the expected display. Built to catch "PASS-bluffs where a feature claims to have worked but the user-visible recording disagrees" (main.go:1-40).
- cmd/recording-analyzer/posthoc.go — the \$11.4.107 liveness correlator (posthoc.go:1-45): SKIP (no ffprobe/ffmpeg), FAIL (frame count < min, frozen decoder, or first-frame == prior content's last frame = stale), PASS (frames advance + not stale). Self-validated with golden-good/golden-bad fixtures.

- `pkg/analysis/vision.go` — `VisionAnalyzer` (`vision.go:49`):
`AnalyzeScreenshot` → `provider.Vision(ctx, imageData, prompt)`
(`vision.go:72`) with QA-analyst prompts; `CompareScreenshots` for
before/after regression.
- `pkg/llm/anthropic.go` — real Anthropic vision API; `pkg/llm/`
`{openai,google,ollama,astica}.go` + `vision_ranking.go` are other
vision providers.
- `pkg/vision/` — `detector.go` (UI element detection),
`ocr_tesseract.go` + `ocr_paddle.go` (two OCR engines), `diff.go`,
`perceptual/`, `hash/`; `pkg/gpu/infer/` (Triton/KServe v2), `pkg/`
`visionnav/`, `pkg/issuedetector/`.

Honest GAP: none in HelixQA, all in the WIRING

`lava-api-go/internal/qa/` wraps ONLY HelixQA's text/verdict layer —
config, detector (crash/ANR), evidence (server-side text traces), ticket
(`$6.O` closure logs via `pkg/ticket.Generator`, `internal/qa/ticket/`
`generator.go:173`). There is ZERO import of HelixQA's video, capture,
analysis, vision, screenshot, llm, or `cmd/recording-analyzer` from
anywhere in Lava. So:

- **Today, Lava cannot call HelixQA's video-vision validation through any wired adapter.** Those capabilities run as HelixQA CLIs/packages, configured via HelixQA's own `.env` (vision-provider keys, `ffmpeg/scrcpy` paths). Reaching them is a future wiring task (a Go adapter in `lava-api-go/internal/qa/video` + `lava-api-go/internal/qa/vision`), tracked separately.
 - **Therefore this harness does NOT claim AI-vision validation in its gate path.** It uses the deterministic, honest alternative below.
-

2. The recording + validation flow this harness uses (and why)

`scripts/record-challenge-video.sh` is thin glue that composes two existing, proven pieces:

1. **Serial resolution** via the Containers submodule `cmd/genymotion` CLI (the `$6.AG` "driven by the Containers submodule" requirement). The Genymotion VM is an authorized non-host-direct surface under `$6.AH`; a live/physical ADB device is NEVER targeted (`$6.AG`: those are used by other projects). Default serial when explicitly supplied: `127.0.0.1:6555` (`scripts/run-helixqa-provider-qa.sh:37`).

2. **Screen recording** via `scripts/record-device-session.sh --screenrecord` (the §11.4.128 always-on recorder). It runs `adb -s <serial> shell screenrecord --time-limit 180 /sdcard/lava-rec.mp4` then `adb pull` into the deterministic `<root>/YYYY-MM-DD/<state-hash>/<DEVICE>_<SERIAL>/recording_NNN/` layout (`record-device-session.sh:9, 203-205`). Read-only w.r.t. the app under test (no `pm clear` / `am force-stop`).
3. **The Challenge** via `:app:connectedDebugAndroidTest -Pandroid.testInstrumentationRunnerArguments.class=<FQCN>` — the SAME invocation `scripts/run-genymotion-challenges.sh:113-116` uses, under `--no-daemon --max-workers=2 nice` (§6.T.2 resource caps).

The validation: test-PASS is the gate; the video is the watchable proof

- **Ground truth = the `connectedAndroidTest` verdict** (§11.4.69 / §6.J): PASS ONLY when gradle exits 0 AND the verbatim string `BUILD SUCCESSFUL` is in the captured `connected-test.log`. A Lava Challenge asserts on user-visible Compose state, so its green is "a real user can complete this flow," not "the wiring compiles."
- **The `.mp4` is the human-watchable artifact of that exact run.** The operator watches the screen do what the Challenge asserted. This is the most rigorous REAL alternative to AI-vision validation: it makes no claim the tooling cannot honestly back. It does NOT fabricate "the AI watched the video and it's fine."
- **A deterministic frame-liveness check is available as a next layer** (not in the gate today): pointing HelixQA's `cmd/recording-analyzer/posthoc.go` at the delivered `.mp4` answers "did the recording show live, advancing frames (not a black/frozen screen)." Adding it is a documented enhancement, not a blocker.

Delivery rule (success videos only)

On PASS the script copies `<name>.mp4` to BOTH `$HOME/<name>.mp4` AND `$HOME/Downloads/<name>.mp4` (creating Downloads if missing). On FAIL it copies nothing. A delivered video is therefore itself proof the Challenge passed — there is no path by which a FAIL leaves a video in `$HOME`. If a Challenge passes but no `.mp4` was captured, the script EXITS 1 rather than claim a delivered video that does not exist (§6.J honesty).

3. Prerequisites (run order)

1. A Genymotion VM booted (e.g. "Google Pixel 9", API 35, arm64). The Containers cmd/genymotion CLI resolves its serial; or pass --serial 127.0.0.1:6555.
 2. adb on PATH (the script + recorder both gate on command -v adb).
 3. The debug APK + androidTest APK build for the connected device (the script builds them unless --no-build).
 4. The under-test fixes for the reported issues present in the working tree. (Do NOT run the full pipeline before this — there is nothing yet to validate.)
-

4. Runbook — record + validate the reported-issue Challenges with video

The four operator-reported issues map to these existing Challenge classes under app/src/androidTest/kotlin/lava/app/challenges/:

Reported issue (what the user saw)	Challenge class (FQCN under lava.app.challenges)	Output name
"Select-all": search pre-selects providers never onboarded	Challenge16ApiSupportedFilterTest (provider-filter default)	select-all
Tracker selection / launch (the select surface)	Challenge01AppLaunchAndTrackerSelectionTest	track-select
Password / login shows wrong message on valid creds	Challenge36LoginServiceUnavailableShowsAccurateMessageTest	password-login
Search (authenticated)	Challenge02AuthenticatedSearchOnRuTrackerTest	search-auth
	Challenge03AnonymousSearchOnRuTorTest	search-anon

Reported issue (what the user saw)	Challenge class (FQCN under <code>lava.app.challenges</code>)	Output name
Search (anonymous provider)		
Server-list: RuTracker		
"Main" wrongly in the server list	<code>Challenge26RutrackerMainAbsentFromServerListTest</code>	server list

Adjust the class list to whichever Challenges the landing fixes touch — per §6.Z.3 every Cn whose target file appears in the cycle's git diff MUST run.

One Challenge, one video (positional shorthand)

Boots/locates the Genymotion VM, records, runs ONE Challenge, delivers on PASS.

```
scripts/record-challenge-video.sh \
  lava.app.challenges.Challenge16ApiSupportedFilterTest \
  select-all
```

Explicit serial (skip Containers detection)

```
scripts/record-challenge-video.sh \
  --test-class \
    lava.app.challenges.Challenge36LoginServiceUnavailableShowsAccurateMessage \
  --name password-login \
  --serial 127.0.0.1:6555
```

All four reported-issue areas in sequence

```
set -e # stop on the first FAILED Challenge (no video delivered for it)
```

```
scripts/record-challenge-video.sh \
  lava.app.challenges.Challenge16ApiSupportedFilterTest \
  select-all
```

```
scripts/record-challenge-video.sh \
  lava.app.challenges.Challenge01AppLaunchAndTrackerSelectionTest \
  tracker-select --no-build
```

```
scripts/record-challenge-video.sh \
  lava.app.challenges.Challenge36LoginServiceUnavailableShowsAccurateMessage \
  password-login --no-build
```

```

scripts/record-challenge-video.sh
    lava.app.challenges.Challenge02AuthenticatedSearchOnRuTrackerTest
    search-auth      --no-build
scripts/record-challenge-video.sh
    lava.app.challenges.Challenge03AnonymousSearchOnRuTorTest
    search-anon      --no-build
scripts/record-challenge-video.sh
    lava.app.challenges.Challenge26RutrackerMainAbsentFromServerListTest
    server-list      --no-build

```

After a green run you will find, per passing Challenge:

- `$HOME/<name>.mp4`
- `$HOME/Downloads/<name>.mp4`
- `.lava-ci-evidence/challenge-video/<ts>/` with `connected-test.log`, `verdict.txt`, `device-identity.txt`, and the `<name>.mp4`.
- The raw recording under `.lava-ci-evidence/device-recordings/<date>/<hash>/<DEVICE>_<SERIAL>/recording_NNN/screen.mp4` (git-ignored per §11.4.128).

5. Exit codes

Exit	Meaning
0	Challenge PASSED, video captured + delivered to <code>\$HOME + Downloads</code>
1	Challenge FAILED (no video delivered) OR passed-but-no-video-captured
2	config / usage / device error (missing args, no adb, no VM, no <code>\$HOME</code>)

6. Honest limitations + next layers (not blockers)

- **180 s screenrecord cap.** A single Challenge fits well within it; a longer flow needs the segmented path (HelixQA `pkg/video/scrcpy.go:48` does `segment+concat` — wiring it in is the enhancement).
- **No AI-vision validation in the gate.** By design (§1 gap). The deterministic next layer is `cmd/recording-analyzer/posthoc.go` (frame-liveness PASS/FAIL); the richer layer is `pkg/analysis/vision.go` (LLM-vision) once a `lava-api-go/internal/qa/`

{video,vision} adapter is wired. Both are documented here so the path is auditable; neither is claimed today.

- **macOS host gap (§6.AH-debt).** Containerized/QEMU AVDs do not yet boot on the darwin/arm64 podman VM. The Genymotion VM IS a VM (§6.AH-compliant), so this harness targets it directly — that is the authorized path while §6.AH-debt is open.