

:api-app Firebase Crashlytics Wiring — Implementation Plan

- **Date:** 2026-06-13
 - **Status:** PLAN — not implemented. Touches `google-services.json` (§6.H-sensitive) → operator approval required before any code lands.
 - **Constitutional bindings:** §6.AC (Comprehensive Non-Fatal Telemetry Mandate), §6.O (Crashlytics-Resolved Issue Coverage), §6.H (Credential Security), Decoupled Reusable Architecture rule (no copy-paste between apps), §11.4.6 (no-guessing — file evidence captured; unverified items marked UNCONFIRMED:).
 - **Investigation method:** read-only file inspection. No builds run, no secrets printed, no code edited.
-

0. Verdict (read first)

The audit's framing ("**api-app has NO Crashlytics, needs operator to generate google-services.json**") is **PARTLY OUTDATED**. Two facts change the picture:

1. **CONFIRMED — the gradle Firebase plugins are ALREADY applied to :api-app.** The `lava.android.application` convention plugin (`buildSrc/src/main/kotlin/AndroidApplicationConventionPlugin.kt:18-19`) applies `com.google.gms.google-services` AND `com.google.firebase.crashlytics` to *every* module using `id("lava.android.application")` — and `api-app/build.gradle.kts:21` applies exactly that. So the plugin wiring is inherited, not missing.
2. **CONFIRMED — api-app/google-services.json ALREADY EXISTS** (1163 bytes, dated 2026-06-02, gitignored via `.gitignore:66 **/google-services.json`). It registers BOTH `api-app` application-ids:
 - `digital.vasic.lava.api` (release)

- `digital.vasic.lava.api.dev` (debug) (Verified by grepping `package_name` keys only — NO secret values were read or printed. `mobilesdk_app_id` count = 2, matching the two app-ids.)

What is ACTUALLY missing (the real \$6.AC/\$6.O gap that makes runtime Crashlytics report 404 / no telemetry):

- `:api-app/build.gradle.kts` does NOT depend on the Firebase BOM / analytics / crashlytics artifacts (CONFIRMED: `grep -nE "firebase|core:common|analytics"` returns nothing).
- `ApiApplication.onCreate()` does NOT initialize Firebase (CONFIRMED: `ApiApplication.kt` only publishes `controllerHolder/` `keyStoreHolder`; no `Firebase.crashlytics`, no `FirebaseInitializer`).
- There is NO `AnalyticsTracker` binding in the `api-app` Hilt graph, so the embedded server's Go-side errors and the app's own catch paths have no client-side sink.

Verdict: READY TO IMPLEMENT once the operator confirms the existing `api-app/google-services.json` is the genuine console-generated file for these two app-ids (see §6 checklist item OA-1).

The blocking §6.H artifact appears already present; everything else is code the agent can write. The one thing the agent cannot self-verify is whether the existing JSON is a real console export vs. a placeholder — that is an operator confirmation, not a generation task.

1. :api-app module map (evidence)

Concern	File	Notes
Gradle module decl	<code>settings.gradle.kts:22</code> <code>include(":api-app")</code>	sibling <code>:core:apiengine</code> at line 23
Build script	<code>api-app/build.gradle.kts</code>	plugins: <code>lava.android.application +</code> <code>lava.android.hilt</code>
Release app-id	<code>api-app/build.gradle.kts</code> <code>applicationId =</code> <code>"digital.vasic.lava.api"</code>	<code>versionCode 8 / versionName</code> <code>0.2.4, minSdk 23</code>
Debug app-id	<code>applicationIdSuffix =</code> <code>".dev" →</code> <code>digital.vasic.lava.api.dev</code>	
Manifest		

Concern	File	Notes
Application class	api-app/src/main/AndroidManifest.xml	android:name=".ApiApplication"; foreground ApiEngineService; ApiKeyProvider (signature-permission ContentProvider)
	api-app/src/main/kotlin/lava/api/app/ApiApplication.kt	@HiltAndroidApp; injects ApiEngineController + ApiKeyStore; publishes process-wide holders in onCreate() driven by ApiEngineController (api-app/.../control/ApiEngineController.kt), run inside foreground
Embedded server boot	:core:apiengine (NativeApiEngine) → liblavaapi.so	ApiEngineService (.../service/ApiEngineService.kt); APK packages the Go .so via :core:apiengine
Compose UI	.../ui/ApiControlScreen.kt + ApiControlViewModel (Orbit MVI)	
Challenge tests	api-app/src/androidTest/.../challenges/Challenge0{1..5}*Test.kt	C05 asserts embed source-hash sync

The embedded Go server's errors are already routed Go-side through observability.RecordNonFatal (lava-api-go/internal/observability/nonfatal.go) which (1) always logs structured WARNING/ERROR via OTLP, and (2) optionally posts to Firebase Crashlytics REST when LAVA_API_FIREBASE_CRASHLYTICS_ENABLED=true.

2. The :app Crashlytics pattern to mirror (evidence)

2a. Gradle plugins (inherited, not in app/build.gradle.kts directly)

AndroidApplicationConventionPlugin.kt:

```
apply("com.google.gms.google-services")
apply("com.google.firebase.crashlytics")
```

Plugin classpath in buildSrc/build.gradle.kts:

```
libs.firebase.crashlytics.gradlePlugin +
libs.google.services.gradlePlugin. Catalog (gradle/
libs.versions.toml): firebaseCrashlyticsGradlePlugin = "3.0.4",
firebaseBom = "33.15.0"; libs firebase-bom, firebase-analytics,
firebase-crashlytics, firebase-perf.
```

2b. Runtime deps (app/build.gradle.kts:301-304)

```
implementation(platform(libs.firebase.bom))
implementation(libs.firebase.analytics)
implementation(libs.firebase.crashlytics)
implementation(libs.firebase.perf)
```

2c. Application init (app/src/main/.../LavaApplication.kt)

- FirebaseApp is auto-initialized by FirebaseInitProvider (a ContentProvider the google-services plugin injects) BEFORE Application.onCreate() — so NO manual initializeApp() (manual init was a 2026-05-05 Crashlytics incident root cause).
- LavaApplication.onCreate() calls FirebaseInitializer.initialize(...) (defensively wrapped) passing nullable SDK accessors, isDebug, versionName/Code, applicationId, and a warn logger.
- Then NavTeardownCrashReporter.install(analytics) tags a known upstream crash.

2d. The telemetry surface (the §6.AC contract)

- **Interface (reusable, in core:common):**
lava.common.analytics.AnalyticsTracker —
recordNonFatal(throwable, context), recordWarning(message, context), event/setUserId/setProperty/log, plus Params (feature/module/operation/error_class/error_message/screen) + Events.
core/common/src/main/kotlin/lava/common/analytics/AnalyticsTracker.kt.
- **Impl + DI + initializer (CURRENTLY app-private — digital.vasic .lava.client.firebase):**
 - FirebaseAnalyticsTracker.kt — nullable-SDK-safe; filters CancellationException; truncates values to 1024 chars; recordWarning records a synthetic LavaNonFatalWarning.

- `FirebaseProvidesModule.kt` — Hilt
`@InstallIn(SingletonComponent); @Provides` for
`FirebaseAnalytics?/FirebaseCrashlytics?/FirebasePerformance?`
(all `runCatching` → nullable) and `analyticsTracker(...)`
returning real tracker or `NoOpAnalyticsTracker`.
 - `FirebaseInitializer.kt` — internal object, JVM-unit-testable,
per-SDK guarded.
 - `NoOpAnalyticsTracker.kt` — fallback.
-

3. Step-by-step plan to wire `:api-app`

Decoupled Reusable Architecture note (load-bearing design decision): the `Firebase impl/DI/initializer` in `app/.../firebase/` are internal to `:app` and reference `digital.vasic.lava.client.BuildConfig`. Copy-pasting them into `:api-app` is a forbidden bluff vector (behaviour drifts, fixes don't propagate — the exact failure mode the rule names). **Preferred approach: extract the reusable Firebase wiring to a shared module; have BOTH `:app` and `:api-app` consume it.** A copy-paste fallback is documented but discouraged.

Option A (RECOMMENDED) — extract to a shared `:core:analytics-firebase` module

1. **Create module `core/analytics-firebase/`** applying
`lava.android.library + lava.android.hilt`, depending on
`:core:common` (for `AnalyticsTracker`) + the `Firebase BOM/analytics/crashlytics` deps.
2. **Move** `FirebaseAnalyticsTracker`, `FirebaseProvidesModule`,
`FirebaseInitializer`, `NoOpAnalyticsTracker` into it under a neutral
package (e.g. `lava.analytics.firebase`). Make
`FirebaseInitializer.initialize(...)` take `applicationId/`
`versionName/versionCode` as params (already does) so it is app-
agnostic — no `BuildConfig` reference inside the module.
3. **`:app`** drops the 4 `firebase implementation(...)` lines + the moved
files; adds `implementation(project(":core:analytics-firebase"))`.
`LavaApplication` keeps calling `FirebaseInitializer.initialize(...)`
with `BuildConfig.*` (now imported from the shared module).
4. **`:api-app`** adds `implementation(project(":core:analytics-firebase"))`
+ `implementation(project(":core:common"))`. (The
`Firebase BOM/deps` come transitively from the shared module's
`api(...)` or are re-declared as needed.)

5. NavTeardownCrashReporter is client-nav-specific → STAYS in :app (the api-app has no androidx-navigation back-stack teardown crash).

Option B (fallback, discouraged) — add deps + copy wiring into :api-app

- Add to api-app/build.gradle.kts dependencies:
implementation(platform(libs.firebase.bom)), firebase.analytics, firebase.crashlytics, firebase.perf, implementation(project(":core:common")).
- Recreate the 4 firebase files under lava.api.app.firebase referencing lava.api.app.BuildConfig.
- This duplicates ~250 lines and violates the spirit of the Decoupled rule; only acceptable as a time-boxed transitional step with a tracked extraction TODO.

Application init (both options) — ApiApplication.onCreate()

Mirror LavaApplication exactly:

```
@Inject lateinit var analytics: AnalyticsTracker // from the
Hilt graph
// ... in onCreate(), AFTER super.onCreate():
FirebaseInitializer.initialize(
    crashlytics = { runCatching {
        Firebase.crashlytics }.getOrNull() },
    analytics = { runCatching {
        Firebase.analytics }.getOrNull() },
    performance = { runCatching {
        Firebase.performance }.getOrNull() },
    isDebug = BuildConfig.DEBUG,
    versionName = BuildConfig.VERSION_NAME,
    versionCode = BuildConfig.VERSION_CODE,
    applicationId = BuildConfig.APPLICATION_ID,
    warn = { msg, t -> Log.w(TAG, msg, t) },
)
```

Set a Crashlytics custom key distinguishing the artifact (e.g. setCustomKey("artifact", "api-app")) so api-app vs client crashes are separable in the shared Firebase project.

Manifest (both options)

No manifest change strictly required — FirebaseInitProvider is contributed by the google-services plugin's merged manifest automatically (same as :app). Keep ApiApplication as android:name.

(UNCONFIRMED: whether firebase-perf adds a manifest provider that needs an explicit `tools:node="merge"` — `:app` builds fine without one, so `api-app` should too, but a build is required to prove the manifest merges cleanly; no build was run per task constraint.)

Wiring the embedded Go server's errors to client-side Crashlytics (optional, §6.AC bridge)

Two independent paths already exist; the plan only needs to pick how they reach the dashboard:

- **Go REST bridge (server-side → Firebase directly):** set `LAVA_API_FIREBASE_CRASHLYTICS_ENABLED=true` for the embedded server. The embed reads `env`; `ApiEngineController/ApiEngineService` would need to pass that `env` into `NativeApiEngine`. (UNCONFIRMED: whether the embed currently forwards arbitrary `env` vars to the Go runtime — needs a read of `:core:apiengine` `NativeApiEngine` `env`-passing surface, out of scope for this read-only pass; flag for the implementation cycle.)
- **Kotlin bridge (server-side → app `AnalyticsTracker`):** if `NativeApiEngine.status()` / the engine exposes recent errors to Kotlin, the controller can forward them via `analytics.recordNonFatal(...)` with `feature="api-embed"`. This keeps a single client-side sink and avoids shipping a Go-side Firebase API key. **RECOMMENDED over the REST bridge** because it avoids putting Firebase credentials into the Go embed (§6.H surface reduction).

4. §6.H / operator-action items (the blocking items)

ID	Item	Who	Status
OA-1	Confirm <code>api-app/google-services.json</code> (already present, 2026-06-02, gitignored) is the GENUINE Firebase-console export for app-ids <code>digital.vasic.lava.api + digital.vasic.lava.api.dev</code> — NOT a placeholder. The agent registered the <code>package_names</code>	Operator	Likely already done — needs confirmation only.

ID	Item	Who	Status
	exist but cannot validate the API keys / mobilesdk_app_ids are real console values without reading secrets.		
OA-2	Confirm both api-app Firebase apps exist in the SAME Firebase project as the client apps (so api-app + client crashes share one dashboard). The package_name evidence shows all 4 app-ids; project-level co-location is UNCONFIRMED: (would require reading project_id from the JSONs — a secret-adjacent value, not read per task constraint).	Operator	Confirm in Firebase console.
OA-3	If the Go REST bridge path (§3) is chosen, the operator must provide the Firebase Crashlytics REST credentials/config for the embed and accept the §6.H risk of a key inside the Go .so. Avoidable by choosing the Kotlin-bridge path instead.	Operator	Only if REST bridge chosen.
OA-4	Do NOT commit either google-services.json (both already gitignored via **/google-services.json). Verify no agent step stages them.	Agent + reviewer	Enforced by .gitignore + pre-push.

The agent CANNOT and MUST NOT invent a google-services.json (§6.H). The good news: it does not need to — one already exists for the correct app-ids. The remaining operator action is **confirmation/validation**, not generation.

5. Anti-bluff / verification owed at implementation time (not done here)

- §6.O closure-log + validation test + Challenge for any Crashlytics issue this surfaces.

- A real-stack test that the api-app's AnalyticsTracker binding resolves and recordNonFatal reaches Crashlytics (mirror FirebaseInitializerTest / FirebaseProvidesModule coverage from :app).
 - §6.AC: confirm every catch path in :api-app production code (ApiEngineController, ApiEngineService, MdnsAdvertiser, ApiKeyStore) records non-fatals — currently they have no sink.
 - A build MUST be run (by the gradle-owning stream) to prove the google-services plugin accepts the existing api-app JSON and the manifest merges — this plan ran NO build per task constraint.
-

6. File evidence index (all read-only, this session)

- settings.gradle.kts — :api-app + :core:apiengine includes.
- api-app/build.gradle.kts — app-ids, plugins, deps (no firebase/core:common).
- api-app/src/main/AndroidManifest.xml — ApiApplication, services, provider.
- api-app/src/main/kotlin/lava/api/app/ApiApplication.kt — no Firebase init present.
- buildSrc/src/main/kotlin/AndroidApplicationConventionPlugin.kt — google-services + crashlytics plugins applied to all apps.
- buildSrc/build.gradle.kts — firebase/google-services gradle-plugin classpath.
- gradle/libs.versions.toml — firebase BOM/plugin versions + libs.
- app/build.gradle.kts:301-304 — firebase runtime deps.
- app/src/main/.../LavaApplication.kt — init pattern.
- app/src/main/.../firebase/{FirebaseAnalyticsTracker, FirebaseProvidesModule, FirebaseInitializer, NoOpAnalyticsTracker}.kt — impl/DI/initializer (app-private).
- core/common/src/main/kotlin/lava/common/analytics/AnalyticsTracker.kt — reusable interface.
- lava-api-go/internal/observability/nonfatal.go — Go-side RecordNonFatal + optional REST bridge.
- api-app/google-services.json + app/google-services.json — present, gitignored; package_names only inspected (no secret values read/printed).