

scripts/autonomous-qa/aggregate-evidence.sh — User Guide

Last verified: 2026-07-26 (LVA-018 script-docs backfill cycle)

Inheritance: HelixConstitution §11.4.18 (script docs); Lava §6.J / §6.AK (anti-bluff distribute gate) **Classification:** project-specific

Overview

Rolls up the autonomous-QA per-iteration verdicts (written by run-iteration.sh) into:

1. A cycle-level **CYCLE-SUMMARY.md** (both backends, per-backend + overall totals) under .lava-ci-evidence/autonomous-qa/<date>/.
2. The **§6.AK distribute-gate artifacts** that scripts/check-cycle-coverage.sh consumes, written to .lava-ci-evidence/distribute-changelog/firebase-app-distribution/ (the same --evidence-dir firebase-distribute.sh pins for the client app; both §6.AA stages share it):
 - cycle-coverage-map-<VER>.yaml — top-level version: + fixes: list
 - <VER>-test-evidence.json — version / channel / commit_sha / timestamp + test_results[]

Plan: docs/superpowers/plans/2026-06-29-autonomous-qa-backend-provider-matrix.md.

Usage

```
scripts/autonomous-qa/aggregate-evidence.sh \  
  --date <YYYY-MM-DD> --version <v> --channel <debug|release> \  
  --timestamp <ISO8601> [--evidence-dir <dir>]
```

--date, --version, --channel, --timestamp are required; --channel must be exactly debug or release. --evidence-dir overrides the distribute-changelog evidence directory (used by tests).

Anti-bluff properties (§6.J / §6.AK)

- Every number is derived from the actual `verdict.json` files on disk. A PASS/total is NEVER emitted that is not present in the data.
- A **missing** `verdict.json` is counted FAIL and noted (`verdict.json MISSING – counted FAIL`); a **corrupt** one (no/invalid verdict field) likewise — never silently skipped.
- Unparseable numeric fields default to 0 (never invented).
- **Only iterations whose verdict is PASS** become asserted claims in the cycle-coverage-map — a claim asserts the feature works; asserting a FAILED iteration would be the exact bluff §6.AK forbids. A cycle with zero PASS verdicts emits zero claims, explicitly.
- `test_results[]` records ALL iterations (PASS/SKIP/FAIL) — the full honest device-gate record — each tagged with device `CZ_API34_Phone-containerized` and the covering Challenge `lava.app.challenges.Challenge70AutonomousQaProviderMatrixTest [<backend>/<providers>/<query>]`, with `duration_seconds` recovered from the JUnit XML (`null` when absent).

Outputs

File	Content
<code>.lava-ci-evidence/autonomous-qa/<date>/CYCLE-SUMMARY.md</code>	Full per-iteration table (backend/providers/query/verdict/counts/note), per-backend totals, overall totals
<code><evidence-dir>/cycle-coverage-map-<VER>.yaml</code>	PASS-only claims, each mapped to the covering Challenge
<code><evidence-dir>/<VER>-test-evidence.json</code>	version/channel/commit_sha/timestamp + full <code>test_results[]</code>

Exit codes

- 0 — aggregation completed (a WARN is printed when no iterations exist under the date dir; the artifacts are still written, honestly empty)
- 2 — usage error (missing/invalid flags)

Companion files

- `scripts/autonomous-qa/run-iteration.sh` — the verdict producer

- `scripts/check-cycle-coverage.sh` (+ its doc) — the §6.AK gate that consumes the artifacts
- `scripts/firebase-distribute.sh` (+ its doc) — `pins --evidence-dir` for the client channel