

scripts/check-script-docs-sync.sh

— User Guide

Last verified: 2026-08-26 (§6.J corpus floor — 0 scripts ↔ 0 docs (1:1) and a partial corpus now refuse; LVA vacuous-pass sweep F12)
Inheritance: HelixConstitution §11.4.18 (script documentation mandate) + Lava §6.AD-debt closure (CM-SCRIPT-DOCS-SYNC)

Overview

Bidirectional drift detector between scripts/*.sh and docs/scripts/*.sh.md. Each script **MUST** have a matching doc file and vice versa.

This gate exists to prevent two failure modes:

- **Undocumented scripts:** new gate or helper added without an accompanying user guide. Future operators / agents have no entry-point to understand the script's purpose, usage, exit codes, or anti-bluff falsifiability rehearsal protocol.
- **Stale docs:** scripts removed but their docs left behind. Stale docs mislead readers into believing the script exists.

Usage

```
bash scripts/check-script-docs-sync.sh
```

Or with custom repo root (used by hermetic test):

```
LAVA_REPO_ROOT=/path/to/synthetic/repo bash scripts/check-script-docs-sync.sh
```

Exit codes

Code	Meaning
0	Gate clean — 1:1 mapping, and the corpus actually examined matches what the git index declares. The verdict names both:

Code	Meaning
1	gate clean: <N> scripts ↔ <M> docs (1:1) – corpus floor <N>/<M> (git-index-derived) satisfied. At least one orphan (paths printed to stderr with remediation directive), or a corpus directory was absent, or the gate examined an empty or partial corpus (added 2026-08-26 — see below)

How drift is detected

1. List scripts/*.sh and reduce to basenames (e.g. check-foo.sh).
2. List docs/scripts/*.sh.md and reduce to basenames + strip .md (e.g. check-foo.sh).
3. Compare the two sorted lists; anything in one but not the other is reported.

The detector is line-by-line oriented (not git-diff-based), so it catches all current-state drift regardless of which commit introduced it.

Portability

The script uses `find ... -type f | xargs -n1 basename` instead of GNU `find -printf '%f\n'` so it works on both Linux (GNU find) gate-hosts AND macOS (BSD find) developer workstations.

2026-08-26 update — §6.J corpus floor: 0 ↔ 0 is no longer a 1:1 pass

The defect

Two empty-corpus routes reported success:

Route	Old output	Old exit
scripts/ or docs/ scripts/ absent	skipping – scripts/ or docs/ scripts/ missing	0
Both present, both empty	gate clean: 0 scripts ↔ 0 docs (1:1).	0

The second is the sharper bluff: **0 == 0 satisfies the 1:1 invariant perfectly**, so the gate printed a positive verdict having compared nothing. "Nothing was learned" reported as "nothing failed" is the shape §6.J forbids — the same shape the clause-6.H credential floor in `scripts/check-constitution.sh` already guards against.

Because this gate is what makes CM-SCRIPT-DOCS-SYNC mean anything, an empty-corpus pass silently retired §11.4.18 enforcement for the whole run.

What the gate now refuses

Three refusals, all **exit 1**:

1. **A corpus directory is absent** — replaces the old exit-0 skip. States Examined: 0 scripts, 0 docs, and prints present / MISSING for each of the two directories so the reader can see which one is gone.
2. **Zero scripts compared against zero docs** — runs *before* the clean verdict, because that verdict is the thing that must not be reachable over an empty corpus. The message says so explicitly:
'0 scripts ↔ 0 docs (1:1)' is vacuously true and asserts nothing (§6.J).
3. **A partial corpus** — the gate examined a PARTIAL corpus, with every declared- but-absent path named individually. As the in-source comment puts it: a floor that only fires at exactly zero is a floor with one stair; 2 of 60 scripts present would otherwise pass as cleanly as 60 of 60.

Why the expectation is derived from the git index

Expected comes from `git ls-files -- scripts` and `git ls-files -- docs/scripts`, filtered to depth-correct *.sh and *.sh.md entries — never a literal count. A hardcoded number goes stale the moment a script is added or removed, and a stale floor is this same defect wearing a different mask.

That derived count is also what lets each refusal **distinguish its cause**: if the index declares these paths and the working tree lacks them, this is working-tree drift (a deletion, a partial checkout) and the remedy is `git checkout -- scripts docs/scripts`; if the index declares neither, this is not a Lava checkout or LAVA_REPO_ROOT points elsewhere, and the remedy is to set the root correctly. Two situations, two remedies, never one generic failure.

Two implementation notes for anyone editing this block:

- The counts use `awk`, not `grep -c`. `grep -c` exits 1 on a zero count, which under `set -e` inside a pipeline is its own hazard.
- `git ls-files` is wrapped in `{ ...; } || true`. Outside a repository it exits 128, and under `set -euo pipefail` that would abort the script with **no message at all** — fail-closed, but with a diagnosis so empty it sends the reader nowhere. Degrading to a declared count of 0 lets the not-a-checkout branch say what actually happened.

Note for hermetic-test authors

`LAVA_REPO_ROOT=/path/to/synthetic` still works, but a synthetic tree must now contain at least one `scripts/*.sh` and one matching `docs/scripts/*.sh.md`. A fixture with two empty directories used to pass; it now fails on floor 2, correctly, because it asserts nothing.

§6.J falsifiability rehearsal of the floor itself

1. `LAVA_REPO_ROOT=$(mktemp -d) bash scripts/check-script-docs-sync.sh` (an empty directory) → expect **exit 1**, a corpus directory is `ABSENT`, and the not-a-checkout branch of the diagnosis. Before this change: exit 0.
2. `mkdir -p $T/scripts $T/docs/scripts` in that same tree, re-run → expect **exit 1**, the gate compared `ZERO` scripts against `ZERO` docs. Before this change: exit 0 with gate clean: 0 scripts ↔ 0 docs (1:1).
3. In the real tree, `mv scripts/ci.sh /tmp/hold` → expect **exit 1**, examined a `PARTIAL` corpus, with `scripts/ci.sh` named as missing. Restore → exit 0.

The original orphan-detection rehearsal below still applies unchanged, and exercises the other direction (real 1:1 drift over a full corpus).

§6.J anti-bluff falsifiability rehearsal

1. Remove `docs/scripts/check-no-guessing-vocabulary.sh.md`.
2. Run `bash scripts/check-script-docs-sync.sh` → expect exit 1 with the orphan script listed.
3. Restore the doc; re-run → expect exit 0.

The deliberate-removal rehearsal proves the gate detects real drift in both directions.

Integration

Wired into `scripts/verify-all-constitution-rules.sh` as a standard gate. Pre-push hook transitively runs this via `scripts/check-constitution.sh` → `verify-all-constitution-rules.sh`.

Classification: project-specific (the convention is universal per HelixConstitution §11.4.18; the path layout is Lava-specific).