

scripts/systemd-status.sh — User Guide

Last verified: 2026-08-12 (initial version) **Inheritance:**
HelixConstitution §11.4.18 + Lava §6.B (Container "Up" is not application-healthy)

Overview

Convenience wrapper that reports the `lava-api-go` `systemd --user` unit's state **and** the underlying container's real health, in one command. This exists specifically because of §6.B: a `systemd` unit can report active (via `RemainAfterExit=yes`) while the container inside it has crash-looped — the unit's own status alone is a necessary, never sufficient, signal.

Usage

```
./scripts/systemd-status.sh
```

Output sections

1. `systemctl --user status lava-api.service` — unit-level state (active/inactive, linger dependency).
2. `loginctl show-user <you> --property=Linger` — confirms the unit can start at boot without a login session.
3. `tools/lava-containers/bin/lava-containers -cmd=status` — **the load-bearing signal**: real runtime (podman/docker), Healthy: true/false, LAN IP, and the live `/health` URL. This is the same status command documented in the root `CLAUDE.md` under "Run the proxy locally".

A healthy deployment shows the unit active AND `Healthy: true`. Either one alone is not sufficient evidence the API actually works — see the root `CLAUDE.md` §6.B forensic anchor (the `healthprobe` binary that silently failed while the container reported up).