

Spec — "Choose your API" two-section onboarding (operator request 2026-05-31)

Classification: project-specific.

Goal

The onboarding "Choose your API" step (feature/onboarding/.../steps/ApiSelectionStep.kt) gets TWO sections:

1. **On your network** (existing) — mDNS-discovered local `Endpoint.GoApi` instances.
 2. **Cloud / remote server** (NEW):
 - a manual entry field: address + port → user adds a remote API,
 - a list of pre-installed default options; we have none yet, so ONE placeholder: `https://lava.app:7777`.
- Titles/descriptions updated for the two-section layout.
 - UX: user continues with exactly ONE chosen API (local OR cloud), one selected instance.

Established contracts (researched 2026-05-31)

- `Endpoint` (core/models/lava/models/settings/Endpoint):
 - data class `GoApi(host: String, port: Int = 8443)` — HTTPS host:port. **Cloud uses this.**
 - data class `Mirror(host: String)` — rutracker mirror (NOT for cloud API).
- Selection flow (OnboardingViewModel):
 - `OnboardingAction.SelectApi(endpoint) → onSelectApi: connectionService.isReachable(endpoint) → on success endpointsRepository.add(endpoint) then step = Providers; on`

- fail apiConnectivity = Failure(reason). **Cloud reuses this verbatim — no new persist/probe.**
- RetryApiProbe re-probes state.selectedApi.
- Screen call site: OnboardingScreen.kt lines ~92-100 wires ApiSelectionStep(...).
- §6.R: lava.app + 7777 must NOT be source literals. Pattern = .env → buildConfigField (see app/build.gradle.kts lines 47-52). Add:
 - .env.example: LAVA_DEFAULT_CLOUD_API=https://lava.app:7777 (placeholder, committed).
 - app/build.gradle.kts:


```
buildConfigField("String", "DEFAULT_CLOUD_API", "\"\$
{env[\"LAVA_DEFAULT_CLOUD_API\"].orEmpty()}\"")
```
 - A small parser maps https://host:port → Endpoint.GoApi(host,port) (strip scheme, split host:port; default port 8443 if absent). Lives in a testable pure function (e.g. CloudApiDefaults.parse).

Implementation steps

Stream A — core feature (SINGLE-WRITER; one coherent change)

Files (all feature/onboarding/src/main/kotlin/lava/onboarding/):

1. OnboardingState.kt: add cloud-section UI state: val cloudAddressInput: String = "", val cloudDefaults: List<Endpoint> = emptyList(), val cloudAddressError: String? = null.
2. OnboardingAction.kt: add data class CloudAddressChanged(val value: String), data object AddCloudApi (parse cloudAddressInput → Endpoint.GoApi → SelectApi path), (default-option tap reuses existing SelectApi(endpoint)).
3. OnboardingViewModel.kt:
 - inject the default-cloud config (a provider reading BuildConfig.DEFAULT_CLOUD_API; provide via Hilt so tests can fake it). Populate cloudDefaults on entry (parse the configured default; empty list if blank).
 - handle CloudAddressChanged (reduce input + clear error).
 - handle AddCloudApi: parse input; on parse-fail set cloudAddressError; on success call onSelectApi(parsed).
4. steps/ApiSelectionStep.kt: render two titled sections. Section 1 = existing discovered list (title "On your network"). Section 2 = "Cloud / remote server": a text field bound to cloudAddressInput +

"Add" button (→ AddCloudApi) + the cloudDefaults rendered as ApiRow tappable (→ onSelect). Update headline/subtitle copy. Keep §6.Q (no LazyColumn in verticalScroll). Add contentDescription tags: "api-cloud-input", "api-cloud-add", "api-cloud-default", "api-cloud-error".

5. OnboardingScreen.kt: wire the new state + callbacks into ApiSelectionStep(...).
6. OnboardingHiltModule.kt: bind the default-cloud-config provider.

Stream B — §6.R wiring (independent-ish; touches .env.example + app/build.gradle.kts + a parser)

- .env.example line + app/build.gradle.kts buildConfigField + CloudApiDefaults parser (pure, unit-tested).

Stream C — tests (after A+B compile)

- feature/onboarding/src/test/.../OnboardingViewModelTest.kt: add cases — CloudAddressChanged updates input; AddCloudApi with valid https://h:port → probe→persist→Providers (real VM + fakes); AddCloudApi with garbage → cloudAddressError set, no advance; default-option tap → same success path. Falsifiability rehearsal recorded.
- CloudApiDefaults parser unit test (host/port extraction, default port, reject malformed).
- New Compose Challenge app/src/androidTest/.../ChallengeNNCloudApiSelectionTest.kt: drives the cloud section on a real emulator — types an address, taps Add (fake probe success) → asserts advance; taps the default option → asserts advance; asserts the two section titles render. KDoc FALSIFIABILITY REHEARSAL block. Pattern: copy Challenge26ApiDiscoveryAndConnectivityTest.kt harness (TestOnboarding Hilt fakes).

Stream D — build + §6.Z execute + distribute (serial, after C green)

- §6.Y bump 1.2.34-1054 → 1.2.35-1055 (app/build.gradle.kts) + lava-api-go 2.3.23 → 2.3.24 if touched.
- Auth rotation for new versionCode: fresh pepper + android-1.2.35-1055 client + UUID in .env (§6.AA). NOTE Gate-4 is now version-aware (commit 010c9ecc) — debug+release of 1055 share one pepper.

- build_and_release.sh (T7-backed; .containerignore now excludes .git-backup*+releases/).
- \$6.Z EXECUTE on Pixel_8/API35 host-direct+HVF: C00 + C01 + the new Cloud Challenge + Challenge26 (existing discovery still works). Real attestations.
- \$6.AA two-stage Firebase: --debug-only → --release-only. CHANGELOG 1.2.35-1055 entry + snapshot + evidence.
- Commit + push all (submodules + main) to github+gitlab; converge.

Parallelism balance (honest)

Stream A is single-writer (5 interdependent files). B's parser + C's tests + the Challenge are the genuinely-parallel pieces once A's public shape (actions/state names) is fixed. Recommended: land A's state+action shape first, then fan out B (parser+buildConfig) and C (3 test files) to subagents.

Channel caveat

Bash channel garbles/cancels large parallel batches on this host; the sync alias fires the push hook. Work in small single calls; route output to /tmp; verify HEAD + last-version via `git ls-remote`. Restore byte-churn before commits: `git checkout -- '*.pdf' '*.html' docs/workable_items.db constitution ; rm -rf constitution/scripts/workable-items/bin`.