

scripts/commit-push-all.sh

Dedicated commit + push pipeline that runs the pre-push hook logic as an **explicit stage** instead of a git hook.

Why it exists (2026-07-26)

The git pre-push hook (.githooks/pre-push, wired via core.hooksPath=.githooks) was blocking routine commit/push work: its Layer 2 stage runs the full scripts/ci.sh --changed-only gradle gate (Spotless + unit tests + strict constitutional scans) on **every** push, taking many minutes per invocation and making routine pushes effectively unusable.

Per operator directive, the hook is **disconnected** from git:

```
git config --unset core.hooksPath # main repo
```

.githooks/pre-push itself is kept unmodified — this script invokes its logic explicitly, so no gate is lost; it just no longer fires automatically inside git push.

What it does

Stage	Action
1	Fetch + fast-forward every initialized submodule to its default-branch tip; also inits + syncs the constitution nested submodules (anti_bluff, continuum, session_orchestrator, token_optimizer). helixqa's 27 third-party mirrors under tools/opensource/ are intentionally left uninitialized (reference mirrors, not build inputs).
2	Commits any dirty main-repo state (including updated submodule pins) with the given message.
3	Runs the pre-push hook checks against the exact push range — Layer 1 always (Seventh Law commit-message / forbidden-pattern checks); Layer 2 (scripts/ci.sh --changed-only) unless LAVA_SYNC_SKIP_CI=1.
4	Pushes the main repo to every configured upstream (github + gitlab) and any submodule that has unpushed commits to all of its remotes.
5	

Stage	Action
	Verifies: main repo + all submodules clean, zero unpushed commits anywhere (recursive). Prints GREEN: on success.

Usage

```
scripts/commit-push-all.sh "commit message"      # full pipeline
LAVA_SYNC_SKIP_CI=1 scripts/commit-push-all.sh "msg"  # Layer 1
only
LAVA_SYNC_NO_SUBMODULE_PULL=1 scripts/commit-push-all.sh "msg"
```

Idempotent — safe to re-run; each stage no-ops when there is nothing to do.

Stage contracts

- Every stage function returns 0 when its checks pass — including via an explicit `return 0`, never an incidental exit status (a trailing `[ ... ] && echo` under `set -e` once killed the pipeline after a fully-green validation stage; fixed 2026-07-26 in 725b066a).
- The pipeline NEVER pushes when any validation stage fails.

Relationship to the constitution

The Local-Only CI/CD rule requires the *gate* to run; it does not require the gate to be wired as a git hook. This script preserves every check and makes execution explicit and resumable. `--no-verify` is never used.