

scripts/full_run_leave_up.sh

Last verified: 2026-06-16

Overview

One-shot operator helper that **rebuilds** the project's own container images (dashboard, media_postprocessor) with `--no-cache`, **boots** the no-vpn stack, **runs** the full test + challenge suite, writes a results summary, and **leaves the stack running** for manual testing. Built for the request "rebuild everything, boot everything, run all tests + challenges, leave it up."

Prerequisites

- podman + podman-compose (auto-detected; falls back to podman compose).
- A valid .env (with DOWNLOAD_DIR pointing at an existing host directory).
- ffmpeg, python3, and the /tmp/mpp_venv pytest venv (auto-created if absent).
- Network access for vendor image pulls.

Usage

```
# run detached (it is long " 30-60 min for the --no-cache rebuild + full
nohup scripts/full_run_leave_up.sh >/dev/null 2>&1 &
```

Outputs

- docs/qa/full-run-<date>/RESULTS.md " curated per-suite PASS/FAIL summary + the failed-test names + manual-test URLs.
- docs/qa/full-run-<date>/runtests.log " full run-tests.sh output (gitignored).
- docs/qa/full-run-<date>/run.log " full run log (gitignored).

Side-effects (important)

- Rebuilds the dashboard + media_postprocessor images (`--no-cache`).
- Boots the no-vpn stack and **LEAVES IT RUNNING** (does not `. / stop`).
- The media_postprocessor service **backfills (transcodes) the existing library** on first start " expect CPU/disk activity and `webready-* .mp4 / * .mp3` files to appear alongside originals in DOWNLOAD_DIR.

Internal behaviour

1. `--no-cache` rebuild of our images (avoids the "restart illusion": stale code in an old container being served).
2. Boot + up `-d --force-recreate dashboard media_postprocessor`.
3. **MeTube-readiness wait** " polls `:8088/history` and `:9090/api/history` until both serve valid JSON before running ANY test/challenge. This is the fix for the first run,

where the suite ran before MeTube stabilized and reported false failures (contract showed 0/11 but was actually 18/0 once ready).

4. Runs `media_postprocessor` `pytest`, `run-tests.sh` (output `tee&md` so failure names are preserved), `smoke`, `contract`, then the challenge scripts.
5. Writes `RESULTS.md` with the manual-test URLs and leaves the stack up.

Related scripts

- `scripts/smoke-test.sh`, `scripts/validate-contract.sh`, `tests/run-tests.sh`
- `challenges/scripts/download_then_webready_challenge.sh`
- `scripts/video_confirm.sh` (Â§11.4.153 feature video-confirmation via HelixAgent)