

conventions

Conventions

The genome-init scan reported “No standard lint/format configs detected.” That is accurate — there is no ESLint, Prettier, gofmt-CI or RuboCop config at this root. The conventions below are the ones actually enforced, by gate scripts, by governance carriers, or by review.

Detected by scan

- No standard lint/format configs at the repository root.
- Enforcement lives in gate scripts (`_tools/*.sh`, `_tests/*.sh`) and in `.github/workflows/ci.yml`, not in linter config files.

Commits

- **Use the commit wrapper.** `commit "<message>" → git add . + git commit`
 - `push_all.sh`, which reads `upstreams/*.sh`. No direct `git add / git commit / git push` on the main repo (CLAUDE.md:95-96, :174-181).
- The wrapper stages **everything untracked** — verify `.gitignore` first.
- Never force-push without explicit per-session authorization and a green \$9.1.5 post-op gate.
- Recent history on main is dominated by Auto-commit subjects; release commits use the tag-prefixed form seen on v1.7.1, v1.7.2, v1.8.0.

File layout

- English source content in `_content/` {docs,portfolio,products,sites}/; translations in `_content_<lang>/` — 14 language siblings, same subtree shape minus portfolio/.

- Top-level `_`-prefixed directories are tooling/source (`_tools`, `_tests`, `_content*`, `_analysis`); unprefixed ones are checkouts or outputs.
- Generated site pages belong to `_tools/gen/`; do not hand-edit them inside the site submodules.
- Evidence is tracked on purpose: `.gitignore` carries an explicit `!_tests/evidence/` negation.

CSS / design system

- All classes are `od-` prefixed; all values are `var(--od-*)`. No ad-hoc CSS (`design-system/README.md`).
- Load order: brand CSS → `components-extended.css` → `motion/animations.css`.
- Dark theme defined in **both** `:root[data-theme="dark"]` and `@media (prefers-color-scheme: dark)`.
- Every interactive control ships a `:focus-visible` ring and a `prefers-reduced-motion` guard.

Governance carriers

- Five root carriers must stay in lockstep: `CLAUDE.md`, `AGENTS.md`, `QWEN.md`, `GEMINI.md`, `Constitution.md`. The four agent carriers are byte-identical from line 24 — verify with `tail -n +24 <file> | sha256sum`.
- Every carrier opens with `## INHERITED FROM` (pointer inheritance, never `@import`).
- In this repository the submodule path is `submodules/constitution/`, **not** the `constitution/` used by the constitution's own prose and templates. Any quoted `constitution/<file>` means `submodules/constitution/<file>` here (`CLAUDE.md:41-47`).

Language in reports

- No likely / probably / maybe / seems / appears when reporting a cause (§11.4.6).
- Unrunnable checks are `SKIP-with-reason`, never a pass.
- Deviations are disclosed inline — e.g. the §11.4.65 note at the top of `Constitution.md` and `docs/constitution-adoption/README.md` declaring the missing `.html/.pdf` siblings as known gap G8.

Toolchains

Go 1.26 · Node 20 · Ruby 3.3 + Bundler · poppler-utils · tesseract-ocr (CLAUDE.md:132-134). _tools/gen/go.mod declares module vasic.digital/tools/gen, go 1.26.