

README

Example: Static Landing Page (real e2e snapshot)

This directory is a **verbatim snapshot** of an end-to-end run produced by `scripts/e2e-agent-claude.sh`.

A real Claude Code session was driven through the full SuperSpec workflow (7 stages, all spec-kit + superspec slash commands), and every artifact written to disk by the agent was copied here unchanged. Nothing in this folder is hand-edited — it shows you exactly what spec-kit + superspec look like after a full run.

The end product (`web/index.html`) is a standalone, dependency-free landing page for the SuperSpec project itself — open it in any browser:

open `examples/static-landing-page/web/index.html`

What was generated, in order

Stage	Slash command	Artifact(s) added
1	<code>/speckit.constitution</code>	<code>.specify/memory/constitution.md</code>
2	<code>/speckit.specify</code>	<code>specs/001-static-landing-page/spec.md</code> + <code>checklists/requirements.md</code>
3	<code>/speckit.superspec.brainstorm</code>	(in-place edits to <code>spec.md</code> — Edge Cases, Open Questions, Brainstorm Log)
4	<code>/speckit.plan</code>	<code>plan.md</code> , <code>data-model.md</code> , <code>research.md</code> , <code>quickstart.md</code>
5	<code>/speckit.tasks</code>	<code>tasks.md</code> (29 tasks, 6 phases)
6	<code>/speckit.superspec.execute</code>	

Stage	Slash command	Artifact(s) added
		web/index.html + progress.yml (every task marked complete)
7	/speckit.superspec.review	checklists/review.md (P1/ P2/P3 readiness verdicts)

Directory layout — and why it matters

```

examples/static-landing-page/
├─ CLAUDE.md                                ← agent context file
(spec-kit init)
├─ .specify/
│   └─ memory/
│       └─ constitution.md                ← project constitution
(Stage 1)
├─ specs/
│   └─ 001-static-landing-page/          ← THIS feature's working
folder
│       └─ spec.md                        ← what & why (Stage 2 +
3)
│           └─ plan.md                    ← how (Stage 4)
│               └─ data-model.md          ← Stage 4 sidecar
│                   └─ research.md         ← Stage 4 sidecar
│                       └─ quickstart.md   ← Stage 4 sidecar
│                           └─ tasks.md     ← T001..T029 (Stage 5)
│                               └─ progress.yml ← live execution state
(Stage 6)
│       └─ checklists/
│           └─ requirements.md            ← Stage 2
│               └─ review.md             ← Stage 7
└─ web/
    └─ index.html                        ← the actual deliverable
(Stage 6)

```

Two paths people get wrong — both are illustrated above:

- The **constitution** lives at `.specify/memory/constitution.md`, **not** at `memory/constitution.md` and **not** at the repo root.
- Feature folders live at `specs/NNN-<slug>/`, **not** at `.specify/specs/....` Spec-kit's `create-new-feature.sh` hard-codes `SPECS_DIR="$REPO_ROOT/specs"`; there is no other option (unless you explicitly set `SPECIFY_FEATURE_DIRECTORY`).

Reproducing this snapshot

```
# from repo root
export ANTHROPIC_API_KEY=...      # or `claude login` first
scripts/e2e-agent-claude.sh
```

The script will spin up a fresh temp workdir, run the same 7-stage chain, and assert 23 invariants on the resulting tree. To resume from a specific stage (useful if Anthropic returns a transient socket error):

```
E2E_RESUME_WORKDIR=/path/to/prior/workdir \
E2E_RESUME_FROM=5 \
scripts/e2e-agent-claude.sh
```

What this is not

- Not a runnable example project — `web/index.html` is the only thing meant to be opened. The other files are documentation of the *process* that produced it.
- Not a template — copy `templates/` from the repo root for that.
- Not regenerated by CI. It is a hand-curated snapshot; refresh it manually whenever the workflow changes substantially.