

scripts-jekyll

Hardcoded-content audit — build/scripts/tooling + Jekyll layer

Read-only, multi-pass audit. Mandate: visitor-facing content must be DATA-DRIVEN (sourced from `_data/ui.json`, `MV_I18N`, `ui-i18n.json`, `pdf-i18n.json`, `_content/**`), never baked into scripts or layouts.

VIOLATION = visitor-facing prose/copy/labels/metrics/alt-text hardcoded in a script/layout instead of a data/i18n source. NOT a violation = HTML/CSS structure, Liquid/JS control flow, config keys, build logic, brand names, URLs, email/handle identifiers, schema.org enum values, endonym language names, or text already sourced via `{{ site.data.ui[...] }}` / `data-i18n / T() / t()`.

Scope covered: `_tools/pdf/build-pdfs.sh` (+ `pdf-i18n.json`), `_tools/gen/build.sh`, `_tools/deploy-langs.sh`, `_tools/translate/*`, `_tools/od/*`, `milosvasic.ru Jekyll` (`_config.yml`, `_layouts/*.html`, `_includes/*` [none exist], `_data/*`, `assets/js/*.js`), `vasic.digital` shells. Cross-referenced against the `i18n/data` sources. The Go generator under `_tools/gen/*.go` is the tooling that renders the sites, so it is included where it bakes content (flagged as “generator” — beyond the literal shell list but central to the mandate).

Summary counts

Severity	Count
HIGH	2
MED	5
LOW	6

Clean (no violations): `_tools/gen/build.sh`, `_tools/deploy-langs.sh`, `_tools/gen/shells.go`, `_tools/gen/seo.go`, `_tools/gen/i18n.go`, `_layouts/default.html`, `_data/ui.json` (fully localized ×15), `assets/js/i18n.js`, `assets/js/main.js`, `_tools/translate/*`, most of `_tools/od/*`, vasic.digital generated shells.

Prioritized fix list

1. **[HIGH]** Populate `_tools/pdf/pdf-i18n.json` for all 14 non-EN languages (F-1).
 2. **[HIGH]** Localize the article “Read more” modal strings in `articles.js` (F-6).
 3. **[MED]** Localize PDF figure alt text (F-2).
 4. **[MED]** Move PDF metric values out of the script into data (F-3).
 5. **[MED]** Move creativeHeadings editorial section-heading copy out of the generator (F-7).
 6. **[MED]** Localize the two hero alt texts in `home.go` (F-8).
 7. **[LOW]** F-4, F-5, F-9, F-10, F-11, F-12.
-

PASS 1 — shell scripts emitting content

F-1 **[HIGH]** `pdf-i18n.json` holds ONLY en; every non-EN PDF renders English chrome

- File: `_tools/pdf/pdf-i18n.json:1-28` (top-level keys = `["en"]` only)
- Consumer: `_tools/pdf/build-pdfs.sh:164-175` `t()` — on a missing `lang/key` it returns the EN value + prints `WARN ... EN fallback`.
- The script header (lines 154-161) claims the strings live in `pdf-i18n.json` “EN populated ... 14 langs via the HelixTranslate pipeline + reviewer.” **The 14 translations were never added** — only en exists. So `build-pdfs.sh <lang>` for `ru/sr/de/es/fr/be/zh/kk/hi/ja/ko/ar/tr/fa` emits English for EVERY chrome string: cover eyebrow/role/tagline (`t cv.* / cover.* / pf.*`, lines 474-498), the “At a glance” metric labels (478, 500), the “Selected architecture” heading (`t pf.figures.heading`, 506) and all three figure captions (512-514) — in the personal CV/Cover-Letter/Portfolio AND the vasic.digital company Portfolio (569).
- Why a violation: visitor-facing PDF copy is untranslated in 14 languages. The externalization is HALF-DONE — mechanism is data-driven (good), data is missing (the leak).

- Remediation: add the 14 language blocks to pdf-i18n.json (same keys as en) via the translation + review pipeline. Until then non-EN PDFs are English-chrome.

F-2 [MED] PDF figure alt text hardcoded in English

- File: `_tools/pdf/build-pdfs.sh:512-514`
- Literals: `alt="HelixAgent ensemble debate flow",`
`alt="HelixCluster distributed compute control plane",`
`alt="LLMsVerifier verification source of truth"`
- Only the figure *captions* are localized (`t pf.figure.*`); the alt descriptions are literal English and are embedded in every non-EN PDF (PDF/UA alt). Product names are legit glossary brands; the descriptive tail is prose.
- Remediation: add
`pf.figure.helixagent.alt / .helixcluster.alt / .llmsverifier.alt`
to pdf-i18n.json and render via `t`.

F-3 [MED] PDF “At a glance” metric VALUES baked into the script

- File: `_tools/pdf/build-pdfs.sh:478` (2009, 140+, 43, 6+) and `:500` (140+, 43, 25, 439)
- Factual metrics (repos governed, providers unified, distros provisioned, passing tests) hardcoded as literals in the tooling. Language-neutral, but the audit mandate explicitly names “metrics” as content that must be data-driven.
- Remediation: source from a data file (e.g. a non-translatable metrics block in pdf-i18n.json, or `_content` data) so the figures have one source of truth.

F-4 [LOW] PDF unknown-document fallback branch hardcodes English

- File: `_tools/pdf/build-pdfs.sh:520`
- Literal: `role="AI Engineer"; hright="Document";`
`eyebrow="Document"; tagline=""; contact="milosvasic.ru"`
- Dead in normal runs (only reached for a doc basename other than cv/cover-letter/portfolio) but is an un-localized English literal.
- Remediation: route through `t()` or drop the branch.

F-5 [LOW] PDF contact lines hardcoded in the script

- File: `_tools/pdf/build-pdfs.sh:477, 484, 492, 498`
- Literals: `<b>milos85vasic@gmail.com</b> ... milosvasic.ru ...`
`vasic.digital ... GitHub: ...`

- Borderline: these are language-neutral identifiers (email/URLs/ GitHub org handles), not translatable prose — not a strict violation, but they are content baked into the script rather than a data file.
- Remediation (optional): move to a data file for single-source maintenance.
- NOTE (not a violation): `build-pdfs.sh:244 @bottom-left` content: "milosvasic.ru · vasic.digital" is a brand/URL footer (identifier), legitimately in the print stylesheet.

deploy-langs.sh / gen build.sh — CLEAN

- `_tools/deploy-langs.sh` and `_tools/gen/build.sh`: only build/ deploy logic and operational echo/commit-message strings (not visitor-facing). No content.
-

PASS 2 — Jekyll layout/include hardcoded text

_layouts/default.html — CLEAN (exemplary)

- Every chrome string (skip link, primary nav, lang/theme/menu aria+title, footer text, download-modal heading/choose/close) is rendered from `site.data.ui[page.lang]` with an explicit per-key ... | default: `site.data.ui['en'][...]` and carries `data-i18n*` so `i18n.js` re-localizes at runtime (lines 39-99).
- `_data/ui.json` is fully populated for all 15 languages (verified) — the server-side fallback chain is genuinely localized, not English-masquerading.
- `_includes/` does not exist (nothing to audit).

F-9 [LOW] Download-modal static placeholders (no-JS only)

- File: `_layouts/default.html:88` `<h3 id="dl-title" class="dl-doc-name">CV</h3>` and `:91-93` the static EN / SR / RU dl-lang rows.
- These are overwritten at runtime by `downloads.js` (`nameEl.textContent, render()`), so JS users never see them; the language names shown are endonyms. With JS disabled a no-op English-ish placeholder shows. Low impact.
- Remediation (optional): make the placeholder `dl-doc-name` use `data-i18n="dl.cv"`.

F-10 [LOW] `_config.yml` site tagline/description are English-only

- File: `milosvasic.ru/_config.yml:2` (tagline) and `:3-7` (description)
 - Feed `{% seo %}`. These are the site-level source-of-truth defaults; the Go-generated localized pages carry their own localized SEO (`seo.go + T()`), so impact is limited to any Jekyll-rendered localized page, which would emit English `<meta description>`. Legitimate as EN source, flagged for awareness.
 - Remediation: if Jekyll ever renders non-EN standalone pages, override description per-page/lang; otherwise acceptable.
-

PASS 3 — `_config.yml` visitor-facing values

Covered under F-10. All other keys (title, url, author, social links, logo, plugins, exclude, sass) are legitimate config / identifiers, not violations.

PASS 4 — JS hardcoded user-facing strings (not from `MV_I18N` / `_data`)

F-6 [HIGH] `articles.js` article-modal strings hardcoded in English

- File: `milosvasic.ru/assets/js/articles.js:27-33`
- Literals (`I18N_DEFAULTS`): `loading`: "Loading...", `close`: "Close", `error`: "Sorry, this article could not be loaded.", `retry`: "Retry", `dialog`: "Article".
- `articles.js` does **not** read `window.MV_I18N`. Its `i18n()` (lines 46-52) only checks a `data-i18n-<key>` attr on the trigger or `<html>`, then falls back to these English literals. Cross-ref: those `data-i18n-*` attributes are set NOWHERE in the repo (the only grep hit is the comment on `articles.js:10`). So the "Read more" modal shows English Loading... (every open), the error message, Retry, the close aria-label, and the Article dialog aria-label in ALL 14 non-EN languages.
- Severity: Loading... is shown on every article open → HIGH; error/retry/close/ dialog are MED (error/transient/all) but share the same root cause.
- Remediation: add `article.loading` / `article.close` / `article.error` / `article.retry` / `article.dialog` to `MV_I18N` (and `_data/ui.json`) and have `articles.js` read `window.MV_I18N[lang]`;

OR emit those data-i18n-* attributes on <html> from default.html using site.data.ui.

assets/js/i18n.js — CLEAN

- Lines 22-777 are MV_I18N, the accepted i18n DATA source (15 langs, source copy). The apply logic (783-817) only copies dictionary values into data-i18n* nodes — no literals. MV_LANGS names (4-20) are endonyms.

assets/js/main.js — CLEAN

- Reads MV_I18N/MV_LANGS; theme glyphs */o (13) and code.toUpperCase()
 1. are non-prose UI symbols. No hardcoded copy.

F-11 [LOW] downloads.js missing dl.portfolio key → English fallback

- File: milosvasic.ru/assets/js/downloads.js:79 t('dl.portfolio', 'Portfolio')
 - dl.portfolio is absent from MV_I18N, so the English literal Portfolio is always used for the portfolio modal title. dl.cv/dl.cl DO resolve. “Portfolio” is near-universal, hence LOW.
 - LANG_NAMES (32-36) are endonyms — not a violation.
 - Remediation: add dl.portfolio to each MV_I18N language.
-

PASS 5 — generator baked content (tooling)

F-7 [MED] markdown.go bakes ~40 English editorial section headings

- File: _tools/gen/markdown.go:210-271 (creativeHeadings) + 275-284 (editorialHeading)
- Literals emitted as visible product-page <h2> on the EN site, e.g. “The problem we set out to solve”, “Why this exists”, “The itch we had to scratch”, “Why it changes the game”, “Hard problems, honest solutions”, “Under the hood”, “Status, told straight”. A per-slug hash swaps the canonical brief heading (e.g. ## Why we built it) for one of these variants.
- Why a violation: visitor-facing heading copy invented by the tooling, not sourced from _content. Cross-ref: non-EN product .md translate their headings (verified — DE uses ## Warum wir es entwickelt haben), so they do NOT match the English keys and pass through verbatim (no leak *today*); but the editorial

layer is EN-only, so non-EN pages show plain brief headings while EN shows polished variants, and any future localized doc that retained an English heading would emit an English editorial variant.

- Remediation: move the heading copy into per-language `_content/data` (or drop the editorializer so headings come straight from the localized markdown).
- Related observation (MED, i18n bug, not strictly baked *content*): `markdown.go:286-290` `specialProductSections` and `renderProductBody's find("short description"/"summary"/"long description")` (293-317) use English-only keys, so on non-EN product pages the hero-lede / opening-narrative framing is not applied (those sections render as ordinary labeled sections).

F-8 [MED] home.go hardcodes hero alt text in English

- File: `_tools/gen/home.go:196` `alt="Portrait of Miloš Vasić"` and `:206` `alt="Vasic Digital logo"`
- Emitted on every localized home; the `a11y` alt stays English for all 15 languages. (“Vasic Digital logo” is mostly brand; “Portrait of Miloš Vasić” is descriptive prose.)
- Remediation: source via `T(lang, "alt.portrait") / T(lang, "alt.logo")`.

Generator otherwise CLEAN

- `home.go`, `product.go`, `portfolio.go` render all visible text from data structures via `.render() / esc() + i18nAttr(data-i18n)` — content comes from `_content`. `seo.go` builds title/description/keywords from data / `T()`; its only string literals are `schema.org` enum values (`"DeveloperApplication"`, `"Cross-platform"`, `markdown.go` line ~246) which are language-neutral by spec. `shells.go` is CSS/SVG symbols + a single `T()`-sourced `aria-label`. `i18n.go` is the localization machinery (endonyms + `og:locale` maps are data).
-

PASS 6 — od / translate tooling

F-12 [LOW] od/build-preview.mjs form labels hardcoded

- File: `_tools/od/build-preview.mjs:93-94` — Name, Your name, Message, Say hello.

- This is an OpenDesign COMPONENT-PREVIEW harness (design-system showcase), not shipped visitor content. Noted for completeness; not a production violation.

`_tools/translate/*, other _tools/od/* — CLEAN`

- Pipeline processors (translate-content.sh, finalize-review.sh, glossary_protect.py, cyrillize_sr.py, check_terms.py, matrix.py, run-batch.sh; od/generate.sh, inject-diagrams.mjs, od-mcp-call.mjs, render-diagram.cjs, shoot.cjs, start-daemon.sh). Literals present are LLM prompt instructions / log lines / config, not visitor-facing output content.
-

vasic.digital shells

- vasic.digital/index.html is Go-generator BUILD OUTPUT (content from `_content`), not a hand-authored shell; the shell scaffolding (shells.go) is clean. No hardcoded content in the shells themselves.