

README

v1.8.0 Design-Token Visual Regression

Before/after visual-regression harness for the **v1.8.0 design-token change**. Read-only against production; writes only under `_tests/evidence/v180-visual/`.

The v1.8.0 change SHOULD be a **palette / type / space refinement** — a crimson tonal ramp plus fluid type & spacing — **not** a layout or structural change. So geometry should stay near-identical between before/ and after/; only colors (and possibly type sizing) should shift subtly. Any large geometric diff is a regression, not the intended change.

Page set (per site, 4 pages)

slug	vasic.digital	milosvasic.ru
home	/	/
product	/products/helixtrack.html	/products/catalogizer.html
portfolio	/portfolio/	/portfolio/
sr-home	/sr/	/sr/

Variants (3 per page)

- desktop-light — 1280px, data-theme=light
- desktop-dark — 1280px, data-theme=dark
- mobile-light — 390px, data-theme=light

2 sites x 4 pages x 3 variants = 24 shots per label. All captures are fullPage.

Determinism: navigation waits for networkidle; prefers-reduced-motion is emulated and a `*{animation:none;transition:none}` style is injected so diffs are palette-only, not motion-noise. Theme is seeded via `localStorage` (both sites' keys: `od-theme`, `mv-theme`) plus a forced `documentElement[data-theme]` after load.

Output layout

```
_tests/evidence/v180-visual/  
  shoot.mjs  
  README.md  
  before/    <site>-<page>-<variant>.png    (current live baseline –  
DONE)  
  after/     <site>-<page>-<variant>.png    (capture after v1.8.0  
deploys)
```

Workflow

1. **BEFORE (done)** — current live, pre-token-change (crimson MACHINA / terminal-brutalist):

```
node _tests/evidence/v180-visual/shoot.mjs --label before
```

→ 24/24 shots, all HTTP 200.

2. **AFTER** — once v1.8.0 is deployed to production, re-run with the same page set and variants:

```
node _tests/evidence/v180-visual/shoot.mjs --label after
```

To capture a staging/preview deploy instead of live, override the bases:

```
VASIC_BASE=https://staging.vasic.digital \  
MILOS_BASE=https://staging.milosvasic.ru \  
node _tests/evidence/v180-visual/shoot.mjs --label after
```

3. **DIFF** before/ vs after/ — filenames are identical between labels, so pairs line up 1:1.
 - **pixelmatch is NOT installed** in `_tests/node_modules` (only `pngjs` is). Either add it (`cd _tests && npm i -D pixelmatch`) for an automated per-pair diff, or do a **manual side-by-side** review of each of the 24 pairs.
 - Minimal automated diff once `pixelmatch` is present (writes `diff-*.png` and prints changed-pixel %):

```

// _tests/evidence/v180-visual/diff.mjs (create if
// desired)
import { readFileSync, writeFileSync, readdirSync } from
  'node:fs';
import { PNG } from 'pngjs';
import pixelmatch from 'pixelmatch';
const dir = new URL('.', import.meta.url).pathname;
for (const f of readdirSync(dir + 'before')) {
  const a = PNG.sync.read(readFileSync(dir + 'before/' +
    f));
  const b = PNG.sync.read(readFileSync(dir + 'after/' +
    f));
  const { width, height } = a;
  const out = new PNG({ width, height });
  const n = pixelmatch(a.data, b.data, out.data, width,
    height, { threshold: 0.1 });
  writeFileSync(dir + 'diff-' + f, PNG.sync.write(out));
  console.log(`${(100 * n / (width * height)).toFixed(2)}
    % ${f}`);
}

```

(Requires equal dimensions; if before/after heights differ, that alone signals a layout change worth investigating.)

Expectation for a clean v1.8.0

- Every pair has (near) identical dimensions.
- Diffs concentrate in colored surfaces / accents / text color — the crimson ramp — not in the position of elements.
- No new/missing sections, no reflow.