

README

OpenDesign Learning Kit

A **decoupled, reusable** CSS component library for learning / education platforms. Every class is namespaced `lk-`. The kit is **brand-neutral and theme-driven**: it consumes only the OpenDesign `--od-*` token layer (plus a small `--lk-*` layer derived from it), so it renders correctly in **light and dark** with zero code changes and never hardcodes a brand colour (except as documented token fallbacks).

- **No external dependencies. No build step. No framework.** Plain CSS custom properties and standard selectors.
- **Depends only on the OpenDesign token layer** (`brand-*/milosvasic.css`) — see Constitution §11.4.6 (no bluff): the `--od-*` names below resolve against the real OpenDesign contract.
- **Accessible focus** on every interactive element via `--od-focus`.
- **Respects prefers-reduced-motion: reduce** — non-essential motion is disabled while final visual states are preserved.

Files

File	Purpose
<code>kit-tokens.css</code>	The <code>--lk-*</code> token layer (radius, elevation, gap, ring geometry, flip, skeleton, tints) — all derived from <code>--od-*</code> .
<code>learning-kit.css</code>	The component library (all <code>lk-*</code> classes).
<code>demo.html</code>	Standalone page rendering every component in light and dark. Open directly in a browser.
<code>README.md</code>	This document.

Install / use

Load the OpenDesign token layer first, then the kit tokens, then the components:

```
<link rel="stylesheet" href="brand-milosvasic/milosvasic.css">
<link rel="stylesheet" href="learning-kit/kit-tokens.css">
<link rel="stylesheet" href="learning-kit/learning-kit.css">
```

Or with @import (order matters — tokens before components):

```
@import url("brand-milosvasic/milosvasic.css");
@import url("learning-kit/kit-tokens.css");
@import url("learning-kit/learning-kit.css");
```

Theme switching is inherited from OpenDesign: set data-theme="dark" / data-theme="light" on :root (or leave it to prefers-color-scheme). The kit needs no theme code of its own.

Standalone fallback. If the OpenDesign brand stylesheet is ever absent, kit-tokens.css supplies a neutral fallback palette via an @supports block so the kit still renders — but the OpenDesign layer is the intended dependency.

Kit tokens (kit-tokens.css)

All are declared on :root and derived from --od-*:

Token	Derived from	Purpose
--lk-radius-sm / --lk-radius / --lk-radius-lg / --lk-radius-pill	--od-radius-*	Component corner radii.
--lk-elev-1 / --lk-elev-2 / --lk-elev-3	--od-shadow-color	Elevation ramp (re-tints in dark).
--lk-gap-xs...xl	--od-space-*	Kit spacing scale.
--lk-ring-size / --lk-ring-thickness	— (structural)	Progress-ring geometry.
--lk-ring-track / --lk-ring-fill / --lk-ring-text	--od-surface-2 / --od-accent / --od-text	Progress-ring colours.
--lk-flip-dur / --lk-flip-ease / --lk-flip-perspective	--od-dur-slow / --od-ease-emphasized	Flashcard 3D flip.
--lk-skeleton-base / --lk-skeleton-	--od-surface-2 / --od-text	Loading shimmer.

Token	Derived from	Purpose
sheen / --lk-skeleton-dur		
--lk-tint-accent / --lk-tint-success / --lk-tint-danger	--od-accent / --od-success / --od-danger + --od-surface	Soft semantic washes.
--lk-lift / --lk-z-fab	— (structural)	Hover lift, FAB stacking.

Components

lk-card

Base surface card. Elements: lk-card__title, lk-card__body.

Variants: lk-card--interactive (lifts on hover/focus), lk-card--accent (leading accent rail). **Tokens:** --od-surface, --od-border, --lk-radius, --lk-elev-1/3, --od-accent, --od-focus.

```
<article class="lk-card lk-card--interactive lk-card--accent"
  tabindex="0">
  <h3 class="lk-card__title">Card title</h3>
  <p class="lk-card__body">Supporting copy.</p>
</article>
```

lk-track-card

Learning-track / course card with a media band and a linear progress footer. Elements: lk-track-card__media (drop an inside), lk-track-card__content, lk-track-card__eyebrow, lk-track-card__title, lk-track-card__desc, lk-track-card__footer, lk-track-card__progress, lk-track-card__progress-label. Set progress with the inline custom property --lk-progress (a percentage). **Tokens:** --od-surface, --od-border, --lk-elev-1/3, --od-accent, --od-surface-2.

```
<article class="lk-track-card" tabindex="0">
  <div class="lk-track-card__media"></div>
  <div class="lk-track-card__content">
    <span class="lk-track-card__eyebrow">12 modules · 6h</span>
    <h3 class="lk-track-card__title">Design Systems 101</h3>
    <p class="lk-track-card__desc">Tokens, components, theming and
      accessibility.</p>
  </div>
  <div class="lk-track-card__footer">
    <span class="lk-track-card__progress" style="--lk-progress:64%"></span>
    <span class="lk-track-card__progress-label">64%</span>
  </div>
</article>
```

```
</div>
</article>
```

lk-module-card

Compact lesson/module row: leading index, title + meta, trailing state. Elements: lk-module-card__index, lk-module-card__main, lk-module-card__title, lk-module-card__meta. **Variants/states:** lk-module-card--interactive, lk-module-card--done (accent index), lk-module-card--locked (dimmed, not-allowed). **Tokens:** --od-surface, --od-border, --od-accent, --od-on-accent, --od-surface-2, --lk-elev-1/2.

```
<div class="lk-module-card lk-module-card--done lk-module-card--
  interactive" tabindex="0">
  <span class="lk-module-card__index">✓</span>
  <span class="lk-module-card__main">
    <span class="lk-module-card__title">Introduction to tokens</
      span>
    <span class="lk-module-card__meta">Completed · 18 min</span>
  </span>
  <span class="lk-pill lk-pill--success">Done</span>
</div>
```

lk-flashcard

3D flip card with a front and back face. Toggle with .is-flipped on the root (e.g. via JS on click) — CSS also flips on :focus-within as a no-JS fallback. Elements: lk-flashcard__inner, lk-flashcard__face + lk-flashcard__face--front / lk-flashcard__face--back, plus content helpers lk-flashcard__kicker, lk-flashcard__term, lk-flashcard__definition. **Tokens:** --lk-flip-dur, --lk-flip-ease, --lk-flip-perspective, --od-surface, --od-accent, --od-on-accent, --lk-elev-2, --od-focus.

```
<div class="lk-flashcard" tabindex="0" role="button" aria-
  label="Flip to reveal">
  <div class="lk-flashcard__inner">
    <div class="lk-flashcard__face lk-flashcard__face--front">
      <span class="lk-flashcard__kicker">Term</span>
      <p class="lk-flashcard__term">Cascade</p>
    </div>
    <div class="lk-flashcard__face lk-flashcard__face--back">
      <span class="lk-flashcard__kicker">Definition</span>
      <p class="lk-flashcard__definition">The algorithm that
        resolves which CSS rule wins.</p>
    </div>
  </div>
</div>
```

lk-quiz-option

Selectable answer (<button> recommended). Elements: lk-quiz-option__marker, lk-quiz-option__text. **States:** default; lk-quiz-option--selected (or [aria-checked="true"]); lk-quiz-option--correct; lk-quiz-option--incorrect; plus :disabled / [aria-disabled="true"]. **Tokens:** --od-surface, --od-border, --od-accent, --lk-tint-accent, --od-success, --lk-tint-success, --od-danger, --lk-tint-danger, --od-focus.

```
<button class="lk-quiz-option lk-quiz-option--selected"
  type="button" aria-checked="true">
  <span class="lk-quiz-option__marker">B</span>
  <span class="lk-quiz-option__text">Selected option</span>
</button>
```

lk-progress-ring

Circular progress in two interchangeable forms.

- **SVG variant:** classes lk-progress-ring__svg, lk-progress-ring__track, lk-progress-ring__value. Drive the arc with stroke-dasharray (circumference) and stroke-dashoffset. For r="43" the circumference is 270.18.
- **Conic variant:** lk-progress-ring--conic — no SVG. Set --lk-progress (0–100, unitless) inline.

Both center a lk-progress-ring__label. **Tokens:** --lk-ring-size, --lk-ring-thickness, --lk-ring-track, --lk-ring-fill, --lk-ring-text.

```
<!-- SVG -->
<div class="lk-progress-ring" role="img" aria-label="72 percent
  complete">
  <svg class="lk-progress-ring__svg" viewBox="0 0 96 96">
    <circle class="lk-progress-ring__track" cx="48" cy="48"
      r="43"></circle>
    <circle class="lk-progress-ring__value" cx="48" cy="48" r="43"
      stroke-dasharray="270.18" stroke-dashoffset="75.65"></
      circle>
  </svg>
  <span class="lk-progress-ring__label">72%</span>
</div>

<!-- Conic -->
<div class="lk-progress-ring lk-progress-ring--conic" style="--lk-
  progress:45"
  role="img" aria-label="45 percent complete">
  <span class="lk-progress-ring__label">45%</span>
</div>
```

lk-pill / lk-badge

lk-pill — soft status/label token. **Variants:** lk-pill--accent, lk-pill--success, lk-pill--warning, lk-pill--danger; optional leading lk-pill__dot. lk-badge — tiny count badge; **variant** lk-badge--dot (indicator dot). **Tokens:** --od-surface-2, --lk-tint-accent, --od-accent, --od-success, --od-warning, --od-danger, --od-on-accent, --lk-radius-pill.

```
<span class="lk-pill lk-pill--success">Completed</span>
<span class="lk-pill"><span class="lk-pill__dot"></span>Neutral</span>
<span class="lk-badge">9+</span>
<span class="lk-badge lk-badge--dot" aria-label="new"></span>
```

lk-hero

Course / page hero band with a token-tinted radial wash. Elements: lk-hero__eyebrow, lk-hero__title, lk-hero__lede, lk-hero__actions. **Tokens:** --od-accent, --od-surface, --od-border, --od-text, --od-text-muted, --od-font-display, --lk-radius-lg.

```
<div class="lk-hero">
  <span class="lk-hero__eyebrow">Path · Frontend</span>
  <h2 class="lk-hero__title">Master Modern CSS</h2>
  <p class="lk-hero__lede">Twelve hands-on modules from tokens to
    container queries.</p>
  <div class="lk-hero__actions"><button>Start learning</button></div>
</div>
```

lk-stat

Metric tile. Elements: lk-stat__value, lk-stat__label, lk-stat__trend (+ lk-stat__trend--up / lk-stat__trend--down). **Tokens:** --od-surface, --od-border, --od-accent, --od-success, --od-danger, --lk-elev-1.

```
<div class="lk-stat">
  <span class="lk-stat__value">68%</span>
  <span class="lk-stat__label">Course progress</span>
  <span class="lk-stat__trend lk-stat__trend--up">▲ 12% this
    week</span>
</div>
```

lk-chip

Filter / tag chip. **States:** lk-chip--selected (or [aria-pressed="true"]). Optional trailing lk-chip__remove button. **Tokens:** --od-surface, --od-border, --od-accent, --od-on-accent, --od-focus, --lk-radius-pill.

```
<button class="lk-chip lk-chip--selected" aria-pressed="true">All</button>
<span class="lk-chip">React
  <button class="lk-chip__remove" aria-label="Remove React filter">x</button>
</span>
```

lk-skeleton

Loading placeholder with a shimmer sweep (@keyframes lk-shimmer). **Shapes:** lk-skeleton--text, lk-skeleton--title, lk-skeleton--line-sm, lk-skeleton--line-lg, lk-skeleton--avatar, lk-skeleton--thumb. **Tokens:** --lk-skeleton-base, --lk-skeleton-sheen, --lk-skeleton-dur, --lk-radius. Motion is removed under prefers-reduced-motion.

```
<div class="lk-card" aria-busy="true">
  <div class="lk-skeleton lk-skeleton--thumb"></div>
  <div class="lk-skeleton lk-skeleton--title"></div>
  <div class="lk-skeleton lk-skeleton--text lk-skeleton--line-lg"></div>
</div>
```

lk-nav

Horizontal learning nav / tab strip. Item: lk-nav__item; **active** via lk-nav__item--active, [aria-current="page"] or [aria-selected="true"] (accent underline scales in). **Tokens:** --od-border, --od-text-muted, --od-text, --od-accent, --od-focus.

```
<nav class="lk-nav" aria-label="Course sections">
  <a class="lk-nav__item lk-nav__item--active" href="#" aria-current="page">Overview</a>
  <a class="lk-nav__item" href="#">Modules</a>
  <a class="lk-nav__item" href="#">Practice <span class="lk-badge">3</span></a>
</nav>
```

lk-breadcrumb

Path trail (). Elements: lk-breadcrumb__item, lk-breadcrumb__link, lk-breadcrumb__sep (mark aria-hidden), and the current page via [aria-current="page"] on the item. **Tokens:** --od-text-muted, --od-text, --od-accent, --od-border, --od-focus.

```
<ol class="lk-breadcrumb">
  <li class="lk-breadcrumb__item"><a class="lk-breadcrumb__link"
    href="#">Home</a></li>
  <li class="lk-breadcrumb__sep" aria-hidden="true"></li>
  <li class="lk-breadcrumb__item" aria-current="page">Modern CSS</li>
</ol>
```

lk-fab

Floating action button (position: fixed, bottom-right). **Variant:** lk-fab--icon (circular, icon-only). **Tokens:** --od-accent, --od-accent-hover, --od-on-accent, --lk-elev-3, --od-focus, --lk-z-fab, --lk-radius-pill.

```
<button class="lk-fab">+ New note</button>
<button class="lk-fab lk-fab--icon" aria-label="Add">+</button>
```

lk-toast

Notification inside a stacking lk-toast-region. Elements: lk-toast__icon, lk-toast__body, lk-toast__title, lk-toast__msg, lk-toast__close. **Variants:** lk-toast--success, lk-toast--warning, lk-toast--danger (default is accent). Enter animation @keyframes lk-toast-in; disabled under reduced motion. **Tokens:** --od-surface, --od-text, --od-accent, --od-success, --od-warning, --od-danger, --lk-elev-3, --od-z-toast, --od-focus.

```
<div class="lk-toast-region">
  <div class="lk-toast lk-toast--success" role="status">
    <span class="lk-toast__icon">✓</span>
    <span class="lk-toast__body">
      <span class="lk-toast__title">Module complete</span>
      <span class="lk-toast__msg">You earned the Color & Contrast badge.</span>
    </span>
    <button class="lk-toast__close" aria-label="Dismiss">x</button>
  </div>
</div>
```

Accessibility & motion

- Every interactive control exposes a visible focus ring (outline: `2px solid var(--od-focus)`).
- Semantic marker colours on quiz options / pills use fixed white/near-black text where needed to hold WCAG AA contrast on green/amber/red in both themes (per §11.4.107), rather than a theme-flipping token.
- `@media (prefers-reduced-motion: reduce)` disables hover lifts, the flashcard flip transition, progress transitions, the skeleton shimmer and the toast enter animation, while keeping all final states visible.

Decoupling statement

This kit is **fully self-contained and reusable across projects**. Its only dependency is the OpenDesign `--od-*` token layer. It introduces no JavaScript requirement (the `demo.html` script is illustrative only), no framework binding, and no build tooling. Drop the two CSS files into any OpenDesign-tokened site and the `tk-*` components inherit that site's brand and theme automatically.

Version: 1.0.0