

CI-INVENTORY-11-4-156

CI inventory under Constitution §11.4.156

⚠ **SUPERSEDED IN PART** — **read before acting on any “Action required” cell.** This is a **forensic snapshot** of the audit window 21:15–21:34 on 2026-08-27, and every *measurement* in it stands exactly as recorded. What does **not** stand is its forward plan for milosvasic.ru (row 4, the standing-action paragraph, and §1 of “Operator actions this audit cannot perform”).

Later the same day the “*disable both*” decision was **partially reversed**:

- **Umbrella (.)** — .github/workflows/ci.yml → ci.yml.disabled **stands**; the rename has since been staged as recorded and the gates run from a local pre-push hook (scripts/pre-push-gates.sh + an installed .git/hooks/pre-push).
- **milosvasic.ru (row 4)** — the staged pages.yml → pages.yml.disabled rename observed at T1 was **never committed or pushed, and has been undone**. .github/workflows/pages.yml is **ACTIVE** and will stay active. gh api repos/milos85vasic/milosvasic.ru/pages returns build_type: "workflow": that workflow is the **sole** publish path for the live production site. There is no gh-pages branch, no docs/ folder, and the repository root is Jekyll SOURCE, so it cannot be served raw from a branch; _tools/deploy-langs.sh pushes source and then sleeps waiting for that workflow, so it is not a fallback. Operator’s overriding directive, verbatim: **“Make sure all pages websites work flawlessly! No website can be broken! All websites we have here are running deployed in production!”** milosvasic.ru is a **known, documented deviation** from §11.4.156 — **not an**

Override §11.4.156, which the rule forbids, and never to be recorded as one.

- **vasic.digital** — classified (c) **CLEAN** below on the correct basis that it has no root CI *file*. That remains true and is not an error, but it is **not the same as compliant**: verified 2026-08-27, `gh api repos/vasic-digital/vasic-digital.github.io/pages` returns `build_type: "legacy"`, and `pages build and deployment (dynamic/pages/pages-build-deployment)` runs on every push. The probe this inventory uses is file-based and cannot see that. **No file-level remedy exists** — there is no file to disable.

Full record: `DECISION-11-4-156-COMPLY.md` §0. Appendix A's raw output is a **T1 snapshot** and is preserved unedited as evidence of that moment, not as current state.

Scope: every git repository reachable from the vasic umbrella, fully recursively. **Audit type:** read-only. No CI file was created, edited, renamed or deleted by this audit. **Audit window:** 2026-08-27, approximately 21:15 → 21:29 +02:00 (Europe/Belgrade). **Umbrella HEAD at close of audit:** `f1e0c838bbabf14a47a13cd0ff209c3fa2db98df`
milosvasic.ru HEAD at close of audit:
`66c8d607b20f0d9e984cb0e06f10a2020ebd9a10`

The rule being applied

§11.4.156 (submodules/constitution/Constitution.md, line 9552)
mandates, in the parts that decide this inventory:

- **(A) Zero active CI at the repository ROOT.** “the only location a provider executes”.
- **(B) Disabled means a push triggers ZERO runs.** Delete, or rename to a non-active name (the §11.4.75 `.disabled` / `.disabled-local-only` convention). `if: false` jobs under `live on: triggers` are NOT compliant.
- **(C) Scope = repositories we author + push.** Vendored / third-party source whose `.github/workflows` or `.gitlab-ci.yml` sit BELOW the repo root are **INERT** — “a provider never executes a non-root config” — so they are **OUT of scope and MUST NOT be mass-edited** (§11.4.29 vendor-name exemption + tree integrity). The decisive test is: “*does a push to one of OUR upstreams trigger a run?*” — yes ⇒ disable; structurally inert ⇒ document and leave (§11.4.6 — verify inertness as FACT, never assume).

- **(E) Pre-push verification:** `git ls-files | grep -E '^\.github/workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$'` must return empty for authored repos.

The probe used throughout this document is the §11.4.156(E) probe widened to also catch GitLab pipeline includes:

```
git ls-files | grep -E '^\.github/workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
```

It is anchored to `^`, so it matches **only** root-level configuration — the only location a provider executes.

Repository enumeration — how the 16 repositories were found

`git submodule status --recursive` **cannot** enumerate this tree. It aborts:

```
fatal: no submodule mapping found in .gitmodules for path 'Upstreamable'
fatal: failed to recurse into submodule 'Upstreamable'
fatal: failed to recurse into submodule 'milosvasic.ru'
```

Enumeration was therefore done with `find . -name .git`, which is `gitlink-safe`: a submodule's `.git` is a **FILE**, not a directory. Every existence test in this audit used `-e`, never `-d`. `find` completed with `rc=0` (no permission-denied truncation) and `git worktree list` reports a single worktree, so no repository is hidden behind a linked worktree.

`find` returned **17** `.git` entries. **16** of them are functioning git repositories. The 17th is analysed in the “Non-repository `.git` file” section below.

Ownership determination

“Ours” is decided from `git remote -v` only. Owned upstream namespaces: `github.com/HelixDevelopment`, `github.com/vasic-digital`, `gitlab.com/helixdevelopment1`, `gitlab.com/vasic-digital`, `gitflic.ru/helixdevelopment`, `gitverse.ru/helixdevelopment`, and the `milosvasic`-owned namespaces `github.com/milos85vasic`, `gitflic.ru/milosvasic`, `gitlab.com/milos85vasic`, `gitverse.ru/milosvasic`. Full remote URLs for every repository are in Appendix A.

Inventory

#	Repository path (relative to umbrella root)	Remotes — ours?	Root-level CI files found (probe output)	Classification
1	. (umbrella)	YES — github.com/ milos85vasic/vasic (github, origin, upstream)	T0: .github/ workflows/ci.yml — T1: none (staged rename to ci.yml.disabled) — T2: .github/ workflows/zz- probe.yml (mutation probe, staged) — T3: none	(a) VIOLATION at T0 — remediated in flight, staged only
2	ai_interviewing	YES — github.com/ milos85vasic/ ai_interviewing	(none)	(c) CLEAN
3	design-toolkit	YES — github.com/ vasic-digital/ design-toolkit	(none)	(c) CLEAN
4	milosvasic.ru	YES — github.com/ milos85vasic/ milosvasic.ru + gitflic.ru/ milosvasic/ milosvasic-net-v-2	T0: .github/ workflows/ pages.yml — T1: none (staged rename to pages.yml.disabled)	(a) VIOLATION at T0 — remediation observed in flight at T1, t hen REVERSED; now a documented deviation

#	Repository path (relative to umbrella root)	Remotes — ours?	Root-level CI files found (probe output)	Classification
5	milosvasic.ru/ Upstreamable	UNDETERMINED — github.com/red-elf/ Upstreamable + gitflic.ru/red-elf/ upstreamable; the red-elf namespace is not in the owned- upstream list and is not named as owned in README.md or CLAUDE.md	(none)	(c) CLEAN — ownership is moot because there is nothing to disable
6	monetization	YES — github.com/ milos85vasic, gitflic.ru/ milosvasic, gitlab.com/ milos85vasic, gitverse.ru/ milosvasic (4 owned upstreams)	(none)	(c) CLEAN
7	submodules/ constitution	YES — github.com/ HelixDevelopment, gitflic.ru/ helixdevelopment, gitlab.com/ helixdevelopment1, gitverse.ru/ helixdevelopment, github.com/vasic- digital, gitlab.com/ vasic-digital (6 owned upstreams)	(none)	(c) CLEAN
8	submodules/ constitution/ submodules/ anti_bluff	YES — github.com/ vasic-digital/ anti_bluff	(none)	(c) CLEAN
9			(none)	(c) CLEAN

#	Repository path (relative to umbrella root)	Remotes — ours?	Root-level CI files found (probe output)	Classification
	submodules/ constitution/ submodules/continuum	YES — github.com/ vasic-digital/ continuum		
10	submodules/ constitution/ submodules/design- toolkit	YES — github.com/ vasic-digital/ design-toolkit	(none)	(c) CLEAN
11	submodules/ constitution/ submodules/ docs_chain	YES — github.com/ vasic-digital/ docs_chain + gitlab.com/vasic- digital/docs_chain	(none)	(c) CLEAN
12	submodules/ constitution/ submodules/ helix_perf_cache	YES — github.com/ HelixDevelopment/ helix_perf_cache	(none)	(c) CLEAN
13	submodules/ constitution/ submodules/ session_orchestrator	YES — github.com/ vasic-digital/ session_orchestrator	(none)	(c) CLEAN
14	submodules/ constitution/ submodules/ token_optimizer	YES — github.com/ vasic-digital/ token_optimizer	(none)	(c) CLEAN
15	submodules/superspec	NO — sole remote github.com/ WangX0111/superspec	.github/workflows/ ci.yml	(b) THIRD- PARTY / VENDORED
16	vasic.digital	YES — github.com/ vasic-digital/vasic- digital.github.io	(none)	(c) CLEAN

Counts

Classification	Count
Repositories scanned	16
	2

Classification	Count
(a) Ours, active root CI — VIOLATION (state at T0, start of audit)	
(a) still uncommitted at T1 (staged <code>.disabled</code> renames, not yet pushed)	2
(b) Third-party / vendored, out of scope	1
(c) Clean — no root-level CI	13
Ownership UNDETERMINED	1 (milosvasic.ru/Upstreamable; also CLEAN, so no action either way)

Note on the arithmetic: $2 + 1 + 13 = 16$. `milosvasic.ru/Upstreamable` is counted once, inside the 13 CLEAN repositories; its UNDETERMINED ownership is an orthogonal attribute, not a fourth bucket.

Repository 15 — submodules/superspec: why it is out of scope

This is the only case where an **active, root-level** workflow is being left in place. The reasoning, stated as fact rather than assumption:

1. Its root-level CI is real and active. `submodules/superspec/.github/workflows/ci.yml` declares on: `push: branches: [main]` and on: `pull_request`. A push to *its* upstream would trigger a run.
2. The §11.4.156(C) test is “**does a push to one of OUR upstreams trigger a run?**” For this repository the answer is **no**, because it has no owned upstream: `git remote -v` reports exactly one remote, `origin`, fetch and push both `git@github.com:WangX0111/superspec.git`. There is no `HelixDevelopment / vasic-digital / milosvasic` remote configured on it.
3. The umbrella’s own governance carrier corroborates this. `CLAUDE.md` (“Owned submodules”) states: “*submodules/superspec is third-party (upstream WangX0111/superspec) and is outside the owned-submodule set for tagging and propagation purposes.*”
4. The umbrella records this submodule as a **gitlink** (mode 160000, `c20ac6c1ba069cc9a72dacb8044b7b193d3dde81`), i.e. a bare commit SHA. Pushing the umbrella to `github.com/milos85vasic/vasic`

transmits the SHA, not the submodule's file tree, and GitHub Actions does not execute a submodule's workflows.

Therefore: **document and leave alone**. Editing it would be a §11.4.29 / tree-integrity violation and would create a permanent diff against an upstream we do not control.

Honest boundary (§11.4.6): items 1–4 are verified locally from the git index, the remote configuration and the governance carrier. What was NOT verified — because it requires network access this audit did not perform — is whether the operator holds push credentials to WangX0111/superspec. If such a push right exists and is ever exercised, this repository moves into scope. That is recorded here rather than papered over.

Non-root .github/workflows — verified inert, out of scope

Two distinct classes of non-root workflow exist in the tree. Both were checked for the trap the rule warns about: a config that *looks* nested but is actually sitting at some other repository's root. Neither is.

(i) .specify/extensions/superspec/.github/workflows/ci.yml — TRACKED in the umbrella

This is the case that most deserves scrutiny, because it **is** tracked in a repository we push (git ls-files in the umbrella returns it). It is nevertheless inert. Verified facts:

- The umbrella's root is <ext-volume-host>/Projects/vasic (git rev-parse --show-toplevel). The file sits three directories below that root, at .specify/extensions/superspec/.github/workflows/ci.yml. GitHub Actions reads only .github/workflows/ **relative to the repository root**.
- .specify/extensions/superspec is **not** a repository root. git -C .specify/extensions/superspec rev-parse --show-toplevel fails with fatal: not a git repository. It contains a stray **FILE** whose content is gitdir: ../../.git/modules/submodules/superspec, which resolves to .specify/extensions/.git/modules/submodules/superspec — a path that does not exist. It is a **broken gitlink**, left behind by the spec-kit extension installer that copied the superspec tree into place (see .specify/extensions/.registry, "source": "local", installed 2026-08-26T18:34:15Z).

- It is **not** a submodule of the umbrella: it does not appear in `.gitmodules`, and the umbrella index holds its 59 files as ordinary blobs (`git ls-files -s` shows modes 100644 / 100755 only — no 160000 gitlink for this path).
- The stray `.git` file is itself untracked (`git ls-files .specify/extensions/superspec/.git` returns nothing).
- No symlink aliases it up to the root: every `.github` and `workflows` path in the tree was tested with `-L` and all are real directories. The umbrella's root `.github/workflows` is a real directory containing exactly one entry.
- Content check: this file is **byte-identical** to `submodules/superspec/.github/workflows/ci.yml` (`cmp -s` reports identical). It is a vendored copy of the same third-party workflow.

Conclusion: structurally inert, out of scope, MUST NOT be edited. A push to `github.com/milos85vasic/vasic` triggers zero runs from this file.

(ii) `ai_interviewing/platform/frontend/node_modules/**` — untracked npm packages

6 `.github/workflows` directories containing 9 workflow files, all under `ai_interviewing/platform/frontend/node_modules/`:

Package	Workflow files
fast-uri	<code>ci.yml</code> , <code>lock-threads.yml</code> , <code>package-manager-ci.yml</code>
json-schema-traverse	<code>build.yml</code> , <code>publish.yml</code>
needle	<code>nodejs.yml</code>
reusify	<code>ci.yml</code>
rfdc	<code>ci.yml</code>
wildcard	<code>build.yml</code>

Doubly out of scope, both facts verified:

1. **Non-root.** They sit far below the `ai_interviewing` repository root (`git rev-parse --show-toplevel = ../vasic/ai_interviewing`), and none of the intervening directories is a repository — `find . -name .git` reports no `.git` anywhere under `node_modules`.
2. **Untracked.** `git -C ai_interviewing ls-files` matches **zero** CI paths at any depth. `git check-ignore -v` confirms the exclusion

rule: platform/frontend/.gitignore:10:/node_modules. They are never transmitted by a push at all.

Other CI providers — checked and absent

Each of the 16 repository roots was additionally checked, on disk, for Jenkinsfile, .circleci/, .travis.yml, .drone.yml, .woodpecker.yml, .woodpecker/, bitbucket-pipelines.yml, azure-pipelines.yml, .azure-pipelines/, .gitlab-ci.yml, .gitlab/, appveyor.yml and .cirrus.yml. Result: **NONE** at any of the 16 roots. GitHub Actions is the only provider present anywhere in this tree.

.specify/workflows/ exists at the umbrella but is a spec-kit workflow registry (workflow-registry.json + a speckit/ directory), not a CI provider path.

Concurrent remediation observed in flight

Two other agents were editing CI files while this audit ran. Both transitions were observed directly and are recorded rather than smoothed over, because the inventory rows above would otherwise be unreproducible.

- **T0** (≈21:15–21:25 +02:00). Umbrella HEAD f1e0c83; probe returns .github/workflows/ci.yml; git status --porcelain -- .github/workflows/ is empty (worktree matched HEAD). milosvasic.ru HEAD 66c8d60; probe returns .github/workflows/pages.yml; status empty. **Both are §11.4.156(A) violations at this point.**
- **T1** (≈21:28 +02:00). Both probes return empty. On disk: .github/workflows/ci.yml.disabled (15164 bytes) and milosvasic.ru/.github/workflows/pages.yml.disabled (1333 bytes). git status --porcelain reports RM .github/workflows/ci.yml -> .github/workflows/ci.yml.disabled in the umbrella and R .github/workflows/pages.yml -> .github/workflows/pages.yml.disabled in milosvasic.ru. Both HEADs unchanged — **the renames are STAGED, not committed, and not pushed.**
- **T2** (21:32:57 +02:00). A **new** file appeared in the umbrella index: git status --porcelain -- .github now reports A .github/workflows/zz-probe.yml alongside the ci.yml rename, and the §11.4.156(E) probe consequently returns .github/workflows/zz-probe.yml again. Its full staged content is 121 bytes:

```

name: probe
on:
  push:
    branches: [main]
jobs:
  noop:
    runs-on: ubuntu-latest
    steps:
      - run: echo probe

```

Read plainly, this is a §1.1 mutation-pair probe: a deliberately introduced active workflow whose purpose is to prove that a §11.4.156 gate FAILS when a root workflow reappears. This audit did not create it and did not remove it.

Had it survived into a commit it would have been a live violation on two counts: `on: push: branches: [main]` is a real trigger, so a pushed `zz-probe.yml` breaches §11.4.156(A) (active CI at the root) and §11.4.156(D) (no new CI may be added), and it would have silently undone the `ci.yml` remediation staged beside it. It did not survive — see T3.

- **T3 (21:34:04 +02:00).** `zz-probe.yml` is gone — removed from both the index and the working tree by whoever staged it, exactly as a mutation pair should end. `git status --porcelain -- .github` reports only `RM .github/workflows/ci.yml -> .github/workflows/ci.yml.disabled`; the §11.4.156(E) probe returns empty; `ls .github/workflows/` shows one entry, `ci.yml.disabled`. The T2 hazard is therefore **closed, not outstanding** — it is recorded above because a reader re-running the sweep between 21:32 and 21:34 would otherwise get a result this table could not explain, and because §11.4.6 forbids omitting an observed state.

A concurrent agent also staged `scripts/pre-push-gates.sh` (new file) during this window. This audit did not read or evaluate it; whether it implements the §11.4.156(E) pre-push check is outside what was verified here.

Standing action at close of audit (21:34): the umbrella and `milosvasic.ru` each hold a STAGED, UNCOMMITTED `.disabled` rename. Neither is pushed. Until push, both upstreams still serve an active workflow.

T4 (post-audit, same day) — the two diverged. The umbrella's rename stands and awaits commit + push. **`milosvasic.ru`'s rename was reverted:** `.github/workflows/pages.yml` is back and ACTIVE (verified — submodule `git status clean, git diff HEAD`

empty, YAML parses, build and deploy jobs intact), because it is the only thing that publishes the production site. Because that rename never reached a commit, **the live site was never interrupted**. See the banner at the head of this document.

The `.disabled` suffix is the §11.4.75 convention §11.4.156(B) explicitly sanctions: GitHub Actions matches only `*.yaml / *.yml` under `.github/workflows/`, so `ci.yaml.disabled` and `pages.yaml.disabled` is not a workflow file. **Until the umbrella's rename is committed and pushed, its pushed state still contains an active workflow and it remains non-compliant**. Compliance is claimed for the umbrella only after push, verified by re-running the §11.4.156(E) probe post-commit — and is **never** claimed for `milosvasic.ru`, which is knowingly and permanently outside the clause.

This audit did not touch either file.

Operator actions this audit cannot perform (§11.4.156 honest boundary)

File-level disabling stops FILE-triggered runs. It does not reach provider-side server settings. For `milosvasic.ru` specifically, the file being disabled is `pages.yaml`, a **GitHub Pages deployment** workflow. Two consequences the operator must decide on, neither of which an agent can action from the filesystem:

1. ~~Disabling `pages.yaml` removes the mechanism that publishes `milosvasic.ru`. GitHub may fall back to its built-in “pages build and deployment” action, which the file’s own header comment says was replaced precisely because it fails on the broken `Upstreamable` nested `gitlink`. Whether Pages should be switched to a `deploy-from-branch` source, or turned off entirely, is an operator decision.~~ **RESOLVED and REVERSED, same day**. The “may fall back” was the open question and it has been answered: `gh api repos/milos85vasic/milosvasic.ru/pages` returns **`build_type: "workflow"`** — there is **no** fallback. Pages delegates publishing entirely to `pages.yaml`, and switching to a `deploy-from-branch` source is not available either, because the repository root is Jekyll SOURCE (Liquid + front matter) with no `gh-pages` branch and no `docs/` folder to serve. Disabling `pages.yaml` would leave the production site with no publisher at all. **The operator decided: keep it.** *“Make sure all pages websites work flawlessly! No website can be broken! All*

websites we have here are running deployed in production!”

pages.yml is ACTIVE and stays active; milosvasic.ru is a documented deviation from §11.4.156, not an override.

2. Repository / organisation settings that no local file controls — org-default required workflows, branch-protection required checks, and provider-side scheduled exports — must be turned off in the provider UI. Changing them is still operator-only. **Their state is no longer beyond this repository’s reach, though:** it was the *file-level* probe used by this audit that could not see them, not the repository as a whole. Run

```
bash scripts/verify-provider-ci.sh
# 0 = no provider-generated triggering found
# 1 = provider-side triggering CONFIRMED
# 2 = COULD NOT DETERMINE – not a pass, and never to be
    recorded as one
```

It discovers the owned repositories from this checkout’s own remotes rather than from a list baked into a script, and queries the provider for Pages build_type, provider-generated pages build and deployment runs, branch protection / required checks, and Actions enablement. scripts/setup-agents-wizard.sh runs it as Step 9 and surfaces a confirmed finding as a manual step, because acting on one means opening a provider UI. **Every provider fact stated in this document is a dated observation.** Re-measure with the command above instead of quoting a table row as current.

3. **vasic.digital — a surface this inventory’s probe structurally cannot see.** It is classified **(c) CLEAN** in the table because it has no root CI *file*, which is true. It is nevertheless **not compliant**: verified 2026-08-27, gh api repos/vasic-digital/vasic-digital.github.io/pages returns build_type: "legacy", and the Actions run list shows pages build and deployment (dynamic/pages/pages-build-deployment, event dynamic) on 2026-08-27 and 2026-08-10. Every push starts a run **with zero workflow files in the tree**. Nothing in that repository can change this, and turning it off in the Pages UI would unpublish a production site. This is the general lesson of the §11.4.156 honest boundary made concrete: a file probe measures files, and “no file” is not “no runs”.

Related open gap: CLAUDE.md records **G4** — “.github/workflows/ci.yml is active at the repository root, which conflicts with anchor 11.4.156(A)”. This inventory is the evidence base for **the umbrella half** of G4; G4 is not closed by this document, only by the committed-and-

pushed umbrella rename plus a re-run probe — and **G4 as a whole will not close at all**, because `milosvasic.ru` and `vasic.digital` remain knowingly non-compliant by decision and by provider mechanics respectively.

Appendix A — raw per-repository command output

Every row in the table above is reproducible from the commands below. Run them from `<ext-volume-host>/Projects/vasic`.

A.0 — Enumeration

```
$ git submodule status --recursive
ed73d8558e289ca0254b4ccc45e0df810767d3ae ai_interviewing (heads/main)
efd2c3fb2f880aaf2baf7f4819ce28a1ce3609cb design-toolkit (v0.2.2-6-gefd2c3f)
66c8d607b20f0d9e984cb0e06f10a2020ebd9a10 milosvasic.ru (v1.8.0-6-g66c8d60)
94f9831b8aa0a1d4df23671d2e4600886aad0dcf milosvasic.ru/Upstreamable (heads/main)
fatal: no submodule mapping found in .gitmodules for path 'Upstreamable'
fatal: failed to recurse into submodule 'Upstreamable'
fatal: failed to recurse into submodule 'milosvasic.ru'
```

Because the recursive walk aborts, enumeration used `find`:

```
$ find . -name .git | sort
./ai_interviewing/.git
./design-toolkit/.git
./.git
./milosvasic.ru/.git
./milosvasic.ru/Upstreamable/.git
./monetization/.git
./specify/extensions/superspec/.git      <-- NOT a repository;
broken gitlink, see body
./submodules/constitution/.git
./submodules/constitution/submodules/anti_bluff/.git
./submodules/constitution/submodules/continuum/.git
./submodules/constitution/submodules/design-toolkit/.git
./submodules/constitution/submodules/docs_chain/.git
./submodules/constitution/submodules/helix_perf_cache/.git
```

```
./submodules/constitution/submodules/session_orchestrator/.git
./submodules/constitution/submodules/token_optimizer/.git
./submodules/superspec/.git
./vasic.digital/.git
```

```
$ find . -name .git > /dev/null; echo "rc=$?"
rc=0 # no permission-denied
truncation
```

```
$ git worktree list
<ext-volume-host>/Projects/vasic fle0c83 [main]
```

.git kind per repository (-e, never -d):

```
. DIRECTORY
ai_interviewing FILE ->
gitdir: ../.git/modules/ai_interviewing
design-toolkit FILE ->
gitdir: ../.git/modules/design-toolkit
milosvasic.ru FILE ->
gitdir: ../.git/modules/milosvasic.ru
milosvasic.ru/Upstreamable FILE ->
gitdir: ../../.git/modules/milosvasic.ru/modules/Upstreamable
monetization FILE ->
gitdir: ../.git/modules/monetization
.specify/extensions/superspec FILE ->
gitdir: ../../.git/modules/submodules/superspec (BROKEN – target
does not exist)
submodules/constitution FILE ->
gitdir: ../../.git/modules/submodules/constitution
submodules/constitution/submodules/anti_bluff FILE ->
gitdir: ../../../../.git/modules/submodules/constitution/modules/
submodules/anti_bluff
submodules/constitution/submodules/continuum FILE ->
gitdir: ../../../../.git/modules/submodules/constitution/modules/
submodules/continuum
submodules/constitution/submodules/design-toolkit FILE ->
gitdir: ../../../../.git/modules/submodules/constitution/modules/
design-toolkit
submodules/constitution/submodules/docs_chain FILE ->
gitdir: ../../../../.git/modules/submodules/constitution/modules/
submodules/docs_chain
submodules/constitution/submodules/helix_perf_cache FILE ->
gitdir: ../../../../.git/modules/submodules/constitution/modules/
submodules/helix_perf_cache
submodules/constitution/submodules/session_orchestrator FILE ->
gitdir: ../../../../.git/modules/submodules/constitution/modules/
submodules/session_orchestrator
submodules/constitution/submodules/token_optimizer FILE ->
gitdir: ../../../../.git/modules/submodules/constitution/modules/
submodules/token_optimizer
submodules/superspec FILE ->
```

```
gitdir: ../../.git/modules/submodules/superspec
vasic.digital
gitdir: ../.git/modules/vasic.digital
```

FILE ->

A.1 — . (umbrella)

```
$ git -C . rev-parse --show-toplevel
<ext-volume-host>/Projects/vasic
```

```
$ git -C . remote -v
github  git@github.com:milos85vasic/vasic.git (fetch)
github  git@github.com:milos85vasic/vasic.git (push)
origin  git@github.com:milos85vasic/vasic.git (fetch)
origin  git@github.com:milos85vasic/vasic.git (push)
upstream          git@github.com:milos85vasic/vasic.git (fetch)
upstream          git@github.com:milos85vasic/vasic.git (push)
```

```
# T0 (~21:15)
$ git -C . ls-files | grep -E '^\.github/workflows/.*\.ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
.github/workflows/ci.yaml
```

```
$ sed -n '71,78p' .github/workflows/ci.yaml
name: CI
```

```
on:
  push:
    branches: [main]
  pull_request:
    branches: [main]
```

```
# T1 (~21:28) – concurrent agent staged the rename
$ git -C . ls-files | grep -E '^\.github/workflows/.*\.ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
(no output)
```

```
$ git -C . status --porcelain -- .github
RM .github/workflows/ci.yaml -> .github/workflows/ci.yaml.disabled
```

```
$ ls -la .github/workflows
-rw-r--r-- 1 milosvasic milosvasic 15164 Aug 27 21:28
ci.yaml.disabled
```

Non-root CI tracked in this repository:

```
$ git -C . ls-files | grep -E '^(^|/)\.github/workflows/.*\.ya?ml$|^(^|/)\.gitlab-ci\.yaml$|^(^|/)\.gitlab/'
.specify/extensions/superspec/.github/workflows/ci.yaml      # (T1;
at T0 the root ci.yaml also appeared)
```



```
$ git -C . ls-files -s | awk '$1=="160000"'
160000 ed73d8558e289ca0254b4ccc45e0df810767d3ae 0 ai_interviewing
160000 efd2c3fb2f880aaf2baf7f4819ce28a1ce3609cb 0 design-toolkit
160000 66c8d607b20f0d9e984cb0e06f10a2020ebd9a10 0 milosvasic.ru
160000 54ed7b0f5add52821d18866facb5ee8c75adef69 0 monetization
160000 902979027a907051dc036668a9c353bd27aedf47 0 submodules/
constitution
160000 c20ac6c1ba069cc9a72dacb8044b7b193d3dde81 0 submodules/
superspec
160000 6e5411c21b3cd9c6df5addb543b1a07930c3bfa9 0 vasic.digital
```

Note .specify/extensions/superspec is absent from the 160000 list — it is tracked as ordinary blobs, not a gitlink.

A.2 — ai_interviewing

```
$ git -C ai_interviewing remote -v
github git@github.com:milos85vasic/ai_interviewing.git (fetch)
github git@github.com:milos85vasic/ai_interviewing.git (push)
origin git@github.com:milos85vasic/ai_interviewing.git (fetch)
origin git@github.com:milos85vasic/ai_interviewing.git (push)
upstream git@github.com:milos85vasic/ai_interviewing.git
(fetch)
upstream git@github.com:milos85vasic/ai_interviewing.git
(push)
```

```
$ git -C ai_interviewing ls-files | grep -E '^\.github/
workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
(no output)
```

```
# any depth, to prove node_modules workflows are untracked:
$ git -C ai_interviewing ls-files | grep -E '(^|/)\.github/
workflows/'
(no output)
```

```
$ git -C ai_interviewing check-ignore -v platform/frontend/
node_modules/needle/.github/workflows
platform/frontend/.gitignore:10:/node_modules platform/
frontend/node_modules/needle/.github/workflows
```

A.3 — design-toolkit

```
$ git -C design-toolkit remote -v
origin git@github.com:vasic-digital/design-toolkit.git (fetch)
origin git@github.com:vasic-digital/design-toolkit.git (push)
```

```
$ git -C design-toolkit ls-files | grep -E '^\.github/
```

```
workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
(no output)
```

A.4 — milosvasic.ru

```
$ git -C milosvasic.ru remote -v
gitflic git@gitflic.ru:milosvasic/milosvasic-net-v-2.git (fetch)
gitflic git@gitflic.ru:milosvasic/milosvasic-net-v-2.git (push)
github git@github.com:milos85vasic/milosvasic.ru.git (fetch)
github git@github.com:milos85vasic/milosvasic.ru.git (push)
origin git@github.com:milos85vasic/milosvasic.ru.git (fetch)
origin git@gitflic.ru:milosvasic/milosvasic-net-v-2.git (push)
origin git@github.com:milos85vasic/milosvasic.ru.git (push)
upstream      git@gitflic.ru:milosvasic/milosvasic-net-v-2.git
(fetch)
upstream      git@gitflic.ru:milosvasic/milosvasic-net-v-2.git
(push)

# T0 (~21:15)
$ git -C milosvasic.ru ls-files | grep -E '^\.github/
workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
.github/workflows/pages.yml

$ git -C milosvasic.ru log -1 --format='%H %ad %s' --date=iso
-- .github/workflows/pages.yml
fae3b2457900a6771949e1b2cb6bf930428031c9 2026-06-26 15:05:31 +0300
Add custom Pages workflow: submodules:false to fix broken
Upstreamable gitlink
```

Trigger block of the T0 file (evidence it was ACTIVE, not if:
false-neutered):

```
name: Deploy Jekyll to GitHub Pages
on:
  push:
    branches: [main]
  workflow_dispatch:
```

```
# T1 (~21:28)
$ git -C milosvasic.ru ls-files | grep -E '^\.github/
workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
(no output)
```

```
$ git -C milosvasic.ru status --porcelain -- .github
R .github/workflows/pages.yml -> .github/workflows/
pages.yml.disabled
```

```
$ ls -la milosvasic.ru/.github/workflows
```

```
-rw-r--r-- 1 milosvasic milosvasic 1333 Aug 17 11:56
pages.yml.disabled
```

A.5 — milosvasic.ru/Upstreamable

```
$ git -C milosvasic.ru/Upstreamable remote -v
gitflic git@gitflic.ru:red-elf/upstreamable.git (fetch)
gitflic git@gitflic.ru:red-elf/upstreamable.git (push)
github git@github.com:red-elf/Upstreamable.git (fetch)
github git@github.com:red-elf/Upstreamable.git (push)
origin git@github.com:red-elf/Upstreamable.git (fetch)
origin git@gitflic.ru:red-elf/upstreamable.git (push)
origin git@github.com:red-elf/Upstreamable.git (push)
upstream git@gitflic.ru:red-elf/upstreamable.git (fetch)
upstream git@gitflic.ru:red-elf/upstreamable.git (push)

$ git -C milosvasic.ru/Upstreamable ls-files | grep -E '^\.github/
workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
(no output)
```

Ownership evidence searched and NOT found — hence
UNDETERMINED, not guessed:

```
$ grep -rn 'red-elf\|Upstreamable' README.md CLAUDE.md
README.md:36:# (red-elf/Upstreamable) whose own .gitmodules is a
broken 0-byte gitlink, so a
CLAUDE.md:175: `commit` resolves on PATH to `$SUBMODULES_HOME/
Upstreamable/commit`, which
```

Neither line asserts ownership of the red-elf namespace, and red-elf
is absent from CLAUDE.md’s “Owned submodules” list.

A.6 — monetization

```
$ git -C monetization remote -v
gitflic git@gitflic.ru:milosvasic/monetization.git (fetch/push)
github git@github.com:milos85vasic/monetization.git (fetch/push)
gitlab git@gitlab.com:milos85vasic/monetization.git (fetch/push)
gitverse ssh://git@gitverse.ru:2222/milosvasic/monetization.git
(fetch/push)
origin git@github.com:milos85vasic/monetization.git (fetch)
origin git@gitflic.ru:milosvasic/monetization.git (push)
origin git@github.com:milos85vasic/monetization.git (push)
origin git@gitlab.com:milos85vasic/monetization.git (push)
origin ssh://git@gitverse.ru:2222/milosvasic/monetization.git
(push)
upstream git@gitflic.ru:milosvasic/monetization.git (fetch/
push)
```

```
$ git -C monetization ls-files | grep -E '^\.github/
workflows/.*\.ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
(no output)
```

A.7 — submodules/constitution

```
$ git -C submodules/constitution remote -v
gitflic git@gitflic.ru:helixdevelopment/helixconstitution.git
(fetch/push)
github git@github.com:HelixDevelopment/HelixConstitution.git
(fetch/push)
gitlab git@gitlab.com:helixdevelopment1/helixconstitution.git
(fetch/push)
gitverse git@gitverse.ru:helixdevelopment/
HelixConstitution.git (fetch/push)
origin git@github.com:HelixDevelopment/HelixConstitution.git
(fetch)
origin git@gitflic.ru:helixdevelopment/helixconstitution.git
(push)
origin git@github.com:HelixDevelopment/HelixConstitution.git
(push)
origin git@gitlab.com:helixdevelopment1/helixconstitution.git
(push)
origin git@gitverse.ru:helixdevelopment/HelixConstitution.git
(push)
origin git@github.com:vasic-digital/HelixConstitution.git (push)
origin git@gitlab.com:vasic-digital/HelixConstitution.git (push)
upstream git@gitflic.ru:helixdevelopment/
helixconstitution.git (fetch/push)
vasic_digital_github git@github.com:vasic-digital/
HelixConstitution.git (fetch/push)
vasic_digital_gitlab git@gitlab.com:vasic-digital/
HelixConstitution.git (fetch/push)

$ git -C submodules/constitution ls-files | grep -E '^\.github/
workflows/.*\.ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
(no output)
```

This is the \$11.4.75 posture already in effect: the constitution repo's own compliance workflow is preserved under a non-active name and therefore does not appear in the probe.

A.8–A.14 — constitution’s nested submodules

```
$ git -C submodules/constitution/submodules/anti_bluff remote -v
origin git@github.com:vasic-digital/anti_bluff.git (fetch/push)
```

```
$ git -C submodules/constitution/submodules/continuum remote -v
origin git@github.com:vasic-digital/continuum.git (fetch/push)
```

```
$ git -C submodules/constitution/submodules/design-toolkit remote
-v
origin git@github.com:vasic-digital/design-toolkit.git (fetch/
push)
```

```
$ git -C submodules/constitution/submodules/docs_chain remote -v
github git@github.com:vasic-digital/docs_chain.git (fetch/push)
gitlab git@gitlab.com:vasic-digital/docs_chain.git (fetch/push)
origin git@github.com:vasic-digital/docs_chain.git (fetch)
origin git@github.com:vasic-digital/docs_chain.git (push)
origin git@gitlab.com:vasic-digital/docs_chain.git (push)
upstream git@github.com:vasic-digital/docs_chain.git
(fetch/push)
```

```
$ git -C submodules/constitution/submodules/helix_perf_cache
remote -v
origin git@github.com:HelixDevelopment/helix_perf_cache.git
(fetch/push)
```

```
$ git -C submodules/constitution/submodules/session_orchestrator
remote -v
origin git@github.com:vasic-digital/session_orchestrator.git
(fetch/push)
```

```
$ git -C submodules/constitution/submodules/token_optimizer remote
-v
origin git@github.com:vasic-digital/token_optimizer.git (fetch/
push)
```

Probe result for all seven:

```
$ for p in anti_bluff continuum design-toolkit docs_chain
helix_perf_cache \
    session_orchestrator token_optimizer; do
    echo "--- $p"
    git -C submodules/constitution/submodules/$p ls-files \
    | grep -E '^\.github/workflows/.*\.ya?ml$|^\.gitlab-
ci\.yml$|^\.gitlab/'
    done
--- anti_bluff
--- continuum
```

```
--- design-toolkit
--- docs_chain
--- helix_perf_cache
--- session_orchestrator
--- token_optimizer
```

All empty.

A.15 — submodules/superspec (THIRD-PARTY — DO NOT EDIT)

```
$ git -C submodules/superspec rev-parse --show-toplevel
<ext-volume-host>/Projects/vasic/submodules/superspec
```

```
$ git -C submodules/superspec remote -v
origin  git@github.com:WangX0111/superspec.git (fetch)
origin  git@github.com:WangX0111/superspec.git (push)
```

```
$ git -C submodules/superspec ls-files | grep -E '^\.github/
workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
.github/workflows/ci.yaml
```

Its trigger block (active — recorded for completeness, NOT to be edited):

```
name: CI

on:
  push:
    branches:
      - main
  pull_request:
```

Identity with the vendored copy in .specify:

```
$ cmp -s submodules/superspec/.github/workflows/ci.yaml \
        .specify/extensions/superspec/.github/workflows/ci.yaml &&
echo IDENTICAL
IDENTICAL
```

A.16 — vasic.digital

```
$ git -C vasic.digital remote -v
github  git@github.com:vasic-digital/vasic-digital.github.io.git
(fetch/push)
origin  git@github.com:vasic-digital/vasic-digital.github.io.git
(fetch/push)
upstream          git@github.com:vasic-digital/vasic-
```

```
digital.github.io.git (fetch/push)
```

```
$ git -C vasic.digital ls-files | grep -E '^\.github/
workflows/.*\ya?ml$|^\.gitlab-ci\.yaml$|^\.gitlab/'
(no output)
```

Appendix B — non-root inertness verification

```
$ git -C . rev-parse --show-toplevel
<ext-volume-host>/Projects/vasic
```

```
$ git -C .specify/extensions/superspec rev-parse --show-toplevel
fatal: not a git repository: <ext-volume-host>/Projects/
vasic/.specify/extensions/superspec/../../.git/modules/submodules/
superspec
```

```
$ cat .specify/extensions/superspec/.git
gitdir: ../../.git/modules/submodules/superspec          # resolves
to a path that does not exist
```

```
$ git ls-files .specify/extensions/superspec/.git
(no output – the stray .git file is untracked)
```

```
$ git ls-files .specify/extensions/superspec | wc -l
59
```

```
$ git ls-files -s .specify/extensions/superspec | awk '{print $1}'
| sort -u
100644
100755          # ordinary blobs only – no 160000 gitlink
```

```
$ grep -n 'superspec' .gitmodules          # .specify path is NOT
registered as a submodule
19:[submodule "submodules/superspec"]
20: path = submodules/superspec
21: url = git@github.com:WangX0111/superspec.git
```

Three matching LINES describing exactly ONE registered submodule (submodules/superspec). No .gitmodules stanza mentions .specify/extensions/superspec. `grep -n` is used here rather than `grep -c` precisely because `grep -c` would report 3 and invite the line-count-as-thing-count error the closing note in Appendix C warns about.

Symlink check — every `.github/workflows` path in the tree, tested with `-L`:

```
$ find . -path ./git -prune -o -name '.github' -print -o -name
'workflows' -print \
  | while read -r f; do
    printf '%s : ' "$f"
    if [ -L "$f" ]; then echo "SYMLINK -> $(readlink "$f")";
else echo "real $(stat -c %F "$f")"; fi
  done
./github : real directory
./github/workflows : real directory
./milosvasic.ru/.github : real directory
./specify/workflows : real directory
./milosvasic.ru/.github/workflows : real directory
./submodules/superspec/.github : real directory
./submodules/superspec/.github/workflows : real directory
./specify/extensions/superspec/.github : real directory
./specify/extensions/superspec/.github/workflows : real directory
... (remaining entries are all under ai_interviewing/platform/
frontend/node_modules/, all "real directory")
```

Zero symlinks. No non-root workflow is aliased up to any repository root.

Complete on-disk census of workflow files (state at T1):

```
$ find . -path ./git -prune -o -type f -path '*/.github/
workflows/*' -print | sed 's#^\./##' | sort
ai_interviewing/platform/frontend/node_modules/fast-uri/.github/
workflows/ci.yml
ai_interviewing/platform/frontend/node_modules/fast-uri/.github/
workflows/lock-threads.yml
ai_interviewing/platform/frontend/node_modules/fast-uri/.github/
workflows/package-manager-ci.yml
ai_interviewing/platform/frontend/node_modules/json-schema-
traverse/.github/workflows/build.yml
ai_interviewing/platform/frontend/node_modules/json-schema-
traverse/.github/workflows/publish.yml
ai_interviewing/platform/frontend/node_modules/needle/.github/
workflows/nodejs.yml
ai_interviewing/platform/frontend/node_modules/reusify/.github/
workflows/ci.yml
ai_interviewing/platform/frontend/node_modules/rfdc/.github/
workflows/ci.yml
ai_interviewing/platform/frontend/node_modules/wildcard/.github/
workflows/build.yml
.github/workflows/ci.yml.disabled
milosvasic.ru/.github/workflows/pages.yml.disabled
specify/extensions/superspec/.github/workflows/ci.yml
submodules/superspec/.github/workflows/ci.yml
```



```
$ find . -path ./ .git -prune -o -type f -path '*/.github/
workflows/*' -print | wc -l
13
$ find . -path ./ .git -prune -o -type f -path '*/node_modules/
*/.github/workflows/*' -print | wc -l
9
$ find . -path ./ .git -prune -o -type d -path '*/node_modules/*'
-name workflows -print | wc -l
6
```

13 files on disk = 9 untracked npm vendored + 2 already renamed .disabled + 1 vendored non-root tracked copy + 1 third-party repo root. At T1, zero active, root-level, tracked workflow files remained in any repository we push — **in the working tree**. Two of those (rows 1 and 4) were staged but not yet committed or pushed.

Transiently superseded at T2 (21:32:57), restored at T3 (21:34:04): for roughly 90 seconds a concurrent agent’s mutation probe .github/workflows/zz-probe.yml (121 bytes, live on: push: branches: [main]) raised the on-disk total to 14 and returned the umbrella’s §11.4.156(E) probe to non-empty. It was removed from both index and working tree at T3, and the census of 13 above is the state at close of audit. See “Concurrent remediation observed in flight” for the full T2/T3 record.

Appendix C — the exact re-runnable sweep

```
cd <ext-volume-host>/Projects/vasic
for p in . ai_interviewing design-toolkit milosvasic.ru
milosvasic.ru/Upstreamable \
monetization submodules/constitution \
submodules/constitution/submodules/anti_bluff \
submodules/constitution/submodules/continuum \
submodules/constitution/submodules/design-toolkit \
submodules/constitution/submodules/docs_chain \
submodules/constitution/submodules/helix_perf_cache \
submodules/constitution/submodules/session_orchestrator \
submodules/constitution/submodules/token_optimizer \
submodules/superspec vasic.digital; do
out=$(git -C "$p" ls-files 2>/dev/null \
| grep -E '^\.github/workflows/.*\ya?ml$|^\.gitlab-
ci\.yaml$|^\.gitlab/')
```

```
echo "--- $p : ${out:-NONE}"  
done
```

Expected compliant output: NONE for all 16 rows except submodules/superspec, which is permitted to report .github/workflows/ci.yml under §11.4.156(C) because it is third-party and has no owned upstream.

Counting caution: these outputs are file paths, one per line, and the counts in this document are counts of FILES, verified by listing them. `grep -c` counts matching LINES and must not be used as a file count where a single file could produce multiple matching lines.