

APPLY

Constitution Propagation — APPLY procedure

Note on filenames. The staged carrier drafts in this directory are stored with a `.staged` suffix (e.g. `AGENTS.md.staged`). The constitution’s propagation gates discover carriers by exact filename (`CLAUDE.md`, `AGENTS.md`, `QWEN.md`, `GEMINI.md`), so drafts named that way inside the repo are counted as real carriers and fail the gate. Drop the `.staged` suffix when you copy a file into its target submodule.

Field	Value
Revision	2
Created	2026-08-26
Last modified	2026-08-27
Status	prepared — NOT applied
Status summary	Ready-to-copy inheritance-pointer carriers for the 5 owned submodules of the <code>vasic</code> umbrella, plus the exact copy/commit/push procedure. Nothing in this directory has been applied. No submodule working tree was written to and no mutating git command was run while producing it. Revision 2 (2026-08-27): every staged carrier was rewritten — the Revision-1 drafts opened with a >blockquote / a ## Helix Constitution inheritance

Field	Value
	heading, neither of which satisfies the propagation gates' is_pointer_carrier() predicate, so applying them as written would have taken the fleet from 5 MISSING carriers / 85 MISSING lines to 8 / 136 (§4.6 alone) or 24 / 408 (§4.2 – §4.6). Every carrier now opens with a real, non-fenced, line-anchored ## INHERITED FROM constitution/<BASE> heading and keeps the conditional / standalone prose. Proven in a temp-dir gate run — see PROOF.md .
Continuation	Operator executes §4 below, submodule-by-submodule, in the order given. Read PROOF.md first — it is the empirical before/after for the corrected set.

Read **[RISKS.md](#)** before running anything in §4. It names the push fan-out per repository, the third-party exclusion, and everything that could not be verified from a read-only checkout.

1. What this directory contains

```
docs/constitution-adoption/propagation/
├─ APPLY.md                                     ← this
file
├─ RISKS.md
├─ PROOF.md                                     ←
temp-dir gate proof
├─ ai_interviewing/{AGENTS,CLAUDE,QWEN,GEMINI}.md.staged  (→ 4
new files)
├─ design-toolkit/{AGENTS,CLAUDE,QWEN,GEMINI}.md.staged  (→ 4
new files)
├─ milosvasic.ru/{AGENTS,CLAUDE,QWEN,GEMINI}.md.staged  (→ 4
new files)
├─ monetization/{AGENTS,CLAUDE,QWEN,GEMINI}.md.staged    (→ 4
new files)
└─ vasic.digital/
    ├─ AGENTS.md.staged  CLAUDE.md.staged  GEMINI.md.staged  (→ 3
new files)
```

└─ QWEN.insert-block.md ← block to INSERT at the top of the EXISTING
vasic.digital/QWEN.md (after its H1 title)

Every draft carrier is stored with a `.staged` suffix, for the reason the note at the top of this file gives: a file literally named `CLAUDE.md` inside this repository is discovered by the propagation gates as a real fleet carrier. The `cp` commands in §4 therefore copy **from** `<name>.md.staged` **to** `<name>.md`; the suffix is dropped by the copy, never by a rename in place.

19 files to create + 1 block to insert into 1 existing file. **No existing file is replaced anywhere.**

submodules/superspec gets nothing — see [RISKS.md §3](#).

2. Survey — what each owned submodule already has

Tracked-file survey via `git -C <sub> ls-files` (tracked only; untracked and ignored paths deliberately not counted).

Submodule	Upstream (<code>.gitmodules</code>)	Tracked agent-instruction files	Other tracked govern adjacent content
ai_interviewing	git@github.com:milos85vasic/ai_interviewing.git	none	README.{md,html,pdf,d platform/, scripts/, up GitHub.sh — 911 track README purpose: “Int preparation corpus an due-diligence ... a self- exhaustively-research kit”.
design-toolkit	git@github.com:vasic-digital/design-toolkit.git	none	README.md, agents/ (11 specialist recipe .md, n canonical carrier), doc generators/, knowledge proposed/, qa/, submodu tracked files. README reusable, license-clean capability layer ... Sta

Submodule	Upstream (.gitmodules)	Tracked agent-instruction files	Other tracked govern adjacent content
milosvasic.ru	git@github.com:milos85vasic/milosvasic.ru.git	none (see note)	INCREMENT — review scaffold.” README.md, README.pdf, (_layouts, _config.yml, dirs), Upstreams/{GitFlic, GitHub}.sh, . nested submodule Upstreams/ 1017 tracked entries. R purpose: personal CV / README.md (“Projects m Monetization of existin docs/, repos.txt, upstr {GitFlic, GitHub, GitLa — 8 tracked files total.
monetization	git@github.com:milos85vasic/monetization.git	none	README.md, commit (cust wrapper), Upstreams/G LOGO_CONVERSION.md, st language dirs — 1130 t
vasic.digital	git@github.com:vasic-digital/vasic-digital.github.io.git	QWEN.md (55 lines, tracked)	

2.1 Correction to INVENTORY.md §6.2 — where the reference implementation actually lives

INVENTORY.md §6.2 lists milosvasic.ru/Upstreamable/AGENTS.md and .../CLAUDE.md as evidence and §7.3 calls that file “the reference implementation for the propagation work”. Both files exist on disk and both were read for this document — but they are **not tracked by milosvasic.ru**. milosvasic.ru/.gitmodules reads:

```
[submodule "Upstreamable"]
  path = Upstreamable
  url = git@github.com:red-elf/Upstreamable.git
```

and `git -C milosvasic.ru ls-files -s | grep ^160000` returns

```
160000 94f9831b8aa0a1d4df23671d2e4600886aad0dcf 0    Upstreamable
```

so Upstreamable is a gitlink to a **third repository** (red-elf/Upstreamable, push URLs `git@github.com:red-elf/Upstreamable.git` + `git@gitflic.ru:red-elf/upstreamable.git`). Consequence:

milosvasic.ru itself carries **zero agent-instruction files**, and editing the reference implementation would mean committing into a fourth-level repository that is outside the 5-submodule scope of this task. Nothing here touches Upstreamable.

2.2 What already exists in **vasic.digital/QWEN.md** (must be preserved)

55 lines, headed `# Vasic-Digital GitHub Pages Project`. It documents: the project overview, a repository-structure tree, the `commit` script (reads `env.properties`, honours `DEFAULT_COMMIT_MESSAGE / PROJECT_NAME`), `Upstreams/GitHub.sh` (exports the upstream URL), the environment-configuration contract, the development workflow, and usage notes. `grep -in constitution vasic.digital/QWEN.md` returns **zero hits** — confirming `INVENTORY.md §6.2`.

All 55 lines stay. The pointer block is inserted **after line 1**, before the existing `## Project Overview` heading.

3. The pointer form standardised on, and why

3.1 The path problem this form exists to solve

Every template and every quoted snippet in the constitution says `constitution/...`. Three independent facts make **any** literal path wrong inside an owned submodule:

1. **The umbrella's real path is not `constitution/`.** It is `submodules/constitution/` (`.gitmodules:1-3`). From inside a submodule the `constitution` is not at either name — from `monetization/` it is at `../submodules/constitution/`, and from `milosvasic.ru/Upstreamable/` it is at `../../submodules/constitution/`. The relative distance is a function of checkout depth, which the submodule cannot know.
2. **The same repository is checked out at two different depths simultaneously.** `design-toolkit` is a gitlink of the umbrella *and* a gitlink of the constitution: `git submodule status → 16e4e76... design-toolkit (v0.2.2-4-g16e4e76); git -C submodules/constitution/submodules/design-toolkit rev-parse HEAD → 16e4e76d57ab61b5f3b46fae3372b2e6d6cc73e3` — same commit of `git@github.com:vasic-digital/design-toolkit.git`. One file, committed once, must be correct at depth 1 (`design-toolkit/`) *and*

at depth 3 (submodules/constitution/submodules/design-toolkit/).
No relative path satisfies both.

3. **A standalone clone has no constitution at all.** `git clone git@github.com:milos85vasic/monetization.git` produces a tree with no parent and no constitution/ anywhere. Any hardcoded path is then a dangling link, and any sentence asserting “these rules apply unconditionally” is false.

Two further consequences follow, and both rule out the project-root forms:

- **@constitution/CLAUDE.md MUST NOT be used in a submodule carrier.** The Claude-Code import resolves relative to the importing file’s directory, so inside monetization/CLAUDE.md it would resolve to monetization/constitution/CLAUDE.md, which does not exist — it silently resolves to nothing. INVENTORY.md §7 names this “the single highest-risk detail in the whole change”.
- **Hardcoding submodules/constitution/ would itself be a violation.** §11.4.28(B) (Constitution.md:2411-2418): “Owned submodules MUST remain **fully decoupled** from any specific consuming project. No project-specific context, **hardcoded paths**, hostnames, asset names, naming schemes, or runtime assumptions may be introduced into an owned submodule’s source tree. Every owned submodule MUST be: **Project-not-aware** — its code, tests, and docs make no reference to which parent project consumes it.”
submodules/constitution/ is the umbrella’s layout, i.e. exactly such a hardcoded parent-project path.

The resolution the constitution ships is the runtime resolver submodules/constitution/find_constitution.sh. Its Phase 1 walks up parents trying both layouts —

```
local rels=( "constitution" "submodules/constitution" )
```

— and its Phase 2 follows `git rev-parse --show-superproject-working-tree` recursively “if we are inside a submodule ... Repeat until at top-level”, which is precisely the submodule-at-any-depth case. It exits 1 with `ERROR: constitution submodule not found above <pwd>` when there is none, which is the standalone case. So the carrier names the *helper*, not a path, and states the inheritance **conditionally**.

3.2 The exact conditional form (reproduced from the in-tree reference)

Quoted verbatim from `milosvasic.ru/Upstreamable/AGENTS.md` lines 3-16 — the form `INVENTORY.md` §7.3 designates as the reference implementation:

```
> **Base agent rules:** when this module is consumed inside a
> project that includes the Helix Constitution submodule, the file
> `constitution/AGENTS.md` is authoritative for any topic not
> covered here. Locate it from any nested depth using the
> constitution's `find_constitution.sh` helper.
>
> When this module is consumed standalone (no constitution
> submodule reachable in any parent), only the module-local notes
> below apply.
>
> Canonical reference:
> https://github.com/HelixDevelopment/HelixConstitution
```

and the CLAUDE-side twin, verbatim from `milosvasic.ru/Upstreamable/CLAUDE.md` lines 6-24:

`## Helix Constitution inheritance`

When this module is consumed inside a project that includes the Helix Constitution as a git submodule (<https://github.com/HelixDevelopment/HelixConstitution>), the rules in ``constitution/CLAUDE.md`` and the ``constitution/Constitution.md`` it references apply unconditionally. Use the constitution's ``find_constitution.sh`` helper to locate it from any nested depth.

When this module is consumed standalone (no ``constitution/`` submodule reachable in any parent), only the module-local notes below apply.

This module stays fully decoupled and reusable per the Helix Constitution's §11.4.28 (Submodules-As-Equal-Codebase + Decoupling + Dependency-Layout mandate). No project-specific context is injected here.

The reference form's **substance** — the two-case conditional, the resolver instead of a path, the standalone case stated plainly — is correct and is kept verbatim in spirit below. Its **shape** is not usable on its own, and that is what Revision 2 changed.

3.2.1 Why the shape had to change: `is_pointer_carrier()`

The reference opens with a > blockquote (`AGENTS.md`) or with a `## Helix Constitution inheritance` heading (`CLAUDE.md`). Neither is visible to the mechanism that decides whether a carrier is allowed to omit the anchor literals.

Every `CM-COVENANT-114-*`-`PROPAGATION` gate sources one shared predicate, `scripts/gates/lib/pointer_carrier.sh`, whose entire body is:

```
BEGIN { fenced = 0; found = 0 }
/^(``|~~)/ { fenced = !fenced; next }
!fenced && /^## INHERITED FROM / { found = 1; exit }
END { exit !found }
```

A carrier satisfies it **iff** it contains a line-anchored, non-fenced `## INHERITED FROM` heading at column zero. Nothing else counts — not a blockquote, not a differently-worded H2, not a mid-line mention in backticks (a decoy the predicate’s own self-test exercises). A carrier that fails the predicate and does not restate the anchor literal is scored `MISSING`, so each Revision-1 draft would have **added** a new failing carrier to the fleet instead of clearing one. Measured, not argued: see [PROOF.md](#).

Three facts about the predicate decide the corrected form:

1. It requires the **heading**, and only the heading. It never opens, resolves, or stats the path written after `## INHERITED FROM`.
2. It scans the whole file, so the heading may sit under the document’s H1 title — which is exactly the shape of the four repository-root carriers that pass all 17 gates today, and of the predicate’s own golden-good fixture (`# CLAUDE.md ... ## INHERITED FROM constitution/CLAUDE.md`).
3. It is inherited by reference by both gate families — the 12 legacy bare-literal gates and the 5 fence-aware §11.4.227(B) block-integrity gates — so one heading satisfies all 17.

So both constraints hold at once. The carrier opens with the canonical heading `## INHERITED FROM constitution/<BASE>` — the exact form the constitution’s own examples use — and immediately below it states the inheritance **conditionally**, names `find_constitution.sh` as the resolver, and says plainly that a standalone clone inherits nothing. The path inside the heading is the canonical **name** of the base file, resolved

by the helper; the carrier says so in as many words, so no reader mistakes it for a filesystem path, and no depth-dependent path is hardcoded anywhere (§11.4.28(B) intact).

3.3 Provenance of each of the four carriers

Carrier	Form used	Authority
AGENTS.md	## INHERITED FROM constitution/ AGENTS.md heading + the reference's conditional / standalone prose	heading form: submodules/ constitution/CLAUDE.md "How to consume" + the is_pointer_carrier() predicate (§3.2.1); prose substance: milosvasic.ru/Upstreamable/ AGENTS.md:3-16
CLAUDE.md	## INHERITED FROM constitution/ CLAUDE.md heading + the same conditional / standalone prose	§11.4.35 invariant 6 (Constitution.md:2910-2916) names ## INHERITED FROM constitution/CLAUDE.md as the portable pointer-block form; prose substance: milosvasic.ru/ Upstreamable/CLAUDE.md:6-24
QWEN.md	derived — same heading + prose with constitution/ QWEN.md substituted	submodules/constitution/ README.md "How to consume" §2: "Same for AGENTS.md (any AI-agent tooling) and (since 2026-05-20) QWEN.md for Qwen Code:" followed by the blockquote form. No QWEN.project.md.template ships — submodules/constitution/ templates/ contains exactly AGENTS.project.md.template, CLAUDE.project.md.template, Constitution.project.md.template. A QWEN-specific consumer form is not specified ; this is the README's own substitution.
GEMINI.md	derived — same heading + prose with	§11.4.157 (Constitution.md:9566): "GEMINI.md is a FIRST-CLASS governance context carrier,

Carrier	Form used	Authority
	constitution/ GEMINI.md substituted	EQUAL to CLAUDE.md / AGENTS.md / QWEN.md — NEVER an optional or best-effort sibling.” submodules/ constitution/GEMINI.md:29-38 prescribes for consumers a ## INHERITED FROM constitution/ GEMINI.md heading — the heading form is adopted here verbatim; only its <i>unconditional</i> wording (“apply unconditionally”) is replaced by the two-case conditional, which is what a project-unaware module can honestly assert (§3.1). No GEMINI.project.md.template ships.

A module-level Constitution.md is **not** included. The only Constitution template that ships (Constitution.project.md.template) opens “This constitution **extends** the Helix Universal Constitution at constitution/Constitution.md” and requires ## Owned-submodule set and ## Project-specific remotes sections — it is a *project* scaffold. Whether an owned, project-unaware submodule must also carry its own Constitution.md is **not specified** anywhere in templates/, in README “How to consume”, or in §11.4.28. Nothing is invented here.

3.4 Deviation from the reference: carrier count

The reference implementation carries 2 carriers (AGENTS.md, CLAUDE.md). This propagation prepares 4 (adding QWEN.md, GEMINI.md), following INVENTORY.md §7.3 (“all four carriers”) and §11.4.157’s first-class-GEMINI mandate. If the operator prefers strict parity with the reference, apply only AGENTS.md + CLAUDE.md per submodule and drop the other two — the files are independent and the commit/push steps below are unchanged.

4. The procedure

4.0 Preconditions (verified read-only at preparation time — re-verify)

Check	Command	Value observed 2026-08-26
Every target on a branch, not detached	git -C <sub> symbolic-ref -q HEAD	all 5 on refs/heads/main
Every target clean	git -C <sub> status --porcelain	all 5 → 0 lines
No carrier filename is git-ignored	git -C <sub> check- ignore -v CLAUDE.md AGENTS.md QWEN.md GEMINI.md	no match in any of the 5

If any target is dirty or detached when the operator runs this, **stop** — the steps below assume a clean main.

4.1 Ordering — submodules first, parent last

Constitution.md:203-215 (§3, “Submodule changes propagate through submodule commits first”):

1. **Commit inside the submodule first** (the submodule’s own `git add + git commit`), since the parent project’s commit wrapper does not commit submodule source — it only captures the updated submodule pointer.
2. **Push the submodule commit** to **all** remotes of that submodule.
3. **Then** run the parent project’s commit wrapper to capture the updated submodule pointer in main and push main.

Skipping step 1 produces parent commits / tags that point at old submodule HEADs without the actual source.

So: all five submodule commit+push rounds (§4.2 – §4.6) complete **before** the umbrella capture (§4.7).

4.2 ai_interviewing — CREATE 4

cd <ext-volume-host>/Projects/vasic
P=docs/constitution-adoption/propagation

```

cp "$P/ai_interviewing/AGENTS.md.staged" ai_interviewing/
    AGENTS.md
cp "$P/ai_interviewing/CLAUDE.md.staged" ai_interviewing/
    CLAUDE.md
cp "$P/ai_interviewing/QWEN.md.staged" ai_interviewing/QWEN.md
cp "$P/ai_interviewing/GEMINI.md.staged" ai_interviewing/
    GEMINI.md

git -C ai_interviewing add AGENTS.md CLAUDE.md QWEN.md GEMINI.md
git -C ai_interviewing commit -m "docs: add Helix Constitution
    inheritance pointers (conditional form, §11.4.28(B) +
    §11.4.35)"
git -C ai_interviewing push origin main

```

Blast radius: origin has **1 push URL** — `git@github.com:milos85vasic/ai_interviewing.git`. The github and upstream remotes resolve to that same single URL, so pushing all three remotes still writes to 1 distinct repository.

Caveat before you run this one: the carrier text ends “No project-specific context is injected here.” For `ai_interviewing` that sentence is *aspirational, not descriptive* — its own `README.md` opens “**Interview-preparation corpus and employer due-diligence** for the CauseMatch *Senior Full-Stack Engineer ...* position — built for the candidate at milosvasic.ru”. Either accept the sentence as the forward §11.4.28(B) obligation it states, or delete that one paragraph from `ai_interviewing/{AGENTS, CLAUDE, QWEN, GEMINI}.md` before committing. See [RISKS.md §5](#).

4.3 design-toolkit — CREATE 4

```

cd <ext-volume-host>/Projects/vasic
P=docs/constitution-adoption/propagation
cp "$P/design-toolkit/AGENTS.md.staged" design-toolkit/AGENTS.md
cp "$P/design-toolkit/CLAUDE.md.staged" design-toolkit/CLAUDE.md
cp "$P/design-toolkit/QWEN.md.staged" design-toolkit/QWEN.md
cp "$P/design-toolkit/GEMINI.md.staged" design-toolkit/GEMINI.md

git -C design-toolkit add AGENTS.md CLAUDE.md QWEN.md GEMINI.md
git -C design-toolkit commit -m "docs: add Helix Constitution
    inheritance pointers (conditional form, §11.4.28(B) +
    §11.4.35)"
git -C design-toolkit push origin main

```

Blast radius: origin has **1 push URL** — `git@github.com:vasic-digital/design-toolkit.git`. It is the only remote.

Two-parent consequence — read before running. The same repository at the same commit is also the constitution’s own submodule at `submodules/constitution/submodules/design-toolkit`.

Pushing a new design-toolkit commit makes the **constitution's** recorded gitlink stale. Bringing the constitution back in sync means a commit inside submodules/constitution, whose origin fans out to **6 push URLs** (see [RISKS.md §2](#)). That step is **out of scope here and is not prepared** — decide it deliberately.

4.4 milosvasic.ru — CREATE 4

```
cd <ext-volume-host>/Projects/vasic
P=docs/constitution-adoption/propagation
cp "$P/milosvasic.ru/AGENTS.md.staged" milosvasic.ru/AGENTS.md
cp "$P/milosvasic.ru/CLAUDE.md.staged" milosvasic.ru/CLAUDE.md
cp "$P/milosvasic.ru/QWEN.md.staged" milosvasic.ru/QWEN.md
cp "$P/milosvasic.ru/GEMINI.md.staged" milosvasic.ru/GEMINI.md

git -C milosvasic.ru add AGENTS.md CLAUDE.md QWEN.md GEMINI.md
git -C milosvasic.ru commit -m "docs: add Helix Constitution
    inheritance pointers (conditional form, §11.4.28(B) +
    §11.4.35)"
git -C milosvasic.ru push origin main
```

Blast radius: origin has **2 push URLs**, and they are *not* the origin fetch URL:

```
git@gitflic.ru:milosvasic/milosvasic-net-v-2.git
git@github.com:milos85vasic/milosvasic.net.v2.git
```

git remote get-url origin (fetch) is git@github.com:milos85vasic/milosvasic.ru.git — the URL .gitmodules declares — and **no configured push URL writes to it**. One git push origin main therefore publishes to two repositories, neither of which is the one the umbrella records as this submodule's source. See [RISKS.md §2.1](#).

This does **not** touch milosvasic.ru/Upstreamable (a separate red-elf/Upstreamable repository — §2.1 above).

4.5 monetization — CREATE 4 (widest fan-out)

```
cd <ext-volume-host>/Projects/vasic
P=docs/constitution-adoption/propagation
cp "$P/monetization/AGENTS.md.staged" monetization/AGENTS.md
cp "$P/monetization/CLAUDE.md.staged" monetization/CLAUDE.md
cp "$P/monetization/QWEN.md.staged" monetization/QWEN.md
cp "$P/monetization/GEMINI.md.staged" monetization/GEMINI.md

git -C monetization add AGENTS.md CLAUDE.md QWEN.md GEMINI.md
```

```
git -C monetization commit -m "docs: add Helix Constitution
    inheritance pointers (conditional form, §11.4.28(B) +
    §11.4.35)"
git -C monetization push origin main
```

Blast radius: origin has **4 push URLs** across 4 providers:

```
git@gitflic.ru:milosvasic/monetization.git
git@github.com:milos85vasic/monetization.git
git@gitlab.com:milos85vasic/monetization.git
ssh://git@gitverse.ru:2222/milosvasic/monetization.git
```

A single `git push` publishes to GitFlic, GitHub, GitLab and GitVerse at once. The repo currently tracks **8 files** — this commit adds 4 more, a 50 % increase in its tracked-file count, to 4 providers.

4.6 vasic.digital — CREATE 3 + INSERT into the existing QWEN.md

Revision 2 — what changed and why it matters here. Revision 1 of this section copied three carriers that opened with `# CLAUDE.md – vasic.digital / a > blockquote / ## Helix Constitution inheritance`, and inserted a blockquote into `QWEN.md`. None of those four files satisfied `is_pointer_carrier()` (§3.2.1), and none carried a single one of the 17 anchor literals — so applying §4.6 as written turned `vasic.digital` into **three additional MISSING carriers** while leaving `QWEN.md` MISSING too. Measured in a temp-dir gate run: the fleet went from **5 MISSING carriers / 85 MISSING lines to 8 / 136**, with all 17 gates still FAILing, louder. The four staged files below now each open with a real, non-fenced, line-anchored `## INHERITED FROM constitution/<BASE> heading`; the same measurement on the corrected set gives **4 MISSING carriers / 68 MISSING lines** — `vasic.digital/QWEN.md` leaves the failing set. Full before/after, including the control run on the uncorrected copies, is in `PROOF.md`.

The three new carriers:

```
cd <ext-volume-host>/Projects/vasic
P=docs/constitution-adoption/propagation
cp "$P/vasic.digital/AGENTS.md.staged" vasic.digital/AGENTS.md
cp "$P/vasic.digital/CLAUDE.md.staged" vasic.digital/CLAUDE.md
cp "$P/vasic.digital/GEMINI.md.staged" vasic.digital/GEMINI.md
```

The existing carrier — **insert, do not append, and do not replace**.
 vasic.digital/QWEN.md line 1 is # Vasic-Digital GitHub Pages Project;
 the block goes immediately after it, ahead of the existing ## Project
 Overview heading, because README “How to consume” §2 says “Add a
 clearly-marked pointer **at the top** of your project’s root CLAUDE.md ...
 Same for AGENTS.md ... and ... QWEN.md”, and §11.4.35 invariant 6
 (Constitution.md:2910-2916) says the consumer carrier “**MUST start**
 with” the pointer. Appending at end-of-file would satisfy neither.

Keeping the existing H1 title on line 1 and putting the pointer heading
 immediately under it is the shape of the four repository-root carriers
 that pass all 17 propagation gates today (# vasic – CLAUDE.md, then ##
 INHERITED FROM ... on line 3) and of the predicate’s own golden-good
 fixture. The pointer is the document’s first section either way, and
 is_pointer_carrier() scans the whole file, so the heading is found
 (verified on the produced file — PROOF.md §4).

All 55 existing lines are preserved verbatim:

```
cd <ext-volume-host>/Projects/vasic/vasic.digital
B=../docs/constitution-adoption/propagation/vasic.digital/
  QWEN.insert-block.md
{ head -n 1 QWEN.md; echo; cat "$B"; tail -n +2 QWEN.md; } >
  QWEN.md.new
# verify before swapping: the diff must be pure insertion, zero
  deletions
diff <(tail -n +2 QWEN.md) <(tail -n +51 QWEN.md.new) && mv
  QWEN.md.new QWEN.md
```

(The block is **48** lines; with the blank separator line the insertion is 49
 lines, so the original body resumes at **line 51** of the new file — the new
 file is 104 lines, and ## Project Overview lands on line 52. The diff
 must print nothing. If it prints anything, **do not** mv — the insertion is
 wrong.)

Then confirm the produced file is a pointer carrier before committing
 — this is the check whose absence made Revision 1 defective, and it
 takes one command:

```
cd <ext-volume-host>/Projects/vasic
. submodules/constitution/scripts/gates/lib/pointer_carrier.sh
for f in vasic.digital/{AGENTS,CLAUDE,QWEN,GEMINI}.md; do
  is_pointer_carrier "$f" && echo "OK   pointer carrier: $f" \
    || echo "FAIL not a pointer carrier: $f"
done
```

All four must print OK. A FAIL means the file will be scored MISSING by
 all 17 propagation gates — stop and fix it before committing.

Then commit. vasic.digital ships its own commit wrapper — the tracked script commit, which “Reads configuration from env.properties ... Supports default commit messages via DEFAULT_COMMIT_MESSAGE” (its own QWEN.md). The constitution’s AGENTS.project.md.template restates “**Use the project’s commit wrapper.** No direct git add / git commit / git push on main repo.” Prefer:

```
cd <ext-volume-host>/Projects/vasic/vasic.digital
./commit "docs: add Helix Constitution inheritance pointers
        (conditional form, §11.4.28(B) + §11.4.35)"
```

The wrapper’s exact behaviour (whether it stages all changes and whether it pushes) was **not executed or read line-by-line** for this document — inspect vasic.digital/commit before relying on it. The plain-git equivalent:

```
git -C vasic.digital add AGENTS.md CLAUDE.md GEMINI.md QWEN.md
git -C vasic.digital commit -m "docs: add Helix Constitution
    inheritance pointers (conditional form, §11.4.28(B) +
    §11.4.35)"
git -C vasic.digital push origin main
```

Blast radius: origin has **1 push URL** — git@github.com:vasic-digital/vasic-digital.github.io.git. Note this is a GitHub **Pages** repository: a push to its default branch triggers a site rebuild/redeploy. Four Markdown files land at the site root; whether the Jekyll build ignores or publishes them was **not verified** (see RISKS.md §6).

4.7 Umbrella — capture the five updated gitlinks, last

Only after all five submodule pushes succeed:

```
cd <ext-volume-host>/Projects/vasic
git status --short
    # expect exactly 5 gitlink modifications + this docs/ dir
git add ai_interviewing design-toolkit milosvasic.ru monetization
    vasic.digital \
    docs/constitution-adoption/propagation
git commit -m "chore: capture owned-submodule constitution-
    inheritance pointers (§3 submodule-first ordering)"
git push origin main
```

Blast radius: the umbrella’s origin has **1 push URL** — git@github.com:milos85vasic/vasic.git. Its github and upstream remotes carry the same single URL.

4.8 Total blast radius if everything in §4.2 – §4.7 is applied

Repository	Commits	git push origin writes to	Distinct URLs
ai_interviewing	1	GitHub ×1	1
design-toolkit	1	GitHub ×1	1
milosvasic.ru	1	GitFlic ×1, GitHub ×1	2
monetization	1	GitFlic, GitHub, GitLab, GitVerse	4
vasic.digital	1	GitHub ×1 (Pages redeploy)	1
umbrella vasic	1	GitHub ×1	1
Total	6	—	10

10 push URLs across 4 providers (GitHub, GitLab, GitFlic, GitVerse), from 6 commits in 6 separate repositories. submodules/constitution (6 URLs) and submodules/superspec (1 URL) are **not** in this total — neither is touched. Re-syncing the constitution’s design-toolkit gitlink (§4.3) would add its 6 URLs, taking the total to 16.

5. Post-apply verification (read-only)

```
cd <ext-volume-host>/Projects/vasic
# 1. Every owned submodule now tracks the carriers
for s
    in ai_interviewing design-toolkit milosvasic.ru
    monetization vasic.digital; do
    echo "== $s"; git -C "$s" ls-files | grep -E '^(AGENTS|CLAUDE|
    QWEN|GEMINI)\.md$'
done

# 2. Every carrier names the base file and the resolver, and none
    hardcodes the
# umbrella layout (a hit here is a §11.4.28(B) violation)
for s
    in ai_interviewing design-toolkit milosvasic.ru
    monetization vasic.digital; do
    for f in AGENTS CLAUDE QWEN GEMINI; do
    grep -q 'find_constitution.sh' "$s/$f.md" || echo "MISSING
    resolver: $s/$f.md"
    grep -q 'submodules/constitution' "$s/$f.md" && echo
    "HARDCODED PARENT PATH: $s/$f.md"
    grep -q '@constitution/' "$s/$f.md" && echo "DANGLING
    @import: $s/$f.md"
    done
done
```

```

# 3. vasic.digital/QWEN.md kept all 55 original lines (pure
    insertion, 0 deletions)
diff <(git -C vasic.digital show HEAD~1:QWEN.md) \
    <(head -n 1 vasic.digital/QWEN.md; tail -n +51 vasic.digital/
        QWEN.md)

# 4. The resolver actually resolves from inside each submodule
for s
    in ai_interviewing design-toolkit milosvasic.ru
    monetization vasic.digital; do
    echo -n "$s -> "; (cd "$s" && bash ../submodules/constitution/
        find_constitution.sh)
done

# 5. THE GATE-FACING CHECK – every applied carrier is recognised
    as a §11.4.35
#    pointer consumer by the very predicate the 17 propagation
    gates source.
#    A FAIL here means the file is scored MISSING by all 17. (This
    is the check
#    whose absence made Revision 1 of this directory defective.)
. submodules/constitution/scripts/gates/lib/pointer_carrier.sh
for s
    in ai_interviewing design-toolkit milosvasic.ru
    monetization vasic.digital; do
    for f in AGENTS CLAUDE QWEN GEMINI; do
        [ -f "$s/$f.md" ] || continue
        is_pointer_carrier "$s/$f.md" \
            && echo "OK    pointer carrier: $s/$f.md" \
            || echo "FAIL not a pointer carrier: $s/$f.md"
    done
done

# 6. Fleet-level before/after – MISSING carriers must not
    increase, and
#    vasic.digital/QWEN.md must have left the MISSING set.
G=submodules/constitution/scripts/gates
for a in 162 167 176 187 191 196 199 200 201 202 207 213 230 231
    232 233 235; do
    bash "$G/cm_covenant_114_${a}_propagation.sh" --root . || true
done 2>&1 | tee /tmp/sweep-after-apply.txt | grep -c '    MISSING'
grep '    MISSING' /tmp/sweep-after-apply.txt \
    | sed 's/.*MISSING *//; s/ *-*.*//' | sort -u

```

Check 4 is the mechanical proof that the conditional form works from every depth. It was **not run** during preparation (it only reads, but it is listed here as the operator's confirmation step).

Checks 5 and 6 are the ones that decide whether this propagation helps or hurts, and both **were** run during preparation of Revision 2 — against a temp directory mirroring this fleet, never against the live submodules. Expected values, reproduced in PROOF.md: check 5 prints

OK for all 20 carriers; check 6 prints 68 and lists exactly the four third-party carriers (`milosvasic.ru/Upstreamable/{AGENTS,CLAUDE}.md`, `submodules/superspec/examples/static-landing-page/CLAUDE.md`, `.specify/extensions/superspec/examples/static-landing-page/CLAUDE.md`) — down from 85 and five. The 17 gates still exit 1 on those four: they are category (c) in `GATE-TRIAGE.md` §3.1 and no change in this directory can clear them. A check-6 number **above** 85 means the applied carriers are not pointer carriers — revert before committing.

6. What this procedure does NOT do

- It does not create the umbrella-root carriers (`CLAUDE.md`, `AGENTS.md`, `QWEN.md`, `GEMINI.md`, `Constitution.md`) that `INVENTORY.md` §7.1 specifies — submodule pointers alone do not close G1/G2 (`INVENTORY.md` §6.4: the 175 CM-COVENANT-114-N-PROPAGATION gates check carriers “across the project”). **State note, 2026-08-26 22:58:** four untracked root carriers (`AGENTS.md`, `CLAUDE.md`, `GEMINI.md`, `QWEN.md`, ~9.6 KB each) appeared in the umbrella working tree *during* the preparation of this directory, written by work outside this task. They use the unconditional project-root form (`## INHERITED FROM submodules/constitution/CLAUDE.md`), which is correct **at the repository root** — the path is real from there and the root is allowed to be project-aware. They are complementary to, not in conflict with, the conditional submodule form standardised in §3: the two layers are governed by different clauses (§11.4.35 invariant 6 for the root, §11.4.28(B) for owned submodules). Since Revision 2 the two forms share the same *heading* — `## INHERITED FROM ...` — and differ only in what follows it: the root names a real relative path and asserts inheritance unconditionally (both true at the repository root), while a submodule carrier names the base file’s canonical name, resolves it with `find_constitution.sh`, and states the inheritance conditionally (the only honest form for a module that can be cloned alone). Those four root carriers are also the working reference Revision 2 was measured against — they are the carriers that pass all 17 propagation gates today. Nothing in this directory reads, modifies, or depends on them.
- It does not create any gate, sweep, hook, or `helix-deps.yaml` (`INVENTORY.md` §7.4). Per §11.4.32 (`Constitution.md`:2079-2082) “Without it, new rules cascade as anchors but never get enforced in the codebase” — these pointers are, until then, unenforced.
- It does not generate the `.html` / `.pdf` siblings that §11.4.65 requires. Its scope table (`Constitution.md`:5989) INCLUDES “Owned-

submodule trees ... top-level README.md / CLAUDE.md / AGENTS.md”. Every file created in §4 is therefore born non-compliant with §11.4.65 until exported. Same known, disclosed deviation INVENTORY.md §1 records for itself, and it applies to APPLY.md / RISKS.md / PROOF.md and the 20 prepared files in this directory too.

- It does not touch submodules/superspec, submodules/constitution, or milosvasic.ru/Upstreamable.
- It does not clear all 17 propagation gates, and Revision 2 does not claim it does. Four category-(c) third-party carriers (GATE-TRIAGE.md §3.1, §7) hold every one of the 17 FAILing no matter what happens in this directory. What the procedure now does is stop *adding* to that set, and remove one carrier from it (vasic.digital/QWEN.md): 85 MISSING lines → 68, five MISSING carriers → four. Measured, not asserted — PROOF.md.