

SAFETY-AND-ROLLBACK

Safety and Rollback

Authoritative reference for the transactional backup manifest written by `scripts/setup-agents-wizard.sh` and for the rollback tool that replays it, `scripts/rollback-agents-wizard.sh`.

Every statement here was read out of those two scripts. For the wizard's own reference see `MANUAL.md`; for symptom-first fixes see `TROUBLESHOOTING.md`.

The short version:

```
./scripts/rollback-agents-wizard.sh --list      # which runs can
          be undone
./scripts/rollback-agents-wizard.sh --dry-run   # what would
          change
./scripts/rollback-agents-wizard.sh --yes
          # undo the newest run
```

What gets backed up, and where

The wizard calls `backup_init` once, immediately after it prints the project root and **before Step 1**. That creates a fresh **session directory** named for the UTC start time and prints it:

```
Backup session: /home/<you>/.local/share/setup-agents-wizard/
backups/20260826T210411Z
```

```
Undo everything later with: /path/to/repo/scripts/rollback-
agents-wizard.sh
```

Layout:

```
~/.local/share/setup-agents-wizard/      <- WIZARD_STATE_DIR
├─ backups/                             <- BACKUP_ROOT
│   └─ 20260826T210411Z/                 <- one session per
wizard run
```

```

    |   |─ manifest.tsv                                <- the transaction
log
    |   |─ files/                                       <- byte-exact
copies of the originals
    |   |   |─ 9f2c1ab30e7d4415___.bashrc
    |   |   |─ 4b7e0d9a1c6f2238___.bash_profile
    |   |   |─ 2d5ae8b17c034f90___.settings.json
    |   |─ pre-rollback-20260826T221530Z/              <- written by the
rollback tool, not the wizard
    |   |─ 20260827T090300Z/                            <- the next run
gets its own session
    |   |─ latest -> 20260827T090300Z                  <- symlink to the
newest session

```

Property	Value
State directory	\$WIZARD_STATE_DIR, default \$HOME/.local/share/setup- agents-wizard
Backup root	\$WIZARD_STATE_DIR/backups
Session id	date -u +%Y%m%dT%H%M%SZ — e.g. 20260826T210411Z
Manifest	<session>/manifest.tsv, tab- separated, one header row
Stored originals	<session>/files/<first-16-hex- of-sha256(target- path)>__<basename>
Newest session	<backup root>/latest, a symlink refreshed by ln -sf on every run
Copy mode	cp -p — content, permissions and timestamps are preserved (test G7)

WIZARD_STATE_DIR is re-resolved **inside backup_init**, not when the script is sourced, so exporting it after sourcing the wizard in library mode still takes effect:

```

SETUP_WIZARD_LIB_ONLY=1 . scripts/setup-agents-wizard.sh
export WIZARD_STATE_DIR="$PWD/.wizard-state"
backup_init          # session lands under $PWD/.wizard-state/
                     backups/

```

The rollback tool reads the same variable, so both sides must agree:

```
WIZARD_STATE_DIR="$PWD/.wizard-state" ./scripts/rollback-agents-  
wizard.sh --list
```

The familiar .bak.<ts> siblings are still written

backup_file does **two** things: it registers the file in the manifest *and* keeps the old sibling copy next to the original, <file>.bak.YYYYMMDDHHMMSS (local time, unlike the UTC session id). Those siblings accumulate — nothing rotates or removes them, including rollback. Prune them yourself:

```
ls -l ~/.bashrc.bak.* ~/.bash_profile.bak.* ~/.local/bin/  
lumen.bak.* \  
~/.claude/*.bak.* ~/.kimi-code/*.bak.* ~/.qwen/*.bak.* 2>/  
dev/null
```

install_lumen_completion uses snapshot_before directly rather than backup_file, so ~/.local/share/bash-completion/completions/lumen is in the manifest but gets **no** .bak.<ts> sibling.

In the other direction, ~/.bashrc collects **two** siblings per run: both configure_telemetry_optout and configure_lumen_shell call backup_file on it. The manifest still holds a single row for it, because the first snapshot wins.

What is *not* recorded

The manifest covers what the wizard writes itself. It does not cover work delegated to third-party installers or to other tools:

Not recorded	Why
Bun (~/.bun), WOZCODE	Vendor curl \ bash installers; they write their own files and may edit rc files themselves
ashlr (~/.claude/plugins/cache/ashlr-marketplace/ashlr/)	Vendor curl \ bash installer. It clones a plugin directory and creates no binary — remove it with rm -rf on that path. Whatever /plugin install then registers inside Claude Code is Claude Code’s state, not the wizard’s
<project>/MANUAL-STEPS.md	Written on every run from the manual-step registry. It is a regenerated snapshot of what is

Not recorded	Why
	still pending, not a wizard “edit” — <code>rm</code> it, or <code>.gitignore</code> it
<code><project>/.ashlr/ashlr-genome/</code>	Created by <code>/ashlr:ashlr-genome-init</code> inside Claude Code. The wizard only detects its absence
<code><project>/lumen-reindex.log</code>	Appended by <code>scripts/lumen-reindex.sh</code>
<code>/etc/sysconfig/ollama</code>	Written only by <code>scripts/ollama-vulkan-remediation.sh --apply</code> , never by the wizard (test A41). It has its own undo: <code>--rollback</code>
Ollama, its <code>systemd</code> unit, and the pulled embedding model	Installed by <code>https://ollama.com/install.sh</code> / <code>brew</code> , enabled with <code>systemctl</code>
<code>~/claude/plugins/marketplaces/Sagargupta16/...</code> and <code>~/JCodesMore/...</code>	Plain <code>git</code> clones, skipped when the directory already exists
<code>submodules/</code> , <code>submodules/superspec/</code> , <code>.specify/</code> , <code>specs/</code>	Project content created in Step 6 — treat it as repository state, not wizard leftovers
<code>~/local/share/lumen/</code>	Index databases written by <code>lumen index</code> , never by the wizard. Use <code>lumen purge</code>
<code><project>/codegraph/</code>	The CodeGraph database, created by <code>codegraph init</code> in the opt-in Step 8 (and updated in place by <code>codegraph sync</code>). Written by CodeGraph, not the wizard. Remove with <code>rm -rf .codegraph</code>
<code>~/codegraph/telemetry.json</code>	Written by <code>codegraph telemetry off</code> during the Step 3 telemetry opt-out. CodeGraph owns the file; the wizard only invokes the CLI

`uv tool install specify-cli` used to be on this list. It is not any more — see Components — it records `ACTION uv tool uninstall specify-cli` under the `speckit` component, so `--run-actions` **will** `uninstall` `SpecKit` unless you scope the rollback with `--component`.

The manifest format

manifest.tsv is tab-separated with exactly six columns and one header row:

component	action	target	backup	sha256_before	timestamp
Column	Meaning				
component	Which part of the wizard made the change — the unit -- component filters on				
action	MODIFIED, CREATED, ACTION or NOTE (below)				
target	Absolute path of the file, or for ACTION rows the literal undo command, or for NOTE rows the prose describing what cannot be undone				
backup	Absolute path of the stored original, or -				
sha256_before	sha256sum of the file before the change, or -				
timestamp	date -u +%Y-%m-%dT%H:%M:%SZ when the row was written				

The four action types

Action	Recorded when	Rollback does
MODIFIED	The target already existed	Restores the stored copy over it with cp -p — byte-exact, mode preserved
CREATED	The target did not exist	Deletes the target (rm -f)
ACTION	The change is not a file at all — an npm install -g, a claude mcp registration, an ollama-tune.sh -- revert	Prints the undo command. Executes it only with --run-actions

Action	Recorded when	Rollback does
NOTE	The change is real and has no undo at all	Prints NOT DONE (no undo exists) [component] ..., counts it in the NOT undone tally, and never executes anything . It exists so the summary cannot imply a reversal that did not happen (§11.4.6)

The only NOTE the wizard writes today comes from Step 7: applying the ollama concurrency tuning restarts the service, and --revert restarts it again but cannot resurrect the embedding requests the first restart aborted. Written by record_note immediately after the paired record_action, so a manifest that carries the undo also carries the honest limit of that undo.

Worked example

A first run on a machine that has Claude Code, Kimi, Opencode and Qwen Code installed, and that was missing glyphdown and specify, produces a manifest like this (rows appear in execution order; sha256_before is a full 64-character digest, abbreviated here):

component	action	target	backup	sha256_before
npm	ACTION	npm uninstall -g glyphdown	-	-
speckit	ACTION	uv tool uninstall specify-cli	-	-
shell	MODIFIED	/home/you/.bashrc	.../files/9f2c1ab30e7d4415___.bashrc	c1f9a4...
qwen	MODIFIED	/home/you/.qwen/settings.json	.../files/aa17bf3c25e60d84___.settings.json	55c2ab...
lumen	CREATED	/home/you/.local/bin/lumen	-	-
lumen	CREATED	/home/you/.local/share/bash-completion/completions/lumen	-	-

component	action	target	backup	sha256
shell	MODIFIED	/home/ you/.bash_profile	.../files/ 4b7e0d9a1c6f2238__bash_profile	7a0233
claude	ACTION	claude mcp remove lumen -s user	-	-
claude	MODIFIED	/home/ you/.claude/ settings.json	.../files/ 2d5ae8b17c034f90__settings.json	3e11bd
kimi	MODIFIED	/home/you/.kimi- code/mcp.json	.../files/ 8c04f2a99b1d3e57__mcp.json	1b7c40
opencode	MODIFIED	/home/ you/.config/ opencode/ opencode.json	.../files/ 61ae3c008df4b912__opencode.json	d904e7

Two things to read out of that shape:

- **~/ .bashrc and ~/ .qwen/settings.json are snapshotted in Step 3**, by `configure_telemetry_optout`, before the Lumen block and the MCP merge touch them again in Steps 3 and 5. First snapshot wins, so one row covers every later edit to the same file.
- **Every MODIFIED above assumes the file already existed.** On a clean machine `~/ .claude/settings.json`, `~/ .kimi-code/mcp.json` and `~/ .qwen/settings.json` are recorded `CREATED` instead, and `rollback` deletes them rather than restoring an empty `{}`.

Read it directly whenever you want to know what a run touched:

```
column -t -s $'\t' ~/.local/share/setup-agents-wizard/backups/  
latest/manifest.tsv  
awk -F'\t' 'NR>1 {print $1, $2, $3}' ~/.local/share/setup-agents-  
wizard/backups/latest/manifest.tsv
```

First snapshot wins

`snapshot_before` skips a target that is already present in column 3 of this session's manifest. Several wizard steps can touch the same file within one run; only the **first** snapshot is kept, so the stored copy is always the true pre-run original and `rollback` restores that, not an intermediate state. Test **G6** asserts exactly this.

Consequently a session's manifest holds **at most one row per file path**, and rows for a file whose `cp -p` failed are omitted entirely — the wizard prints `Could not back up <path>` in that case.

Components

Component	Written by	Covers
lumen	install_lumen_wrapper, install_lumen_completion (Step 3)	~/.local/bin/lumen, ~/.local/share/bash-completion/completions/lumen
shell	configure_lumen_shell and configure_telemetry_optout (both Step 3)	~/.bashrc, ~/.bash_profile. Both functions call backup_file "\$HOME/.bashrc" shell, so that file gets two .bak.<ts> siblings per run but only one manifest row
claude	Step 5	ACTION claude mcp remove lumen -s user, ~/.claude/settings.json for the Glyphdown hooks, and ~/.claude.json for the Lumen mirror that MiMo and other inheritors read
kiml	Step 5	~/.kiml-code/mcp.json
opencode	Step 5	~/.config/opencode/ opencode.json
qwen	Step 3 (telemetry) and Step 5 (MCP)	~/.qwen/settings.json — snapshotted by whichever step touches it first, so one row covers both the .usageStatisticsEnabled edit and the .mcpServers merge
npm	npm_install_if_missing (Step 2)	One ACTION npm uninstall -g <pkg> per package the wizard actually installed
speckit	The uv branch of Step 2	One ACTION uv tool uninstall specify-cli,

Runs under `set -uo pipefail` (no `-e`). It takes no positional arguments.

Option	Short	Effect
<code>--list</code>	—	Print every session that has a <code>manifest.tsv: id</code> , change count, components. Exits immediately afterwards
<code>--session <id\ latest></code>	—	Choose a session by directory name, e.g. <code>20260826T210411Z</code> . latest, or omitting the option, selects the newest session by name
<code>--component <name></code>	<code>-c</code>	Restrict the rollback to one component. Repeatable. all matches everything. Default: every component in the manifest
<code>--dry-run</code>	<code>-n</code>	Print the plan and exit 0 without changing anything (test G10)
<code>--yes</code>	<code>-y</code>	Skip the Apply this rollback? [y/N] prompt
<code>--run-actions</code>	—	Also eval the undo command of every ACTION row. Without it those rows are printed only
<code>--help</code>	<code>-h</code>	Print the script's header comment as usage and exit 0

Any other argument prints `Unknown option: ...` and exits 2.

Exit codes

Code	Condition
0	Rollback applied with no failures. Also: <code>--list</code> , <code>--help</code> , <code>--dry-run</code> , “nothing to roll back for the selected components”, and answering <code>n</code> at the prompt
1	At least one entry failed — a missing backup file, or a <code>cp/rm</code> that did not succeed. Also: no backup root at all, or no <code>manifest.tsv</code> for the chosen session
2	An unrecognised option

A failed ACTION undo command does not affect the exit code, but it is no longer reported as an equivocation. It prints `NOT UNDONE` [component] undo command exited N: ..., is counted in the NOT undone tally on the summary line, and is listed again at the end under ... change(s) were NOT undone by this run followed by `Do not record this rollback as a full reversal.`

The previous wording — “undo command failed (may already be undone)” — let a change that is still in place read as reversed. Whether something else undid it earlier is unknown, and unknown is now reported as unknown.

What a run looks like

```
$ ./scripts/rollback-agents-wizard.sh --dry-run

=====
Rollback plan
=====
  Session   : 20260826T210411Z
  Components: all
  DRY RUN - nothing will be changed.
  manual    [npm] npm uninstall -g glyphdown    (use --run-actions
to execute)
  delete    [lumen] /home/you/.local/bin/lumen
  delete    [lumen] /home/you/.local/share/bash-completion/
completions/lumen
  restore   [shell] /home/you/.bashrc
  restore   [shell] /home/you/.bash_profile
```

```
manual [claude] claude mcp remove lumen -s user (use --run-
actions to execute)
restore [claude] /home/you/.claude/settings.json
restore [kimi] /home/you/.kimi-code/mcp.json
restore [opencode] /home/you/.config/opencode/opencode.json
restore [qwen] /home/you/.qwen/settings.json
```

Without --dry-run it asks once, then applies, then reports:

```
Apply this rollback? [y/N] y
Current state is being saved to /home/you/.local/share/setup-
agents-wizard/backups/20260826T210411Z/pre-
rollback-20260826T221530Z
```

```
=====
Applying rollback
=====
" restored [shell] /home/you/.bashrc
"
...
=====
Rollback complete
=====
restored/removed: 8 failures: 0
Pre-rollback state kept at: .../pre-rollback-20260826T221530Z
Open a new shell for PATH changes to take effect.
```

ACTION rows are printed twice by design — once in the plan, once while applying — which is what test **G14** pins down. They are never executed without --run-actions.

Rollback is itself reversible

Before touching anything (and only after the prompt is answered), the tool creates

```
<session>/pre-rollback-<UTC timestamp>/
```

and copies the **current** on-disk content of every file it is about to restore or delete into it, under the same <16-hex>__<basename> naming scheme as files/. Nothing the rollback overwrites or removes is lost. Test **G13** asserts the snapshot is created.

ACTION rows are not snapshotted — there is no file to copy. Redo them by hand (see [Reversing a rollback](#)).

Recipes

All commands are run from the repository root.

See what can be undone

```
./scripts/rollback-agents-wizard.sh --list
```

```
=====
Backup sessions
=====
  20260826T210411Z      11 changes   components: claude kimi lumen
npm opencode qwen shell speckit
  20260827T090300Z      4 changes   components: claude shell
```

Each session is **one wizard run** and contains only what *that* run changed.

Undo the newest run completely

```
./scripts/rollback-agents-wizard.sh --dry-run    # read the plan
first
./scripts/rollback-agents-wizard.sh --yes
exec bash -l                                     # pick up the
restored PATH
```

Add `--run-actions` to also undo the claude mcp registration and the npm global installs:

```
./scripts/rollback-agents-wizard.sh --run-actions --yes
```

Undo only the shell PATH changes

Restores `~/.bashrc` and `~/.bash_profile` byte-exactly as they were before the run — which removes the managed lumen and user bin on PATH blocks along with them, and preserves whatever else you had in those files.

```
./scripts/rollback-agents-wizard.sh --component shell --dry-run
./scripts/rollback-agents-wizard.sh --component shell --yes
exec bash -l
```

Nothing else is touched — test **G11** asserts that a component filter leaves other components alone.

Remove Lumen from Opencode only

```
./scripts/rollback-agents-wizard.sh -c opencode -n  
./scripts/rollback-agents-wizard.sh -c opencode -y  
jq '.mcp.lumen' ~/.config/opencode/opencode.json # -> null
```

Restart Opencode afterwards; MCP servers are launched at session start.

Undo one or two agents, keep the rest

--component is repeatable:

```
./scripts/rollback-agents-wizard.sh -c kimi -c qwen --yes
```

-c all is accepted and is equivalent to passing no filter.

Unregister Lumen from Claude Code

The registration is an ACTION row, so it needs --run-actions:

```
./scripts/rollback-agents-wizard.sh -c claude --run-actions --dry-run  
./scripts/rollback-agents-wizard.sh -c claude --run-actions --yes  
claude mcp get lumen # -> not found
```

Note that component claude also owns ~/.claude/settings.json (the Glyphdown hooks), so that file is restored in the same pass. To undo *only* the MCP registration, run the undo command the manifest records, by hand:

```
claude mcp remove lumen -s user
```

Undo the npm global installs

```
./scripts/rollback-agents-wizard.sh -c npm --run-actions --dry-run # see exactly which packages  
./scripts/rollback-agents-wizard.sh -c npm --run-actions --yes
```

Only packages the wizard actually installed have an ACTION row — npm_install_if_missing skips anything already on PATH, so a pre-existing glyphdown is never uninstalled.

Undo the SpecKit install

SpecKit is not an npm package, so it has its own component:

```
./scripts/rollback-agents-wizard.sh -c speckit --run-actions --  
dry-run  
./scripts/rollback-agents-wizard.sh -c speckit --run-actions --  
yes # uv tool uninstall specify-cli
```

The reverse matters too: a bare `--run-actions --yes` with **no** `--` component will uninstall SpecKit along with everything else. Scope the rollback if you want to keep it.

Roll back an older run

```
./scripts/rollback-agents-wizard.sh --list  
./scripts/rollback-agents-wizard.sh --session 20260826T210411Z --  
dry-run  
./scripts/rollback-agents-wizard.sh --session 20260826T210411Z --  
yes
```

Undo several runs

Sessions are independent snapshots taken at different times. Roll them back **newest first**, one at a time, so each restore lands on the state that session expected:

```
./scripts/rollback-agents-wizard.sh --session 20260827T090300Z --  
yes  
./scripts/rollback-agents-wizard.sh --session 20260826T210411Z --  
yes
```

Rolling back only the newest session returns you to the state immediately before *that* run — not to a pristine machine.

Reversing a rollback

Every applied rollback leaves `<session>/pre-rollback-<UTC>/` holding the content that was on disk at that moment. Files are named `<first-16-hex-of-sha256(path)>__<basename>`, the same scheme as `files/`.

```
SESSION=~/.local/share/setup-agents-wizard/backups/  
20260826T210411Z  
ls -l "$SESSION"/pre-rollback-*/
```

To put one file back, compute its key and copy it over:

```
PRE="$SESSION/pre-rollback-20260826T221530Z"  
KEY=$(printf '%s' "$HOME/.bashrc" | sha256sum | cut -c1-16)  
cp -p "$PRE/${KEY}__bashrc" "$HOME/.bashrc"
```

To put everything back, walk the snapshot and match each file to its manifest target:

```
PRE="$SESSION/pre-rollback-20260826T221530Z"
awk -F'\t' 'NR>1 && ($2=="MODIFIED" || $2=="CREATED") {print $3}'
    "$SESSION/manifest.tsv" |
while read -r target; do
    key=$(printf '%s' "$target" | sha256sum | cut -c1-16)
    src="$PRE/${key}__$(basename "$target")"
    [ -f "$src" ] && cp -p "$src" "$target" && echo "restored
    $target"
done
```

ACTION rows have no snapshot. Redo them explicitly:

```
claude mcp add-json lumen "{\"command\":\"\\\"$HOME/.local/bin/
    lumen\\\",\\\"args\\\":[\\\"stdio\\\"]}\" -s user
npm install -g glyphdown
```

Or simply re-run the wizard — it is idempotent, and it opens a new backup session of its own.

Manual uninstall, if the manifest is lost

Use this when `~/.local/share/setup-agents-wizard/` was deleted, when `WIZARD_STATE_DIR` pointed somewhere that no longer exists, or when you want to remove the wizard's footprint without a session to replay. Each block is independent — skip anything you want to keep.

lumen — launcher and completions

```
rm -f ~/.local/bin/lumen ~/.local/bin/lumen.bak.*
rm -f ~/.local/share/bash-completion/completions/lumen
```

shell — the managed PATH blocks

Reuse the wizard's own remover in library mode, so the markers (which contain regex metacharacters) and the file's mode and inode are handled correctly:

```
cd /path/to/this/repo
SETUP_WIZARD_LIB_ONLY=1 . scripts/setup-agents-wizard.sh
strip_managed_block "$HOME/.bashrc" "$LUMEN_BLOCK_START"
    "$LUMEN_BLOCK_END"
```



```
strip_managed_block "$HOME/.bashrc" "$PRIVACY_BLOCK_START"
"$PRIVACY_BLOCK_END"
strip_managed_block "$HOME/.bash_profile" "$USERBIN_BLOCK_START"
"$USERBIN_BLOCK_END"
```

There are three blocks, not two: ~/.bashrc carries both the Lumen block and the telemetry opt-out block.

Verify:

```
grep -c '>>> lumen semantic search' ~/.bashrc # -> 0
grep -c '>>> telemetry opt-out' ~/.bashrc # -> 0
grep -c '>>> user bin on PATH' ~/.bash_profile # -> 0
```

claude — MCP registration, hooks, marketplace clones

```
claude mcp remove lumen -s user
tmp=$(mktemp) && jq 'del(.mcpServers.lumen)' ~/.claude.json >
"$tmp" && mv "$tmp" ~/.claude.json
```

Two commands, because there are two places. claude mcp owns the registration in the **active** CLAUDE_CONFIG_DIR, and the wizard additionally jq-merges the single .mcpServers.lumen key into ~/.claude.json so that tools inheriting from the default config — MiMo Code lists its servers as claude:~/.claude.json — can see it. Never hand-edit the rest of ~/.claude.json; it also holds session and project state.

A full -c claude rollback restores ~/.claude.json byte-exactly, which removes the mirror along with the Glyphdown hooks and the claude mcp ACTION.

Remove the Glyphdown PreToolUse / PostToolUse entries while preserving your own hooks:

```
tmp=$(mktemp)
jq '
  def strip: (. // []) | map(select((.[.hooks[]?.command] |
    index("glyphdown")) | not));
  .hooks.PreToolUse |= strip | .hooks.PostToolUse |= strip
' ~/.claude/settings.json > "$tmp" && mv "$tmp" ~/.claude/
settings.json
```

The two marketplace repositories the wizard cloned:

```
rm -rf ~/.claude/plugins/marketplaces/Sagargupta16/claude-cost-
optimizer
rm -rf ~/.claude/plugins/marketplaces/JCodesMore/jcodesmore-
plugins
```

kimi — ~/.kimi-code/mcp.json

```
tmp=$(mktemp)
jq 'del(.mcpServers.lumen, .mcpServers.codegraph)' ~/.kimi-code/
  mcp.json > "$tmp" \
  && mv "$tmp" ~/.kimi-code/mcp.json
```

opencode — ~/.config/opencode/opencode.json

Opencode uses a .mcp object, **not** .mcpServers, and the wizard only adds lumen there:

```
tmp=$(mktemp)
jq 'del(.mcp.lumen)' ~/.config/opencode/opencode.json > "$tmp" \
  && mv "$tmp" ~/.config/opencode/opencode.json
```

qwen — ~/.qwen/settings.json

Two separate edits live in this file: the MCP merge from Step 5 and the .usageStatisticsEnabled flag from the Step 3 telemetry opt-out. Remove whichever you want back:

```
tmp=$(mktemp)
jq 'del(.mcpServers.lumen, .mcpServers.codegraph)' ~/.qwen/
  settings.json > "$tmp" \
  && mv "$tmp" ~/.qwen/settings.json

tmp=$(mktemp)
jq 'del(.usageStatisticsEnabled)' ~/.qwen/settings.json > "$tmp" \
  && mv "$tmp" ~/.qwen/settings.json      # back to Qwen's own
                                          default
```

speckit — the SpecKit CLI

```
uv tool uninstall specify-cli
```

This is the exact command the manifest records under component speckit, so ./scripts/rollback-agents-wizard.sh -c speckit --run-actions --yes does the same thing.

Telemetry settings

The ~/.bashrc opt-out block is covered by the shell block above, and the Qwen flag by the qwen block. CodeGraph's own switch is out of band — the wizard ran codegraph telemetry off, and CodeGraph persists that in ~/.codegraph/telemetry.json:

```
codegraph telemetry --help    # its own re-enable command
```

There is nothing to undo for Lumen: it ships no telemetry, so the wizard never set anything for it.

MiMo Code

There is no MiMo-specific config file to undo. MiMo **inherits** MCP servers from `~/.claude.json` (it lists them as `claude:~/.claude.json`), so removing the mirror is what removes Lumen from MiMo:

```
jq 'del(.mcpServers.lumen)' ~/.claude.json > /tmp/cj &&  
mv /tmp/cj ~/.claude.json  
mimo mcp list | grep lumen    # should now find nothing
```

Restart MiMo afterwards — MCP servers are launched at session start.

npm and uv — global CLI tools

Uninstall only what you want gone, and only if the wizard installed it (it skips anything already present):

```
npm uninstall -g @colbymchenry/codegraph glyphdown @qwen-code/  
qwen-code  
uv tool uninstall specify-cli
```

Kimi, Opencode and MiMo Code are **not** npm-installed by the wizard — they ship their own installers and are only detected. Remove them with their vendors' instructions.

Everything else

```
lumen purge    # drop every index  
               under ~/.local/share/lumen (do this before deleting the  
               launcher)  
rm -rf ~/.local/share/setup-agents-wizard    # the backup  
               sessions themselves — only once you are sure
```

Bun (`~/.bun`), the ashlr **plugin** (`~/.claude/plugins/cache/ashlr-marketplace/ashlr/` — a clone, not a binary), Ollama and the embedding model were installed by their own vendors' scripts; see [FAQ.md](#) for the full ordered procedure. The wizard-adjacent project files it also leaves behind:

```
rm -f MANUAL-STEPS.md .lumen-reindex.log      # regenerated
      artifacts, not in the manifest
rm -rf .ashlrcode                             # the ashlr genome,
      if you ran /ashlr:ashlr-genome-init
./scripts/ollama-vulkan-remediation.sh --rollback  # ONLY if you
      applied it; restores the defect
```

Safety guarantees

What is reversible

Guarantee	Mechanism
A file the wizard modified is restored byte-exactly, with its original permissions	cp -p both ways; sha256_before records the original digest for verification (tests G5 , G7 , G8)
A file the wizard created is deleted	CREATED rows (test G9)
An agent config the wizard had to create from scratch is deleted, not left behind as an empty {}	configure_mcp_for_agent and the Glyphdown hook step call snapshot_before before seeding {}, so the row is CREATED. Applies to ~/.kimi-code/mcp.json, ~/.qwen/settings.json and ~/.claude/settings.json on a clean machine (tests G16 , G17 ; G18 checks a pre-existing config still restores to its real content)
A file touched by several steps restores to its true pre-run original	First snapshot wins in snapshot_before (test G6)
Every install the wizard performs itself can be undone	npm_install_if_missing writes an ACTION under npm, and the uv branch writes uv tool uninstall specify-cli under speckit (test A28). Only the third-party installers — Bun, ashlr, WOZCODE — record nothing
You can preview any rollback without risk	--dry-run changes nothing and exits 0 (test G10)

Guarantee	Mechanism
You can undo one part without disturbing the others	- - component, repeatable (tests G11, G12)
The rollback itself can be undone	<session>/pre-rollback-<UTC>/ is written before anything is touched (test G13)
Non-file changes are never executed behind your back	ACTION rows are printed; - - run-actions is required to run them (test G14)
Your own content in ~/.bashrc / ~/.bash_profile survives both directions	The wizard only rewrites its marker-delimited blocks; rollback restores the whole file from its snapshot
Pre-existing MCP servers and config keys survive	Every merge is a jq merge that preserves foreign keys (test D4)

What is *not* reversible, or not covered

- **Anything outside the manifest.** Bun, ashlr, WOZCODE, Ollama, its systemd unit, the pulled embedding model, the two git cloned marketplaces, specify init output, the SuperSpec checkout, <project>/.codegraph/, <project>/MANUAL-STEPS.md, <project>/.ashlr/code/genome/, <project>/.lumen-reindex.log and ~/.codegraph/telemetry.json have no rows and are untouched by rollback.
- **Nothing the three operational scripts do is in the manifest.** They run outside the wizard's transaction entirely, and each has its own undo:

Change	Made by	Undo
GGML_VK_VISIBLE_DEVICES=-1 in /etc/sysconfig/ollama, plus a service restart	ollama-vulkan-remediation.sh - - apply	./scripts/ollama-vulkan-remediation.sh - - rollback (needs sudo; restores the defect)
A rebuilt Lumen index	lumen-reindex.sh	lumen purge <path>, then re-index

Change	Made by	Undo
<project>/. lumen-reindex.log	lumen-reindex.sh	rm it
(nothing)	lumen-index-doctor.sh	Read-only by construction — it opens the database mode=ro and never calls the embedding backend (tests I10, I14)

See `OPERATIONAL-SCRIPTS.md`.

- **The telemetry opt-out is only *partly* covered.** The `~/.bashrc` block is inside the shell snapshot and the `~/.qwen/settings.json` edit inside the `qwen` one, so both come back with a normal restore. But `codegraph telemetry off` is an out-of-band CLI call with no `ACTION` row — CodeGraph keeps that state in `~/.codegraph/telemetry.json`, and you re-enable it yourself (`codegraph telemetry --help`).
- **Changes you made after the wizard ran are overwritten** by a `MODIFIED` restore. They are not lost — they are in the `pre-rollback-<UTC>` snapshot — but they do not survive in place. Run `--dry-run` first.
- **`ACTION` failures do not fail the run.** A failed undo command warns and the exit code stays 0. Verify with `claude mcp get lumen` or `npm ls -g`.
- **The manifest stores absolute paths.** Moving or renaming the state directory after a run breaks restore: `MODIFIED` rows fail with `Backup missing for <target> (<backup>)` and the tool exits 1.
- **A session is one run, not a machine state.** Rolling back the newest session returns you to the state immediately before it, not to a pristine system.
- **`.bak.<ts>` siblings are never removed** by rollback, and neither are the session directories themselves.
- **Lumen indexes are out of scope.** `~/.local/share/lumen/` is written by `lumen index`; use `lumen purge`.

- **Rollback does not restart anything.** Open a new shell for PATH changes, and restart each agent for MCP changes — the tool prints the reminder for the shell case.
-

Related

- [README.md](#) — what the wizard installs, and the doc index.
- [MANUAL.md](#) — function-by-function reference, including `backup_init`, `snapshot_before`, `record_action` and `_sha`.
- [TROUBLESHOOTING.md](#) — restoring from a session, and Backup missing failures.
- [FAQ.md](#) — the full uninstall procedure.
- [OPERATIONAL-SCRIPTS.md](#) — the three post-install scripts, none of which is covered by this manifest, and how to undo each of them.
- [ACTION-REQUIRED.md](#) — [MANUAL-STEPS.md](#) and the other artifacts the rollback tool deliberately leaves alone.
- `scripts/rollback-agents-wizard.sh` — the tool itself; `--help` prints its header comment.