

Fronde Documentation

Étienne Deparis

March 17, 2024

Contents

1	Introduction	2
1.1	Summary	2
1.2	Nomenclature	2
1.3	Frequently Asked Questions	2
1.3.1	Why do you think we need another static website generator?	2
1.3.2	Where does this name come from?	2
1.3.3	Opinionated you say?	3
1.3.4	What will come next?	3
1.4	Source code	4
2	Getting started	4
2.1	Installation	4
2.1.1	Install ruby with your system package manager	4
2.1.2	Install ruby with RVM	5
2.1.3	Install Fronde	5
2.1.4	Build Fronde from sources	5
2.2	Creation of a website	5
2.3	Creation or edition of a page	7
2.4	Building the website	8
2.5	Publishing the website	9
3	Advanced usage	9
3.1	Config File	9
3.1.1	author	9
3.1.2	domain	10
3.1.3	gemini_public_folder	10
3.1.4	gemini_remote	10
3.1.5	html_public_folder	11

3.1.6	html_remote	11
3.1.7	lang	11
3.1.8	sources	11
3.1.9	templates	13
3.2	Preamble, Postamble, and Templates formatting tags	14
3.3	Rake tasks	16

1 Introduction

1.1 Summary

Fronde is a static website generator for [Org](#), written in Ruby and Emacs Lisp (elisp). It enables you to concentrate on your writing, and manage all the needed steps to build and publish your website.

You can refer to the [read me file](#) for a quick list of the main features.

1.2 Nomenclature

This project name is fronde and will always be written normally though this document to refer to this project as a whole. As such, it will also be capitalized when used as the first word of a sentence. But when it is written as fronde, it will always refer to the provided program you can call in your terminal.

This document uses the short name Emacs to refer to the [GNU Emacs](#) editor or capabilities.

1.3 Frequently Asked Questions

1.3.1 Why do you think we need another static website generator?

My main reason to write fronde, is that I was looking for a static website generator, which provides (good) support for Org as a source format. But they somehow all lack of it. The second main reason I wrote this, instead of dealing with a pure Org publish config, was my need to easily amend the generated HTML. I'm not an elisp expert and I would like to have some generic solution for all the tiny websites I'm maintaining. In short, the main feature of this project is surely its [templates support](#).

1.3.2 Where does this name come from?

A *fronde* is the french word for a [sling](#). This name was chosen as a tribute to the french newspaper « La Fronde », created by [Marguerite Durand](#) in France in

1897. This was the first all-women written and edited newspaper in the world. Marguerite Durand said about it in one of her editorial¹ that her newspaper was « comme les autres journaux... pas plus amusant » (which may be translated as “just like other newspapers... as boring”).

As such, fronde is like all other static website generator... as boring. However, like its illustrious reference, fronde wishes to help empowering people, offering them a tool to express themselves on the Web.

1.3.3 Opinionated you say?

Fronde is built with some strong opinion about what a static website generator should be, and more specifically, what should it be for Org.

- Org is a powerful tool that enables you to publish your writings in a wide range of formats. Its markup is easy to learn and as readable and as convenient as Markdown’s. That’s why fronde will never support any other markup language.
- However Org HTML export should be more easily expandable. That’s why fronde gives you the [templates feature](#) and introduces [new formatting tags](#) for the preamble and postamble sections.
- Org writers should already be Emacs users, that’s why fronde will directly call Emacs to convert your Org files to HTML. There is no need to use Pandoc or org-ruby if you already have Emacs.
- You may want to author a wide variety of things, and managing all these projects inside your Emacs configuration may be a nightmare. You also may want to apply different settings for different projects. That’s why fronde is totally independent from your Emacs settings and enables you to organize your projects as you wish.

1.3.4 What will come next?

We are already aware of some limitations we would like to remove:

TODO Allow themes to provide configuration options Themes should be able to declare a set of default templates or specific Org export options

¹Marguerite Durand. « En cinq ans ». La Fronde, n° 1832. 15th December 1902. <https://gallica.bnf.fr/ark:/12148/bpt6k67059454.item>

TODO Better protected upgrade For example, Rakefile should only be overwritten after upgrade of the gem.

TODO Create a themes portfolio

1.4 Source code

The canonical repository is located at <https://git.umaneti.net/fronde>. A mirror also exists on [Github](#).

2 Getting started

2.1 Installation

Fronde is a [Ruby gem](#) and thus you need a working Ruby environment to use it. Fronde requires at least ruby 2.7 to work (though this version is no more maintained, you should really move to ruby 3.1 as soon as possible).

You may already have Ruby installed on your computer. You can check inside a terminal emulator by typing: `ruby -v`. You also need the `rubygems` package manager, which may also be already installed on your system. You can check it too with the following command: `gem -v`.

2.1.1 Install ruby with your system package manager

See the [official ruby lang website](#) to find out about options when installing a ruby environment on your system.

Some operating systems already package the right ruby version to use:

Archlinux-like On Archlinux, Manjaro or Parabola, you just have to install the packages `rubygems` (which will install `ruby` as a dependency):

```
sudo pacman -S ruby rubygems
```

Listing 1: Ruby installation procedure on Archlinux-like system

Debian-like On Debian, Ubuntu, Mint... you just have to install the package `ruby` (which will install `ruby-rubygems` as a dependency):

Others Ruby seems to be well packaged for Fedora, Red Hat or OpenMandriva, thus it should not be a problem for you to install it.

```
sudo apt install ruby
```

Listing 2: Ruby installation procedure on Debian-like system

2.1.2 Install ruby with RVM

RVM allows you to install different ruby versions on the same machine. It could be interesting when you are already a ruby developer.

We recommend that you use a dedicated gemset for fronde, to avoid polluting your other projects.

```
rvm get latest  
rvm install ruby-3.2.2  
rvm use ruby-3.2.2@fronde --create
```

Listing 3: Ruby installation procedure with RVM

2.1.3 Install Fronde

As soon as you have a working ruby environment, you just need to install it as any other gem:

```
gem install fronde
```

Listing 4: Fronde gem installation procedure

2.1.4 Build Fronde from sources

You may also want to install a development version of fronde, directly from its source code repository. We won't describe this procedure in detail as it should only be used by developers or advanced users. But still, here are the commands you can use to build fronde from the sources.

Then, you can install fronde from this new locally built gem file (obviously, you must adapt the following command with the fronde version number you just built):

2.2 Creation of a website

A fronde project is essentially just a folder containing the configuration of your website and a subfolder containing the org files to publish. fronde requires a local

```
git clone https://git.umaneti.net/fronde
cd fronde
gem install bundler
bundle install
gem build fronde.gemspec
```

Listing 5: Build sources procedure

```
gem install fronde-0.4.0.gem
```

Listing 6: Fronde installation procedure from local gem file

installation of org-mode to work, and will generate various configuration files you are not expected to modify. To set up all these things, you must use the `fronde init` command.

Thus, to create a new fronde website, you must create an empty folder and move to this new folder in your terminal:

```
mkdir yourproject
cd yourproject
```

Listing 7: Create a fronde project directory

Now, you can run the `fronde init` command with some arguments:



The following arguments are allowed:

- a (-author)** Set up the default author name (see the [author config key](#))
- l (-lang)** Set up the default lang of your website (see the [lang config key](#))
- t (-title)** Set up the title of your first page

At the end of the init process, fronde will automatically open Emacs on the first page of your website. You can directly write in it or close it and come back to it later. This file is stored in the default `src source` subfolder as `src/index.org`.

Your project now consist of the following file hierarchy:

```
fronde init -t "My brand new website"
```

Listing 8: Initialize a fronde project

```
yourproject/
├─ config.yml      # main config file
├─ .dir-locals.el  # Emacs per-directory local variables file
├─ lib/            # required dependencies
├─ public_html/    # output folder
│   └─ assets/
├─ Rakefile        # fronde-generated ruby related file
├─ src/
│   └─ index.org   # your first website page
└─ var/            # variable files used during operation
```



Fronde relies a lot on files stored in the `lib` and `var` folders. You should never try to remove them by yourself.

2.3 Creation or edition of a page

To create a new page for your website, or to edit an already existing one, you are totally free to use the tool you want. Pages are just regular Org files, without any specific modifications. If you already have a bunch of them, you can use them without any changes.

By default, without any other configuration options, the website pages must be stored in a folder named `src` at the root of your project. However you can configure any other [sources folder](#) you want, even one that is not in your project directory.

In parallel to your regular Org workflow, fronde provides command to help you create or edit pages for your website: the `fronde open` command.

The most simple use case is to call `fronde open` with a file path and it will open that file in your default EDITOR (which should be Emacs).

```
fronde open src/index.org
```

Listing 9: Open a page with the fronde open command

When creating a new page, this command accepts the following arguments:

-a (-author) Set the author name of the page

-l (-lang) Set the language of the page

-t (-title) Set the title of the page

If you use the `--title` argument, instead of giving a full file path argument, you can just give the folder path where you want to save the new file, and the command will create the document with a web-ready name.

```
fronde open -a Alice -t "My new page's shiny, isn't it?" src
ls src
> index.org  my-new-page-s-shiny-isn-t-it.org
```

Listing 10: Creation of a new page with the title argument

And now `src/my-new-page-s-shiny-isn-t-it.org` contains:

```
#+title: My new page's shiny, isn't it?
#+date: <2020-11-12 Thu. 11:25:58>
#+author: Alice
#+language: en
```

2.4 Building the website

Once you have written some content, you can convert your org files to HTML with the `fronde build` command.

```
fronde build
```

Listing 11: Build a fronde project



Because this building process makes a direct use of the org-mode publishing feature, it will rebuild only files changed since the last command invocation. If you want to force a full rebuild, you can pass the `--force` argument to the command.

```
fronde build -f
```


To review what you just built, you can use the `fronde preview` command, which will start a local webserver and open your default web browser on the home page of your project.

```
fronde preview
```

Listing 12: Build a fronde project

2.5 Publishing the website

3 Advanced usage

3.1 Config File

All the fronde configuration is stored in one **YAML** file named `config.yml` and stored at the root of your project. If the file does not exist a default one will be created the first time you run any fronde command.

The following explains all possible configuration options for fronde, which may be put in file named `config.yml` at the root of your static website project. The options are listed in alphabetical order. However, they can be put in any order in the `config.yml` file.

3.1.1 author

The author option stores the default author name of your org files. This value is used when you create a new file. **It is not used by the regular Org mode publishing process.** You must be sure that your org files contains an `#+author:` metadata field before publishing them.

This value is used in the generation of the blog index page and the main atom feed.

```
---
author: Alice Doe
```

Listing 13: Example of an author setting



The default author setting is your user name on your current computer session.

3.1.2 domain

The domain name pointing to where your static website is expected to be hosted. This value is used to generate absolute path to your files on your expected host name (for example in the Atom feeds).



Its value is expected to **not** end with a slash. That is to say `https://example.com` is **valid**, whereas `https://example.com/` is **not**.

By default, your static website is expected to be hosted at the root of your domain name (like `https://example.com/index.html`). If it is not the case and your fronde static website is hosted in a subfolder of your main website, you must add this subfolder to the domain value. Thus, `https://example.com/example` or `https://example.com/complex/example` are **valid** values too.

```
---  
domain: https://alice.doe.name
```

Listing 14: Example of a domain setting



The default domain value is an empty string.

3.1.3 gemini_public_folder

The `gemini_public_folder` option stores the path to the folder, which will contains the generated gemtext files, ready for Gemini publication.



The default `gemini_public_folder` value is `public_gmi` (at the root of your project).

3.1.4 gemini_remote

The `gemini_remote` option contains an *rsync* like destination string, which will be used to published your capsule when using the `sync:push` *rake* task. For example `user@domain:/var/www/mycapsule/`



There is no default value for `gemini_remote`. Publication of your capsule will be skipped if there is no value for `gemini_remote`.

3.1.5 html_public_folder

The `html_public_folder` option stores the path to the folder, which will contains the HTML generated files, ready for Web publication.



The default `html_public_folder` value is `public_html` (at the root of your project).

3.1.6 html_remote

The `html_remote` option contains an *rsync* like destination string, which will be used to published your website when using the `sync:push` *rake* task. For example `user@domain:/var/www/mywebsite/`



There is no default value for `html_remote`. Publication of your website will be skipped if there is no value for `html_remote`.

3.1.7 lang

The main locale your website will be written in. Its value must comply with the [ISO 639-1](#) standard.

```
---  
lang: en
```

Listing 15: Example of a lang setting



The default `lang` setting is that of your current computer.

3.1.8 sources

The `sources` option stores an array of all source folders, where your org files to be published are. This enables you to gather from various different places (even at some absolute path in your computer) in your website.

Each source listed in that array is an object, which must use the following keys:

path [string] path to the folder containing the file to exports

name [string, optional] key used to generate the [Org “project” name](#). This name never appears in a generated file, it is more like an internal id. Defaults to the last `dirname` of the `path` value.

title TODO

recursive [boolean, optional] whether the path should be exported recursively.
Defaults to True

exclude [string, optional] Regexp of files to not export for this source. Default
to nothing (no files to exclude).

target [string, optional] Path where to put the exported files, relative to the
html_public_folder or gemini_public_folder folder. Defaults to the source
name at the root of the *public* folder.

is_blog [boolean, optional] Whether this source should be considered as a blog
and thus, serves to generate blog index, tags indexes and atom feeds.

theme [string, optional] Theme name to use for this source. Defaults to “default”.

type [string, optional] Type of the exporter to use. Fronde currently supports
only “html” and “gemini”. Defaults to “html”.



If one of your sources is expected to use all default settings, instead of an object, you can just provide the source path as a string. Look at the src source in the example bellow.

```
---  
sources:  
- src  
- path: src/news  
  is_blog: true
```

Listing 16: Example of a sources array setting

If you don’t provide any sources option, it fallbacks to support only one source folder named src at the root of your project directory, as if the sources option has been:

```

---
sources:
- path: src
  target: .
  name: src
  recursive: yes

```

Listing 17: Default value of the sources option



Not setting the sources option is different from giving it the following exact value:

```

---
sources:
- src

```

In the first case, as nothing has been given for the sources option, its default value will use `.` as its target directory, which means to put generated HTML files directly at the root of the `html_public_folder` (which defaults to `public_html`). But in the later case, the generated target will be the `src` folder *inside* the `html_public_folder`, which will be, by default, `public_html/src`.

Thus, if you have a very simple website with only one source, you should avoid setting the sources options, or be very precise in what you specify.

3.1.9 templates

The `templates` option enables you to customize the built HTML files, whatever source they come from. The main idea behind this is to add HTML fragments to the generated files.

The `templates` option stores an array of *template*, each one documenting an HTML fragment to insert or move at some place in a specified generated file. Each template listed in that array is an object, which must use the following keys:

type [string] how the template should be inserted or moved in the HTML document. Can be either `before`, `after` or `replace`. It defaults to `after`.

content [string] the HTML fragment to insert or replace. This value will be evaluated before insertion and some tags will be replaced in a context sensitive

manner. See the [Preamble/Postamble/Templates formatting tags](#) section for the details.

- selector** [string] a CSS selector specifying where to insert the new fragment. For example, if this value is `#main p:first-child` and the current template type is `after`, then the current content will be placed *after* the first HTML tag `p` inside a container, which has an id of `main`.
- path** [string, optional] the current template will apply only to generated HTML files matching this glob pattern. This pattern must match against a published path. That means, for a HTML document stored at `public_html/some/folder/doc.html`, the path could be `/some/folder/doc.html` or `/some/folder/*.html`, but not `public_html/....`
- source** [string, optional] The aim of this option is to target, with a CSS selector, any part of the HTML document, in order to move it elsewhere. See example below.



The content and the source options are incompatible: either you have a content or a source, never both of them. This is because either you want to *add* a new content to your document (using `content`) or you want to *move* an existing content of your document (using `source`). In both case, the destination is taken from the `selector` option.

For example, if you want to hide social media meta tags in the *head* of your generated HTML files, you can use the following templates setting, which will add a bunch of meta tags *before* the title of any generated HTML file:

Another example: if you want, for example, to move the generated Org table of content before the main `#content` div (by default, the Org publish process puts it *inside* this div). As we specified a path option, this replacement occurs only for HTML documents under the `/docs` folder.

3.2 Preamble, Postamble, and Templates formatting tags

This section documents the percent-tags you can use in the preamble or postamble of your [sources](#), or in any of your [templates](#). This tags will be replaced by their corresponding content when you will build your website. The values are context sensitive, taken from the currently evaluated Org file, or by default from the config of your project.

```

---
templates:
- type: before
  selector: title
  content: |
    <link rel="schema.dc" href="http://purl.org/dc/elements/1.1/">
    <meta property="dc.publisher" content="%a">
    <meta property="dc.type" content="text">
    <meta property="dc.format" content="text/html">
    <meta property="dc.title" lang="%l" content="%t">
    <meta property="dc.description" lang="%l" content="%x">
    <meta property="dc.language" content="%l">
    <meta property="dc.date" content="%I">
    <meta property="dc.rights" content="%L">
    <meta name="twitter:card" content="summary">
    <meta name="twitter:creator" content="@fsfe">
    <meta property="og:type" content="article">
    <meta property="og:title" content="%t">
    <meta property="og:article:published_time" content="%I">
    <meta property="og:url" content="%u">
    <meta property="og:locale" content="%l">
    <meta property="og:description" content="%x">
    <meta property="og:site_name" content="My wonderfull website">

```

Listing 18: Templates setting to add social media meta tags

```

- type: before
  selector: div#content
  source: nav#table-of-contents
  path: "/docs/*.html"

```

Listing 19: Templates setting to move the table of content outside the #content div

%a the raw author name of the current Org file, or the one given in the config file.

%A the HTML rendering of the author name, equivalent to `%a`.

%d a short date HTML representation, equivalent to `<time datetime="%I">%i</time>`.

%D the full date and time HTML representation.

%i the raw short date and time.

%I the raw ISO 8601 date and time.

%k the current Org file keywords separated by commas.

%K the HTML list rendering of the keywords.

%l the lang of the document, or the one given in the config file.

%L the license information, taken from the config file.

%n the fronde name and version.

%N the fronde name and version with a link to the project home.

%s the subtitle of the current Org file (from `#+subtitle:`).

%t the title of the current Org file (from `#+title:`).

%u the web path to the related published HTML document.

%x the raw description (x as in eXcerpt) of the current Org file (from `#+description:`).

%X the description, enclosed in an HTML p tag, equivalent to `<p>%x</p>`

3.3 Rake tasks

Like a lot of ruby project, fronde exposes some **Rake** tasks. You can discover them with the `rake -T` command.