


Revisiting `acm.graphics`


- **collage** model
 - create image by adding objects to a canvas



- Newer objects obscure those added earlier
- Layering is called the **stacking order** (or *z*-order)


Using portions of slides by Eric Roberts

Structure of `acm.graphics` Package




Using portions of slides by Eric Roberts

Structure of `acm.graphics` Package



Using portions of slides by Eric Roberts

Structure of `acm.graphics` Package



Using portions of slides by Eric Roberts

GCanvas

- Used to represent background canvas of collage
- **GraphicsProgram** automatically creates **GCanvas** that fills the entire program window
- When you call **add(...)** in **GraphicsProgram**, it is *forwarding* your call to the **GCanvas**
 - Forwarding is just when receiver of message then calls some other object with that same message

Using portions of slides by Eric Roberts

Methods in GCanvas and GraphicsProgram

The following methods are available in both the `GCanvas` and `GraphicsProgram` classes:


add (<i>object</i>)	Adds the object to the canvas at the front of the stack
add (<i>object</i> , <i>x</i> , <i>y</i>)	Moves the object to (<i>x</i> , <i>y</i>) and then adds it to the canvas
remove (<i>object</i>)	Removes the object from the canvas
removeAll ()	Removes all objects from the canvas
getElementAt (<i>x</i> , <i>y</i>)	Returns the frontmost GObject at (<i>x</i> , <i>y</i>), or null if none
getWidth ()	Returns the width in pixels of the entire canvas
getHeight ()	Returns the height in pixels of the entire canvas
setBackground (<i>c</i>)	Sets the background color of the canvas to <i>c</i> .

The following methods are available in **GraphicsProgram** only:

pause (milliseconds)	Pauses the program for the specified time in milliseconds
waitForClick()	Suspends the program until the user clicks the mouse

Using portions of slides by Eric Roberts

Class hierarchy of GObject



Using portions of slides by Eric Roberts

Methods Common to All GObject

setLocation(x, y)	Resets the location of the object to the specified point
move(dx, dy)	Moves the object <i>dx</i> and <i>dy</i> pixels from its current position
getX()	Returns the x coordinate of the object
getY()	Returns the y coordinate of the object
getWidth()	Returns the horizontal width of the object in pixels
getHeight()	Returns the vertical height of the object in pixels
contains(x, y)	Returns true if the object contains the specified point
setColor(c)	Sets the color of the object to the Color <i>c</i>
getColor()	Returns the color currently assigned to the object
setVisible(flag)	Sets the visibility flag (false =invisible, true =visible)
isVisible()	Returns true if the object is visible
sendToFront()	Sends the object to the front of the stacking order
sendToBack()	Sends the object to the back of the stacking order
sendForward()	Sends the object forward one position in the stacking order
sendBackward()	Sends the object backward one position in the stacking order

Using portions of slides by Eric Roberts

Methods Defined by Interfaces

GFillable (GRect, GOval, GArc, GPolygon)

setFilled(flag)	Sets the fill state for the object (false =outlined, true =filled)
isFilled()	Returns the fill state for the object
setFillColor(c)	Sets the color used to fill the interior of the object to <i>c</i>
getFillColor()	Returns the fill color

GResizable (GOval, GRect, GImage)

setSize(width, height)	Sets the dimensions of the object as specified
setBounds(x, y, width, height)	Sets the location and dimensions together

GScalable (GLine, GOval, GRect, GArc, GCompound, GImage, GPolygon,)

scale(sf)	Scales both dimensions of the object by <i>sf</i>
scale(sx, sy)	Scales the object by <i>sx</i> horizontally and <i>sy</i> vertically


Using portions of slides by Eric Roberts

A little animation demo: BouncingBall.java

The GLabel Class

```


public class HelloProgram extends GraphicsProgram {
    public void run() {
        GLabel label = new GLabel("hello, world", 100, 75);
        label.setFont("SansSerif-36");
        label.setColor(Color.RED);
        add(label);
    }
}
  
```



Using portions of slides by Eric Roberts

The Geometry of the GLabel Class


- The **GLabel** class typesetting concepts:
 - baseline**: imaginary line on which the characters rest.
 - origin**: point on the baseline at which the label begins.
 - height** (of font): distance between successive baselines.
 - ascent**: distance characters rise above the baseline.
 - descent**: distance characters drop below the baseline.



Using portions of slides by Eric Roberts

The **GArc** Class

- **GArc** – arc formed by taking section from perimeter of oval.
- Conceptually, steps necessary to define an arc:
 - Specify the coordinates and size of the bounding rectangle
 - Specify **start angle** (angle at which the arc begins)
 - Specify **sweep angle** (how far the arc extends)
- Angles measured in degrees starting at the $+x$ axis (the 3:00 o'clock position) and increasing **counterclockwise**.
- Negative values for the *start* and *sweep* angles signify a clockwise direction.




Using portions of slides by Eric Roberts


GArc Geometry

Assume: **cx** and **cy** are coordinates of window center
d (diameter) is 0.8 times the screen height.

```
GArc a1 = new GArc(d, d, 0, 90);
add(a1, cx - d / 2, cy - d / 2);
```



```
GArc a2 = new GArc(d, d, 45, 270);
add(a2, cx - d / 2, cy - d / 2);
```



```
GArc a3 = new GArc(d, d, -90, 45);
add(a3, cx - d / 2, cy - d / 2);
```



```
GArc a4 = new GArc(d, d, 0, -180);
add(a4, cx - d / 2, cy - d / 2);
```




Using portions of slides by Eric Roberts

Filled Arcs

- **GArc** class implements **GFillable** interface
- Filled **GArc** is the pie-shaped wedge formed by the center and the endpoints of the arc

```
public void run() {
    GArc arc = new GArc(0, 0, getWidth(), getHeight(),
                        0, 90);
    arc.setFilled(true);
    add(arc);
}
```



Using portions of slides by Eric Roberts

The **GImage** Class

- **GImage** class is used to display an image from a file

```
new GImage (image file , x, y)
```

image file: name of a file containing image

x and *y*: coordinates of upper left corner of image

- Looks for file in current project directory and then in a subdirectory named **images**.
- GIF (**.gif**) and JPEG (**.jpg** or **.jpeg**) supported

Using portions of slides by Eric Roberts

Example of the **GImage** Class

```
public void run() {
    GImage image = new GImage("StanfordSeal.gif");
    add(image, 0, 0);
}
```



Using portions of slides by Eric Roberts


Resizing **GImages**

```
public void run() {
    GImage image = new GImage("StanfordSeal.gif");
    image.scale(1.5, 0.5);
    add(image, 0, 0);
}
```



Using portions of slides by Eric Roberts

Class hierarchy of GObject



Using portions of slides by Eric Roberts

The GPolygon Class

- **GPolygon**: represent graphical objects bound by line segments.



diamond



hexagon

- A **GPolygon** has a **reference point** that is convenient for that particular shape
- Position the vertices relative to that reference point.
- Convenient reference point is often center of object.

Using portions of slides by Eric Roberts

Constructing a GPolygon Object

- Create an empty polygon
- Add vertices one at a time using **addVertex** (x, y)
 - x and y relative to **reference point** of polygon
- After setting initial vertex using **addVertex** (x, y), can add remaining ones using:
 - **addVertex** (x, y) adds a new vertex relative to the reference point
 - **addEdge** (dx, dy) adds a new vertex relative to the preceding one
- Polygon "closed" for you
 - automatically attaches first and last vertices


Using portions of slides by Eric Roberts

Drawing a Diamond (addVertex)

The following program draws a diamond using **addVertex**:

```

public void run() {
    private GPolygon createDiamond(double width, double height) {
        GPolygon diamond = new GPolygon();
        diamond.addVertex(-width / 2, 0);
        diamond.addVertex(0, -height / 2);
        diamond.addVertex(width / 2, 0);
        diamond.addVertex(0, height / 2);
        return diamond;
    }
}
    
```



slip simulation

Using portions of slides by Eric Roberts

The GCompound Class

- **GCompound** allows for combining several graphics objects so they behave like one **GObject**
- Add objects to a **GCompound** (like it was a canvas)
- You can treat whole **GCompound** as one object
- Similar to **GPolygon**, a **GCompound** has a reference point that all objects are added with respect to
- When **GCompound** is added to canvas, it is placed relative to its reference point
- Let's draw a face:



Using portions of slides by Eric Roberts