I. Simulation of ions in a Penning trap

Ions are confined radially by a magnetic field $\mathbf{B}$, with an ideal quadrupolar trapping potential of V_T. The potential and field near the centre of the trap is approximated as

$$\Phi_T(x,y,z) = V_T(\gamma' - \frac{\alpha'}{2l^2}(x^2+y^2-2z^2)) \qquad \mathbf{E} = -\nabla\Phi_T(x,y,z) = \frac{\alpha}{l^2}(-x\mathbf{i} - y\mathbf{j} + 2z\mathbf{k}) \tag{1}$$

where $\gamma' = 1/3$ and $\alpha' = 2.77373$ are geometric factors for the cubic trap, and l is the edge length[1]. The force experienced by an ion in the trap is

$$\mathbf{F} = q(\mathbf{E} + \mathbf{v} \times \mathbf{B}) \tag{2}$$

Charges and mass are simulated in atomic units, lengths in nm and time in ns.

A. Integration scheme

The code uses the Boris integrator[2] as formulated in Birdsall and Langdon[3]. This is a modified leapfrog scheme in which positions are calculated at times $..., n-1, n, n+1, ...$ and velocities at times $..., n^{-1/2}$, $n^{+1/2}, ...$

$$\mathbf{v}^- = \mathbf{v}^{n-1/2} + \frac{q\mathbf{E}}{m}\frac{\Delta t}{2} \tag{3}$$

$$\mathbf{v}' = \mathbf{v}^- + \mathbf{v}^- \times \mathbf{t} \qquad \mathbf{t} = \frac{q\mathbf{B}}{m}\frac{\Delta t}{2} \tag{4}$$

$$\mathbf{v}^+ = \mathbf{v}^- + \mathbf{v}' \times \mathbf{s} \qquad \mathbf{s} = \frac{2\mathbf{t}}{1+t^2} \tag{5}$$

$$\mathbf{v}^{n+1/2} = \mathbf{v}^+ + \frac{q\mathbf{E}}{m}\frac{\Delta t}{2} \tag{6}$$

B. Ion motion

The cyclotron frequency ω_c is predicted by $\omega_c = \frac{qB}{m}$[1]. To achieve 1% phase error in simulated cyclotron frequency requires $\Omega\Delta t \lesssim 0.3$[3], [4]. The cyclotron radius r is predicted by $r = \frac{mv}{|q|B}$ and is measured for a single particle simulation by the distance between maxima in the x dimension.

The electric field gives rise to a magnetron motion of a lower frequency ω_z. In a quadrupolar trapping potential of V_T, the modified cyclotron frequency ω_+ is predicted by

$$\omega_+ = \frac{\omega_c}{2} + \sqrt{\frac{\omega_c^2}{4} - \frac{\omega_z^2}{2}} \qquad \omega_z = \left(\frac{2\alpha q V_T}{ml^2}\right)^{1/2} \tag{7}$$

The modified cyclotron frequency is measured by peaks in the Fourier transform of the induced current time signal.

C. Induced current

FTICR-MS measures the current induced between detector plates on opposite walls of the cube parallel to the magnetic field. In the simulation, current is induced by the movement of the 'image' $\mathbf{E}_{image}(\mathbf{r})$ associated with each ion, that is, the difference in the electric field generated by the ion at each of the two detector plates[1].

$$I = \sum_{i=1}^{N} q_i \mathbf{v}_i \cdot \mathbf{E}_{image}(\mathbf{r}_i) \qquad \mathbf{E}_{image}(\mathbf{r}) = -\frac{\beta'}{l} r_j \qquad \beta' = 0.72167 \tag{8}$$

D. Simulation results

TABLE I
Replicating: Han and Shin[5]. Input, predicted and measured simulation parameters

$B = 0.7646T, V_T = 1.0V, l = 0.047$											
				predicted		**measured**		**error: timestep**			
species	**charge**	**mass**	v_0 **(m/s)**	$\omega_+/2\Pi$ **(Hz)**	r **(mm)**	$\omega'_+/2\Pi$ **(Hz)**	r' **(mm)**	Δt **(ns)**	$\epsilon : \Delta t$	$\epsilon : \Delta t$ **/ 10**	$\epsilon : \Delta t$ *** 10**
HCO^+	1	29.0182	10^4	394,022	3.933	403,800	3.933	118			
CH_3CO^+	1	43.04462	10^4	262,028	5.835	272,360	5.835	175			

TABLE II
REPLICATING: LEACH ET AL.[6]. INPUT, PREDICTED AND MEASURED SIMULATION PARAMETERS

$B = 7.0T, V_T = 1.0V, l = 0.0508$											
				predicted		**measured**		**error: timestep**			
species	**charge**	**mass**	v_0 **(m/s)**	$\omega_+/2\Pi$ **(Hz)**	r **(mm)**	$\omega'_+/2\Pi$ **(Hz)**	r' **(mm)**	Δt **(ns)**	$\epsilon : \Delta t$	$\epsilon : \Delta t$ **/ 10**	$\epsilon : \Delta t$ *** 10**
Cs^+	1	132.9054	2.7×10^3	807,826	5.313	807,656	5.319	59			
$\mathsf{Xx}^+(\frac{\mathsf{m}}{\mathsf{q}} = 150)$	1	150.0	2.7×10^3	715,652	5.996	715,781	5.997	67			

TABLE III
CONVERSION FACTORS

property	**unit**	**SI unit**
mass	amu	$1.660538921 \times 10^{-27} kg$
charge	e	$1.60217653 \times 10^{-19} C$

REFERENCES

[1] S. Guan and A. G. Marshall, “Ion traps for Fourier transform ion cyclotron resonance mass spectrometry: principles and design of geometric and electric configurations,” *Int. J. Mass Spectrometry and Ion Processes*, vol. 146/147, pp. 261–296, 1995.

[2] J. Boris, “Relativistic plasma simulation-optimization of a hybrid code,” in *Proc. 4th Conf. Num. Sim. Plasmas*, 1970, pp. 3–67.

[3] C. Birdsall and A. Langdon, *Plasma Physics via Computer Simulation*. McGraw-Hill, New York, 1985.

[4] L. Patacchini and I. Hutchinson, “Explicit time-reversible orbit integration in Particle In Cell codes with static homogeneous magnetic field,” *J. Comp. Phys.*, vol. 228, p. 2604, 2009, 10.1016/j.jcp.2008.12.021.

[5] S.-J. Han and S. Shin, “Space-charge effects on Fourier transform ion cyclotron resonance signals : Experimental observations and three-dimensional trajectory simulations,” *J. Am. Soc. Mass Spectrometry*, vol. 8, pp. 319–326, Mar 1997.

[6] F. Leach, A. Kharchenko, R. Heeren, E. Nikolaev, and I. Amster, “Comparison of particle-in-cell simulations with experimentally observed frequency shifts between ions of the same mass-to-charge in Fourier transform ion cyclotron resonance mass spectrometry,” *J. Am. Soc. Mass Spectrometry*, vol. 21, pp. 203–208, Oct 2009, 10.1016/j.jasms.2009.10.001.