

Secure Coding – Vulnerability Fix Implementation

Course: Secure Software Design - Fall 2025

Assignment: 03

Student Names:

- Abdullah Nadeem (22I-1759)
- Abdul Wahab (22I-1714)
- Abdul Mueed Malik (22I-1622)

Section: 7B

Table of Contents

1. Password Security	4
Vulnerability Description	4
Evidence of Vulnerability	4
Applied Solution.....	4
After Fixing.....	5
2. Access Control.....	5
Vulnerability Description	5
Evidence of Vulnerability	5
Applied Solution.....	6
After Fixing.....	6
3. Resource Ownership	6
Vulnerability Description	6
Evidence of Vulnerability	6
Applied Solution.....	7
4. Data Exposure	7
Vulnerability Description	7
Evidence of Vulnerability	8
Applied Solution.....	8
After Fixing.....	8
5. Rate Limiting	8
Vulnerability Description	8
Evidence of Vulnerability	9
Applied Solution.....	9
After Fixing.....	10
6. Mass Assignment	10
Vulnerability Description	10
Evidence of Vulnerability	10
Applied Solution.....	11
After Fixing.....	11
7. JWT Security	11
Vulnerability Description	11
Evidence of Vulnerability	11
Applied Solution.....	12

8. Error Handling.....	13
Vulnerability Description.....	13
Evidence of Vulnerability.....	13
Applied Solution.....	14
After Fixing.....	14
9. Input Validation	15
Vulnerability Description.....	15
Evidence of Vulnerability.....	15
Applied Solution.....	15
After Fixing.....	15
Summary.....	15
Git Repository	15
Conclusion.....	16

1. Password Security

Vulnerability Description

OWASP API Security Top 10 Mapping: API2 - Broken Authentication


The application stores user passwords in **plaintext** in the database and compares them directly during authentication without any hashing or encryption.

Evidence of Vulnerability

Database Evidence: When accessing H2 Console at <http://localhost:8080/h2-console> and query:

```
SELECT * FROM APP_USER;
```

Result shows passwords stored as: alice123, bob123



The screenshot shows the H2 Console interface. At the top, there are buttons for 'Run', 'Run Selected', 'Auto complete', and 'Clear', followed by a text input for the 'SQL statement:'. Below this, the query 'SELECT * FROM APP_USER;' is entered. The results are displayed in a table with 6 columns: ID, EMAIL, IS_ADMIN, PASSWORD, ROLE, and USERNAME. The table contains two rows of data. Below the table, it indicates '(2 rows, 1 ms)' and there is an 'Edit' button.

ID	EMAIL	IS_ADMIN	PASSWORD	ROLE	USERNAME
1	alice@cydea.tech	FALSE	alice123	USER	alice
2	bob@cydea.tech	TRUE	bob123	ADMIN	bob

Applied Solution

Added BCrypt password encoder

SecurityConfig.java

```
// FIX #1: Add BCrypt password encoder for secure password hashing
// BCrypt automatically handles salting and uses adaptive hashing to prevent rainbow table attacks
@Bean
public org.springframework.security.crypto.password.PasswordEncoder passwordEncoder() {
    return new org.springframework.security.crypto.bcrypt.BCryptPasswordEncoder();
}
```

AuthController.java

```
public AuthController(AppUserRepository users, JwtService jwt, org.springframework.security.crypto.password.PasswordEncoder passwordEncoder) {  
    this.users = users;  
    this.jwt = jwt;  
    this.passwordEncoder = passwordEncoder;    // FIX #1: Inject password encoder  
}
```

After Fixing

Run

Run Selected

Auto complete

Clear

SQL statement:

SELECT * FROM APP_USER;

SELECT * FROM APP_USER;

ID	EMAIL	IS_ADMIN	PASSWORD	ROLE	USERNAME
1	alice@cydea.tech	FALSE	\$2a\$10\$rmDkjY3e/q/cnpMKK9r8ueDuQU9/bLYjME2NR4uG2YwLEFHI5SJAG	USER	alice
2	bob@cydea.tech	TRUE	\$2a\$10\$iedVwutl6h1TILOWQ3mv6.5cHtBlrwH5Lfr7nLRZeW3M87MUEXVK	ADMIN	bob

(2 rows, 4 ms)

Edit

The passwords are being stored in hashed form now.

2. Access Control

Vulnerability Description

OWASP API Security Top 10 Mapping: API7 - Security Misconfiguration

The application has **overly permissive access control** rules in the SecurityFilterChain, allowing unauthenticated users to access sensitive endpoints.

Evidence of Vulnerability

Test Without Authentication:

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03> curl.exe http://localhost:8080/api/users  
[{"id":1,"username":"alice","password":"alice123","role":"USER","email":"alice@cydea.tech","admin":false}, {"id":2,"username":"bob","password":"bob123","role":"ADMIN","email":"bob@cydea.tech","admin":true}]
```

Admin Endpoint Exposed:

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03> curl.exe http://localhost:8080/api/admin/metrics  
{"javaVersion":"17.0.16","threads":23,"uptimeMs":7041442}
```

Applied Solution

```
http.authorizeHttpRequests(reg -> reg
    .requestMatchers("/api/auth/**", "/h2-console/**").permitAll()
    // VULNERABILITY: broad permitAll on GET allows data scraping (API1/2 depending on context)
    // FIX #2: Remove overly permissive GET access - require authentication for all API endpoints
    .requestMatchers("/api/admin/**").hasRole("ADMIN")
    .requestMatchers("/api/**").authenticated() // FIX #2: Require authentication for all /api/** endpoints
    .anyRequest().authenticated()
);
```

After Fixing

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> curl.exe
-i http://localhost:8080/api/users
HTTP/1.1 403
X-Content-Type-Options: nosniff
X-XSS-Protection: 0
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Expires: 0
Content-Length: 0
Date: Sat, 25 Oct 2025 16:53:26 GMT
```

Now the unauthenticated access is blocked successfully.

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> curl.exe
-i http://localhost:8080/h2-console
HTTP/1.1 302
X-Content-Type-Options: nosniff
X-XSS-Protection: 0
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
Location: http://localhost:8080/h2-console/
Content-Length: 0
Date: Sat, 25 Oct 2025 16:53:43 GMT
```

And the public endpoints are still working.

3. Resource Ownership

Vulnerability Description

OWASP API Security Top 10 Mapping: API1 - Broken Object Level Authorization (BOLA/IDOR)

The application does not verify that authenticated users can only access **their own resources**. Users can access other users' data and accounts by simply changing IDs in the URL.

Evidence of Vulnerability

Test (curl -s http://localhost:8080/api/admin/metrics):

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> curl.exe
-s http://localhost:8080/api/admin/metrics
{"javaVersion":"17.0.16","threads":23,"uptimeMs":86142}
```

Admin-only endpoint accessible to anyone.

Applied Solution

In the AccountController.java:

```
// FIX #3: Add ownership validation to prevent BOLA (Broken Object Level Authorization)
@GetMapping("/{id}/balance")
public ResponseEntity<> balance(@PathVariable Long id, Authentication auth) {
    Account account = accounts.findById(id)
        .orElseThrow(() -> new RuntimeException("Account not found"));

    // FIX #3: Verify the account belongs to the authenticated user
    AppUser currentUser = users.findByUsername(auth.getName())
        .orElseThrow(() -> new RuntimeException("User not found"));

    if (!account.getOwnerUserId().equals(currentUser.getId())) {
        // FIX #3: Return 403 Forbidden if user tries to access someone else's account
        Map<String, String> error = new HashMap<>();
        error.put("error", "forbidden");
        error.put("message", "You do not have permission to access this account");
        return ResponseEntity.status(403).body(error);
    }

    return ResponseEntity.ok(account.getBalance());
}
```

```
// FIX #3: Add ownership validation to prevent unauthorized transfers (BOLA)
@PostMapping("/{id}/transfer")
public ResponseEntity<> transfer(@PathVariable Long id, @RequestParam Double amount, Authentication auth) {
    Account a = accounts.findById(id).orElseThrow(() -> new RuntimeException("Account not found"));

    // FIX #3: Check if the current user is the owner of the account
    AppUser currentUser = users.findByUsername(auth.getName()).orElseThrow(() -> new RuntimeException("User not found"));

    if (!a.getOwnerUserId().equals(currentUser.getId())) {
        // FIX #3: Return 403 Forbidden if the user does not own the account
        Map<String, String> error = new HashMap<>();
        error.put("error", "forbidden");
        error.put("message", "You cannot transfer from an account you do not own");
        return ResponseEntity.status(403).body(error);
    }
}
```

4. Data Exposure

Vulnerability Description

OWASP API Security Top 10 Mapping: API3 - Excessive Data Exposure

The application returns complete entity objects directly to clients, exposing **sensitive fields** that should never be visible externally.

Evidence of Vulnerability

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> curl.exe http://localhost:8080/api/users [{"id":1,"username":"alice","password":"alice123","role":"USER","email":"alice@cydea.tech","admin":false},{ "id":2,"username":"bob","password":"bob123","role":"ADMIN","email":"bob@cydea.tech","admin":true}]
```

Passwords, isAdmin, internal IDs are exposed.

Applied Solution

```
// FIX #4: Return only safe fields using UserResponse DTO to prevent data exposure
@GetMapping("/{id}")
public UserResponse get(@PathVariable Long id) {
    AppUser u = users.findById(id).orElseThrow(() -> new RuntimeException("User not found"));
    return UserResponse.from(u); // FIX #4: Excludes password, role, isAdmin fields
}
```

```
// FIX #4: Return only safe fields using UserResponse DTO (excludes password, role, isAdmin)
@GetMapping("/search")
public List<UserResponse> search(@RequestParam String q) {
    return users.search(q).stream().map(UserResponse::from).collect(Collectors.toList());
}

// FIX #4: Prevent excessive data exposure by returning only safe user fields via DTO
@GetMapping
public List<UserResponse> list() {
    return users.findAll().stream().map(UserResponse::from).collect(Collectors.toList());
}
```

After Fixing

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> Start-Sleep -Seconds 3 ; curl.exe http://localhost:8080/api/users [{"id":1,"username":"alice","email":"alice@cydea.tech"}, {"id":2,"username":"bob","email":"bob@cydea.tech"}]
```

Password, role, isAdmin (extra information) is not visible now.

5. Rate Limiting

Vulnerability Description

OWASP API Security Top 10 Mapping: API4 - Unrestricted Resource Consumption

The application has **no rate limiting** on sensitive endpoints, allowing unlimited requests that can lead to brute-force attacks, denial of service, and resource exhaustion.

Evidence of Vulnerability

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab>
for ($i=1; $i -le 20; $i++) { curl.exe -s http://localhost:8080/api/users | Out-Null; Write-Host "Request $i
completed" }
Request 1 completed
Request 2 completed
Request 3 completed
Request 4 completed
Request 5 completed
Request 6 completed
Request 7 completed
Request 8 completed
Request 9 completed
Request 10 completed
Request 11 completed
Request 12 completed
Request 13 completed
Request 14 completed
Request 15 completed
Request 16 completed
Request 17 completed
Request 18 completed
Request 19 completed
Request 20 completed
```

There is no Rate Limiting implemented.

Applied Solution

Added

```
// FIX #5: Add rate limiting filter to prevent brute force and DoS attacks
http.addFilterBefore(rateLimitFilter, org.springframework.security.web.authentication.UsernamePasswordAuthenticationFilter.class);
```

In SecurityConfig.java

After Fixing

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> Start-Sleep -Seconds 5 ;
for ($i=1; $i -le 25; $i++) { $response = curl.exe -s -w "%{HTTP_CODE}" http://localhost:8080/api/auth/login; Write-Host "Request $i : $($response -split 'HTTP_CODE:' | Select-Object -Last 1)" }
Request 1 : 500 fbbf-68a4-400e-94b0-eb4925e7a4f2
Request 2 : 500
Request 3 : 500
Request 4 : 500
Request 5 : 500
Request 6 : 500
Request 7 : 500
Request 8 : 500
Request 9 : 500
Request 10 : 500
Request 11 : 429
Request 12 : 429
Request 13 : 429
Request 14 : 429
Request 15 : 429
Request 16 : 429
Request 17 : 429
Request 18 : 429
Request 19 : 429
Request 20 : 429
Request 21 : 429
Request 22 : 429
Request 23 : 429
Request 24 : 429
Request 25 : 429
```

Rate limiting working now.

6. Mass Assignment

Vulnerability Description

OWASP API Security Top 10 Mapping: API6 - Mass Assignment

The application binds request bodies directly to entity objects, allowing clients to set **sensitive fields** like role and isAdmin, leading to privilege escalation.

Evidence of Vulnerability

Current Code:

```
@PostMapping
public AppUser create(@Valid @RequestBody AppUser body) {
    // Binds ALL fields from JSON, including role and isAdmin!
    return users.save(body);
}
```

Test - Creating Admin User:

```
curl -X POST http://localhost:8080/api/users \
-H "Content-Type: application/json" \
-d '{
  "username": "hacker",
  "password": "hack123",
  "email": "hacker@evil.com",
```

```
"role": "ADMIN",
"isAdmin": true
}'
```

Response: User created with admin privileges!

```
{
  "id": 3,
  "username": "hacker",
  "role": "ADMIN",
  "isAdmin": true
}
```

Applied Solution

```
// FIX #4: Return only safe fields using UserResponse DTO to prevent data exposure
@GetMapping("/{id}")
public UserResponse get(@PathVariable Long id) {
    AppUser u = users.findById(id).orElseThrow(() -> new RuntimeException("User not found"));
    return UserResponse.from(u); // FIX #4: Excludes password, role, isAdmin fields
}
```

After Fixing

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> $body = @({username='attacker'; password='attack123'; email='attacker@test.com'; role='ADMIN'; isAdmin=$true} | ConvertTo-Json; Invoke-WebRequest -Uri http://localhost:8080/api/users -Method POST -Body $body -ContentType 'application/json' | Select-Object -ExpandProperty Content)
{"id":3,"username":"attacker","email":"attacker@test.com"}
```

Even though the input role is 'Admin', the request ignores such fields.

7. JWT Security

Vulnerability Description

OWASP API Security Top 10 Mapping: API8 - Security Misconfiguration (Weak Authentication)

The JWT implementation has multiple critical weaknesses: 1. **Weak secret key** (secret123) 2. **Extremely long TTL** (30 days) 3. **No issuer or audience validation** 4. **Silent failure** on invalid tokens

Evidence of Vulnerability

Weak Key Encryotion Configuration:

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> curl.exe -X POST http://localhost:8080/api/auth/login -H "Content-Type: application/json" -d '{"username":"alice","password":"alice123"}'
{"error":"io.jsonwebtoken.security.WeakKeyException","message":"The signing key's size is 72 bits which is not secure enough for the HS256 algorithm. The JWT JWA Specification (RFC 7518, Section 3.2) states that keys used with HS256 MUST have a size >= 256 bits (the key size must be greater than or equal to the hash output size). Consider using the io.jsonwebtoken.security.Keys class's 'secretKeyFor(SignatureAlgorithm.HS256)' method to create a key guaranteed to be secure enough for HS256. See https://tools.ietf.org/html/rfc7518#section-3.2 for more information."}
```

Applied Solution

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> Invoke-RestMethod -Uri http://localhost:8080/api/auth/login -Method POST -Body '{"username":"alice","password":"alice123"}' -ContentType 'application/json'
```

token

eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJhbG1jZSI6InJvbGUiOiJVV0VSIlwiaXNBZG1pbSI6ZmFsc2UsIm1hdCI6MTc2MTQyMjI4OSwiZXhwIjoxNzYxNDIzMTg5LC...

Now the login returns a JWT token.

DECODED HEADER

JSON CLAIMS TABLE COPY ↗

```
{  
  "alg": "HS256"  
}
```

DECODED PAYLOAD

JSON CLAIMS TABLE COPY ↗

```
{"sub":"alice","role":"USER","isAdmin":false,"iat":1761422395,"exp":176142:  
api-vuln-lab","aud":"owasp-api-us
```

JWT SIGNATURE VERIFICATION (OPTIONAL)

Enter the secret used to sign the JWT below:

SECRET COPY CLEAR

Valid secret

a-string-secret-at-least-256-bits-long

Token clearly shows better security claims and a shorter expiration time.

```

PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> $loginResponse = Invoke-RestMethod -Uri http://localhost:8080/api/auth/login -Method POST -Body '{"username":"alice","password":"alice123"}' -ContentType 'application/json'; $token = $loginResponse.token; Write-Host "Token obtained. Testing authenticated endpoint..."; Invoke-RestMethod -Uri http://localhost:8080/api/users -Method GET -Headers @{Authorization="Bearer $token"}
Token obtained. Testing authenticated endpoint...

id username email
--
1 alice alice@cydea.tech
2 bob bob@cydea.tech
3 attacker attacker@test.com

```

The app is accessible using the token.

8. Error Handling

Vulnerability Description

OWASP API Security Top 10 Mapping: API7 - Security Misconfiguration (Information Disclosure)

The application exposes **detailed error messages and stack traces** to clients, revealing internal implementation details, file paths, and system information.

Evidence of Vulnerability

```

PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> curl.exe -s http://localhost:8080/api/users/9999
{"error":"java.lang.IllegalArgumentException","message":"Name for argument of type [java.lang.Long] not specified, and parameter name information not available via reflection. Ensure that the compiler uses the '-parameters' flag."}

```

Exposing too many error details.

Applied Solution

```
// VULNERABILITY(API7): overly verbose error responses
// FIX #8: Sanitize error responses to avoid leaking sensitive information
@ControllerAdvice
public class GlobalExceptionHandler {

    private static final Logger log = LoggerFactory.getLogger(GlobalExceptionHandler.class);

    @ExceptionHandler(Exception.class)
    public ResponseEntity<> all(Exception e) {
        log.error("Internal error: {}", e.getMessage(), e); // Log full details server-side
        Map<String, String> errorMap = new HashMap<>();
        errorMap.put("error", "internal_error");
        errorMap.put("message", "An unexpected error occurred. Please contact support.");
        return ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ERROR)
            .body(errorMap);
    }

    @ExceptionHandler(DataAccessException.class)
    public ResponseEntity<> db(DataAccessException e) {
        log.error("Database error: {}", e.getMessage(), e);
        Map<String, String> errorMap = new HashMap<>();
        errorMap.put("error", "database_error");
        errorMap.put("message", "A database error occurred.");
        return ResponseEntity.status(500).body(errorMap);
    }
}
```

```
# # Expose error details (VULNERABILITY: API7-Security Misconfiguration)
# server.error.include-message=always
# server.error.include-stacktrace=always

# FIX #8: Restrict error details exposure
server.error.include-message=never
server.error.include-stacktrace=never

logging.level.root=INFO
```

After Fixing

```
PS D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> Invoke-WebRequest -Uri
"http://localhost:8080/api/users/9999" -Method GET
Invoke-WebRequest : The remote server returned an error: (403) Forbidden.
At line:1 char:1
+ Invoke-WebRequest -Uri "http://localhost:8080/api/users/9999" -Method ...
+ ~~~~~
+ CategoryInfo          : InvalidOperation: (System.Net.HttpWebRequest:HttpWebRequest) [Invoke-WebRequest], WebException
+ FullyQualifiedErrorId : WebCmdletWebResponseException,Microsoft.PowerShell.Commands.InvokeWebRequestCommand
```

The same command request as above but now, the app is not giving any information revealing error messages.

9. Input Validation

Vulnerability Description

OWASP API Security Top 10 Mapping: API9 - Improper Assets Management / Lack of Input Validation

The application does not validate user inputs, allowing: - **Negative transfer amounts** (increases balance!) - **Extremely large values** (potential overflow) - **No overdraft protection** - **Invalid email formats**

Evidence of Vulnerability

Current Code (AccountController):

```
@PostMapping("/{id}/transfer")
public ResponseEntity<?> transfer(@PathVariable Long id, @RequestParam Double
amount) {
    Account a = accounts.findById(id).orElseThrow();
    a.setBalance(a.getBalance() - amount); // No validation!
    accounts.save(a);
    return ResponseEntity.ok(Map.of("status", "ok", "remaining",
a.getBalance()));
}
```

Applied Solution

```
// FIX #9: Validate transfer amount
if (amount == null || amount <= 0 || amount > 1_000_000) {
    Map<String, String> error = new HashMap<>();
    error.put("error", "invalid_amount");
    error.put("message", "Transfer amount must be positive and less than or equal to 1,000,000.");
    return ResponseEntity.badRequest().body(error);
}
```

After Fixing

```
P5 D:\Uni\Secure Software Design\Assignment 03\ssd_ass03\owasp-api-vuln-lab-assignment-03\owasp-api-vuln-lab> curl -X POST "http://localhost:8080/api/accounts/1/transfer?amount=1000001"
Invoke-WebRequest : A parameter cannot be found that matches parameter name 'X'.
At line:1 char:6
+ curl -X POST "http://localhost:8080/api/accounts/1/transfer?amount=10 ...
+ ~~~~~
+ CategoryInfo          : InvalidArgument: (:) [Invoke-WebRequest], ParameterBindingException
+ FullyQualifiedErrorId : NamedParameterNotFound,Microsoft.PowerShell.Commands.InvokeWebRequestCommand
```

Summary

Git Repository

<https://github.com/mimiky-101/owasp-api-vuln-lab-assignment-03>

- **Vulnerable Branch:** main (original code)
- **Fixed Branch:** security-fixes

Conclusion

This report demonstrates the identification and remediation of 10 critical security vulnerabilities in the OWASP API Vulnerable Lab application. Each vulnerability was:

1. **Identified** with specific code locations
2. **Documented** with proof-of-concept exploits
3. **Fixed** using industry best practices
4. **Tested** with integration tests
5. **Committed** with clear messages and inline comments

The application is now secure and follows OWASP API Security Top 10 guidelines.