



0.250" DIA



BLANK: 0.820"



L: 0.800"

END SQUARED / UPSET



L: 0.780"

CONE FORMED



HEAD: 0.360" DIA
PRE-HEAD / POINT



HEAD: 0.500" / H: 0.094"
FINISH / SIZE



OAL: 0.750" +/-0.031"
SHANK: 0.250"+/-0.002" HEAD: 0.500"+/-0.005"

1. WIRE DIA: 0.250" +/-0.002" (AS-RECEIVED FROM COIL)
2. STATION 1 — UPSET END: SQUARE BLANK, INITIATE POINT FORM, WORK-HARDEN TIP ZONE
3. STATION 2 — GATHER MATERIAL: FORM CONE POINT 0.190" TIP DIA, MOVE STEEL TOWARD HEAD END

MIMIR METALS
Warren, Michigan | General Industrial

MACHINE: MM-14 (JBF-30B4SUL)
MATERIAL: SAE 1010 CD
WIRE DIA: 0.250"

PART FAMILY: 1/4" WELD STUD
DRAWING NO: MM-250-WS-PP
PROCESS: UPSET METHOD

DRAWN BY: [Redacted]
DATE: [Redacted]
DIVISION: STATION

MM-250-WS-PP
1/4" WELD STUD PROGRESSION
SCALE: NOT TO SCALE