



0.500" DIA



BLANK: 2.130"



L: 2.095"

END SQUARED / UPSET




L: 2.060"


CONE FORMED



HEAD: 0.720" DIA
PRE-HEAD / POINT



HEAD: 1.000" / H: 0.156"
FINISH / SIZE



OAL: 2.000" +/- 0.031"
SHANK: 0.500" +/- 0.002" HEAD: 1.000" +/- 0.005"

1. WIRE DIA: 0.500" +/- 0.002" (AS-RECEIVED FROM COIL)
2. STATION 1 — UPSET END: SQUARE BLANK, INITIATE POINT FORM, WORK-HARDEN TIP ZONE
3. STATION 2 — GATHER MATERIAL: FORM CONE POINT 0.390" TIP DIA, MOVE STEEL TOWARD HEAD END

MIMIR METALS
Warren, Michigan | General Industrial

MACHINE: MM-14 (JBF-30B4SUL)
MATERIAL: SAE 1010 CD
WIRE DIA: 0.500"

PART FAMILY: 1/2" WELD STUD
DRAWING NO: MM-500-WS-PP
PROCESS: UPSET METHOD

DESIGNED BY:
DATE:
DRAWN BY:
CHECKED BY:

MM-500-WS-PP
1/2" WELD STUD PROGRESSION
SCALE: NOT TO SCALE