

CSE-170 Computer Graphics

Lecture 11

Textures and Other Mappings


Dr. Renato Farias
rfarias2@ucmerced.edu

Mapping Techniques

- Texture mapping
 - used to improve realism
 - extremely common
- Reflection mappings
 - A way to display reflections in real-time, for ex. computed from ray tracing
- Light maps
 - Lighting effects from texture mapping
- Bump maps and Displacement maps
 - To improve geometry detail appearance
- etc.

Mapping Techniques

- Mapping techniques usually involves mapping a 2D data array onto the surface of a 3D object
 - Ex: map a height field or an image to a surface



Texture Mapping


Texture Mapping

- Can be seen as extension to Phong's model
 - Rewrite the diffuse component I_d as a function of the texture map
 - Better name would be “color mapping”
- Powerful effects




Texture Mapping

- Main problem: the mapping
 - For every triangle to be rendered, we have to define how to map the triangle to the texture image



Texture Mapping

- Main problem: the mapping
 - Many tools exist to help “design” the mapping




Texture Mapping

- Textures can become rather complex




Texture Mapping

- In OpenGL
 - Each vertex will be associated with (u, v) texture coordinates:
 - Texture coordinates are *always in $[0, 1]$*



Texture Mapping



- Mapping using intermediate surface
 - First map to an “easy” surface
 - Then, map to the final object
 - ex: cylinder mapping




Texture Mapping

- Mapping using intermediate surface
 - First map to an “easy” surface
 - Then, map to the final object
 - ex: cylinder mapping
- $(\theta, h) \rightarrow (u, v) : (u, v) = (\theta / \theta_{\max}, h / h_{\max})$

2D texture map




Intermediate surface





Texture Mapping

- Mapping using intermediate surface
 - Several possibilities for the final mapping:
 - intersection of reflected view ray
 - intersection of surface normal
 - intersection of a line from object center
 - intermediate surface normal



Texture Mappings

- Common intermediate mappings
 - Cylindrical
 - Spherical
 - Projection
 - Orthogonal
 - etc.




Texture Mappings

- Spherical mappings
 - Texture mapping can be used to alter some or all of the constants in the illumination equation: diffuse color, alter the normal, etc.
 - GLSL uses keyword *sampler* to access the colors in the texture:


```
uniform sampler2D texId;
```




Diffuse Color



Diffuse Texture Color




Texture used as Label



Texture used as Diffuse Color


Texture Mappings

- Difficulties
 - Textures do not define geometry
 - should really be thought as color mappings
 - Lighting may not appear correctly
 - Aliasing effects




Texture Mappings

- Aliasing is the under-sampling of a signal, and it's especially noticeable during animation
 - Details may pop in and out of view
 - Solution: mipmapping



Texture Mappings


- Mipmapping
 - Original high-resolution texture map is scaled and filtered into multiple resolutions before it is applied to a surface
 - *multum in parvo*: "many things in a small space."
 - The texture can appear in full detail if it is seen in a close-up, or can be rendered quickly and smoothly from a lower MIP level when the object appears smaller or further away
 - Usually, powers of 2 are used for the MIP Map levels (for ex. if the highest resolution is 1024x1024, the next levels would be 512x512, 256x256, 128x128, etc.)



Billboards

Billboards



- Texture map is treated as a 3D object in a scene
 - it is not mapped to a solid object surface
 - it is just a plane with the image
 - the plane rotates to always face the viewer
 - parts of the texture can be transparent
 - ex: trees



Bump Mapping







Bumps by Normal Vector Perturbation

- Bump mapping
 - Heightmap buffer with perturbations to be applied to the surface normals, creating the effect of a different surface
 - New normals are used for illumination
(contrary to simple textures)
 - The geometry does not actually change!




Bump Mapping


- Bump mapping




Bump Mapping




Sphere w/Diffuse Texture






Bump Map



Sphere w/Diffuse Texture & Bump Map




Bump Mapping



Bump Mapping


- Limitations
 - It is not possible to create bumps on the silhouette of a bump-mapped object
 - Bump maps do not resolve self-occlusion



Displacement Mapping

Displacement maps


- Use the texture map to actually move the surface point
- The geometry must be displaced before visibility is determined



Environment Mapping

Environment Maps


- We can simulate reflections by using the direction of the reflected ray to index a spherical texture map at "infinity".



Environment Maps

- Ex:

Box Map



Environment Maps

- Ex:



Light Maps

Light Maps

- First use a global renderer to realistically render the scene with lights, shadows, etc.
- Then use the image as a color map in the illumination of real-time environments
 - popular in games

