
Ontypology

- From difference to division, from division to type, from type to understanding – the brain has walked this path for aeons.
- A century ago, logic was philosophy; once seen clearly, it became an established science.
- Today we explore "Type" (a brain concept) as philosophy; Ontypology makes "Type" clear, turns it into an established science, and puts it into practice as Mind AI.



AI information security: the method of confirmation and the framework

the complete enterprise adoption plan — the essential ideas of all eight parts

attribute
dimension × scale
grading and labelling

composition
parts and BOM
decomposition and resilience

container
identity and scope
boundary and trust

Protect AI
the new defence line for model, data and prompt

AI for security
the intelligent SOC loop and automation


Governance and compliance
write responsibility as a judgeable Type

*This volume takes Ontypology as its theoretical base and Mind AI as the underlying platform, giving enterprises an eight-part blueprint for adoption in practice.

MIND AI

The new threat landscape of the AI era: from a “static list” to a “dynamic Type”

[Old map: traditional security]



objects: host, network, identity

protection: static boundary, privilege control, fingerprint comparison

result: massive failure against AI misuse

[New continent: three variables of AI security]

1. Uncertainty

model output is probabilistic: the same input, a different output.

2. Generativity

can produce malicious content and disinformation; the cost of attack falls.

3. Agents

once AI gets tool access, “saying it wrong” upgrades to “doing”.

List-based management has failed — the asset becomes**“a Type that changes”**.

MIND AI

a new language for security: Ontypology at a glance

Y axis { } composition

bill of materials (BOM): what it is made of, and what happens if a part breaks

responsible for decomposition and resilience

X axis [ ] attribute

dimension × scale: how sensitive, how usable

responsible for grading and labelling

Z axis ( ) container

identity and boundary: who can get in, how big the scope is

responsible for boundary and trust

THE SKELETON

unit Type Set =

[{parts, (content), [category]}]

a unit is not a thing; a unit is a Type you can re-check

PLATFORM SKELETON (MIND AI)

two libraries
Type library
function library

→

one hub
three-layer judgement
four-week scheduling

→

one loop
incident response
continuous learning

ONE SENTENCE "Write the asset as a Type, the attack as a function, walk the judgement through three layers — and protection has grounds."


MIND AI

forming the asset: breaking the AI black box into three security ledgers

Weights
the learned parameters

Architecture
the structure that carries them

→



→

System prompt
the instructions the model obeys

Training pipeline
the data and process that shaped it

X attribute axis → grading
records "how sensitive": confidentiality, integrity, scale of usability (public to secret).

Y composition axis → parts
records "what it is made of, what happens if it breaks": BOM list and dependent packages.

Z container axis → boundary
records "who can get in, how big the scope is": id(C) recognises identity, S(C) marks the scope.

INVENTORY "If you cannot name your own parts, you cannot hold its security. Inventory turns the attack surface from a slogan into a list."

MIND AI

space defence strategy: find the seams, build resilience, hold the boundary

threat Types: the attack surface = the seams between Types

supply-chain seam
third-party component handover

data seam
label and import handover

organisational seam
privilege and process handover

human–machine seam
prompt-to-model handover — the prompt-injection field

each seam is a handover: a place where one Type becomes another

Remove three levels (the resilience map)

Essential part
remove it and it fails

keep backup, failover and drills — budget for it first

Degraded part
remove it and function degrades

keep a degraded-mode plan and a switch

Optional part
remove it and things still run

remove it outright; shrink the attack surface

Zero trust **( ) container**: not only people —**model output is not trusted by default; judge before use.**

MIND AI

attacks and defences as functions: Types of malice vs protection cards


[Attack Type]	Input shape	Output shape	[Defence / guardrails]
1. Prompt injection	malicious text + legitimate context	privilege escalation	separate instructions from content; privilege convergence
2. Data poisoning	poisoned material	the skewed model	supply-chain Type check (source id and label consistency)
3. Model extraction	a flood of queries	shadow / pirated model	query quota limits; limit output precision; inject noise
4. Jailbreak	role play / encoding / mixed	output review	three shields: input intent inspection, process sandbox, output format lock

read each row as a function: the same attack Type always leaves the same input and output shape — the defence is the card you play against it.

FUNCTION The attack is a function; protection is a card. Name the input and output shape, and the guardrail follows.

MIND AI

AI for security: the Type-in, Type-out intelligent SOC loop



THREE DETECTION FUNCTION FAMILIES

rules family
fast but solid — guards the known

statistics family
catches the unknown

model family
core: humans must feed it criteria

the strongest in practice? **mixed** — rules hold the line, statistics widen the net, the model generalises.

THE POINT "Handle it and extract nothing, and the organisation fights the same battle next year. The value of the three Types lies in *it keeps growing*."

MIND AI

a re-checkable judgement: proof of six steps and a real-scenario walkthrough

1 Describe the whole

the customer-service system × the third-party LLM × the data flow.

→

2 Describe by axis

X (data grade), Y (by component), Z (API boundary).

→

3 Write the Type Set

{model, (customer dialogue, FAQ), [high sensitivity]}.

4 Fix the proposition

May it enter? Attach what control?

→

5 Judgement reasoning

data-leaving risk detected → de-identification + contract + audit.

→

6 Three-layer check

contract, module and use — all three must pass.

THE SCENE

a customer-service system wants to connect a third-party LLM — **allowed or not?**

THREE-LAYER CHECK

J_C	contract identity	✓ passed
J_B	de-identification module	✓ passed
J_T	use classification	✓ passed

CONCLUSION "Yes, subject to three conditions" — replacing the vague "probably fine". The conclusion must be executable and re-checkable.

MIND AI

pitfalls and quick reference: the four misuse groups compared, and the eight-week checklist

Pitfall	Common error	Memory phrase
Layer error	treating the grade label as the protection itself	a label is not protection.
Identity layer	treating anonymisation as a get-out-of-jail card	anonymity is not exemption — the responsibility container must still be kept.
Structure error	testing only the main model, not the outside	the BOM list must be complete.
Judgement error	treating "nothing happened" as "safe"	nothing happening is not safety — it needs a re-checkable judgement.

eight-week pocket card

- [ ] Weekly — the whole
- [ ] Two-week — three axes
- [ ] Three-week — Type Set
- [ ] Four-week — identity
- [ ] Five-week — criteria
- [ ] Six-week — three layers
- [ ] Seven-week — seven-question misuse


eight-week review

Fill whatever is missing: rules **[ ]**, identity **( )**, structure **{ }**.

MIND AI

governance, compliance and standards mapping: write responsibility as a judgeable Type

RISK TIER → DUTY



WRITE IT IN THE ( ) CONTAINER

Responsibility Type

1. Who provides it (id)?
2. Where is it deployed (scope S(C))?
3. Who is responsible (judgement J)?

NIST CSF 2.0	→	turned into six groups of time Types
OWASP LLM Top 10	→	turned into a threat-Type quick reference
MITRE ATLAS	→	turned into an attack-function index

MIND AI

the three-rung maturity ladder for enterprise adoption

L3 Act
response automated, minute-level handling, the loop self-running

L2 Judge
three-layer judgement becomes routine, controllable, re-checkable

L1 See
assets formed, BOM clear, attack surface countable

THE LESSON OF SKIPPING LEVELS

The commonest failure is never reaching **See**. Automate too early and you let a black box take the blame for you.

Every level must presuppose a Type.

Philosophy what a Type is and how it works

Method six steps, eight weeks

Practice two libraries, one hub, one loop

MIND AI

organisational capability enablement: from personal productivity to organisational assets

1

Learn

the protection skeleton: three axes, three bracket signals.

2

Practice

keep the chain; write the asset Type card.

3

Use

practise the six-step judgement at work → personal productivity.

4

Teach

bring people along: teaching, and the eight-week checklist.

5

Build

build the Type and function libraries — converted into something that does not depend on people.

Three acceptance gates
for building the library

- ✓ Type cards (every asset has a Type)
- ✓ clear criteria (every judgement has one)
- ✓ the loop turns (every case enters the library)

THE PRINCIPLE "Building is not building documents; knowledge Types must return to the library — or the loop breaks."

MIND AI

timeline and entry rhythm: small steps, fast pace; fast pilot, slow scale

W1	W2	W3	W4	W5	W6	W7	W8

W1–W2
theory basics and asset formation

output: your own AI asset Type cards

W3–W4
threat Types and protection Types


output: the attack-function library and control Types

W5–W6
the six-step loop and the eight-week method

output: the judgement result

W7–W8
platform practice and self-assessment

output: a comprehensive drill report



Stage 1 — Pilot
pick one high-value scenario (e.g. customer-service LLM). Condition: the six steps run through.

Stage 2 — Expand
extend to 2–3 scenarios. Condition: judgement is stable across scenarios.

Stage 3 — Scale
the whole organisation runs it routinely; the loop turns by itself.

The costliest mistake

Mass production first. Run the six steps in a small setting until it is trustworthy — **then** talk about scale.

MIND AI

Conclusion and vision: see, hold, judge, grow

See

assets formed, attack surface countable

tools: unit Type decomposition, three ledgers, find the seams

Guard

control formed, checkpoints deep in the seams

tools: three protection cards, supply-chain inspection, zero trust on the output

A defence that judges is the defence of the AI era. A system that cannot judge security does not count as real intelligence.

Judge

precise = re-checkable

tools: six steps, eight weeks, three-layer check ($J_C \wedge J_B \wedge J_T$)

Grow

incident response, continuous learning

tools: two libraries, one hub, one loop; learn, use, teach, build

MIND AI

Appendix: AI security practice quick-reference card (print and keep)

blank template for the unit Type and the three-layer judgement

[ ] attribute (dimension / scale / score)
how sensitive, how usable

{ } composition (parts / essential / degraded / optional)
the BOM, and what fails if a part goes

( ) container (id / scope / responsible party)
who can get in, how big the scope is

three-layer check [ ][ ][ ] J [ ] — valid only if all pass

attack function — quick reference

data poisoning	supply-chain Type check
prompt injection	separate instructions from content
model extraction	limit queries / limit precision
sample inference	adversarial training / verification


SIX-STEP PROOF — QUICK NOTE

1. Describe the whole	2. Describe by axis	3. Write the Type Set
4. Fix the proposition	5. Judgement reasoning	6. Three-layer check

print it, pin it, and check the case against it before you say “probably fine”.

MIND AI

LonGreat Vision: to create intelligent life that understands the essence of the world



MIND AI

"We aim to make artificial intelligence not merely a tool, but a system of intelligent life that truly possesses the abilities to understand, reason, learn, and create."

From the unification of knowledge, to the unification of thought, and finally toward the unification of intelligence – this is the eternal path to AGI that LonGreat pursues.

www.longreat.net

Chang Chang-Feng

gamma@livemail.tw

Chang Ting-Ying

mindaiworks@gmail.com