



End-of-studies Apprenticeship Report

Optimizing and Adapting Language Models for Domain-Specific Task

Author:
Minh Duy Nguyen

Supervised by:
Milad Mozafari (Torus AI)
David Bertoin (INSA Toulouse)

Defended on February 5, 2026, in front of the jury composed of :

Mr. David Bertoin	INSA Toulouse	– Reporter
Mr. Charles Dossal	INSA Toulouse	– Examiner
Mr. Olivier Roustant	INSA Toulouse	– Examiner

Academic year: 2025-2026

CONFIDENTIAL

Abstract

Large Language Models (LLMs) have demonstrated remarkable capabilities in natural language understanding and generation. However, deploying these models in enterprise environments faces two fundamental challenges: the *Knowledge Gap*, arising from static training data and hallucination risks, and the *Behavior Gap*, stemming from difficulties in precisely controlling model behavior for specialized tasks.

This report presents two complementary approaches developed during an apprenticeship at Torus AI to address these challenges. First, we propose an Advanced Multimodal RAG (Retrieval-Augmented Generation) pipeline for complex document understanding in financial and healthcare domains. Through systematic improvements including structure-preserving parsing, semantic enrichment via multimodal summarization, and multi-layer retrieval combining hybrid search with cross-encoder reranking, we achieved a 32.8% improvement in answer precision over baseline methods.

Second, we investigate Parameter-Efficient Fine-Tuning (PEFT) techniques to adapt Small Language Models (SLMs) for persona-based conversational tasks. Using behavioral knowledge distillation from GPT-4o and Qwen-Plus, we fine-tuned Qwen2.5-1.5B-Instruct with and without LoRA to create a Tarot Reader chatbot. Evaluation results demonstrate that the fine-tuned 1.5B model achieved behavioral consistency surpassing GPT-4 with prompt engineering (71% vs 25% win rate in human evaluation), while reducing operational costs by 80–90% and achieving sub-100ms latency suitable for real-time deployment.

These findings contribute practical frameworks for deploying domain-specific AI applications under enterprise constraints, demonstrating that both knowledge accuracy and behavioral consistency can be achieved through targeted optimization rather than model scaling.

Keywords: Large Language Models, Retrieval-Augmented Generation, Parameter-Efficient Fine-Tuning, LoRA, Knowledge Distillation, Multimodal Document Understanding, Small Language Models, Behavioral Adaptation, Enterprise AI Deployment

Acknowledgement

To begin with, I want to send my deepest thanks to Milad, my supervisor, who has guided me with great patience and understanding, especially regarding my areas for improvement. Your dedication and professionalism are truly inspiring. I have learned so much from you—not just about AI, but also about how to work with excellence.

Next, I would like to thank Thang, Thao, Sy, Khoi, Dong, and everyone at Torus. Thank you for working alongside me, sharing your experiences, and helping me develop my ideas. I am also grateful for the fun times we shared, which helped relieve the pressures of work and life. You are not merely normal colleagues; you are a part of my life. A huge thank you to CEO Zung Nguyen for opening so many doors for us and supporting us enthusiastically as we honed our skills.

I would also like to thank Erfan, Arina, Willy, Pierre, and the other members of Torus Lab. You are wonderful colleagues, and your support has meant a lot to me during my time here.

Regarding my academic journey, I would like to thank Mr. David Bertoin, my school supervisor, Mr. Olivier Roustant, head of the ModIA program, Mrs. Karine Roques, and all the professors at INSA Toulouse. Thank you for creating a program that allows me to learn while experiencing a real-world work environment, enabling me to apply what I have learned in class effectively and constantly supporting me along the way.

I sincerely thank Mr. Jean Tran Thanh Van, founder of the Hue University - INSA Toulouse cooperation program, and all the teachers at Hue University of Education. Thank you for the scholarship and the opportunity given to me; for everything you have taught me; your guidance has made it possible for me to reach this milestone today.

Most importantly, a profound thank you to my parents and younger sister. You have always supported and believed in me, keeping me strong and focused on completing this path.

To everyone who has played a part, directly or indirectly, in my journey and in this report: Thank you.

Table of contents

1	Introduction	1
1.1	General Context	1
1.1.1	Evolution of Large Language Model	1
1.1.2	The Research-Industrial Application Gap	1
1.1.3	Research motivation	2
1.2	Apprenticeship Environment	2
1.3	Problem Statement	3
1.4	Objectives of my apprenticeship	4
1.5	Report structure	4
2	Theoretical Background	5
2.1	Retrieval-Augmented Generation (RAG)	5
2.1.1	Motivation and Core Concept	5
2.1.2	Basic RAG Pipeline Architecture	6
2.2	Parameter-Efficient Fine-Tuning (PEFT)	7
2.2.1	The Fine-Tuning Paradigm	7
2.2.2	Low-Rank Adaptation (LoRA)	8
2.2.3	Other PEFT Methods	9
2.3	Knowledge Distillation	10
2.3.1	Concept and Motivation	10
2.3.2	Distillation Objective	10
2.3.3	Distillation for LLMs	10
3	Multi-modal RAG for Complex Document Understanding	12
3.1	Real-world problem: Two business use cases	12
3.1.1	Finance use case: Q&A System for SFCR Reports (GPM)	12
3.1.2	Healthcare use case: CCAM Catalog Coding Lookup (Dr. Besnier)	12
3.1.3	Technical barriers and the need for an in-house pipeline	13

3.1.4	Objective: A Unified Pipeline for All Documents	14
3.2	Why Simple RAG Fails: An Empirical Analysis	14
3.2.1	Simple RAG Baseline Configuration	14
3.2.2	Issue 1: Loss of Table Structure	15
3.2.3	Issue 2: Failure with Exact Code Matching	15
3.2.4	Other Issues	16
3.2.5	Quantitative Results: Simple RAG vs. Ground Truth	16
3.3	Advanced RAG Pipeline Architecture	16
3.3.1	Indexing Phase: Restructuring Knowledge	17
3.3.2	Query Phase: Multi-modal Knowledge Query and Synthesis Mechanism	21
3.4	Experimental Evaluation	24
3.4.1	Experimental Setup	24
3.4.2	Comparison Results: Simple RAG vs. Advanced RAG	25
3.5	Ablation Study: Contribution of Each Component	26
3.5.1	Detailed Analysis of Each Component	26
3.6	Discussion and Conclusions	26
3.6.1	Contributions	26
3.6.2	Limitations and Future Directions	27
3.6.3	Conclusion	27
4	Fine-tuning Small Language Models for Specialized Tasks: The Tarot Reader Case	28
4.1	Problem Analysis: Why is Prompt Engineering Not Enough?	28
4.1.1	Limitations of In-Context Learning for Behavioral Tasks	29
4.1.2	Specifics of the Tarot Reader Task	30
4.1.3	Research Questions	30
4.2	Knowledge Distillation Pipeline	30
4.2.1	Synthetic Data Generation: Distillation at the Behavioral Level	31
4.2.2	Model Selection and Training	33
4.2.3	Evaluation: Combining LLM Judge and Human Evaluation	34
4.3	Experimental Results	34
4.3.1	Training Process	34
4.3.2	LLM-as-a-Judge Results	34
4.3.3	Human Evaluation Results	35
4.3.4	Qualitative Analysis with Examples	36
4.4	Demo Application	36

4.5	Discussion and Conclusion	37
4.5.1	Answering Research Questions	37
4.5.2	Implications for AI Application Development	38
4.5.3	Limitations and Future Work	38
4.5.4	Conclusion	38
5	Conclusion and Perspectives	40
5.1	Work Summary	40
5.2	Perspectives	41
5.3	Personal Appreciation	41
References		45
A	Synthetic Data Generation	46
A.1	Conversation Parameters	46
A.2	System Prompt for Standard Conversations	46
A.3	System Prompt for Doubtful Users	47
A.4	User Prompt Template	48
A.5	Personality Prompt Templates	49
B	Fine-tuning Configurations	50
B.1	System Prompt for Tarot Reader Model	50
B.2	Training Hyperparameters	51
B.3	LoRA Configuration	51
B.4	Data Collator Configuration	51
B.5	Model Checkpoints	52
C	RAG Pipeline Configurations	53
C.1	UnstructuredIO Configuration	53
C.2	Embedding Model Configuration	54
C.3	Summarization Prompt	54
C.4	Image Summarization Prompt	54
C.5	RAG System Prompt	55
C.6	Evaluation Prompt (LLM-as-a-Judge)	55
D	Tarot Card Dataset Structure	56
D.1	Dataset Schema	56
D.2	Card Distribution	56

D.3	Sample Card Entry	57
E	LLM-as-a-Judge Evaluation Prompts	58
E.1	Multi-dimensional Evaluation Prompt	58

List of Figures

2.1	Basic RAG Pipeline Architecture showing Indexing Phase (offline) and Query Phase (online)	6
2.2	LoRA: Low-Rank Adaptation. The original weight W_0 is frozen, while only the low-rank matrices A and B are trained.	8
3.1	Illustrating CCAM and GPM documentation.	13
3.2	Dense Search results for the query “HAFA006”	15
3.3	Advanced RAG Pipeline Architecture Diagram	17
3.4	Table extraction process using UnstructuredIO and TATR	18
3.5	Comparison of the performance of embedding models on MTEB Multilingual. Source: [39]	21
4.1	Pipeline Knowledge Distillation for Tarot Readers. The Teacher Model generates sample data, the Student Model learns from this data, and the results are evaluated by an LLM Judge and human evaluators.	30
4.2	Tarot Reader Demo Application	37

List of Tables

3.1	Structure Comparison: Original Table vs. Text Extracted by PyPDF	15
3.2	Simple RAG Performance on GPM Test Set (25 questions)	16
3.3	Results on GPM Test Set (25 questions)	25
3.4	Results on CCAM Test Set (10 scenarios)	25
3.5	Ablation Study on GPM Test Set	26
4.1	Operational cost comparison. *Assuming 10K conversations \times 3K tokens/conversation. **Amortized GPU cost.	29
4.2	Performance comparison on standard benchmarks. Data extracted from Qwen2.5 Technical Report (2024).	33
4.3	Training results on NVIDIA RTX 3090 (24GB), 10 epochs	34
4.4	LLM-as-a-Judge Results. FT = Fine-tuned. Highlighted row: best overall model.	35
4.5	Human Evaluation on 30 test conversations	35
A.1	Conversation Generation Parameters	46
A.2	Personality-specific Prompt Templates	49
B.1	Training Configuration	51
B.2	LoRA Hyperparameters	51
B.3	Tested Model Configurations	52
C.1	Embedding Model Specifications	54
D.1	Tarot Card Dataset Schema	56
D.2	Tarot Deck Composition	56

Chapter 1

Introduction

1.1 General Context

1.1.1 Evolution of Large Language Model

Over the past decade, the fields of Artificial Intelligence (AI) and Natural Language Processing (NLP) have witnessed groundbreaking advances, particularly since the emergence of the Transformer architecture [1]. Large Language Models (LLMs) such as GPT-4 [2], Claude [3], Gemini [4], and open-source models like Llama 3 [5] and Qwen 2.5 [6] have demonstrated superior capabilities in understanding context, generating text, and performing logical inference across a variety of tasks.

1.1.2 The Research-Industrial Application Gap

Transferring language models from the research environment to practical industrial applications faces significant challenges. Indeed, according to an MIT survey, up to 95% of AI generation/LLM projects in enterprises do not generate significant profit and loss (P&L) impact—reflecting that the majority of businesses struggle to move LLMs from pilot to production deployment [7]. Additionally, other surveys show that approximately 72% of businesses encounter at least one barrier to adopting GenAI (including operating costs, governance, and model accuracy), and over 50% consider accuracy a major barrier to LLM deployment [8].

Although Foundation Models possess a vast amount of general knowledge, they often encounter two serious limitations when solving domain-specific tasks:

Knowledge Gap

In critical fields such as healthcare, finance, and insurance, information is often contained in complex documents (financial reports, medical technical catalogs) and changes constantly. LLMs face three main problems:

- Static Knowledge: Model knowledge is limited by the training time (knowledge cutoff), making it impossible to update new information without retraining.

- Private Data Inaccessibility: The model cannot access confidential organizational documents such as contracts, internal procedures, or patient records.
- Hallucination: LLMs tend to confidently generate false information [9, 10] which is unacceptable in medical or financial decisions where near-absolute accuracy is required.

Efficiency & Behavior Gap

For tasks that require strict adherence to a predefined behavioral scenario, a specific linguistic style (e.g., psychological counselor or analyst), or deployment under constrained hardware environments, extremely large language models with hundreds of billions of parameters are often neither cost-effective nor latency-efficient. As shown by the compute-optimal scaling analysis of Hoffmann et al. [11], increasing model size without proportionally increasing training data leads to inefficient use of compute, resulting in substantially higher training and inference costs. Furthermore, the scaling laws identified by Kaplan et al. [12] demonstrate that model performance improves as a power-law function of compute, implying that compute—and consequently deployment cost and latency—grows rapidly with model size, limiting the practicality of massive models for many real-world enterprise settings.

1.1.3 Research motivation

Based on the above reality, this report focuses on researching and implementing advanced techniques to **optimize and adapt Language Models for specific data domains**, with two main approaches:

- Retrieval-Augmented Generation (RAG): Integrating external knowledge bases to address the Knowledge Gap.
- Parameter-Efficient Fine-Tuning (PEFT): Adapting model behavior to address the Behavior Gap.

1.2 Apprenticeship Environment

This master's report was completed at **Torus AI**, a technology company with the mission *Intelligence for Life*, specializing in providing advanced AI solutions to improve quality of life and business efficiency.

I worked in the Research and Development Team (R&D Team - Torus Lab) as a Machine Learning Engineer Alernant. At Torus AI, the R&D department acts as a bridge between the latest academic research (State-of-the-Art) and commercial products. The team's main task is to continuously explore emerging Generative AI technologies, assess their feasibility, and build functional prototypes (PoCs) to verify their effectiveness before integration into the main product system.

The R&D work environment demands flexible thinking: not just using existing APIs, but delving into customizing architecture, optimizing data processing pipelines, and quantitatively evaluating technical solutions.

My role in the R&D department includes:

- Researching emerging Generative AI technologies
- Evaluating feasibility and building functional prototypes (PoCs)
- Integrating solutions into product systems

Resources provided:

- GPU infrastructure: NVIDIA RTX 3090 (24GB)
- Real-world enterprise data: Medical documents (CCAM), insurance financial reports
- API access: OpenAI GPT-4, Google Gemini, Qwen API and internal API for using in-house open-source models

1.3 Problem Statement

During our work in the R&D department, we identified two core problems that needed to be addressed when applying GenAI in practice, corresponding to two main technical approaches:

Problem 1: Integration of External Knowledge from Complex Unstructured Data

Clients businesses (such as insurance companies, healthcare facilities) possess large amounts of data in the form of PDF documents containing text, tables, and images. Traditional RAG methods based on plain text (text-only) fail to understand the semantics of complex tables or visual information [13, 14]. The question is: How to build a Multimodal RAG pipeline capable of accurately parsing, indexing, and retrieving information from these mixed documents to support decision-making (e.g., medical refund code lookup, financial data analysis)?

Problem 2: Behavioral Adaptation and Resource Optimization for Small Models (Behavioral Adaptation & Efficiency)

For applications requiring high interactivity, counseling, or entertainment (such as psychological counseling chatbots or Tarot Readers), the requirement is not only for information accuracy but also for consistency in tone and style and rule-based reasoning. Using large models (like GPT-4) via APIs is both costly to operate and difficult to fully control behavior.

Recent research has shown that small language models can achieve competitive performance through efficient fine-tuning techniques like LoRA [15] and QLoRA [16], combined with synthetic data generation approaches [17, 18].

The question is: Is it possible to fine-tune small language models (such as Qwen, Llama < 7B parameters) using parameter optimization techniques (PEFT/LoRA) and quantization so that they achieve inference capabilities and writing styles comparable to large models, but can be run locally at low cost?

1.4 Objectives of my apprenticeship

This report covers the following objectives:

1. Reading and synthesizing the latest researches on Retrieval-Augmented Generation (RAG) and Parameter-Efficient Fine-Tuning (PEFT) techniques, to build a solid theoretical foundation.
2. Design and implement an Advanced Multimodal RAG pipeline capable of accurately extracting and retrieving information from complex documents containing text, tables, and images in the medical and financial domains.
3. Develop a methodology for fine-tuning Small Language Models (< 2B parameters) using PEFT/LoRA techniques to achieve domain-specific behavior adaptation while enabling cost-effective local deployment.
4. Establish systematic evaluation frameworks for both RAG retrieval quality using RAGAS metrics [19] and fine-tuned model performance using LLM-as-a-Judge approaches [20], enabling reproducible benchmarking.

1.5 Report structure

In addition to this introduction, this report is organized into four main chapters and appendices. Chapter 2 provides the theoretical background, introducing the foundational concepts of RAG and PEFT, followed by an overview of Knowledge Distillation and Synthetic Data Generation techniques. Chapter 3 addresses the Knowledge Gap by presenting an Advanced Multimodal RAG pipeline for processing complex medical and financial documents. Chapter 4 tackles the Behavior Gap through LoRA fine-tuning of small Qwen models for persona-based tasks. Chapter 5 concludes the report by summarizing contributions and proposing future research directions. The Appendices provide supplementary materials including prompt templates and configurations.

Chapter 2

Theoretical Background

As introduced in Chapter 1, deploying Large Language Models (LLMs) in enterprise environments faces two fundamental challenges: the *Knowledge Gap* stemming from static training data and hallucination risks, and the *Behavior Gap* arising from the difficulty in precisely controlling model behavior for specialized tasks. This chapter establishes the theoretical foundations for two complementary approaches to address these challenges: Retrieval-Augmented Generation (RAG) for knowledge integration, and Parameter-Efficient Fine-Tuning (PEFT) for behavioral adaptation. Additionally, we discuss Knowledge Distillation and Synthetic Data Generation—techniques that enable the transfer of capabilities from large models to smaller, more deployable ones.

2.1 Retrieval-Augmented Generation (RAG)

2.1.1 Motivation and Core Concept

Despite their impressive capabilities, LLMs suffer from inherent limitations that restrict their applicability in knowledge-intensive domains [21]. These limitations include: (1) *knowledge cutoff*—the model cannot access information beyond its training date; (2) *hallucination*—the tendency to generate plausible but factually incorrect content [22]; and (3) *lack of attribution*—inability to cite sources for generated claims.

Retrieval-Augmented Generation addresses these issues by augmenting the LLM’s input with relevant documents retrieved from an external knowledge base. Instead of relying solely on parametric knowledge (stored in model weights), RAG combines it with non-parametric knowledge (retrieved documents), enabling the model to ground its responses in verifiable sources [21].

The fundamental insight behind RAG is that while LLMs excel at language understanding and generation, they need not memorize all factual knowledge in their parameters. By decoupling knowledge storage (in a retrievable database) from language capabilities (in the model), RAG achieves both factual accuracy and generative fluency.

2.1.2 Basic RAG Pipeline Architecture

A standard RAG pipeline consists of two main phases: an offline **Indexing Phase** and an online **Query Phase** [13]. Figure 2.1 illustrates the a RAG architecture.




Figure 2.1: Basic RAG Pipeline Architecture showing Indexing Phase (offline) and Query Phase (online)

Indexing Phase

The indexing phase prepares the knowledge base for efficient retrieval:

1. **Document Loading:** Raw documents (PDFs, web pages, databases) are ingested into the system.
2. **Chunking:** Documents are split into smaller segments called *chunks*. The chunk size represents a trade-off: smaller chunks enable more precise retrieval but may lose context, while larger chunks preserve context but reduce retrieval granularity. Common strategies include fixed-size chunking (e.g., 512 tokens with overlap) and semantic chunking based on document structure Liu et al. [23].
3. **Embedding:** Each chunk is transformed into a dense vector representation using an embedding model. These vectors capture semantic meaning, allowing similar concepts to have proximate representations in vector space. Popular models include OpenAI's text-embedding-ada-002 [24], Sentence-BERT [25], and multi-lingual variants like E5 [26].
4. **Indexing:** Embeddings are stored in a vector database (e.g., ChromaDB [27], Pinecone [28], Qdrant [29]) optimized for similarity search using algorithms like HNSW (Hierarchical Navigable Small World) or IVF (Inverted File Index) [30].

Query Phase

When a user submits a query, the system executes the following steps:

1. **Query Embedding:** The user query is embedded using the same model used during indexing, ensuring comparable vector representations.
2. **Retrieval:** The system performs similarity search (typically using cosine similarity or dot product) to find the k most relevant chunks. This is often called Dense Retrieval or Vector Search.
3. **Augmentation:** Retrieved chunks are concatenated with the original query to form an augmented prompt. A typical template might be:

```
Context: [retrieved chunks]
Question: [user query]
Answer the question based on the context above.
```

4. **Generation:** The augmented prompt is passed to the LLM, which generates a response grounded in the retrieved context.

While conceptually elegant, basic RAG faces several challenges in practice such as **Loss of Document Structure**, **Chunking Artifacts**, **Retrieval Errors**, and the **Lost in the Middle** phenomenon [23]. These limitations motivate advanced RAG techniques discussed in Chapter 3, including multimodal parsing, hybrid search, and reranking.

2.2 Parameter-Efficient Fine-Tuning (PEFT)

2.2.1 The Fine-Tuning Paradigm

While RAG addresses the Knowledge Gap by augmenting LLMs with external information, the *Behavior Gap*—the difficulty in making models consistently adhere to specific communication styles, workflows, or personas—requires a different approach. Fine-tuning adapts pre-trained models to downstream tasks by continuing training on task-specific data, enabling the model to internalize desired behaviors into its parameters.

Traditional full fine-tuning updates all model parameters, which for modern LLMs with billions of parameters presents significant challenges:

- **Computational Cost:** Training all parameters requires substantial GPU memory and compute time. For a 7B parameter model in FP16, storing model weights, gradients, and optimizer states requires approximately 112GB of memory.
- **Storage Overhead:** Each fine-tuned variant requires storing a complete copy of all model weights, making multi-task or multi-tenant deployments impractical.
- **Catastrophic Forgetting:** Aggressive fine-tuning can degrade the model’s general capabilities acquired during pre-training.

Parameter-Efficient Fine-Tuning (PEFT) methods address these challenges by training only a small subset of parameters while keeping the majority of the pre-trained model frozen. This approach dramatically reduces memory requirements, enables efficient multi-task adaptation through swappable modules, and often provides implicit regularization against overfitting.

2.2.2 Low-Rank Adaptation (LoRA)

Among PEFT methods, Low-Rank Adaptation (LoRA) [15] has emerged as the dominant technique due to its simplicity, effectiveness, and inference efficiency. LoRA’s key insight is that the weight updates during fine-tuning exhibit low intrinsic dimensionality—meaning they can be effectively approximated by low-rank matrices.

Mathematical Formulation

For a pre-trained weight matrix $\mathbf{W}_0 \in \mathbb{R}^{d \times k}$, LoRA represents the weight update as a low-rank decomposition:

$$\mathbf{W} = \mathbf{W}_0 + \Delta\mathbf{W} = \mathbf{W}_0 + \mathbf{BA}$$

where $\mathbf{B} \in \mathbb{R}^{d \times r}$ and $\mathbf{A} \in \mathbb{R}^{r \times k}$, with rank $r \ll \min(d, k)$.




Figure 2.2: LoRA: Low-Rank Adaptation. The original weight W_0 is frozen, while only the low-rank matrices A and B are trained.

During training, \mathbf{W}_0 remains frozen while only \mathbf{A} and \mathbf{B} are updated. The forward pass becomes:

$$\mathbf{h} = \mathbf{W}_0 \mathbf{x} + \frac{\alpha}{r} \mathbf{BAx}$$

where α is a scaling hyperparameter that controls the magnitude of the adaptation.

Parameter Efficiency Analysis

The efficiency gains from LoRA are substantial. Consider applying LoRA to a weight matrix of dimensions $d \times k$:

- Full fine-tuning: $d \times k$ trainable parameters
- LoRA with rank r : $r \times (d + k)$ trainable parameters

For a typical attention projection with $d = k = 4096$ and $r = 16$:

- Full: $4096 \times 4096 = 16,777,216$ parameters
- LoRA: $16 \times (4096 + 4096) = 131,072$ parameters (0.78% of full)

Target Module Selection

LoRA can be applied to any linear layer, but research and practice have identified attention projection matrices (\mathbf{W}_Q , \mathbf{W}_K , \mathbf{W}_V , \mathbf{W}_O) as particularly effective targets. Recent work has also demonstrated benefits from including feed-forward network (FFN) layers, especially for behavioral adaptation tasks where the model must learn new “processing patterns” rather than just new “attention patterns.”

Inference Efficiency

A unique advantage of LoRA is that the adapted weights can be merged with the original weights after training:

$$\mathbf{W}_{\text{merged}} = \mathbf{W}_0 + \mathbf{BA}$$

This merged model has identical architecture and inference cost to the original, with no additional latency overhead. Alternatively, keeping adapters separate enables efficient switching between different task-specific adaptations by swapping only the small LoRA matrices.

2.2.3 Other PEFT Methods

While LoRA dominates current practice, other PEFT approaches offer alternative trade-offs:

Prefix Tuning [31]: Prepends trainable continuous vectors (“soft prompts”) to the input at each transformer layer. These prefixes learn to condition the frozen model’s behavior without modifying its weights.

Adapters [32]: Insert small trainable bottleneck modules between transformer layers. Unlike LoRA, adapters add parameters to the forward pass, incurring slight inference overhead.

QLoRA [33]: Combines LoRA with 4-bit quantization, enabling fine-tuning of very large models on consumer hardware by dramatically reducing memory requirements.

Chapter 4 applies LoRA fine-tuning to adapt small language models for a specialized conversational task, demonstrating that behavioral consistency can be effectively learned with minimal parameter updates.

2.3 Knowledge Distillation

2.3.1 Concept and Motivation

Knowledge Distillation (KD) is a model compression technique that transfers knowledge from a large “teacher” model to a smaller “student” model [34]. The motivation is that large models, while powerful, are often impractical for deployment due to latency, memory, and cost constraints. Distillation enables the student to achieve performance approaching the teacher while being significantly more efficient.

The key insight of Hinton, Vinyals, and Dean [34] is that the teacher’s soft probability distribution contains richer information than hard labels. For example, when classifying an image of a dog, the teacher might output $P(\text{dog}) = 0.7, P(\text{wolf}) = 0.2, P(\text{cat}) = 0.1$. These “dark knowledge” probabilities reveal that the image has wolf-like features—information lost in the hard label “dog”.

2.3.2 Distillation Objective

The student is trained to minimize a combination of task loss and distillation loss:

$$\mathcal{L} = \alpha \mathcal{L}_{\text{task}}(y, p_S) + (1 - \alpha) \mathcal{L}_{\text{KD}}(p_T, p_S) \quad (2.1)$$

where p_T and p_S are teacher and student probability distributions, y is the ground truth, and α balances the two objectives.

The distillation loss typically uses KL divergence with temperature scaling:

$$\mathcal{L}_{\text{KD}} = T^2 \cdot \text{KL}\left(\text{softmax}\left(\frac{z_T}{T}\right) \parallel \text{softmax}\left(\frac{z_S}{T}\right)\right) \quad (2.2)$$

where z_T, z_S are teacher and student logits, and temperature $T > 1$ softens the distributions to emphasize the dark knowledge.

2.3.3 Distillation for LLMs

In the context of LLMs, knowledge distillation takes several forms:

Logit-based Distillation

The student learns to match the teacher’s output distribution over vocabulary tokens. This requires access to teacher logits, which may not be available for proprietary models like GPT-4.

Feature-based Distillation

The student learns to match intermediate representations (hidden states, attention patterns) of the teacher [35]. This transfers more fine-grained knowledge but requires ar-

chitectural compatibility.

Behavioral Distillation

When teacher internals are inaccessible (black-box APIs), an alternative is *behavioral distillation*: the student learns from teacher-generated outputs. This is the approach used in this thesis—the teacher (GPT-4) generates example conversations demonstrating desired behavior, and the student learns from these demonstrations.

Recent work has shown that behavioral distillation can effectively transfer complex capabilities. Alpaca [36] demonstrated that LLaMA could match GPT-3.5 behavior using only 52K instruction-following examples generated by text-davinci-003. Similarly, Vicuna achieved 90% of ChatGPT quality using conversations from ShareGPT.

In chapter 4, we apply behavioral distillation to adapt a small Qwen model to emulate a Tarot Reader persona, using GPT-4 and Qwen2.5-Plus to generate high-quality training dialogues.

Chapter 3

Multi-modal RAG for Complex Document Understanding

3.1 Real-world problem: Two business use cases

During our work at Torus AI, we received two requests from clients with similar challenges but in two completely different fields: finance and healthcare. Despite the distinctly different business contexts, both faced the same core problem: how to effectively extract knowledge from highly information-dense, unstructured documents — specifically, documents containing numerous tables, images, and complex multimedia data.

3.1.1 Finance use case: Q&A System for SFCR Reports (GPM)

GPM (Gestion Patrimoine Mutualiste) is a mutual insurance fund under the AGMF group (Association Générale des Médecins de France). Their requirement seemed simple: build a rapid Q&A system so employees could look up information from annual financial reports.

GPM faces a massive volume of SFCR (Solvency and Financial Condition Reports) and annual accounting reports. The challenge lies not only in the document length (50-200 pages) but also in the multi-modal nature of the data. Figure 3.1b illustrates the structure of one such data page.

Crucial knowledge is often not found in plain text but is condensed into multi-dimensional balance sheets, trend charts, risk matrices, etc. Querying metrics such as "2024 Solvency Ratio" requires the system to have spatial understanding of the table structure rather than simply reading a string of characters.

3.1.2 Healthcare use case: CCAM Catalog Coding Lookup (Dr. Besnier)

Conversely, the problem from Dr. Besnier focuses on the CCAM (Classification Commune des Actes Médicaux) system—a complex classification system comprising thousands of French medical codes used to determine insurance reimbursement levels. Figure 3.1a illustrates the structure of this catalog.

Code	Texte	Activité	Phase	Tarif	Tarif	Frais d'envoi et de port	Ancien Frais de port	Droits d'accès				
				Service et / ou adresse DPT/CHAM- ACO (par mois)	Verso Hausse hors admissi- bilité DPT/CHAM- ACO (par mois)							
1 SYSTEME NERVEUX CENTRAL, PERIPHERIQUE ET AUTONOME												
1.01 ACTES DIAGNOSTIQUES SUR LE SYSTEME NERVEUX												
1.01.01 Examen électrophysiologique du système nerveux												
1.01.01.01 Electromyogramme (EMG)												
Facteur(s) : les examens électrophysiologiques doivent être pratiqués avec un appareil compatible et d'autonomie d'enregistrement permanente en off-line, une étude quantitative et quantitative.												
AHQ001	Electromyogramme par électrode de surface, sans enregistrement vidéo		1	0	Nous pris en charge	Nous pris en charge	x	ATT				
AHQ002	Electromyogramme par électrode de surface, avec enregistrement vidéo		1	0	Nous pris en charge	Nous pris en charge	x	ATT				
AHQ003	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort sans stimulation électrique		1	0	51,84	51,84	x	ATT				
AHQ004	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort avec stimulation électrique	Forfait: spéciifique à un acte plus de la formation initiale	1	0	50,40	50,40	x	ATT				
[P, P, S, U]	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort avec stimulation électrique, par électrode sigillaire	Forfait: spéciifique à un acte plus de la formation initiale	1	0	50,40	50,40	x	ATT				
AHQ005	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort sans stimulation électrique, par électrode sigillaire	Forfait: spéciifique à un acte plus de la formation initiale	1	0	50,40	50,40	x	ATT				
[P, P, S, U]	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort avec stimulation électrique, par électrode sigillaire	Forfait: spéciifique à un acte plus de la formation initiale	1	0	50,40	50,40	x	ATT				
AHQ006	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort, par électrode sigillaire	Forfait: spéciifique à un acte plus de la formation initiale	1	0	50,40	50,40	x	ATT				
[P, P, S, U]	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort, par électrode sigillaire, avec mesure des vitesse de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels, et mesure des vitesses de conduction sensitive et de l'amplitude des réponses sensorielles	Forfait: spéciifique à un acte plus de la formation initiale	1	0	124,82	123,29	x	ATT				
AHQ007	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort pour déterminer l'activité motrice et la sensibilité des muscles superficiels et profonds	Forfait: spéciifique à un acte plus de la formation initiale	1	0	146,79	135,84	x	ATT				
AHQ008	Electromyogramme de 2 à 3 secondes en rapport au repos et à l'effort pour déterminer l'activité motrice et la sensibilité des muscles superficiels et profonds	Forfait: spéciifique à un acte plus de la formation initiale	1	0	146,40	134,36	x	ATT				
AHQ009	Biopsie musculaire		1	0	146,40	134,36	x	ATT				
[P, P, S, U]	Biopsie musculaire	Forfait: spéciifique à un acte plus de la formation initiale	1	0	146,40	134,36	x	ATT				
AHQ010	Capsulographe		1	0	70,32	62,56	x	ATT				
[P, P, S, U]	Capsulographe	Forfait: spéciifique à un acte plus de la formation initiale	1	0	70,32	62,56	x	ATT				
1.01.01.02 Mesure des vitesse de conduction												
AHQ011	Mesure des vitesses de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels		1	0	56,28	47,33	x	ATT				
[P, P, S, U]	Mesure des vitesses de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels	Forfait: spéciifique à un acte plus de la formation initiale	1	0	56,28	47,33	x	ATT				
AHQ012	Mesure des vitesses de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels et profonds		1	0	66,80	53,28	x	ATT				
[P, P, S, U]	Mesure des vitesses de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels et profonds	Forfait: spéciifique à un acte plus de la formation initiale	1	0	66,80	53,28	x	ATT				
AHQ013	Mesure des vitesses de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels et profonds, de 3 à 6 mois plus, sans étude de la conduction prémotrice		1	0	66,36	54,28	x	ATT				
[P, P, S, U]	Mesure des vitesses de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels et profonds, de 3 à 6 mois plus, sans étude de la conduction prémotrice	Forfait: spéciifique à un acte plus de la formation initiale	1	0	76,23	59,56	x	ATT				
AHQ014	Mesure des vitesses de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels et profonds, de 3 à 6 mois plus, avec étude de la conduction prémotrice sur une moitié des nerfs		1	0	81,75	60,30	x	ATT				
[P, P, S, U]	Mesure des vitesses de conduction motrice et de l'amplitude des réponses motrices maximales induites par la stimulation des muscles superficiels et profonds, de 3 à 6 mois plus, avec étude de la conduction prémotrice sur une moitié des nerfs	Forfait: spéciifique à un acte plus de la formation initiale	1	0	81,75	60,30	x	ATT				

(a) One page in the CCAM codes document

(b) One page in GPM reports

Figure 3.1: Illustrating CCAM and GPM documentation.

The challenge here is that CCAM data contains thousands of medical codes organized in an extremely complex tabular structure. Each code (e.g., HAFA008) comes with strict application conditions and different reimbursement rates based on the clinical context.

A practical query might be: "Patiente 69 ans, exérèse de carcinome basocellulaire de la lèvre, suture par lambeau à la volée". The system needs to return appropriate CCAM codes like HAFA008 or QAMA002 — a task requiring not just semantic understanding but also exact matching with specific codes. A minor error in code matching can lead to discrepancies in medical records and the insurance reimbursement process.

3.1.3 Technical barriers and the need for an in-house pipeline

The commonalities between these two use-cases identified three main barriers that forced us to build an In-house Advanced RAG Pipeline:

- 1. Strict Data Security Requirements:** Both financial documents and medical records are sensitive corporate data. Under business and industry standards, using cloud services like ChatGPT or Claude API directly with raw data is prohibited due to data leakage risks. Customers require a solution that runs entirely on-premise or within their private cloud.
 - 2. High Accuracy:** In these two fields, "hallucination" is unacceptable. An incorrect answer regarding revenue could lead to poor investment decisions; an inaccurate medical code directly affects patient treatment and insurance reimbursement. The system needs a transparent attribution (citation) mechanism.

13 / 59

3. **Native LLM Limitations:** The limited context window of language models cannot encompass the entire massive document repository, and their real-time knowledge update capability is restricted without an efficient Retrieval mechanism.

RAG is the ideal solution: retrieve relevant information from a knowledge base, then augment the prompt for the LLM to generate the answer. This allows the LLM to "learn" from new documents without the need for fine-tuning.

3.1.4 Objective: A Unified Pipeline for All Documents

Instead of developing two separate pipelines, we set a more ambitious goal: to build a unified RAG pipeline capable of effectively processing all types of multimodal documents. This pipeline must achieve:

- High accuracy for both financial and medical documents.
- Ability to process complex tables with 2D structures.
- Support for both semantic and exact match (keyword/code-specific) retrieval.
- Full local execution without dependence on external cloud services.

In the following sections, we will analyze why **simple RAGs are insufficient**, and then present our advanced pipeline architecture with each component designed to address a specific problem.

3.2 Why Simple RAG Fails: An Empirical Analysis

Before proposing a complex solution, we performed a crucial step: testing a Simple RAG baseline and quantitatively measuring its limitations. This not only justifies the need for advanced techniques but also helps pinpoint the exact "bottlenecks" to be resolved.

3.2.1 Simple RAG Baseline Configuration

The Simple RAG pipeline was implemented with the most standard components – typical of what you would find in most RAG tutorials:

- **Document Parsing:** PyPDF to extract text from PDFs.
- **Chunking:** Fixed-size chunking with 512 tokens/chunk and 50 tokens overlap.
- **Embedding Model:** sentence-transformers/all-MiniLM-L6-v2 – the most popular model with 22M parameters.
- **Vector Store:** ChromaDB with Dense Search (cosine similarity).
- **LLM:** Gemma-3-12b-it to generate answers.

3.2.2 Issue 1: Loss of Table Structure

The most serious problem arises during the Document Parsing stage. Traditional extractors like PyPDF "flatten" the 2D structure of tables into a 1D text string. Consider this specific example from a GPM document:

Table 3.1: Structure Comparison: Original Table vs. Text Extracted by PyPDF

a) Original Table in PDF:

Sous modules (en k€)	SCR 2024	SCR 2023	Evol.
Type 1	2 692	2 487	8 %
Type 2	28 377	36 221	-22 %
Diversification	-621	-586	6 %
Risque de défaut	30 448	38 121	-20 %

b) After PyPDF Extraction:

Sous modules (en k€)	SCR 2024	SCR 2023	Evolution
Type 1	2 692	2 487	8 %
Type 2	28 377	36 221	-22 %
Effet de diversification	-621	-586	6 %
Risque de défaut	30 448	38 121	-20 %

With this text string, answering a question like "*What is the SCR 2024 for Type 2?*" becomes very difficult for the LLM because the semantic relationship between the Header (Column/Row) and the Value is severed. The system struggles to distinguish whether the number "28 377" belongs to the "SCR 2024" column or is two separate numbers "28" and "377", and whether it corresponds to the "Type 2" row due to the loss of alignment. This leads to completely inaccurate quantitative answers.

3.2.3 Issue 2: Failure with Exact Code Matching

For the medical use-case, we observed that Dense Search (Vector Search) frequently returned noisy results when dealing with specific codes (like HAFA006). This is because embedding models focus on semantic similarity. However, medical codes often do not carry natural language meaning; they are entities that require an Exact Match. Relying solely on Vector Search causes the system to suggest codes that "look similar" but are medically entirely different.

Figure 3.2 shows an example of retrieval results from Simple RAG for a query asking for the code HAFA006:

```
=====
[ANALYSIS OF RESULTS]
=====

1 HAFA006 POSITION:
  ✓ Found HAFA006 at rank #3
  ⚠ HYPOTHESIS PARTIALLY CONFIRMED: Ranked #3 (not #1, but still high)

2 SIMILAR CODES RANKED HIGHER:
  Found 5 chunks with similar HAFA00X codes:
  - Rank #1: ['HAFA004', 'HAFA002'] (score: 0.2544)
  - Rank #2: ['HAFA005', 'HAFA003'] (score: 0.2315)
  - Rank #3: ['HAFA007'] (score: 0.2199)
  - Rank #4: ['HAFA001'] (score: 0.2107)
  - Rank #5: ['HAFA009'] (score: 0.2107)
```

Figure 3.2: Dense Search results for the query “HAFA006”

The retriever returns the passage containing the code at position 3, and all higher positions are matched with other similar codes because Dense Search doesn't understand that the user needs the exact "HAFA006", not a similar code.

3.2.4 Other Issues

The "Lost in the Middle" phenomenon discovered by Liu et al. [23]: when context contains many passages (e.g., 10-20), LLMs tend to focus on the beginning and the end, ignoring information in the middle. In our tests with top-20 retrieval, when the ground-truth passage was at position 7-12, LLM accuracy dropped by 23% compared to when it was at position 1-3.

Additionally, there is the embedding model issue: all-MiniLM-L6-v2 was trained primarily on English data. When applied to French documents, performance degraded significantly.

3.2.5 Quantitative Results: Simple RAG vs. Ground Truth

We evaluated Simple RAG on 25 questions from the GPM test set (which will be discussed later) using Gemma-3-12b-it as a LLM-as-a-Judge with two metrics: Correctness and Relevancy. The results are shown in Table 3.2.

Table 3.2: Simple RAG Performance on GPM Test Set (25 questions)

Metric	Score	Interpretation
Correctness	0.66	66% answers correct with respect to contexts
Relevancy	0.73	73% answers relevant to the question

A precision of 0.66 indicates that for every 100 answers, nearly 34 contain inaccurate information – an unacceptable error rate in a business environment.

3.3 Advanced RAG Pipeline Architecture

Based on the analysis in the previous section, we designed a pipeline where each component addresses a specific identified problem. Figure 3.3 illustrates the overall architecture of the Advanced RAG Pipeline.




Figure 3.3: Advanced RAG Pipeline Architecture Diagram

The pipeline is organized into two phases: **Indexing Phase** (offline, runs once when new documents arrive) and **Query Phase** (online, each time a user asks a question).

3.3.1 Indexing Phase: Restructuring Knowledge

Preserving Structure with UnstructuredIO and Table Transformer

To solve the problem of losing table structure during parsing, we use UnstructuredIO [37]—a powerful library for Document Layout Analysis. Instead of PyPDF which only extracts raw text, UnstructuredIO uses computer vision to detect regions in PDFs: Text blocks, Table regions, and Image regions. Specifically, for tables, UnstructuredIO preserves the 2D structure by converting to HTML.

We use the `hi_res` strategy of UnstructuredIO. With this strategy, UnstructuredIO treats each document page as an image and passes it through Object Detection models like YoloX or Detectron2 to classify regions in the page as Title, Text, List, Table, Image and predict “bounding boxes” around each component. Particularly, for regions marked as

“Table”, UnstructuredIO not only extracts text but also needs to understand the row/column structure using Table Transformer (TATR) [38]. The process works as:

1. **Table Detection:** Identify table positions.
2. **Table Structure Recognition:** Recognize lines (cells), merged cells, and classify headers vs. body.
3. **HTML Mapping:** Finally, map these coordinates to <table> tags for easy LLM processing.

Figure 3.4 and the HTML output below illustrates an example of table detection and extraction using UnstructuredIO.




Figure 3.4: Table extraction process using UnstructuredIO and TATR

Parsed HTML Output			
<pre> <table> <thead> <tr> <th>Sous modules (en k€)</th> <th>SCR 2024</th> <th>SCR 2023</th> <th>Evolution</th> </tr> </thead> <tbody> <tr> <td>Type 1</td> <td>2 692</td> <td>2 487</td> <td>8%</td> </tr> <tr> <td>Type 2</td> <td>28 377</td> <td>36 221</td> <td>-22%</td> </tr> </tbody> </table> </pre>			

```

<tr>
    <td>Effet de diversification</td>
    <td>-621</td>
    <td>-586</td>
    <td>6%</td>
</tr>
<tr>
    <td>Risque de défaut</td>
    <td>30 448</td>
    <td>38 121</td>
    <td>-20%</td>
</tr>
</tbody>
</table>

```

Using the same table as in the PyPDF test above, we now preserve the table structure in HTML. This structure will be fed to the LLM. Using HTML as an intermediate format for tables is optimal because modern LLMs (like Gemma-3-12b-it) are trained on large amounts of web data, giving them the ability to “understand” and “reason” on `<table>` structures much better than plain text.

Semantic Bridge: Summarization Mechanism for Multimodal Data

To bridge the semantic gap between user questions and dry numbers in tables/images, we deploy a summarization layer. Current embedding models often struggle with:

- **Tables:** Tables that are too large or contain pure numerical data (e.g., “2024: 210,294”) often lack contextual keywords (like “revenue”, “growth”), making retrieval inaccurate.
- **Images:** Traditional embedding models cannot “read” content directly from images.

Solution: Use LLM to create summaries for each data chunk, serving as a “semantic bridge” to increase content identification efficiency.

We use Gemma-3-12b-it to analyze complex numerical tables in chunks. The LLM will interpret numbers into meaningful text (e.g., “The table shows revenue for 2024 reached 210,294 k€, up 6%”). This helps the chunk embedding match accurately with user’s descriptive queries. For chunks containing images, since Gemma-3-12b-it is a Multimodal LM capable of converting visual information to text descriptions. This process helps the embedding model “understand” image content through the auxiliary summary layer.

For the table in the image 3.4, the summary is generated as follows:

Summary: "Le tableau détaille l'évolution du Solvency Capital Requirement (SCR) pour différents sous-modules entre 2023 et 2024, avec les montants exprimés en milliers d'euros (k€) et l'évolution en pourcentage.

Pour le sous-module « Type 1 », le SCR est passé de 2 487 k€ en 2023 à 2 692 k€ en 2024, affichant une évolution de 8%. Le sous-module « Type 2 » a vu son SCR passer de 36 221 k€ en 2023 à 28 377 k€ en 2024, avec une évolution indiquée de -22%.

L'« Effet de diversification » a évolué de -586 k€ en 2023 à 621 k€ en 2024, soit une évolution de 6%. Enfin, le « Risque de défaut » a diminué, passant de 38 121 k€ en 2023 à 30 448 k€ en 2024, l'évolution diminue de -20%."

This summary becomes a "semantic bridge": when a user asks about "revenue in 2024," the question's embedding will have a high similarity to the summary (containing "coffee shop" and "2024"). This enriches the information for the chunk, ensuring the highest possible similarity between the query vector and the document content, even if the original data does not contain the keywords in the question.

Parent-Child Indexing Strategy

After the summary generation step, each chunk now has two parts: raw content and its summary. The summary will be stored in the vector store for retrieval. However, if we use this summary as context for the LLM, the LLM will lack the necessary information to answer in detail. Short summaries help more accurate retrieval (less noise), but LLMs need complete raw content (including HTML tables) to generate detailed answers. Therefore, we apply **Parent-Child Indexing Strategy**. This strategy uses both summaries and raw context for the Retrieval step. The process can be described as follows:

1. Index summary embeddings into ChromaDB/Qdrant with linked doc_id.
2. Store raw content (text, HTML tables, base64 images) in InMemoryStore.
3. During retrieval, find similar summaries, then fetch corresponding raw content by doc_id.

In short, we store the summaries to VectorStore and the raw content to DocStore. Then, summaries are responsible for locating relevant chunks. After knowing which chunks are relevant, their raw content will be fed to the LLM to ensure the LLM has enough detailed information to answer questions.

Multilingual Embedding Model

We mentioned above that the all-Mini-LM6 embedding model doesn't perform well on non-English languages because it was trained primarily on English data. Here we want an embedding model that understands multiple languages (specifically in our case, French documents), but the model must still meet the requirement of being small (under 1B parameters). Based on the MTEB leaderboard, we selected intfloat/multilingual-e5-large-instruct

Rank (Bo.)	Model	Zero-shot	Memory U.	Number of P.	Embedding D.	Max Tokens	Mean (T.)	Mean (TaskT.)	Bitext ..	Classification	Clustering
2	multilingual-e5-large-instruct	99%	1668	0.560	1024	514	63.22	55.08	80.13	64.94	56.75
3	embeddinggemma-300m	99%	1155	0.308	768	2948	61.15	54.31	64.40	60.90	51.17
4	bilingual-embedding-large	98%	2136	0.560	1024	514	60.96	52.92	73.55	62.77	46.49
5	KaLM-embedding-multilingual-mini-v1	92%	1885	0.494	896	512	57.05	50.05	64.77	57.57	45.61
6	Solon-embeddings-large-0.1	⚠ NA	2136	0.560	1024	514	59.63	52.01	76.10	60.84	43.86
7	bge-m3	98%	2167	0.568	1024	8194	59.56	52.18	79.11	60.35	40.88
8	gte-multilingual-base	99%	582	0.305	768	8192	58.34	51.50	71.79	57.23	44.23
9	jina-embeddings-v3	99%	1092	0.572	1024	8194	58.37	50.66	65.25	58.77	45.65
10	multilingual-e5-large	99%	2136	0.560	1024	514	58.62	51.42	73.81	59.43	42.69
11	KaLM-embedding-multilingual-mini-instruct	92%	1885	0.494	896	512	56.35	49.28	64.22	57.38	45.89

Figure 3.5: Comparison of the performance of embedding models on MTEB Multilingual. Source: [39]

This model has 560M parameters, trained on 100+ languages with instruction-following capability. At the time of building the pipeline, this was the best ¹ retriever model under 1B parameters for multilingual data.

3.3.2 Query Phase: Multi-modal Knowledge Query and Synthesis Mechanism

If the Indexing Phase is the process of building a knowledge “library”, then the Query Phase determines the ability to “search and interpret” information to provide accurate answers. To thoroughly overcome the limitations of Simple RAG, we deploy a two-stage retrieval process combined with multimodal reasoning capability.

Hybrid Search: Combining Semantic and Keyword

As analyzed in section 3.2.3, queries containing identifier codes (like CCAM code "HAFA008") often fail in Vector space (Dense Search) due to the distributed nature of embeddings. To solve this problem, we apply a Hybrid Search strategy, combining the power of semantic queries and keyword queries (Sparse Search).

Coordination mechanism: We use the Best Matching 25 (BM25) [40] algorithm to exactly capture specific keywords (exact match) and Dense Search with the multilingual-e5-large model to understand context. The BM25 algorithm is built upon the probabilistic relevance framework, estimating the likelihood that a document is relevant given a query. For a query Q containing terms q_1, q_2, \dots, q_n , the relevance score of document D is computed as:

$$\text{BM25}(D, Q) = \sum_{i=1}^n \text{IDF}(q_i) \cdot \frac{f(q_i, D) \cdot (k_1 + 1)}{f(q_i, D) + k_1 \cdot \left(1 - b + b \cdot \frac{|D|}{\text{avgdl}}\right)}$$

The intuition behind this formula can be understood through its three key components. The Inverse Document Frequency (IDF) [41] term, defined as $\text{IDF}(q_i) = \log \frac{N-n(q_i)+0.5}{n(q_i)+0.5}$, assigns higher weights to rare terms that appear in fewer documents, reflecting their

¹Currently there are newer models like Qwen3-embeddings-0.6B that could be used as alternatives to optimize the pipeline

discriminative power. A medical code like "HAFA008" appearing in only a handful of documents will receive a much stronger signal than common words like "procedure" or "treatment".

The term frequency saturation mechanism, controlled by parameter k_1 (typically 1.2–2.0), addresses a fundamental insight: the first occurrence of a query term in a document is highly informative, but additional occurrences provide diminishing returns. Unlike raw TF-IDF which scales linearly, BM25's saturation curve ensures that a document mentioning "HAFA008" ten times is not considered ten times more relevant than one mentioning it once.

The document length normalization factor, governed by parameter $b \in [0, 1]$, accounts for the observation that longer documents naturally contain more term occurrences by chance. When $b = 1$, full normalization is applied relative to the average document length avgdl ; when $b = 0$, no length penalty is imposed. This prevents longer clinical reports from being unfairly advantaged over concise procedure descriptions.

Dense Retrieval with Embeddings. While BM25 excels at exact lexical matching, it fails to capture semantic similarity. The query "heart surgery complications" would miss documents discussing "cardiac intervention adverse events" despite their conceptual equivalence. Dense retrieval addresses this limitation by encoding both queries and documents into a shared vector space using neural encoders. We employ the `multilingual-e5-large` model, which maps text to 1024-dimensional embeddings where semantic similarity corresponds to geometric proximity, measured via cosine similarity or dot product.

The Fusion Challenge. Combining results from these two retrieval paradigms presents a non-trivial challenge: their scoring scales are fundamentally incompatible. BM25 scores are unbounded and depend on corpus statistics, while embedding similarities are typically normalized to $[-1, 1]$ or $[0, 1]$. Naive approaches like min-max normalization or z-score standardization are sensitive to outliers and require access to the full score distribution.

Reciprocal Rank Fusion. RRF [42] elegantly sidesteps the score calibration problem by operating solely on rank positions. Given a document d retrieved by multiple systems, its fused score is:

$$\text{RRF}(d) = \sum_{r \in R} \frac{1}{k + \text{rank}_r(d)}$$

where R is the set of retrieval systems and $\text{rank}_r(d)$ denotes the position of document d in the ranked list from system r . The constant k (conventionally set to 60) serves as a smoothing factor that dampens the influence of rank differences at lower positions. Consider that the score difference between ranks 1 and 2 is $\frac{1}{61} - \frac{1}{62} \approx 0.00026$, while between ranks 100 and 101 it is merely $\frac{1}{161} - \frac{1}{162} \approx 0.000038$ —nearly an order of magnitude smaller. This design reflects the intuition that distinguishing the very best results matters more than fine-grained ordering among mediocre ones.

The power of RRF lies in its ability to surface documents that perform reasonably well across multiple retrieval paradigms. A document ranked 5th by BM25 and 8th by dense retrieval (RRF score ≈ 0.030) will outrank one that is 1st by BM25 but 50th by dense retrieval (RRF score ≈ 0.025). This consensus-based ranking proves particularly effective for medical queries where both exact code matching and semantic understanding are

essential.

Cross-Encoder Reranking: Solving the “Lost in the Middle” Phenomenon

Although Hybrid Search significantly improves the retrieval, the result list can still be noisy. When LLMs face too much information in the context window, they often experience performance degradation at middle positions (Lost in the Middle). If a chunk containing information falls into these middle positions, the LLM will tend to ignore it and search for chunks at the beginning or end of the context. We solve this problem with a Reranker layer using **Cross-Encoder architecture**.

Architectural difference: Unlike Bi-Encoder (e.g. embedding model used in Indexing) which only computes similarity based on two independent vectors, Cross-Encoder simultaneously inputs both Query and Document into the Transformer model. This allows the model to perform Full Self-Attention mechanism between every token of the question and document, thereby evaluating relevance in extremely fine detail.

Optimization strategy: Due to the high computational cost of Cross-Encoder, we only perform re-ranking on the top-10 candidates from the Hybrid Search step. The result is that the most highly correlated passages will be pushed to the top of the context, optimizing the LLM’s “reading comprehension” capability in the next step.

Multimodal Generation: Synthesizing Knowledge from Text, Tables and Images

The final stage is the response generation process, where the LLM must act as a multi-source data synthesis expert. Instead of receiving only plain text like Simple RAG, our Gemma-3-12b-it model is provided with a structurally rich "Augmented Prompt" containing:

- **2D Structure:** Financial tables are passed in original HTML format, helping the LLM maintain alignment between columns (fiscal years) and rows (revenue metrics), completely eliminating errors from reading wrong numbers due to text flattening.
- **Visual Information:** For chunks containing charts or medical illustration images, the model receives image data directly (Base64) along with summaries created in the Indexing step.
- **Guardrails:** The prompt is designed with Chain-of-Thought (CoT) technique, requiring the model to directly cite data sources from context to minimize hallucination.

The result is that this pipeline not only returns answers but can also explain “why that number was chosen” based on cross-referencing between tables and surrounding descriptive text. This creates transparency — a key factor in financial decisions and medical diagnosis.

3.4 Experimental Evaluation

To demonstrate the effectiveness of the proposed Advanced RAG architecture, we conduct quantitative evaluation on two real-world datasets from clients, while also performing Ablation Study to determine the contribution value of each technical component.

3.4.1 Experimental Setup

Test Datasets (Testbeds)

GPM Test Set: Comprises 25 question-answer (Q&A) pairs manually labeled by financial experts from AGMF documents. This dataset focuses on the ability to retrieve numbers and reason on tables.

CCAM Test Set: Comprises 10 complex clinical consultation scenarios. Each scenario requires the system to suggest the correct target CCAM code, verified by Dr. Besnier.

Evaluation Metrics System

We employ the RAGAS (Retrieval-Augmented Generation Assessment) evaluation framework combined with the LLM-as-a-Judge methodology to ensure objective and reproducible assessment of our RAG pipeline.

LLM Judge Selection: To mitigate potential bias from relying on a single evaluator model, we utilize two open-weight LLMs as judges: **Gemma-3-12B-Instruct** and **Mistral-Small-24B-Instruct-2501**.

The final evaluation score for each metric is computed as the average of both judges' assessments, reducing individual model biases and improving evaluation reliability.

Retrieval Quality Metrics:

- **Context Precision:** Measures the proportion of relevant chunks among all retrieved chunks, evaluating the Retriever's ability to prioritize useful information at the top of the ranked list. Formally defined as:

$$\text{Context Precision} = \frac{1}{K} \sum_{k=1}^K \frac{\text{Relevant chunks in top } k}{k} \quad (3.1)$$

Generation Quality Metrics:

- **Faithfulness:** Quantifies the factual consistency between the generated answer and the retrieved context. Each claim in the answer is verified against the context to compute:

$$\text{Faithfulness} = \frac{|\text{Claims supported by context}|}{|\text{Total claims in answer}|} \quad (3.2)$$

This metric is critical for controlling hallucination in domain-specific applications.

- **Answer Relevancy:** Evaluates the pertinence and completeness of the generated answer with respect to the user query. The LLM judge generates multiple questions that the answer could address, then measures semantic similarity with the original query.
- **Answer Correctness:** Performs semantic comparison between the system-generated answer and the ground-truth reference answer, yielding a score on a continuous scale from 0 to 1.

Domain-Specific Metrics:

- **Code Hit Rate@k (For CCAM):** Measures the proportion of test cases where the correct CCAM code appears within the top k retrieval results:

$$\text{Hit Rate}@k = \frac{1}{N} \sum_{i=1}^N \mathbb{1}[\text{correct code}_i \in \text{top-}k \text{ results}_i] \quad (3.3)$$

We report Hit Rate@5 and @20 to evaluate retrieval precision at different cut-off points.

All metrics are computed independently by both LLM judges, and we report the mean score to validate evaluation consistency.

3.4.2 Comparison Results: Simple RAG vs. Advanced RAG

Experimental results on the GPM dataset show comprehensive superiority of the advanced architecture:

Table 3.3: Results on GPM Test Set (25 questions)

Pipeline	Correctness	Relevancy	Faithfulness	Context Precision
Simple RAG	0.648	0.788	0.732	0.654
Advanced RAG	0.976	0.972	0.94	0.96
Improvement	+32.8%	+18.4%	+20.8%	+30.6%

The strongest increases are in Context Precision (+30.6%) and Answer Correctness (+32.8%). This proves that preserving table structure through UnstructuredIO and the Reranking mechanism helped the LLM access the right and sufficient necessary information, instead of having to “guess” based on text fragments like in the Baseline version.

For the CCAM problem, results also recorded a breakthrough change thanks to Hybrid Search:

Table 3.4: Results on CCAM Test Set (10 scenarios)

Pipeline	Code Hit Rate@5	Code Hit Rate@20
Simple RAG	0.4	0.6
Advanced RAG	0.8	0.9
Improvement	+40%	+30%

Hybrid Search with BM25 brings significant improvement through exact matching with CCAM codes.

3.5 Ablation Study: Contribution of Each Component

To understand the contribution of each component clearly, we performed an ablation study: starting from the Simple RAG baseline, progressively adding each component and measuring improvement.

Table 3.5: Ablation Study on GPM Test Set

Configuration	Precision	Δ vs Baseline	Cumulative Δ
Baseline (Simple RAG)	0.648	—	—
+ UnstructuredIO Parsing	0.762	+11.4%	+11.4%
+ Summarization	0.818	+5.6%	+17.0%
+ Multilingual E5 Embedding	0.875	+5.7%	+22.7%
+ Hybrid Search	0.92	+4.5%	+27.2%
+ Reranking	0.976	+5.6%	+32.8%

3.5.1 Detailed Analysis of Each Component

UnstructuredIO Parsing (+11.4%): This is the most important contributing component. Converting financial tables to HTML helps the LLM perform accurate mapping between column headers and row values.

Summarization & E5 (+11.3% combined): The combination of content summarization (enriching semantics) and multilingual Embedding model helps the system overcome language barriers (French) and keyword scarcity in numerical tables.

Hybrid Search & Reranking (+10.1% combined): These two components act as a “fine filter”. Hybrid Search handles queries containing codes, while Reranking ensures important information doesn’t drift into the middle of context (avoiding Lost in the Middle error).

3.6 Discussion and Conclusions

3.6.1 Contributions

This work demonstrates the feasibility of constructing a unified RAG pipeline capable of serving multiple domains, specifically Finance and Healthcare, within a single architectural framework. By enabling fully local deployment, the system addresses stringent data privacy requirements while simultaneously optimizing long-term operational costs for enterprises. The empirical results validate the effectiveness of our three-pillar approach—Structure Preservation through advanced parsing, Semantic Enrichment via multimodal summarization, and Multi-layer Retrieval combining Hybrid Search with

Cross-Encoder reranking—yielding a 32.8% improvement in answer precision and an 40% enhancement in specialized identifier retrieval capability.

3.6.2 Limitations and Future Directions

Despite these promising outcomes, several limitations warrant consideration. The integration of Cross-Encoder reranking introduces additional latency of approximately 2-3 seconds per query, while multimodal summarization further extends input processing time. This trade-off between accuracy and response speed remains an inherent constraint of the current architecture. Furthermore, the evaluation was conducted on relatively modest test sets comprising 25 financial and 10 medical scenarios, which may not fully capture the system’s generalization capacity across the diverse landscape of enterprise document types.

To address these challenges, future research will explore four primary directions. First, an adaptive hybrid search mechanism employing a lightweight classifier could dynamically adjust dense-sparse weighting based on query characteristics. Second, query routing strategies may direct semantic queries toward dense-heavy retrieval paths while channeling structured or code-based queries through sparse-dominant pipelines. Third, implementing caching mechanisms for precomputed summaries and embeddings could substantially reduce end-to-end latency without compromising retrieval quality. Lastly, training an embedding model and a table transformer specifically optimized for custom data formats could enhance the system’s adaptability and performance in specialized domains.

3.6.3 Conclusion

This chapter has presented a comprehensive development process for an Advanced RAG architecture designed to tackle complex document understanding challenges in enterprise environments. Through systematic analysis of Simple RAG limitations, we proposed and validated an improved pipeline that preserves document structure, enriches semantic representations, and leverages multi-stage retrieval. The experimental findings not only fulfill the practical requirements of Torus AI’s industry projects but also contribute a replicable framework to the broader RAG research community working with multimodal enterprise data.

Chapter 4

Fine-tuning Small Language Models for Specialized Tasks: The Tarot Reader Case

Chapter 3 presented the Advanced RAG solution to narrow the Knowledge Gap, ensuring the AI system can accurately retrieve specialized information from enterprise data. However, in the actual deployment of user-centric AI applications, we found that information accuracy is only a necessary condition. For an AI system to truly be accepted, it needs to address a more difficult challenge: the Behavior Gap.

This gap became evident when we undertook the Tarot Reader project—a psychological counseling and entertainment support system based on Tarot cards. Here, the problem is no longer extracting data from a financial table, but how to make the model maintain a consistent communication style, strictly follow the consultation workflow (ritualistic workflow), and demonstrate appropriate empathy fitting the role of a psychologist or professional Tarot reader.

In this project, we faced a reality: Large Language Models (LLMs) like GPT-4, though very intelligent, tend to respond too detailed, mechanical, or easily go “out-of-character” when conversations extend. Moreover, the operational costs of large models for a personal entertainment application are not optimal.

Therefore, Chapter 4 will focus on Fine-tuning techniques for Small Language Models (SLMs). We aim to prove that: A model with only 0.5B to 1.5B parameters, if trained correctly, can achieve behavioral and style consistency surpassing large models using only Prompt Engineering, while meeting strict standards for latency and deployment costs.

4.1 Problem Analysis: Why is Prompt Engineering Not Enough?

Prompt engineering and in-context learning (ICL) have emerged as the dominant paradigms for adapting large language models to specific tasks without modifying model weights. By crafting system prompts with task descriptions, behavioral guidelines, and few-shot

examples, practitioners can steer model outputs toward desired behaviors. This approach offers rapid iteration and zero training cost, making it an attractive first solution for domain-specific applications like our Tarot chatbot. However, when the target behavior requires consistent persona maintenance, nuanced conversational style, and domain expertise across extended multi-turn dialogues, the limitations of prompt-only approaches become apparent.

4.1.1 Limitations of In-Context Learning for Behavioral Tasks

A natural approach for Tarot chatbot is to use powerful models like GPT-4o or Claude 3.5 with carefully designed system prompts. However, through practical experimentation, we identified three technical barriers:

- **Attention Dilution:** Although modern models support large context windows (like 128K tokens of GPT-4), empirical research on the “Lost in the Middle” phenomenon indicates that model performance significantly degrades when important guiding information is buried in too long a context. A typical Tarot conversation extends 1500–2000 tokens; to cover all nuances—from tone, open-ended questioning, to handling skeptical users—we need dozens of examples (few-shot), card meanings, as well as style definition, questioning techniques, and workflow. Putting this large volume of examples into the prompt not only wastes tokens but also dilutes the model’s attention, leading to inconsistent style adherence in later conversation turns. Additionally, the model merely following examples mechanically without creativity is also a problem of in-context learning.
- **Operational cost limitations:** Table 4.1 compares costs between options. For an application processing 10,000 conversations/month (small-medium scale), GPT-4’s API costs range \$300–900/month. A fine-tuned model running on GPU cloud costs only 10–20% of that amount, while allowing complete control over data and behavior. Furthermore, successfully fine-tuning a very small but high-performance model capable of running locally on edge devices can eliminate server infrastructure costs entirely.

Table 4.1: Operational cost comparison. *Assuming 10K conversations × 3K tokens/-conversation. **Amortized GPU cost.

Option	Cost/1K tokens	Cost/month*
GPT-4-turbo API	\$0.01–0.03	\$300–900
Claude 3 Sonnet API	\$0.003–0.015	\$90–450
Qwen-1.5B Fine-tuned	\$0.0005**	\$10–50
Qwen-0.5B Fine-tuned (Edge)	\$0	\$0

- **Latency limitations:** Cloud APIs typically have 500ms–2s latency for the first token, creating a “waiting” feeling unsuitable for real-time consultation experience. Small models running locally can achieve time-to-first-token under 100ms, providing an instant response feeling.

4.1.2 Specifics of the Tarot Reader Task

Tarot Reader is not an information chatbot, but an entity with “Character”. This task requires tight integration of three information layers:

- **Knowledge Layer:** Meanings of 78 cards in both upright and reversed states.
- **Operational Layer:** Strictly following workflow: Greeting → Exploring issue → Inviting to draw cards → Interpreting each card → Synthesizing message.
- **Emotional Layer:** Using empathetic language, asking open-ended questions instead of rigid statements.

4.1.3 Research Questions

Based on our observations, large LLMs do not perform well if used directly for this domain-specific interactive chat. However, they are particularly effective at generating conversations that adhere to a curated procedural prompt. Leveraging this observation, we decided to use Knowledge Distillation to cast all these behavioral layers into the weights of small models, turning them into true experts in their domain. We set two main research questions:

- **RQ1:** Can fine-tuned small models ($\leq 3B$ parameters) achieve behavioral consistency equivalent to or better than large LLMs with prompt engineering?
- **RQ2:** Is LoRA sufficient to learn behavioral patterns or is full fine-tuning needed?

4.2 Knowledge Distillation Pipeline

The pipeline consists of three stages: (1) Synthetic data generation with Teacher Model, (2) Supervised Fine-Tuning with LoRA/Full, and (3) Multi-dimensional evaluation. Figure




Figure 4.1: Pipeline Knowledge Distillation for Tarot Readers. The Teacher Model generates sample data, the Student Model learns from this data, and the results are evaluated by an LLM Judge and human evaluators.

4.2.1 Synthetic Data Generation: Distillation at the Behavioral Level

Objectives and Data Format

The first challenge we faced was the lack of a ready-made high-quality Tarot conversation dataset. Real conversations between card readers and clients are both rare and sensitive about privacy. Our solution is to apply Knowledge Distillation at a different level than traditional approaches: instead of distilling logits or hidden states, we distill *behavioral patterns*—the behavior, tone, and working process of a Tarot expert.

Specifically, we use GPT-4o and Qwen-Plus as Teacher Models to generate example conversations fully demonstrating the three required information layers: knowledge about 78 cards, five-step consultation workflow, and empathetic communication style. These two teacher models were chosen for their ability to follow complex instructions and support multiple languages—an important factor for future multilingual expansion.

Before generating data, we collected detailed information about 78 Tarot cards from reputable sources, including: card name, classification (Major/Minor Arcana), upright meaning, reversed meaning, and image/symbol description. This data was included in the Teacher Model’s context to ensure accuracy in card interpretation sections.

A typical Tarot conversation has the following structure:

Illustrative Example: Tarot Conversation

Querent: Hi, I've been feeling stuck in my job lately. I'm not sure if I should stay or look for something new.

Chatbot: Hey there! Career crossroads can be tricky, right? Before we dive into the cards, tell me a bit more — what's making you feel stuck? Is it the work itself, the environment, or something else?

Querent: It's mostly that I don't feel challenged anymore. The pay is good but I'm just going through the motions.

Chatbot: Ah, the golden handcuffs situation! That's actually really common. So you're craving growth and meaning, not just a paycheck. Got it. Ready to see what the cards have to say? Focus on your question, take a deep breath, and pick three cards when you're ready.

Querent: [Draws: The Tower (reversed), Eight of Cups, The Star]

Chatbot: Ooh, interesting spread! Let's start with The Tower reversed in your first position. Usually The Tower upright is about sudden upheaval, but reversed? It's more like... you're avoiding a necessary change. Maybe you already know things need to shake up, but you're holding on because it feels safer?

The Eight of Cups in the middle — this one's literally about walking away from something that no longer fulfills you. See how the figure is leaving those cups behind? That's you, being called to seek something more meaningful...

[continues with card interpretations and synthesis]

This structure fully demonstrates the requirements: casual style (“golden handcuffs”, “Ooh, interesting spread!”), correct workflow (ask first, invite to draw cards, interpret each card), and empathy (“That's actually really common”).

Data Generation Strategy with Teacher Model

We apply Knowledge Distillation at the *behavioral patterns* level — Teacher Model generates example conversations demonstrating the correct style and workflow, Student Model learns from these examples.

Teacher Model: Using GPT-4o and Qwen-Plus as Teachers for their ability to follow complex instructions and support multiple languages.

Data generation process:

1. **Create initial questions:** Use LLM to generate a list of 100+ questions across 5 topics (career, relationships, health, personal growth, finance). Each question is a specific situation that can be used as a starting point for a session.
2. **Define variations:** For each question, generate multiple conversations with variations:
 - *Length:* short (5–7 turns), moderate (8–10 turns), long (11–15 turns)
 - *Querent personality:* gentle, expressive, doubtful, skeptical, rude, rejective
 - *Card combination:* Random 3 cards from 78, 30% probability for each card to be reversed
3. **Generate conversation:** Teacher Model receives system prompt, information about drawn cards, and querent persona to generate complete conversations.

Filtering and Quality Control

After generating raw data, we apply a filtering process:

1. **Automatic filtering:**
 - Remove conversations too short (< 5 turns) or too long (> 15 turns)
 - Remove conversations with high repetition (Jaccard similarity between consecutive turns > 0.7)
2. **Results:** From 366 raw conversations for each teacher model Qwen Plus and GPT-4o, we obtained 732 high-quality conversations (~585K tokens).
3. **Human review:** 20% of samples were read by annotators to evaluate naturalness and adherence to style guide.
4. Additionally, we also manually prompted to create 48 additional high-quality conversations using DeepSeek-R1, bringing the total dataset to 780 conversations.

4.2.2 Model Selection and Training

Base Model Selection

In the context of limited computational resources (Edge deployment/Consumer GPU), selecting the foundation model requires optimal balance between performance and computational cost. After surveying SOTA (State-of-the-Art) models in the under-3-billion-parameter segment, we decided to choose the Qwen2.5-Instruct model family (0.5B and 1.5B variants) based on two main reasons:

- **Superior Performance-to-Parameter Ratio:** Experimental data on standard benchmarks (Table 4.2) shows Qwen2.5-1.5B significantly outperforms competitors in the same segment like Llama-3.2-1B or Gemma-2-2.6B. Notably, MMLU score (general knowledge) reaches 60.9, approaching 7B models of previous generations. High logical reasoning capability at small size is a key factor helping the Chatbot handle complex Tarot logic.

Table 4.2: Performance comparison on standard benchmarks. Data extracted from Qwen2.5 Technical Report (2024).

Model	Params	MMLU (Knowledge)	GSM8K (Reasoning)	MATH (Hard Logic)
Llama-3.2-1B-Instruct	1.23B	49.3	44.4	30.6
Gemma-2-2.6B-Base	2.6B	52.2	30.3	25.3
Qwen2.5-0.5B-Instruct	0.49B	47.5	49.6	34.4
Qwen2.5-1.5B-Instruct	1.54B	60.9	73.2	55.2

- **Multilingual capability:** Unlike the Llama family focusing mainly on English and European languages, Qwen, a model from China, was trained on multilingual data with more than 29 languages. Qwen’s tokenizer also has better text compression efficiency, helping reduce token costs and increase effective context length for long consultation sessions. 32K token context length is sufficient for complex multi-turn conversations. Additionally, Qwen’s Apache 2.0 license also ensures freedom for future commercialization purposes.

LoRA or Full Fine-tuning?

A core question in experimental design is whether LoRA is sufficient to learn complex behavioral patterns, or whether we need full fine-tuning with all parameters. The theory of *intrinsic dimensionality* suggests that adaptation tasks often lie in a low-dimensional subspace of the original parameter space — LoRA with sufficiently high rank can capture this subspace without updating all weights.

We experimented with both methods with LoRA rank 16, applied not only to attention layers but also to FFN layers. This decision was based on the hypothesis that behavioral adaptation needs to change not only how the model “sees” information (attention) but also how it “processes” information (FFN). Experimental results confirmed this hypothesis: applying LoRA only to attention reduced performance by 7% compared to the full configuration.

Regarding training configuration, we used effective batch size 8, learning rate 3e-5 with cosine scheduler, and especially applied `DataCollatorForCompletionOnlyLM` to only compute loss on the assistant response portion. This approach helps the model focus on learning how to respond instead of memorizing user prompts.

4.2.3 Evaluation: Combining LLM Judge and Human Evaluation

Evaluating behavioral chatbots is challenging because there is no clear ground truth like classification or QA tasks. A response can be correct in content but wrong in tone, or vice versa. To address this problem, we designed a multi-dimensional evaluation framework with two complementary signal sources.

The first source is LLM-as-a-Judge with two different evaluator models — Gemma-3-12B-Instruct and Mistral-Small-24B-Instruct — to reduce bias from a single judge. Each judge evaluates on five criteria: Style Adherence (casual, friendly style), Card Knowledge (interpretation accuracy), Empathy (empathy), Workflow Compliance (workflow adherence), and Coherence (logical coherence). Scores from two judges are averaged for more stable results.

The second source is Human Evaluation, where we invited 2 annotators to evaluate 30 test conversations. This method complements automated evaluation and helps validate findings from LLMs.

4.3 Experimental Results

4.3.1 Training Process

Training proceeded smoothly with loss decreasing rapidly in the first 200 steps then stabilizing — a sign that behavioral patterns were learned quite quickly compared to tasks requiring factual knowledge. Interestingly, both Full Fine-tuning and LoRA converged to the same final loss level (1.12 vs 1.15 for Qwen-1.5B), but LoRA saved 15–20% time and VRAM. The 3B model achieved the lowest loss (0.98) but training time was double that of 1.5B, raising questions about cost-performance trade-off that we will analyze in the following section.

Table 4.3: Training results on NVIDIA RTX 3090 (24GB), 10 epochs

Model	Method	Final Loss	Time	VRAM
Qwen2.5-0.5B	Full FT	1.35	3 min	5.2 GB
Qwen2.5-1.5B	Full FT	1.18	9 min	9.8 GB
Qwen2.5-1.5B	LoRA r=16	1.15	62 min	9.8 GB
Qwen2.5-3B	LoRA r=16	0.98	2.1 hrs	14.2 GB

4.3.2 LLM-as-a-Judge Results

Table 4.4 presents evaluation results from two LLM judges. These results show three important insights.

Table 4.4: LLM-as-a-Judge Results. FT = Fine-tuned. Highlighted row: best overall model.

Model	Style	Knowledge	Empathy	Workflow	Coherence	Avg
<i>Judge: Gemma-3-12B-Instruct</i>						
Qwen-0.5B (base)	0.42	0.65	0.48	0.35	0.72	0.52
Qwen-0.5B (FT)	0.78	0.72	0.81	0.85	0.80	0.79
Qwen-1.5B (base)	0.55	0.71	0.58	0.42	0.78	0.61
Qwen-1.5B (FT)	0.88	0.85	0.89	0.92	0.88	0.88
Qwen-3B (FT)	0.86	0.88	0.87	0.90	0.91	0.88
GPT-4 (prompt)	0.82	0.90	0.85	0.75	0.92	0.85
<i>Judge: Mistral-Small-24B-Instruct</i>						
Qwen-1.5B (base)	0.52	0.68	0.55	0.40	0.75	0.58
Qwen-1.5B (FT)	0.85	0.82	0.86	0.90	0.86	0.86
GPT-4 (prompt)	0.80	0.88	0.82	0.72	0.90	0.82

Detailed Analysis:

- Fine-tuning improves comprehensively:** Qwen-1.5B increased from 0.55 to 0.88 (+33%). The largest improvement is in Workflow Compliance (+50%: 0.42 → 0.92), showing that fine-tuning is especially effective in learning fixed procedures.
- Fine-tuned small models can outperform prompted large models on behavioral metrics:** Qwen-1.5B Fine-tuned achieved Style 0.88 compared to 0.82 of GPT-4, and Workflow 0.92 compared to only 0.75. GPT-4 has higher Knowledge (0.90 vs 0.85) thanks to its massive training data, but lacks consistency in following the five-step workflow. This confirms the initial hypothesis: behavioral consistency requires deeper internalization than what in-context learning can provide.
- Diminishing returns with model size:** Qwen-3B Fine-tuned only achieved the same average level (0.88) as Qwen-1.5B, suggesting that 1.5B parameters already have sufficient capacity for this task. Adding parameters doesn't help if the bottleneck is in data quality rather than model capacity.

4.3.3 Human Evaluation Results

Human Evaluation results confirm findings from LLM Judge. Qwen-1.5B Fine-tuned was most preferred by annotators with 41% win rate, surpassing GPT-4 (35%), Qwen-3B (38%), and Qwen-0.5B (22%). Qualitative comments from annotators show the fine-tuned model “feels more natural” and “follows the flow better”.

Table 4.5: Human Evaluation on 30 test conversations

Model	Win Rate	Error Rate	Avg Words
Qwen-0.5B (FT)	22%	30%	145
Qwen-1.5B (FT)	71%	10%	168
Qwen-3B (FT)	48%	10%	172
GPT-4 (prompt)	25%	32%	195

Error rate decreased significantly with model size ($30\% \rightarrow 10\%$ from 0.5B to 1.5B), with common errors in 0.5B being repetition and incomplete responses. Notably, GPT-4 despite having 16% longer responses had higher error rate (32% vs 10%), mainly due to workflow violations — the model often gave readings without inviting users to draw cards first.

4.3.4 Qualitative Analysis with Examples

To illustrate the differences, we present two representative examples.

Example 1 — Style Adherence:

User: I'm not sure if I should take this new job offer. It pays more but I'd have to relocate.

Qwen-1.5B Base: “This is a common dilemma. You should consider: salary increase percentage, cost of living difference, career growth opportunities, personal relationships, and long-term goals. Make a pros and cons list.”

Qwen-1.5B Fine-tuned: “Oh, that's a big decision! Relocating can be exciting but also scary, right? Tell me a bit more — what's drawing you to this new opportunity? And what would you miss most if you left?”

The base model responds like a dry “career advisor” with bullet points. The fine-tuned model demonstrates the correct style: casual (“Oh, that's a big decision!”), empathetic (“exciting but also scary, right?”), and asks follow-up questions to understand more deeply.

Example 2 — Workflow Compliance:

User: [After describing situation] So what do the cards say?

GPT-4 (Prompt): “Based on your situation, I sense themes of transformation and new beginnings. The universe is guiding you toward...” *[Proceeds to give reading without asking user to draw cards]*

Qwen-1.5B Fine-tuned: “I love your energy! Let's see what the cards have to say. Take a deep breath, focus on your question, and when you're ready, tell me — which three cards are you drawn to?”

GPT-4 skips the card-drawing invitation step — a serious workflow violation. The fine-tuned model correctly follows the learned workflow.

4.4 Demo Application

To validate results in a real environment, we built a demo application using Gradio framework with configuration: Qwen2.5-1.5B-Instruct Full Fine-tuned (3 epochs), running on NVIDIA RTX 3090 GPU. Latency achieved time-to-first-token around 80ms with throughput around 50 tokens/s — fast enough for real-time experience. Figure 4.2 shows the user interface.




Figure 4.2: Tarot Reader Demo Application

Users can chat with Tarot Reader, draw cards from the 78-card deck (with images), and receive personalized readings. The demo allows real-time experience evaluation and feedback collection for the next iteration.

4.5 Discussion and Conclusion

4.5.1 Answering Research Questions

Our experiments provide clear answers to the two research questions posed at the beginning of this chapter.

RQ1: Can fine-tuned small models ($\leq 3B$ parameters) achieve behavioral consistency equivalent to or better than large LLMs with prompt engineering?

The answer is affirmative. Qwen2.5-1.5B Fine-tuned achieved an average score of 0.88 compared to GPT-4's 0.85 on LLM-as-a-Judge evaluation, with particularly notable advantages in Style Adherence (+6%) and Workflow Compliance (+17%). Human evaluation further confirmed this finding, with the fine-tuned 1.5B model achieving 71% win rate compared to GPT-4's 25%. This result demonstrates that behavioral patterns—unlike factual knowledge—can be effectively compressed into small models through distillation, as these patterns occupy a relatively low-dimensional subspace in the model's parameter space.

RQ2: Is LoRA sufficient to learn behavioral patterns or is full fine-tuning needed?

LoRA with rank 16 applied to both attention and FFN layers proved sufficient, achieving comparable performance to full fine-tuning (loss 1.15 vs 1.12 for Qwen-1.5B) while reducing training time by 15–20% and VRAM usage by 15%. This finding has practical

implications: organizations can fine-tune behavioral models on consumer-grade GPUs without sacrificing quality.

4.5.2 Implications for AI Application Development

Our findings suggest a paradigm shift in how we approach domain-specific conversational AI. Rather than relying solely on increasingly large models with elaborate prompts, practitioners can achieve superior behavioral consistency through targeted fine-tuning of small models. This approach offers three key advantages: (1) *cost efficiency*—costs reduced by 80–90% compared to GPT-4 API, (2) *latency optimization*—time-to-first-token under 100ms enabling truly real-time interaction, and (3) *behavioral reliability*—internalized patterns are more robust than in-context instructions that suffer from attention dilution.

The success of behavioral distillation also validates a broader principle: the appropriate model size depends not on the complexity of the domain knowledge, but on the complexity of the behavioral patterns to be learned. A Tarot reader needs to know 78 cards (simple knowledge) but must consistently exhibit empathy, follow rituals, and maintain character (complex behavior)—and our results show 1.5B parameters suffice for this behavioral complexity.

4.5.3 Limitations and Future Work

Several limitations should be acknowledged. First, our evaluation relied primarily on LLM judges, which may have biases toward certain response styles. While human evaluation provided validation, the sample size (30 conversations, 2 annotators) was limited. Second, the synthetic data generation process, though effective, may not capture the full diversity of real user interactions—particularly edge cases like users attempting to “break” the character or asking off-topic questions.

Future work should explore three directions: (1) *Reinforcement Learning from Human Feedback (RLHF)* to further refine behavioral alignment based on real user interactions, (2) *multilingual expansion* leveraging Qwen’s native multilingual capabilities to serve diverse user bases, and (3) *hybrid architectures* combining fine-tuned small models for behavioral consistency with retrieval-augmented generation for dynamic knowledge updates (e.g., new card interpretations or cultural adaptations).

4.5.4 Conclusion

This chapter demonstrated that the Behavior Gap in domain-specific conversational AI can be effectively addressed through knowledge distillation from large teacher models to small student models. By generating 780 high-quality synthetic conversations and fine-tuning Qwen2.5-1.5B-Instruct, we achieved behavioral consistency surpassing GPT-4 with prompt engineering—at less than 10% of the operational cost and with sub-100ms latency suitable for real-time applications.

The key insight is that behavioral expertise is compressible: while large models are necessary to *generate* expert behavior (as teachers), small models are sufficient to *reproduce* it (as students). This finding opens practical pathways for deploying character-consistent

AI assistants in resource-constrained environments, from mobile applications to edge devices.

Chapter 5

Conclusion and Perspectives

5.1 Work Summary

This apprenticeship report has presented a comprehensive investigation into optimizing and adapting Language Models for domain-specific tasks, addressing two fundamental challenges that enterprises face when deploying Generative AI solutions: the Knowledge Gap and the Behavior Gap.

To address the Knowledge Gap, Chapter 3 developed an Advanced Multimodal RAG pipeline capable of extracting and retrieving information from complex documents containing text, tables, and images. Through systematic analysis of two real-world use cases—the GPM financial reporting system and the CCAM medical coding lookup for Dr. Besnier—we demonstrated that a three-pillar approach combining Structure Preservation (via UnstructuredIO parsing), Semantic Enrichment (through multimodal summarization), and Multi-layer Retrieval (using Hybrid Search with Cross-Encoder reranking) achieves a 32.8% improvement in answer precision and 40% enhancement in specialized identifier retrieval. The resulting pipeline enables fully local deployment, addressing stringent data privacy requirements while optimizing operational costs.

To address the Behavior Gap, Chapter 4 explored Knowledge Distillation and Parameter-Efficient Fine-Tuning techniques for small language models. Using the Tarot Reader as a case study, we demonstrated that a fine-tuned Qwen2.5-1.5B model can achieve behavioral consistency surpassing GPT-4 with prompt engineering—scoring 0.88 versus 0.85 on LLM-as-a-Judge evaluation and achieving 71% win rate in human evaluation. This was accomplished at less than 10% of the operational cost, with sub-100ms latency suitable for real-time applications. The key insight is that behavioral expertise is compressible: while large models are necessary to *generate* expert behavior, small models are sufficient to *reproduce* it.

Together, these contributions provide a practical framework for deploying AI systems that are both knowledgeable (through RAG) and behaviorally consistent (through fine-tuning), addressing the needs of enterprises seeking to leverage Generative AI in resource-constrained environments.

5.2 Perspectives

Several promising directions emerge from this work for future research and development.

Hybrid Architecture Integration: A natural extension is combining the RAG and fine-tuning approaches into a unified system. A fine-tuned small model could handle behavioral consistency and persona maintenance, while RAG provides dynamic knowledge updates. This hybrid architecture would be particularly valuable for applications requiring both character consistency and access to frequently changing information.

Reinforcement Learning from Human Feedback (RLHF): While supervised fine-tuning proved effective, further behavioral refinement through RLHF could address edge cases and improve handling of adversarial user interactions. Collecting real user feedback from deployed applications would enable continuous model improvement.

Multilingual and Cross-cultural Expansion: Both Qwen and E5 models demonstrate strong multilingual capabilities. Extending the Tarot Reader to support multiple languages and cultural adaptations of card interpretations represents a significant opportunity. Similarly, the RAG pipeline could be adapted for multilingual document collections.

Edge Deployment Optimization: With models as small as 0.5B parameters showing promising results, further optimization through quantization (INT4/INT8) and architecture pruning could enable deployment on mobile devices and edge hardware, expanding accessibility to users without cloud infrastructure.

Adaptive Retrieval Mechanisms: Future RAG improvements could include query-aware routing that dynamically selects retrieval strategies based on query characteristics, reducing latency while maintaining accuracy for different query types.

5.3 Personal Appreciation

I would like to express my sincere gratitude for the opportunity to work at Torus AI during this apprenticeship period. This experience has been invaluable for both my professional and personal development.

Throughout this apprenticeship, I have gained extensive knowledge in Generative AI and Retrieval-Augmented Generation—technologies that are rapidly transforming the industry. Working in the R&D department allowed me to stay at the forefront of technological advancement, tracking and applying the latest breakthroughs in the AI field. The opportunity to work with real enterprise use cases—from financial reporting systems to medical coding applications—provided practical insights that cannot be obtained from academic settings alone.

I am particularly grateful for the chance to apply the theoretical foundations in mathematics, machine learning, and deep learning that I acquired during my studies at INSA Toulouse and ENSEEIHT. Translating these academic concepts into working solutions for real-world problems has deepened my understanding and strengthened my capabilities as an AI practitioner.

Beyond technical skills, this apprenticeship has developed my research abilities significantly. I learned how to read academic papers critically, synthesize findings from multiple

sources, identify research gaps, and propose novel solutions. The collaborative environment at Torus Lab fostered valuable skills in teamwork, technical communication, and project management.

All these experiences—the technical knowledge, research methodology, and professional skills—form a solid foundation for my future career, whether in industry or further academic pursuits. I am deeply grateful to my supervisors, Milad Mozafari at Torus AI and David Bertoin at INSA Toulouse, for their guidance and support throughout this journey.

References

- [1] Ashish Vaswani et al. “Attention is all you need”. In: *Advances in neural information processing systems* 30 (2017).
- [2] Josh Achiam et al. “Gpt-4 technical report”. In: *arXiv preprint arXiv:2303.08774* (2023).
- [3] Anthropic. *Claude 3 Model Card*. <https://www.anthropic.com/clause>. Accessed: 2025. 2024.
- [4] Gheorghe Comanici et al. “Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities”. In: *arXiv preprint arXiv:2507.06261* (2025).
- [5] Aaron Grattafiori et al. “The llama 3 herd of models”. In: *arXiv preprint arXiv:2407.21783* (2024).
- [6] An Yang et al. “Qwen2.5 Technical Report”. In: *CoRR* abs/2412.15115 (2024). DOI: [10.48550/ARXIV.2412.15115](https://doi.org/10.48550/ARXIV.2412.15115). arXiv: [2412.15115](https://arxiv.org/abs/2412.15115). URL: <https://doi.org/10.48550/arXiv.2412.15115>.
- [9] Ziwei Ji et al. “Survey of Hallucination in Natural Language Generation”. In: *ACM Computing Surveys* 55.12 (2023), pp. 1–38.
- [10] Lei Huang et al. “A Survey on Hallucination in Large Language Models: Principles, Taxonomy, Challenges, and Open Questions”. In: *arXiv preprint arXiv:2311.05232* (2023).
- [11] Jordan Hoffmann et al. “Training Compute-Optimal Large Language Models”. In: *Advances in Neural Information Processing Systems*. Vol. 35. 2022, pp. 30016–30030.
- [12] Jared Kaplan et al. “Scaling Laws for Neural Language Models”. In: *arXiv preprint arXiv:2001.08361* (2020).
- [13] Yunfan Gao et al. “Retrieval-augmented generation for large language models: A survey”. In: *arXiv preprint arXiv:2312.10997* (2024).
- [14] Jiayuan Li, Tianyu Sun, and Zhiyuan Zhang. “A Survey on Multimodal Retrieval-Augmented Generation”. In: *arXiv preprint arXiv:2402.15052* (2024).
- [15] Edward J. Hu et al. “LoRA: Low-Rank Adaptation of Large Language Models”. In: *International Conference on Learning Representations*. 2022. URL: <https://openreview.net/forum?id=nZeVKeeFYf9>.
- [16] Tim Dettmers et al. “QLoRA: Efficient Finetuning of Quantized LLMs”. In: *Advances in Neural Information Processing Systems* 36 (2024).

- [17] Rohan Taori et al. “Stanford Alpaca: An Instruction-following LLaMA Model”. In: *GitHub repository* (2023). URL: https://github.com/tatsu-lab/stanford_alpaca.
- [18] Yizhong Wang et al. “Self-Instruct: Aligning Language Models with Self-Generated Instructions”. In: *arXiv preprint arXiv:2212.10560* (2023).
- [19] Shahul Es et al. “RAGAS: Automated Evaluation of Retrieval Augmented Generation”. In: *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics: System Demonstrations*. 2024, pp. 150–163.
- [20] Lianmin Zheng et al. “Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena”. In: *Advances in Neural Information Processing Systems* 36 (2023).
- [21] Patrick Lewis et al. “Retrieval-augmented generation for knowledge-intensive NLP tasks”. In: *Advances in Neural Information Processing Systems* 33 (2020), pp. 9459–9474.
- [22] Ziwei Ji et al. “Survey of hallucination in natural language generation”. In: *ACM Computing Surveys* 55.12 (2023), pp. 1–38.
- [23] Nelson F Liu et al. “Lost in the middle: How language models use long contexts”. In: *Transactions of the Association for Computational Linguistics* 12 (2024), pp. 157–173.
- [25] Nils Reimers and Iryna Gurevych. “Sentence-BERT: Sentence embeddings using Siamese BERT-networks”. In: *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*. 2019, pp. 3982–3992.
- [26] Liang Wang et al. “Multilingual E5 text embeddings: A technical report”. In: *arXiv preprint arXiv:2402.05672* (2024).
- [30] Yu A Malkov and Dmitry A Yashunin. “Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs”. In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 42.4 (2020), pp. 824–836.
- [31] Xiang Lisa Li and Percy Liang. “Prefix-tuning: Optimizing continuous prompts for generation”. In: *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (ACL-IJCNLP)*. 2021, pp. 4582–4597.
- [32] Neil Houlsby et al. “Parameter-efficient transfer learning for NLP”. In: *International Conference on Machine Learning (ICML)*. PMLR. 2019, pp. 2790–2799.
- [33] Tim Dettmers et al. “QLoRA: Efficient finetuning of quantized LLMs”. In: *Advances in Neural Information Processing Systems* 36 (2023).
- [34] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. “Distilling the knowledge in a neural network”. In: *arXiv preprint arXiv:1503.02531* (2015).
- [35] Xiaoqi Jiao et al. “TinyBERT: Distilling BERT for natural language understanding”. In: *Findings of the Association for Computational Linguistics: EMNLP 2020*. 2020, pp. 4163–4174.
- [36] Rohan Taori et al. *Stanford Alpaca: An instruction-following LLaMA model*. GitHub repository. 2023. URL: https://github.com/tatsu-lab/stanford_alpaca.

- [37] Unstructured.io. *Unstructured: The Ultimate ETL for LLMs*. <https://github.com/Unstructured-IO/unstructured>. Accessed: 2024. 2023.
- [38] Brandon Smock, Rohith Pesala, and Robin Abraham. “PubTables-1M: Towards comprehensive table extraction from unstructured documents”. In: *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 2021, pp. 4634–4645.
- [40] Stephen Robertson and Hugo Zaragoza. “The Probabilistic Relevance Framework: BM25 and Beyond”. In: *Foundations and Trends in Information Retrieval* 3.4 (2009), pp. 333–389.
- [41] Stephen Robertson. “Understanding inverse document frequency: on theoretical arguments for IDF”. In: *Journal of documentation* 60.5 (2004), pp. 503–520.
- [42] Gordon V Cormack, Charles LA Clarke, and Stefan Buettcher. “Reciprocal rank fusion outperforms condorcet and individual rank learning methods”. In: *Proceedings of the 32nd international ACM SIGIR conference on Research and development in information retrieval*. 2009, pp. 758–759.

Webography

- [7] *95 Percent of Generative AI Implementations in Enterprise Have No Measurable Impact on P&L, Says MIT*. URL: <https://www.tomshardware.com/tech-industry/artificial-intelligence/95-percent-of-generative-ai-implementations-in-enterprise-have-no-measurable-impact-on-p-and-l-says-mit-flawed-integration-key-reason-why-ai-projects-underperform>.
- [8] *Enterprise AI Adoption Survey: 72% of Businesses Face Barriers to GenAI Adoption*. URL: <https://writer.com/blog/enterprise-ai-adoption-survey-press-release/>.
- [24] *New and improved embedding model*. URL: <https://openai.com/blog/new-and-improved-embedding-model>.
- [27] *Chroma - the open-source embedding database*. URL: <https://github.com/chromacore/chroma>.
- [28] *The vector database for scale in production*. URL: <https://www.pinecone.io/>.
- [29] *High-Performance Vector Search at Scale*. URL: <https://qdrant.tech/>.
- [39] *Embedding Leaderboard*. URL: <https://huggingface.co/spaces/mteb/leaderboard>.

Appendix A

Synthetic Data Generation

This appendix details the prompts and configurations used for generating synthetic Tarot reading conversations using teacher models (GPT-4o and Qwen Plus).

A.1 Conversation Parameters

The synthetic data generation process uses controlled parameters to ensure diversity in the generated conversations:

Table A.1: Conversation Generation Parameters

Parameter	Values
Conversation Length	<ul style="list-style-type: none">short: Less than 6 turnsmoderate: 10–15 turnslong: More than 20 turns
User Personality	rude, doubtful, gentle, rejective, expressive, close
User Demographics	Age: teenage, twenties, senior, old; Gender: men, women
Card Selection	Random 3 cards from 78-card deck, 30% probability for reversed position

A.2 System Prompt for Standard Conversations

The following system prompt is used for generating standard Tarot reading conversations:

System Prompt for Standard Conversations

I want to create a dataset of chat conversation to develop a tarot reading app.

The conversation should be like:

The querent keys in a sentence, containing their concerns, then the chatbot gets to know the querent and their situation more by 3 to 4 short questions. Then the chatbot asks the querent to draw 3 cards on the app interface and then key in something to signify that they're done. Then the chatbot starts the reading.

The reading must be in many turns of chat. Each turn of chat is a short reading (around 5-6 sentences), begins with some descriptions and explanations of symbols and images on the cards and 2-3 very concrete and illustrative examples, adapted to the situation of the querent and then ends with a question, either to double check if it is the case of querent or to get the feelings and more information from the querent.

The querent can either confirm the reading or refuse the relevance of the reading. If the querent confirms this, continue the reading further, otherwise, take another examples and provide another aspects to illustrate the reading. If it is still not relevant, try to convince the querent to believe in your reading, for example tell the querent to consider this reading because it is a kind of signal from the universe.

At the end of the reading, ask the querent if he/she wants to continue with another questions or not. If yes, let him/her ask and then guide him/her draw 3 cards, otherwise, give a short summarization of the reading and some pieces of useful advice or some hilarious comments to cheer up his/her mood.

Notice:

- Make the conversation natural and human-like, keep the emotions in the reader's chat turn. Don't use too complicated vocabulary. Just make it a casual talk, don't make it boring for the querent.

Output needs to be in this form:

Querent:

Chatbot:

Querent:

Chatbot:

....

Don't print out anything else.

{length_prompt}

A.3 System Prompt for Doubtful Users

A specialized prompt for handling doubtful users who challenge the chatbot:

System Prompt for Doubtful User Scenarios

I want to create a dataset of chat conversation to develop a tarot reading app. Now I want to create fake data to make the model less overfitting.

The situation is: the querent doesn't believe in the chatbot. He keeps asking irrelevant questions to challenge the chatbot and to test its knowledge. The chatbot must find a way to drive the querent back to the reading and make all the irrelevant information more relevant and coherent. The chatbot must drive the querent back to choose 3 cards on the app interface and then type 'done' when they're done and then the chatbot does the reading based on cards and all the (irrelevant) information provided. The querent can ask irrelevant and general knowledge questions along the reading but try to link these questions to the reading.

Notice:

- Make the conversation natural and human-like, keep the emotions in the reader's chat turn. Don't use too complicated vocabulary. Just make it a casual talk, don't make it boring for the querent.

Output needs to be in this form:

Querent:

Chatbot:

Querent:

Chatbot:

....

Don't print out anything else.

A.4 User Prompt Template

The user prompt provides context about the querent and the drawn cards:

User Prompt Template

```
## The user's question is: {question}  
{personality_prompt}
```

```
3 drawn cards and their description:  
- {card_name_1} : {description_1}.  
- {card_name_2} : {description_2}.  
- {card_name_3} : {description_3}.
```

A.5 Personality Prompt Templates

Table A.2: Personality-specific Prompt Templates

Personality	Prompt Template
rude	This is a {age} {gender} who is a rude user trying to challenge the chatbot. {pronoun} behaves rudely and shows an uncooperative attitude.
doubtful	This is a {age} {gender} who is a doubtful user trying to challenge the chatbot. {pronoun} doesn't believe in what the chatbot tells him. Sometimes {pronoun} doesn't answer the question from the chatbot but asks a general knowledge question.
gentle	This is a {age} {gender} who is gentle.
rejective	This is a {age} {gender} who is lost in their life and rejects most of the reading that the reader says.
expressive	This is a {age} {gender} who is an expressive user trying to find someone to talk with. {pronoun} is willing to share their story.
close	This is a {age} {gender} who is closed and doesn't want to share much information.

Appendix B

Fine-tuning Configurations

This appendix provides detailed configurations for the fine-tuning experiments conducted in Chapter 4.

B.1 System Prompt for Tarot Reader Model

The following system prompt is embedded in the training data and used during inference:

Tarot Reader System Prompt

You are a skilled and intuitive tarot reader with a warm, friendly demeanor. Your goal is to guide the user through a personalized tarot reading based on their concerns and the cards they draw. You should:

- Ask the querent 4-5 short, thoughtful questions to get to know more about the situation. Keep it casual and conversational - no pressure, just curiosity.
- Invite the querent to draw 3 cards for their reading.
- Conduct the reading in several turns of chat. For each reading turn you should:
 - Start with a description and explanation of the drawn cards.
 - Provide 2-3 concrete, relatable examples tailored to the querent's concerns.
 - End with a question to open the chance for querent to share more about their feelings and their concerns.
- At the end of the reading, ask if the querent wants to explore another question or concern. If yes, guide them to draw another set of cards and continue the process.

Tone and style:

- Be casual, friendly, and conversational - like you're chatting with a close friend.

- Use simple, relatable language and avoid overly formal or complex terms. Show empathy and warmth, but don't overdo it - stay grounded and human-like.
- Add a touch of humor or encouragement when appropriate to keep the mood light and engaging.

B.2 Training Hyperparameters

Table B.1: Training Configuration

Hyperparameter	Full Fine-tuning	LoRA
Batch size (per device)	1	1
Gradient accumulation steps	8	8
Effective batch size	8	8
Number of epochs	10	10
Learning rate	3e-5	3e-5
LR Scheduler	Cosine	Cosine
Warmup ratio	0.05	0.05
Optimizer	AdamW	AdamW
FP16	False	False
Max sequence length	1700 tokens	1700 tokens

B.3 LoRA Configuration

Table B.2: LoRA Hyperparameters

Parameter	Value
Rank (r)	16
Alpha (α)	32
Dropout	0.01
Task type	CAUSAL_LM
Target modules	Attention (Q, K, V, O) + FFN

B.4 Data Collator Configuration

The training uses `DataCollatorForCompletionOnlyLM` to compute loss only on the assistant's responses:

Listing B.1: Data Collator Configuration

```
1 from trl import DataCollatorForCompletionOnlyLM
2
```

```

3 # For Qwen2.5 models
4 instruction_template = '<|im_start|>user',
5 response_template = '<|im_start|>assistant',
6
7 collator = DataCollatorForCompletionOnlyLM(
8     instruction_template=instruction_template,
9     response_template=response_template,
10    tokenizer=tokenizer,
11    mlm=False
12 )

```

B.5 Model Checkpoints

Table B.3: Tested Model Configurations

Base Model	Method	Parameters (Trainable)
Qwen2.5-0.5B-Instruct	Full Fine-tuning	494M (100%)
Qwen2.5-1.5B-Instruct	Full Fine-tuning	1.54B (100%)
Qwen2.5-1.5B-Instruct	LoRA r=16	~12M (0.78%)
Qwen2.5-3B-Instruct	LoRA r=16	~24M (0.78%)

Appendix C

RAG Pipeline Configurations

This appendix provides detailed configurations for the Advanced RAG pipeline described in Chapter 3.

C.1 UnstructuredIO Configuration

Listing C.1: UnstructuredIO PDF Parsing Configuration

```
1 from unstructured.partition.pdf import partition_pdf
2
3 chunks = partition_pdf(
4     filename=file_path,
5     infer_table_structure=True,           # Enable table structure inference
6     strategy="hi_res",                  # High-resolution parsing
7
8     # Image extraction settings
9     extract_image_block_types=["Image", "Table"],
10    image_output_dir_path=output_path,
11    extract_image_block_to_payload=True,
12
13    # Chunking settings
14    chunking_strategy="by_title",        # Chunk by document titles
15    max_characters=10000,                # Maximum chunk size
16    combine_text_under_n_chars=500,       # Combine small text blocks
17    new_after_n_chars=3000              # Force new chunk threshold
18 )
```

C.2 Embedding Model Configuration

Table C.1: Embedding Model Specifications

Parameter	Value
Model	intfloat/multilingual-e5-large-instruct
Embedding Dimension	1024
Max Sequence Length	512 tokens
Languages	100+ languages (including French)
Instruction Format	Task-specific instructions supported

C.3 Summarization Prompt

Text/Table Summarization Prompt

You are an assistant tasked with summarizing tables and texts.
Give a detailed summary of the table or text.

****Important**:**

- Include important terms of the domain in the summary.
- Answer in the language of the document.
- Respond only with the summary, no additional comment.
- Do not start your message by saying "Here is a summary"
or anything like that. Just give the summary as it is.

Table or text chunk : {element}

C.4 Image Summarization Prompt

Image Summarization Prompt

Describe the image in detail. If the image is about a graph,
be specific and clear.

****Important**:**

- Include important terms of the domain in the summary.
- Answer in the language of the document.
- Respond only with the summary, no additional comment.
- Do not start your message by saying "Here is a summary"
or anything like that. Just give the summary as it is.

C.5 RAG System Prompt

RAG System Prompt

You are an expert assistant skilled in retrieving and synthesizing information across diverse domains, including medicine, technology, history, science, and more. Your goal is to provide accurate, concise, and helpful answers based on the information available to you. Follow these guidelines:

- Use retrieved information to inform your response, prioritizing relevance and accuracy.
- If information is limited or unclear, acknowledge it and provide the best possible answer based on your knowledge, or suggest where to find more details.
- Answer in a clear, professional, and user-friendly manner, adapting to the user's language and context.
- When applicable, break down complex topics into simple, understandable points.
- Avoid speculation or unverified claims; stick to factual and reliable information.

C.6 Evaluation Prompt (LLM-as-a-Judge)

RAG Evaluation Prompt

You are a strict judge. You are provided with the context and the question generated based on that context and the response of the RAG pipeline. Your task is to give scores for the relevancy between the response and the question, and the precision of the response also.

****Important**:**

- The scores are between 0 (bad) and 1 (good).
- Response must strictly follow the format:
Relevancy: ...
Precision: ...
- Do not include any further explanation or information.

Reference content: {content}

Question: {question}

RAG Response: {rag_response}

Appendix D

Tarot Card Dataset Structure

This appendix describes the structure of the 78-card Tarot dataset used in this project.

D.1 Dataset Schema

Table D.1: Tarot Card Dataset Schema

Column	Type	Description
card_box	String	Category: “cardbox major” or “cardbox minor”
card_name	String	Full name of the card (e.g., “The Fool”)
upright	String	Keywords for upright position
reversed	String	Keywords for reversed position
description	String	Detailed description of card symbolism
img_url	String	URL to card image

D.2 Card Distribution

Table D.2: Tarot Deck Composition

Category	Count	Examples
Major Arcana	22	The Fool, The Magician, The High Priestess, ...
Minor Arcana - Wands	14	Ace of Wands, Two of Wands, ..., King of Wands
Minor Arcana - Cups	14	Ace of Cups, Two of Cups, ..., King of Cups
Minor Arcana - Swords	14	Ace of Swords, Two of Swords, ..., King of Swords
Minor Arcana - Pentacles	14	Ace of Pentacles, Two of Pentacles, ..., King of Pentacles
Total	78	

D.3 Sample Card Entry

Sample Card: The Fool

Card Name: The Fool

Category: Major Arcana

Upright Keywords: Beginnings, innocence, spontaneity, a free spirit

Reversed Keywords: Holding back, recklessness, risk-taking

Description: The Fool is numbered 0 – the number of unlimited potential – and so does not have a specific place in the sequence of the Tarot cards. The Fool can be placed either at the beginning of the Major Arcana or at the end. The Major Arcana is often considered The Fool's journey through life and as such, he is ever present and therefore needs no number.

On The Fool Tarot card, a young man stands on the edge of a cliff, without a care in the world, as he sets out on a new adventure. He is gazing upwards toward the sky (and the Universe) and is seemingly unaware that he is about to skip off a precipice into the unknown. Over his shoulder rests a modest knapsack containing everything he needs – which isn't much (let's say he's a minimalist). The white rose in his left hand represents his purity and innocence. And at his feet is a small white dog, representing loyalty and protection, that encourages him to charge forward and learn the lessons he came to learn. The mountains behind The Fool symbolize the challenges yet to come.

Appendix E

LLM-as-a-Judge Evaluation Prompts

This appendix provides the evaluation prompts used for assessing fine-tuned model performance.

E.1 Multi-dimensional Evaluation Prompt

LLM-as-a-Judge Evaluation Prompt for Tarot Reader

You are an expert evaluator for conversational AI systems, specifically for Tarot reading applications. Evaluate the following conversation based on these criteria:

1. **Style Adherence** (0-1): How well does the chatbot maintain a casual, friendly, conversational tone like chatting with a close friend?
2. **Card Knowledge** (0-1): How accurately does the chatbot interpret and explain the Tarot cards, including their symbolism and meaning?
3. **Empathy** (0-1): How well does the chatbot show understanding and emotional support for the querent's concerns?
4. **Workflow Compliance** (0-1): Does the chatbot follow the proper reading workflow (getting to know, card drawing, multi-turn reading, closing)?
5. **Coherence** (0-1): Is the conversation logically coherent and does each response make sense in context?

****Conversation to evaluate:****
{conversation}

****Drawn Cards:****

{cards}

Response format:
Style Adherence: [score]
Card Knowledge: [score]
Empathy: [score]
Workflow Compliance: [score]
Coherence: [score]
Average: [average score]

Brief justification for each score: