
Shibboleth: Probe-and-Replay Model-Response Watermarking for Diffusion Language Models

Anonymous Author(s)

Affiliation

Address

email


Abstract

1 We propose Shibboleth, a model-response watermarking method for masked dif-
2 fusion language models (DLMs). Unlike an autoregressive sampler, a masked
3 DLM can be re-evaluated on its own output under an arbitrary remasking of the
4 context. Because a practical DLM, unlike an ideal predictor, shifts the likelihood
5 of an emitted token by an amount its own weights determine, a watermarking
6 channel opens in the relation between a text and the model rather than in the tokens.
7 Shibboleth evaluates a keyed family of context probes against each masked block,
8 admits as carriers only the unresolved positions whose block-masked conditional
9 retains mass on both response signs, and resamples at those carriers from the live
10 conditional until the requested sign is committed. Unlike logit-bias methods it
11 leaves the model’s probabilities untouched and conditions only on which model-
12 drawn proposal is accepted, and unlike order-steering methods it spends none of
13 the decoding schedule. Because the admitting gate is invariant to swapping two
14 probes, it stays blind to the sign the key will request, and carriers may therefore be
15 discovered adaptively without disturbing the null. Detection re-masks the finished
16 text, rebuilds the identical probes and carriers, and counts keyed sign matches,
17 whose distribution on text written without the key is exactly binomial, and p -values
18 are therefore exact at finite sample size and under carriers the method itself chose,
19 which no threshold fitted to a corpus can promise. On LLaDA-8B-Instruct it
20 reaches 0.80 TPR at 1% FPR, below the strongest token-based detector but at the
21 only perplexity ratio in the comparison that reads below its own unwatermarked
22 baseline. Verification in exchange costs one rerun of the checkpoint, and evidence
23 written against a prefix degrades under editing — collapsing at low redundancy,
24 halving at high — leaving the method suited to a verifier that holds the checkpoint
25 rather than to open screening.

26 1 Introduction

27 Language models now produce text that readers cannot reliably separate from human writing, which
28 turns provenance into a security problem, since disinformation, phishing, and academic fraud all
29 grow cheaper once authorship can no longer be established [28]. Institutions facing that problem
30 reach first for a post-hoc detector, and academic-integrity screening is the clearest case, given that an
31 essay’s authorship has to be settled after it is submitted [23]. A detector of that kind is nevertheless
32 fitted to one generation process, and its verdicts weaken as deployment moves to models that decode
33 by a different mechanism, masked diffusion models among them. Watermarking is the answer most
34 widely deployed against it, since it plants a keyed statistical signal during generation and lets whoever
35 holds the key test a later document for it [21, 32]. A watermark is nevertheless worth only the
36 guarantee attached to its verdict, given that a false positive is an accusation against a human author,
37 and a deployment therefore needs a false-positive rate it can state in advance rather than one fitted

Token-based watermark



Evidence lives in the token identities, so the detector reads text and key alone, never runs θ , and transfers to anyone holding the key.

Shibboleth (this work)



Evidence lives in the relation between the text and θ , so the detector reruns that same checkpoint at a cost of 144 masked evaluations.

Figure 1: **Two places to keep a watermark.** A token-based watermark biases which tokens are sampled and recovers that bias by reading the text against the key. Shibboleth instead writes the answer the key requests to a keyed probe of the context, which makes the evidence a property of the text together with one checkpoint and obliges the detector to rerun it.

to a calibration corpus. Since adversaries also paraphrase output and learn a key’s behaviour from detector queries [19, 23], the guarantees worth designing for are the ones that survive finite samples and adaptively chosen trials [10, 43].

Existing watermarks place their secret in the tokens, whether by biasing keyed vocabulary subsets [21], by coupling each draw to pseudorandomness [24], or, in recent diffusion language model (DLM) methods, by exploiting unresolved context and denoising order [17]. Detection then reduces to inspecting the text together with the key, and the generator is never consulted. Masked DLMs, by contrast, permit a different arrangement, since a finished text can be fed back to the model with selected context hidden and the likelihood of an emitted token then moves by an amount the checkpoint alone determines. Hiding a keyed subset of the context is in this sense a *context probe*, the direction in which the likelihood moves is the model’s response to it, and provenance can be argued from the agreement between the two. Such a probe is worth applying only where the model has a genuine choice of answer, that is where several plausible tokens coexist at a masked position and react with opposite signs to two patterns.

Moving the secret out of the tokens and into that relation, however, costs two things a token-local detector obtains for nothing, since the verifier must apply exactly the probe the embedder applied, and the choice of carriers must be settled before the accepted answer is known; a gate with sight of the rewarded sign would otherwise inflate the false-positive rate above the level the detector reports. Section 3.2 states both as requirements, and existing DLM watermarks avoid them by keeping detection token-local, whether by removing prefix dependence [9], by averaging a red–green bias over unresolved context [14], or by steering which mask is resolved next [17], none of which asks the model anything about the text it produced.

Shibboleth instead meets each condition with one mechanism (Figure 1). It settles replayability by re-masking the current block together with its suffix before scoring the probe family, and the state it measures therefore follows from the final text alone. A *balanced gate* then admits as carriers only the unresolved positions whose block-masked conditional retains mass on both response signs, scoring them in a way that is invariant to swapping the two patterns and therefore blind to the sign the key will ask for. Writing the answer is the easier half, since Shibboleth draws at most R proposals from the unchanged live row at an admitted position and commits the first one carrying that sign, which amounts to rejection sampling and does change the output distribution, although every committed token remains one the model proposed. Verification afterwards re-applies the same probe, reapplies the gate, and returns an exact binomial tail. Unlike a prefix-based watermark, which can require strict left-to-right decoding, and unlike an order-guided one, which changes which mask is resolved next, Shibboleth acts only after the reference schedule has produced a row, and therefore leaves the block partition and the confidence order untouched.

- We show across 36 settings that this checkpoint’s conditionals are too sharp for answers to be inserted after the fact, and the answer must therefore be written while the conditional is still live (Section 3.2).
- We propose Shibboleth, in which block-and-suffix re-masking makes the probe replayable from the finished text and orientation-blind gating keeps the accepted answer independent of how the

carriers were discovered, which together keep the detector’s p -values exact and free of calibration (Sections 3.3 to 3.5).

- We evaluate Shibboleth on LLaDA-8B-Instruct and report both sides of the trade, since the strongest setting reaches 0.80 TPR at 1% FPR at the best perplexity ratio of any method compared, whereas verification spends 144 masked evaluations and 10% re-denoising collapses TPR at $R = 1$ and halves it at the strongest setting (Section 4).

2 Related Work

Diffusion language models. Discrete and masked diffusion objectives carry diffusion [16] over to text [3, 29, 31, 36, 37] and now support instruction-following systems such as LLaDA and Dream [30, 41, 44], with commercial deployments following the same recipe [25]. Because the order in which positions commit affects quality and throughput [2, 6, 20, 38, 39], and because a run can equally be stopped before its step budget is spent [26], accelerators treat the whole schedule as a tunable degree of freedom. Shibboleth, by contrast, treats it as an invariant and draws on masked-token reconstruction only to define a probe it can later repeat.

Watermarking autoregressive text. Autoregressive watermarks bias keyed token subsets [21] or couple sampling to keyed randomness [1, 13, 24], with later work characterising their reliability and undetectability [10, 22, 43]. Detectors of this family are inexpensive precisely because a key–token hash needs no generator, yet that hash is defined over a resolved prefix and does not transfer unchanged to a context in which most token positions are still masked.

Watermarking diffusion language models. DLM-specific methods restore a well-defined keyed partition by other means, whether by removing prefix dependence [9], by averaging a red–green bias over unresolved context [14], by keyed sampling [4], or by exploiting the decoding order itself [17, 33, 40]. We compare against dgMARK, the strongest order-steering baseline with a zero-inference detector. Shibboleth differs from all of them in where the evidence resides, since dgMARK spends the DLM’s freedom over commit order and reads the outcome off the text, whereas Shibboleth spends nothing from the schedule and instead has the verifier rerun the exact checkpoint, buying a statistic bound to model behaviour at the price of a detector that no longer runs on text alone.

Detector statistics. Detector design has moved past the asymptotic z -test: exact tails (binomial for green counts, Gamma for Gumbel sums) close the gap between nominal and empirical FPR that Gaussian approximations leave open at small α [12], permutation tests give non-asymptotic p -values for otherwise intractable alignment statistics [24], and windowed maxima must either pay an explicit union-bound correction or be calibrated empirically [22]. When edits leave watermark evidence in only a fraction of the text, sum-based pooling is provably dominated by statistics that concentrate on the surviving fraction [27]. Shibboleth’s binomial tail belongs to the exact-test family, and its block structure admits the same sparse-signal statistics; Section 4.2 measures them and finds that under uniformly random edits the damage is dense and pooling wins, exactly the boundary the theory draws.

Detection that consults the model. Every DLM watermark above detects from the text and key alone, but detectors that pay more for their evidence are not new. Kuditipudi et al.’s edit-distance detector costs quadratic alignment under thousands of permutation resamples [24]; with model access, the Neyman–Pearson score strictly dominates the key-only Gumbel statistic [12], and log-likelihood-ratio detection reads both the watermarked and base conditionals [18]. GaussMark places its key in a Gaussian perturbation of the weights and verifies with one forward–backward pass of the generator [7], and watermarks built to expose model theft assume the verifier can query the suspect system [42]. Unlike GaussMark, which ships a perturbed checkpoint, Shibboleth leaves the released weights as they are and puts the key in the questions asked of them, and one deployed model therefore serves every document key.

3 Shibboleth: Watermarking by Model Response

3.1 Decoding and Notation

Masked diffusion language models differ from autoregressive models in that they predict a missing token from an arbitrary subset of revealed tokens, and the same sequence can consequently be produced under many decoding orders. Let x be a prompt and $y = (y_1, \dots, y_N)$ the continuation to be generated, and for a revealed set $I \subset \{1, \dots, N\}$ with a target position $i \notin I$, the model supplies a predictor $p_\theta(y_i \mid y_I, x)$ while the remaining positions carry the mask symbol, so that one sequence evaluation returns that distribution at every unresolved position at once.

Practical decoders nevertheless leave much of that freedom unused, and we study LLaDA’s semi-autoregressive schedule, in which the continuation is partitioned into blocks that finish from left to right while diffusion resolves the masks inside the active block [2, 30], and the reference confidence rule decides which positions commit at each step. Everything below is therefore stated for one block B_b with the prefix F_b that precedes it.

3.2 Problem Setup

Our goal is a watermark whose detector consults the model rather than the text alone, telling a continuation generated under a secret key from one generated without it at a false-positive rate the verifier states in advance, while disturbing the decoding schedule and the output quality as little as the channel allows.

Embedder and verifier. The embedder receives the model, the prompt, a secret key K , and the target bits, whereas the verifier later receives only the completed sequence, the same model, K , and the public parameters, without logits, random seeds, or commit order. Each document then draws its own key from K and a fresh nonce through a keyed hash, $K_d = \text{HMAC}(K, \text{nonce}_d)$, which to anyone without K behaves as a random function of the nonce [5]. That document key generates both the probe family and the accepted answers, and the false-positive guarantee covers any text produced independently of it.

Threat model. Both the model and the algorithm may be public, since secrecy rests entirely in K . Concretely, the detector does not accuse innocent text, meaning that for every text written independently of the document key, machine text from another sampler included, a detector run at nominal level α fires with probability at most α , and the bound holds at finite sample size and under carriers the method itself selects. We claim nothing in the complementary direction, and an adversary willing to edit the output can therefore suppress detection, as Section 4.2 measures. We likewise claim nothing after key disclosure, under the detector-query access that recovers a key’s behaviour [19], or when verification runs a numerically different checkpoint.

Post-hoc substitution. An embedder that swapped tokens in the finished text would be cheaper than one intervening during sampling, and we begin by measuring how much room such a swap has. Write τ for the likelihood budget of a substitution, the number of nats by which a replacement may fall below the live argmax. Across 36 settings that replace tokens after ordinary generation, the median selected position admits exactly one token at $\tau = 3$, the mean rising only from 1.6 at $\tau = 3$ to 5.6 at $\tau = 6$, and the best setting inside a $1.35\times$ perplexity budget reaches no more than 0.10 TPR at 1% FPR. Conditionals this sharp leave too little room for a forced replacement, and the embedder must therefore write while the conditional is still live.

We accordingly formalise the problem with three requirements.

1. **Replayability.** The verifier must be able to put exactly the question the embedder put, from the finished text and the key alone, with no generation trajectory, stored logits, or record of rejected samples.
2. **Blind selection.** The set of positions that carry a bit may depend arbitrarily on the text and the model, but that choice has to be settled before the sign the key rewards is consulted, since otherwise the reported false-positive rate understates the true one.




Figure 2: **How Shibboleth writes a mark and reads it back.** The same three steps run at generation and at verification, which is what makes the evidence replayable, and the gate in the middle step is settled before the key names the sign it accepts, which is what keeps its p -values exact.

173 3. **Schedule preservation.** The block partition and the confidence order must survive unchanged,
 174 so that a production decoder keeps the latency and quality profile it was tuned for.

175 The first two pull against each other, since replayability wants every scored context recoverable from
 176 a text the model helped choose while blind selection wants that choice to say nothing about the sign
 177 the key rewards. Sections 3.3 to 3.5 meet each requirement with one mechanism.

178 3.3 Probing the Model and Gating the Carriers

179 Unlike dgMARK, which obtains its channel by choosing which mask is resolved next, Shibboleth
 180 leaves the decoding schedule as the reference decoder set it. For block B_b , let F_b be the prompt
 181 together with the completed prefix, and let θ denote the reference checkpoint with p_θ for its predictor.
 182 Shibboleth then constructs L equal-size near, far, and keyed pseudorandom *probe patterns* $D_{b,\ell} \subset F_b$
 183 indexed by $\ell \in \{1, \dots, L\}$, each the set of prefix positions it hides, and it masks $D_{b,\ell}$ together with
 184 the current block and the suffix, and one model evaluation therefore yields, for every token position
 185 $i \in B_b$ and every vocabulary item v , the log-probability

$$\lambda_{i,\ell}(v) = \log p_\theta(v \mid F_b \setminus D_{b,\ell}; B_b \text{ and suffix masked}). \quad (1)$$

186 Probing one block therefore costs $L + 1$ sequence evaluations, one per pattern plus an unprobed
 187 baseline, and the verifier later repeats the same set.

188 Re-masking the block and the suffix removes every token unavailable when the probe was first
 189 applied, which is what buys replayability: the verifier restores the same state from the final text alone,
 190 and a transient generation-time response becomes a document statistic. Masking only the probed
 191 prefix would fail on both sides, since token positions committed later in the same block would leak
 192 into verification-time logits while the future suffix was invisible during embedding.

193 For an unordered pair of pattern indices (ℓ, ℓ') and a candidate token z , define the contrast $g_i^{\ell,\ell'}(z) =$
 194 $\lambda_{i,\ell'}(z) - \lambda_{i,\ell}(z)$. Let p_i^{base} denote the block-masked conditional, the model distribution when B_b
 195 and the suffix are masked but no probe pattern is applied. The mass on each sign and the two-sided
 196 score built from them are

$$q_{i,\pm}^{\ell,\ell'} = \sum_z p_i^{\text{base}}(z) \mathbf{1}[\pm g_i^{\ell,\ell'}(z) > 0], \quad S_i^{\ell,\ell'} = 2 \min(q_{i,+}^{\ell,\ell'}, q_{i,-}^{\ell,\ell'}). \quad (2)$$

197 Shibboleth selects, independently at each token position, the pair maximizing $S_i^{\ell,\ell'}$ and stores its
 198 contrast as g_i in the bank $\mathcal{R}_b$, after which the gate admits position i whenever $S_i > s_{\min}$, subject to
 199 an optional per-block cap. Because $S_i^{\ell,\ell'}$ is unchanged when ℓ and ℓ' are swapped, the gate neither
 200 observes nor favours the orientation the key will request, which is what buys blind selection, and
 201 both the pair selection and the gating recompute from the block-masked state. Best-pair selection is
 202 moreover what makes the gate productive, raising the measured mean score from 0.28 for a fixed
 203 near/far pair to 0.45, although the score stays a symmetric proxy computed on the block-masked
 204 conditional while generation runs from an evolving live one.

205 Once the gate has admitted a token position, the key supplies an orientation $\epsilon_i \in \{-1, +1\}$ from
 206 a PRF domain separate from pattern generation, pair selection, carrier assignment, and payload
 207 grouping. A target $w_i \in \{-1, +1\}$ then carries the desired provenance or message bit, so that for a
 208 candidate z the shared embedding-and-verification predicate becomes

$$m_i(z) = \mathbf{1}[w_i \epsilon_i g_i(z) > 0]. \quad (3)$$

Should $g_i(z)$ vanish exactly, a second domain-separated fair bit defines $m_i(z)$, and although such ties cannot be steered, the tie rule keeps the detector’s p -values exact.

3.4 Writing the Requested Answer

Shibboleth inherits the reference confidence order together with the live conditional p_i , and the token positions that the gate rejected are sampled normally. At an admitted carrier define

$$A_i = \left\{ z : w_i \epsilon_i g_i(z) > 0 \text{ and } p_i(z) \geq \kappa \max_v p_i(v) \right\}. \quad (4)$$

It draws from p_i up to R times and commits the first member of A_i , and after R misses it commits one fresh unchecked draw instead. Because the row is never recomputed, those retries cost no model evaluation.

That procedure changes the sampling distribution, and by a stated amount. Let $a_i = p_i(A_i)$ be the acceptance mass and let $q_i = \sum_z p_i(z) m_i(z)$, where $m_i(z)$ applies Eq. (3) and the tie rule to candidate z , so that q_i is the probability that an unconditional draw scores as a detector hit irrespective of the plausibility floor. The committed-token distribution is

$$(1 - (1 - a_i)^R) p_i(\cdot | A_i) + (1 - a_i)^R p_i, \quad (5)$$

and its detector-hit probability is

$$\Pr[m_i = 1] = 1 - (1 - a_i)^R (1 - q_i). \quad (6)$$

Whenever $\kappa = 0$ and the conditional places no mass on exact ties, $a_i = q_i$ and Eq. (6) collapses to $1 - (1 - q_i)^{R+1}$, so that a_i and q_i diverge only under a floor or a tie rule, where an unchecked fallback may score as a hit without belonging to A_i . The floor meanwhile bounds each guided proposal’s model NLL to within $-\log \kappa$ of the live argmax but constrains neither the fallback nor semantic quality, which is why being model-proposed remains a support statement rather than a distortion-free claim.

3.5 Watermark Detection

Given a completed text y , the verifier re-masks each block and suffix, rebuilds the probe from the fixed prefix, reapplies the gate, and evaluates $m_i = m_i(y_i)$ at the admitted positions, so that rejected proposals and the generation trajectory are irrelevant. For provenance-only detection, which is all we evaluate here, the admitted carriers form a presence pool P with $w_i = +1$, whereas a payload implementation would keep the group for each payload bit separate, so that a balanced message cannot cancel positive against negative targets. The presence statistic and its one-sided p -value are

$$T = \sum_{i \in P} m_i, \quad p_{\text{det}} = \Pr[\text{Binomial}(|P|, \frac{1}{2}) \geq T]. \quad (7)$$

Proposition 1 (Exact false-positive control). *Assume the PRF domains above behave as independent random functions. Fix any text y written without the document key, and condition on the carrier set, selected pairs, contrast values, payload roles, and target bits. The orientation bits (and tie bits where needed) remain independent fair coins. Consequently the m_i are independent $\text{Bernoulli}(\frac{1}{2})$ variables and $T \sim \text{Binomial}(|P|, \frac{1}{2})$ exactly, so that p_{det} in Eq. (7) is an exact p -value and thresholding it at α holds the false-positive rate at or below α for every document length and carrier count.*

The conditioning carries the result, since carrier count, selected pair, and contrast magnitude may all depend arbitrarily on the text and the model, yet each is fixed before the independent orientation bit is consulted. Flipping ϵ_i therefore flips m_i whenever $g_i(y_i) \neq 0$, the tie rule supplies a fresh fair bit when it vanishes, and the carriers stay independent of one another throughout. In particular, neither an asymptotic approximation nor a calibration corpus enters anywhere, unlike a z -score whose reference distribution has to be estimated. The guarantee does nevertheless assume text written without the key, together with independence among the several uses of the key, which the domain-separated hash supplies.

Method	Setting	PPL ratio ↓	TPR at FPR ↑		Sequence evaluations ↓	
			1%	0.1%	Generation	Detection
<i>LLaDA-8B-Instruct</i>						
KGW [21]	$\delta = 1$, 256 tok	$1.03\times$	0.93	0.73	256	0
dgMARK [17]	$k = 1$, 256 tok	$1.55\times$	0.74	0.62	256	0
dgMARK [17]	+3-beam, 256 tok	$1.23\times$	0.86	0.82	~1024	0
Shibboleth	$R = 1$, 512 tok	$0.97\times$	0.43	0.20	656	144
Shibboleth	$R = 8, \kappa = 0.1$, 512 tok	$0.87\times$	0.70	0.60	656	144
Shibboleth	$R = 16, \kappa = 0.05$, 512 tok	0.74 $\times$	0.80	0.60	656	144
<i>Dream-7B-Instruct</i>						
KGW [21]	$\delta = 1$, 512 tok	??	??	??	512	0
dgMARK [17]	$k = 1$, 512 tok	??	??	??	512	0
dgMARK [17]	+3-beam, 512 tok	??	??	??	~2048	0
Shibboleth	$R = 1$, 512 tok	??	??	??	656	144
Shibboleth	$R = 8, \kappa = 0.1$, 512 tok	??	??	??	656	144
Shibboleth	$R = 16, \kappa = 0.05$, 512 tok	??	??	??	656	144

Table 1: **Watermark detectability.** Detection rate, perplexity against each method’s own matched unwatermarked baseline, and compute in sequence evaluations. All rows are local reproductions on one checkpoint and prompt protocol, but Shibboleth uses 512-token outputs while the token-based baselines use 256, and each block keeps its own decoding regime, so ratios are comparable within a method and indicative across methods. A PPL ratio below one is not evidence of better semantics. Principal Shibboleth rows use $n = 30$ documents ($n = 20$ for $R = 16$); dgMARK uses $n = 50$. Here δ is KGW’s green-list logit bias and k is dgMARK’s candidate count. Cells marked ?? are pending runs already queued (Dream block; 512-token baseline reruns that will replace the 256-token rows).

249 4 Experiments

250 **Datasets and setup.** We evaluate GSAI-ML/LLaDA-8B-Instruct [30] in fp16 on a single TITAN
251 RTX. Detectability is measured on C4 realnewslike [35] prompts truncated to 300 characters
252 as dgMARK’s protocol prescribes. Shibboleth runs produce 512 tokens in 32-token blocks at one
253 denoising step per token under the native confidence schedule with full-vocabulary multinomial
254 sampling at temperature 0.8; the token-based baselines are local reproductions at 256 tokens under
255 each method’s own decoding regime, and the table states both lengths rather than pretending to
256 one protocol. On top of the reference sampler, Shibboleth adds $L = 8$ probe patterns, threshold
257 $s_{\min} = 0.5$, retry budget R , and an optional floor κ , and we test provenance detection ($w_i = +1$)
258 rather than payload recovery.

259 **Metrics and baselines.** Detectability is TPR at analytic FPR thresholds from Eq. (7), and quality
260 is GPT-2-large [34] perplexity against an unwatermarked baseline drawn from the same decoder,
261 reported as $\exp(\text{mean}(\text{NLL}_{\text{wm}} - \text{NLL}_{\text{ctrl}}))$. That ratio measures the distortion each method adds to
262 its own unwatermarked baseline rather than absolute text quality, and comparisons of ratios across
263 methods are therefore indicative rather than controlled. Compute counts sequence evaluations, and
264 each of the $512/32 = 16$ blocks accordingly needs $L + 1 = 9$ of them, hence 144 for verification
265 against $512 + 144 = 656$ for generation. We compare against KGW [21] under left-to-right decoding
266 and dgMARK [17] under confidence decoding.

267 4.1 Main Results and Analysis

268 **Retry budget and the floor.** Detection scales with the number of guided draws as Eq. (6) predicts,
269 since $R = 1$ reaches 0.43 TPR at 1% FPR and raising R from 2 to 4 to 8 on 30 held-out prompts lifts
270 it from 0.73 to 0.83 to 0.87. Retries cost no model evaluation, and the budget is therefore paid in
271 quality instead, with unfloored perplexity ratios climbing from $1.14\times$ at $R = 2$ to $1.40\times$ at $R = 4$
272 and $1.61\times$ at $R = 8$. The floor converts part of that back, since $(R, \kappa) = (8, 0.1)$ obtains 0.70 TPR
273 at $0.87\times$ and $(16, 0.05)$ obtains 0.80 at $0.74\times$, both below their unwatermarked baselines, although
274 a ratio below one indicates only that GPT-2-large prefers the high-probability tokens the floor admits.

275 **Downstream quality.** Perplexity ratios are a proxy, so we additionally measure GSM8K [11]
276 accuracy on 50 test problems at 256 tokens, comparing the watermarked sampler against its matched
277 unwatermarked control under the identical decoding schedule; results are ?? pending the run.

Model	Method	Greedy decoding			Multinomial decoding		
		MMLU Acc $\uparrow$	GSM8K Acc $\uparrow$	HumanEval Pass@1 $\uparrow$	MMLU Acc $\uparrow$	GSM8K Acc $\uparrow$	HumanEval Pass@1 $\uparrow$
LLaDA-8B-Instruct	Non-watermarked	??	??	??	??	??	??
	KGW [21]	??	??	??	??	??	??
	dgMARK [17]	??	??	??	??	??	??
	dgMARK +3-beam	??	??	??	??	??	??
	Shibboleth	??	??	??	??	??	??
Dream-7B-Instruct	Non-watermarked	??	??	??	??	??	??
	KGW	??	??	??	??	??	??
	dgMARK	??	??	??	??	??	??
	dgMARK +3-beam	??	??	??	??	??	??
	Shibboleth	??	??	??	??	??	??

Table 2: **Text generation quality.** Accuracy on MMLU [15] and GSM8K [11] and pass@1 on HumanEval [8] under greedy and multinomial decoding, with the unwatermarked run of each model as the reference row of its block. Shibboleth uses $R = 16$, $\kappa = 0.05$; all cells are pending measured runs.

Attack	Strength	TPR at FPR $\uparrow$	
		1%	0.1%
<i>Weakest setting: $R = 1$, 512 tokens ($n = 20$)</i>			
None	—	0.35	??
Re-denoising (same model, argmax)	10% of positions	0.05	??
Deletion	10% of positions	0.05	??
Insertion	10% of positions	??	??
Substitution (random)	10% of positions	??	??
Copy–paste	25% kept, 1 segment	??	??
Paraphrase (DIPPER) [23]	lex 20, order 0	??	??
<i>Strongest setting: $R = 16$, $\kappa = 0.05$, 1024 tokens ($n = 16$)</i>			
None	—	0.88	0.88
Re-denoising (same model, argmax)	5% of positions	0.88	0.75
	10% of positions	0.50	0.38

Table 3: **Robustness to post-editing.** Detection after each attack under the deployed pooled detector, scored against the same analytic thresholds as Table 1. Evidence written into a replayable probe is synchronised to the prefix, so at $R = 1$ a 10% edit invalidates nearly every carrier; at the strongest setting the carrier redundancy absorbs a 5% edit outright and a 10% edit halves detection rather than erasing it. Small cohorts: one document is 0.05 ($n = 20$) or 0.06 ($n = 16$) of TPR.

278 **Cost against token-local detectors.** Detection trails the strongest token-based detector: KGW
279 reaches 0.93 TPR at 1% FPR against 0.80 for Shibboleth, and dgMARK’s three-beam variant reaches
280 0.82 at 0.1% FPR against 0.60. Shibboleth instead carries the only perplexity ratio in the comparison
281 that reads below its own unwatermarked baseline, $0.74\times$ against $1.03\times$ for KGW and $1.23\times$ for
282 three-beam dgMARK; every baseline row costs perplexity, whereas the floor discards exactly the low-
283 probability draws a proxy scorer punishes. KGW additionally requires strict left-to-right decoding,
284 and its repeated bigram events must be deduplicated, without which its control measured 37%
285 FPR. Shibboleth alone, against all of that, spends 144 masked evaluations to detect at all, although
286 paying for detection is not unprecedented: edit-distance detection runs a quadratic alignment under
287 thousands of permutation resamples [24], and GaussMark verifies with a forward–backward pass of
288 the generator itself [7]. Cohorts of twenty to fifty documents leave a standard error near 0.08 on a
289 TPR of 0.80, and two rows separated by less than about a tenth should accordingly be read as a tie.

290 4.2 Calibration and Robustness

291 **Calibration under the shipped rule.** Proposition 1 is analytical, which is why we also measure
292 the rule as deployed. Across 20 keys and 120 non-watermarked generations apiece, the mean FPR
293 is 0.0121, 0.0037 and 0.0000 at nominal 0.10, 0.05 and 0.01, and the worst individual key gives
294 0.0583, 0.0250 and 0.0000, and control consequently holds for every key rather than on average
295 alone, which is what binds when one key serves many documents.

Post-editing. Edit robustness is the channel’s principal failure mode, and it degrades abruptly, since same-model argmax re-denoising of a random 10% of token positions takes TPR at 1% FPR from 0.35 to 0.05 on 20 $R = 1$ documents and deleting 10% measures the same. The collapse is one of synchronisation rather than signal strength, because an early edit alters the fixed prefix from which every later probe is rebuilt, and a single change thus invalidates every carrier after it. That cohort uses $R = 1$, and the headline setting at $R = 16$ consequently remains unattacked, which we record as an open gap rather than as evidence of resilience. Redundancy, however, changes the picture: attacking the strongest setting ($R = 16$, $\kappa = 0.05$ at 1024 tokens, $n = 16$) rather than the weakest, re-denoising 5% of positions leaves TPR at 1% FPR unchanged at 0.88 and re-denoising 10% halves it to 0.50 instead of erasing it, with false-positive control holding on the identically attacked controls. We also measured the block-local repair the pooled statistic seems to invite: a per-block exact test combined by Bonferroni over the blocks keeps the document-level guarantee by union bound, yet it never beats pooling here — 0.38 against 0.50 at 1% FPR under the 10% attack, and 0.69 against 0.88 clean — because uniformly random edits damage every block, so the sparse-signal regime in which concentration-type tests dominate sum-based ones [27] never arises. The honest reading is that random re-denoising is the dense-damage case; localized edits and copy–paste, where a min-statistic should win, remain unmeasured.

5 Conclusion

Shibboleth argues provenance from a keyed probe that a masked DLM answers about its own output rather than from a pattern left in the tokens, and because the gate is settled before the key names the sign it accepts, carriers may be discovered adaptively at no cost to the detector’s exact p -values. That trade is worth making where the decoding schedule must not change and the evidence wanted is of the kind a specified model can vouch for, which a key–token hash cannot supply, since anyone holding the key can compute it without the generator. Absent either constraint, a token-local watermark is cheaper and easier to resynchronise after edits.

Limitations. That guarantee is nevertheless one-sided, since soundness holds for any text written without the key while nothing is claimed in the other direction, and editing degrades detection: a single same-model denoising pass over a tenth of the positions takes TPR from 0.35 to 0.05 at $R = 1$, and even at the strongest setting it halves detection (0.88 to 0.50 at 1% FPR, $n = 16$), so Shibboleth claims resilience to light editing at high redundancy and nothing beyond it. Cost is the second boundary, since 144 masked evaluations per document rule out screening a corpus. The evidence is bound to one checkpoint as well, and a verifier holding different weights, or the same weights at a different precision, consequently cannot reproduce the responses at all. Finally, the evaluation is itself narrow, covering one masked diffusion model, one prompt corpus, cohorts of twenty to fifty documents, quality proxies read as ratios against each method’s own unwatermarked baseline, and provenance detection only, with the payload construction of Section 3.5 never measured.

Future work. Each boundary suggests its own repair. Anchoring probe patterns to content rather than to absolute positions would stop an edit from desynchronising every carrier after it, which is the single change most likely to turn an abrupt collapse into a graceful decline, and the remaining attack to run is the localized one — contiguous edits and copy–paste — where a per-block min-statistic should finally beat the pooled count. Verification cost is the easier target, since the binomial tail is monotone in the matches so far and a sequential test could stop once the evidence is decisive. Loosening the checkpoint requirement in turn asks for a contrast quantised coarsely enough that numerical drift cannot flip a sign, trading a little capacity for portability. Adaptive adversaries deserve their own study, since a detector answering queries leaks something about its key. Table 1 finally argues for composition rather than a winner, with a cheap token-local screen deciding what is worth a model-response check.

References

- [1] Scott Aaronson and Hendrik Kirchner. Watermarking GPT outputs, 2023. <https://www.scottaaronson.com/talks/watermark.ppt>.
- [2] Marianne Arriola, Subham Sekhar Sahoo, Aaron Gokaslan, Zhihan Yang, Zhixuan Qi, Jiaqi Han, Justin T. Chiu, and Volodymyr Kuleshov. Block diffusion: Interpolating between autoregressive and diffusion language models. In *ICLR*, 2025.
- [3] Jacob Austin, Daniel D. Johnson, Jonathan Ho, Daniel Tarlow, and Rianne van den Berg. Structured denoising diffusion models in discrete state-spaces. In *NeurIPS*, 2021.
- [4] Arka Bagchi, Akhil Bhimaraju, Moulik Choraria, Daniel Alabi, and Lav R. Varshney. Watermarking discrete diffusion language models. *arXiv preprint arXiv:2511.02083*, 2025.
- [5] Mihir Bellare, Ran Canetti, and Hugo Krawczyk. Keying hash functions for message authentication. In *CRYPTO*, 1996.
- [6] Heli Ben-Hamu, Itai Gat, Daniel Severo, Niklas Nolte, and Brian Karrer. Accelerated sampling from masked diffusion models via entropy bounded unmasking. In *NeurIPS*, 2025.
- [7] Adam Block, Alexander Rakhlin, and Ayush Sekhari. GaussMark: A practical approach for structural watermarking of language models. In *ICML*, 2025.
- [8] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.
- [9] Ruibo Chen, Yihan Wu, Yanshuo Chen, Chenxi Liu, Junfeng Guo, and Heng Huang. A watermark for order-agnostic language models. In *ICLR*, 2025.
- [10] Miranda Christ, Sam Gunn, and Or Zamir. Undetectable watermarks for language models. In *COLT*, 2024.
- [11] Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.
- [12] Pierre Fernandez, Antoine Chaffin, Karim Tit, Vivien Chappelier, and Teddy Furon. Three bricks to consolidate watermarks for large language models. In *2023 IEEE International Workshop on Information Forensics and Security (WIFS)*, 2023.
- [13] Jiayi Fu, Xuandong Zhao, Ruihan Yang, Yuansen Zhang, Jiangjie Chen, and Yanghua Xiao. GumbelSoft: Diversified language model watermarking via the GumbelMax-Trick. In *ACL*, 2024.
- [14] Thibaud Gloaguen, Robin Staab, Nikola Jovanović, and Martin Vechev. Watermarking diffusion language models. In *ICLR*, 2026. arXiv:2509.24368.
- [15] Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *ICLR*, 2021.
- [16] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In *NeurIPS*, 2020.
- [17] Pyo Min Hong and Albert No. dgMARK: Decoding-Guided Watermarking for Diffusion Language Models. In *ICML*, 2026. arXiv:2601.22985.
- [18] Zhengmian Hu, Lichang Chen, Xidong Wu, Yihan Wu, Hongyang Zhang, and Heng Huang. Unbiased watermark for large language models. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024.
- [19] Nikola Jovanović, Robin Staab, and Martin Vechev. Watermark stealing in large language models. In *ICML*, 2024.

- [20] Jaeyeon Kim, Kulin Shah, Vasilis Kontonis, Sham M. Kakade, and Sitan Chen. Train for the worst, plan for the best: Understanding token ordering in masked diffusions. In *ICML*, 2025.
- [21] John Kirchenbauer, Jonas Geiping, Yuxin Wen, Jonathan Katz, Ian Miers, and Tom Goldstein. A watermark for large language models. In *ICML*, 2023.
- [22] John Kirchenbauer, Jonas Geiping, Yuxin Wen, Manli Shu, Khalid Saifullah, Kezhi Kong, Kasun Fernando, Aniruddha Saha, Micah Goldblum, and Tom Goldstein. On the reliability of watermarks for large language models. In *ICLR*, 2024.
- [23] Kalpesh Krishna, Yixiao Song, Marzena Karpinska, John F. Wieting, and Mohit Iyyer. Paraphrasing evades detectors of AI-generated text, but retrieval is an effective defense. In *NeurIPS*, 2023.
- [24] Rohith Kuditipudi, John Thickstun, Tatsunori Hashimoto, and Percy Liang. Robust distortion-free watermarks for language models. *TMLR*, 2024.
- [25] Inception Labs, Samar Khanna, Siddhant Kharbanda, Shufan Li, Harshit Varma, Eric Wang, Sarah Birnbaum, Ziyang Luo, Yanis Miraoui, and Akash Palrecha. Mercury: Ultra-fast language models based on diffusion. *arXiv preprint arXiv:2506.17298*, 2025.
- [26] Chia-Ming Lee, Shao-Kai Liu, Ming-Ching Chang, Xin Li, Yu-Lun Liu, and Chih-Chung Hsu. Commit locally, exit globally: Coordinating adaptive sampling and early exit in diffusion language models, 2026. URL <https://arxiv.org/abs/2607.28166>.
- [27] Xiang Li, Feng Ruan, Huiyuan Wang, Qi Long, and Weijie J. Su. Robust detection of watermarks for large language models under human edits. *Journal of the Royal Statistical Society: Series B*, 2025.
- [28] Yuqing Liang, Jiancheng Xiao, Wensheng Gan, and Philip S. Yu. Watermarking techniques for large language models: A survey. *Artificial Intelligence Review*, 2026.
- [29] Aaron Lou, Chenlin Meng, and Stefano Ermon. Discrete diffusion modeling by estimating the ratios of the data distribution. In *ICML*, 2024.
- [30] Shen Nie, Fengqi Zhu, Zebin You, Xiaolu Zhang, Jingyang Ou, Jun Hu, Jun Zhou, Yankai Lin, Ji-Rong Wen, and Chongxuan Li. Large language diffusion models. In *NeurIPS*, 2025.
- [31] Jingyang Ou, Shen Nie, Kaiwen Xue, Fengqi Zhu, Jiacheng Sun, Zhenguo Li, and Chongxuan Li. Your absorbing discrete diffusion secretly models the conditional distributions of clean data. In *ICLR*, 2025.
- [32] Fabien A. P. Petitcolas, Ross J. Anderson, and Markus G. Kuhn. Information hiding — a survey. In *Proceedings of the IEEE*, 1999.
- [33] Ohad Raban, Ethan Fetaya, and Gal Chechik. LR-DWM: Efficient watermarking for diffusion language models. *arXiv preprint arXiv:2601.12376*, 2026.
- [34] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. Technical report, OpenAI, 2019.
- [35] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67, 2020.
- [36] Subham Sekhar Sahoo, Marianne Arriola, Aaron Gokaslan, Edgar Marroquin Marroquin, Alexander M. Rush, Yair Schiff, Justin T. Chiu, and Volodymyr Kuleshov. Simple and effective masked diffusion language models. In *NeurIPS*, 2024.
- [37] Jiaxin Shi, Kehang Han, Zhe Wang, Arnaud Doucet, and Michalis Titsias. Simplified and generalized masked diffusion for discrete data. In *NeurIPS*, 2024.
- [38] Qingyan Wei, Yaojie Zhang, Zhiyuan Liu, Pengfei Zeng, Yu Wang, Biao Qi, Dong Liu, and Linfeng Zhang. Accelerating diffusion large language models with SlowFast sampling: The three golden principles. In *ICLR*, 2026.

- 436 [39] Chengyue Wu, Hao Zhang, Shuchen Xue, Zhijian Liu, Shizhe Diao, Ligeng Zhu, Ping Luo,
437 Song Han, and Enze Xie. Fast-dLLM: Training-free acceleration of diffusion LLM by enabling
438 KV cache and parallel decoding. In *ICLR*, 2026.
- 439 [40] Linyu Wu, Linhao Zhong, Wenjie Qu, Yifan Li, Yue Liu, Shengfang Zhai, Chunhua Shen, and
440 Jiaheng Zhang. DMark: Order-agnostic watermarking for diffusion large language models.
441 *arXiv preprint arXiv:2510.02902*, 2025.
- 442 [41] Jiacheng Ye, Zhihui Xie, Lin Zheng, Jiahui Gao, Zirui Wu, Xin Jiang, Zhenguo Li, and Lingpeng
443 Kong. Dream 7B: Diffusion large language models. *arXiv preprint arXiv:2508.15487*, 2025.
- 444 [42] Xuandong Zhao, Yu-Xiang Wang, and Lei Li. Protecting language generation models via
445 invisible watermarking. In *ICML*, 2023.
- 446 [43] Xuandong Zhao, Prabhanjan V. Ananth, Lei Li, and Yu-Xiang Wang. Provable robust water-
447 marking for AI-generated text. In *ICLR*, 2024.
- 448 [44] Fengqi Zhu, Rongzhen Wang, Shen Nie, Xiaolu Zhang, Chunwei Wu, Jun Hu, Jun Zhou, Jianfei
449 Chen, Yankai Lin, Ji-Rong Wen, and Chongxuan Li. LLaDA 1.5: Variance-reduced preference
450 optimization for large language diffusion models. *arXiv preprint arXiv:2505.19223*, 2025.