

# Lexical Analysis

## Lecture 3

Prof. Aiken CS 143 Lecture 3

1

## Outline

- Informal sketch of lexical analysis
  - Identifies tokens in input string
- Issues in lexical analysis
  - Lookahead
  - Ambiguities
- Specifying lexers
  - Regular expressions
  - Examples of regular expressions

Prof. Aiken CS 143 Lecture 3

2

## Lexical Analysis

- What do we want to do? Example:  

```
if (i == j)
  Z = 0;
else
  Z = 1;
```
- The input is just a string of characters:  

```
\tif (i == j)\n\t\tz = 0;\n\telse\n\t\tz = 1;
```
- Goal: Partition input string into substrings
  - Where the substrings are tokens

Prof. Aiken CS 143 Lecture 3

3

## What's a Token?

- A syntactic category
  - In English:  
*noun, verb, adjective, ...*
  - In a programming language:  
*Identifier, Integer, Keyword, Whitespace, ...*

Prof. Aiken CS 143 Lecture 3

4

## Tokens

- Tokens correspond to sets of strings.
- Identifier: *strings of letters or digits, starting with a letter*
- Integer: *a non-empty string of digits*
- Keyword: *"else" or "if" or "begin" or ...*
- Whitespace: *a non-empty sequence of blanks, newlines, and tabs*

Prof. Aiken CS 143 Lecture 3

5

## What are Tokens For?

- Classify program substrings according to role
- Output of lexical analysis is a stream of tokens ...
- ... which is input to the parser
- Parser relies on token distinctions
  - An identifier is treated differently than a keyword

Prof. Aiken CS 143 Lecture 3

6



### True Crimes of Lexical Analysis

---

- Is it as easy as it sounds?
- Not quite!
- Look at some history . . .

Prof. Aiken CS 143 Lecture 3

13

### Lexical Analysis in FORTRAN

---

- FORTRAN rule: Whitespace is insignificant
- E.g., `VAR1` is the same as `VA R1`
- A terrible design!

Prof. Aiken CS 143 Lecture 3

14

### Example

---

- Consider
  - `DO 5 I = 1,25`
  - `DO 5 I = 1.25`

Prof. Aiken CS 143 Lecture 3

15

### Lexical Analysis in FORTRAN (Cont.)

---

- Two important points:
  1. The goal is to partition the string. This is implemented by reading left-to-right, recognizing one token at a time
  2. “Lookahead” may be required to decide where one token ends and the next token begins

Prof. Aiken CS 143 Lecture 3

16

### Lookahead

---

- Even our simple example has lookahead issues
  - `i` vs. `if`
  - `=` vs. `==`
- Footnote: FORTRAN Whitespace rule motivated by inaccuracy of punch card operators

Prof. Aiken CS 143 Lecture 3

17

### Lexical Analysis in PL/I

---

- PL/I keywords are not reserved  
`IF ELSE THEN THEN = ELSE; ELSE ELSE = THEN`

Prof. Aiken CS 143 Lecture 3

18

## Lexical Analysis in PL/I (Cont.)

- PL/I Declarations:  
`DECLARE (ARG1,..., ARGN)`
- Can't tell whether `DECLARE` is a keyword or array reference until after the `)`.
  - Requires arbitrary lookahead!
- More on PL/I's quirks later in the course . . .

Prof. Aiken CS 143 Lecture 3

19

## Lexical Analysis in C++

- Unfortunately, the problems continue today
- C++ template syntax:  
`Foo<Bar>`
- C++ stream syntax:  
`cin >> var;`
- But there is a conflict with nested templates:  
`Foo<Bar<Bazz>>`

Prof. Aiken CS 143 Lecture 3

20

## Review

- The goal of lexical analysis is to
  - Partition the input string into lexemes
  - Identify the token of each lexeme
- Left-to-right scan => lookahead sometimes required

Prof. Aiken CS 143 Lecture 3

21

## Next

- We still need
  - A way to describe the lexemes of each token
  - A way to resolve ambiguities
    - Is `if` two variables `i` and `f`?
    - Is `==` two equal signs `=` `=`?

Prof. Aiken CS 143 Lecture 3

22

## Regular Languages

- There are several formalisms for specifying tokens
- *Regular languages* are the most popular
  - Simple and useful theory
  - Easy to understand
  - Efficient implementations

Prof. Aiken CS 143 Lecture 3

23

## Languages

**Def.** Let **S** be a set of characters. A *language over S* is a set of strings of characters drawn from **S**

Prof. Aiken CS 143 Lecture 3

24

## Examples of Languages

- Alphabet = English characters
- Language = English sentences
- Not every string of English characters is an English sentence
- Alphabet = ASCII
- Language = C programs
- Note: ASCII character set is different from English character set

Prof. Aiken CS 143 Lecture 3

25

## Notation

- Languages are sets of strings.
- Need some notation for specifying which sets we want
- The standard notation for regular languages is *regular expressions*.

Prof. Aiken CS 143 Lecture 3

26

## Atomic Regular Expressions

- Single character

$$'c' = \{ "c" \}$$

- Epsilon

$$\varepsilon = \{ "" \}$$

Prof. Aiken CS 143 Lecture 3

27

## Compound Regular Expressions

- Union

$$A + B = \{ s \mid s \in A \text{ or } s \in B \}$$

- Concatenation

$$AB = \{ ab \mid a \in A \text{ and } b \in B \}$$

- Iteration

$$A^* = \bigcup_{i \geq 0} A^i \text{ where } A^i = A \dots i \text{ times } \dots A$$

Prof. Aiken CS 143 Lecture 3

28

## Regular Expressions

- **Def.** The *regular expressions over S* are the smallest set of expressions including

$\varepsilon$

$'c'$  where  $c \in \Sigma$

$A + B$  where  $A, B$  are rexp over  $\Sigma$

$AB$  " " "

$A^*$  where  $A$  is a rexp over  $\Sigma$

Prof. Aiken CS 143 Lecture 3

29

## Syntax vs. Semantics

- To be careful, we should distinguish syntax and semantics.

$$L(\varepsilon) = \{ "" \}$$

$$L('c') = \{ "c" \}$$

$$L(A + B) = L(A) \cup L(B)$$

$$L(AB) = \{ ab \mid a \in L(A) \text{ and } b \in L(B) \}$$

$$L(A^*) = \bigcup_{i \geq 0} L(A^i)$$

Prof. Aiken CS 143 Lecture 3

30

### Segue

- Regular expressions are simple, almost trivial
  - But they are useful!
- Reconsider informal token descriptions . . .

Prof. Aiken CS 143 Lecture 3

31

### Example: Keyword

Keyword: “else” or “if” or “begin” or ...

`'else' + 'if' + 'begin' + ...`

Note: `'else'` abbreviates  
`'e' 'l' 's' 'e'`

Prof. Aiken CS 143 Lecture 3

32

### Example: Integers

Integer: *a non-empty string of digits*

`digit = '0' + '1' + '2' + '3' + '4' + '5' + '6' + '7' + '8' + '9'`

`integer = digit digit*`

Abbreviation:  $A^+ = AA^*$

Prof. Aiken CS 143 Lecture 3

33

### Example: Identifier

Identifier: *strings of letters or digits, starting with a letter*

`letter = 'A' + ... + 'Z' + 'a' + ... + 'z'`

`identifier = letter (letter + digit)*`

Is  $(\text{letter}^* + \text{digit}^*)$  the same?

Prof. Aiken CS 143 Lecture 3

34

### Example: Whitespace

Whitespace: *a non-empty sequence of blanks, newlines, and tabs*

$(\text{' ' + '\n' + '\t'})^+$

Prof. Aiken CS 143 Lecture 3

35

### Example: Phone Numbers

- Regular expressions are all around you!
- Consider (650)-723-3232

$\Sigma = \text{digits} \cup \{-, (, )\}$

`exchange = digit3`

`phone = digit4`

`area = digit3`

`phone_number = '(' area ')' '-' exchange '-' phone`

Prof. Aiken CS 143 Lecture 3

36

### Example: Email Addresses

---

- Consider *anyone@cs.stanford.edu*

$\Sigma$  = letters  $\cup \{.,@\}$   
name = letter<sup>+</sup>  
address = name '@' name '.' name '.' name

Prof. Aiken CS 143 Lecture 3

37

### Example: Unsigned Pascal Numbers

---

digit = '0'+'1'+'2'+'3'+'4'+'5'+'6'+'7'+'8'+'9'  
digits = digit<sup>+</sup>  
opt\_fraction = ('.' digits) +  $\epsilon$   
opt\_exponent = ('E' ('+'+'-' +  $\epsilon$ ) digits) +  $\epsilon$   
num = digits opt\_fraction opt\_exponent

Prof. Aiken CS 143 Lecture 3

38

### Other Examples

---

- File names
- Grep tool family

Prof. Aiken CS 143 Lecture 3

39

### Summary

---

- Regular expressions describe many useful languages
- Regular languages are a language specification
  - We still need an implementation
- Next time: Given a string  $s$  and a rexp  $R$ , is

$s \in L(R)?$

Prof. Aiken CS 143 Lecture 3

40