Question Editorial Solution

My Submissions (/problems/validate-binary-search-tree/submissions/)

Total Accepted: 136527 Total Submissions: 609084 Difficulty: Medium Contributors: Admin

Given a binary tree, determine if it is a valid binary search tree (BST).

Assume a BST is defined as follows:

- The left subtree of a node contains only nodes with keys less than the node's key.
- The right subtree of a node contains only nodes with keys greater than the node's key.
- Both the left and right subtrees must also be binary search trees.

Example 1:

```
2
/\
1 3
```

Binary tree [2,1,3], return true.

Example 2:

```
1
/\
2 3
```

Binary tree [1,2,3], return false.

Subscribe (/subscribe/) to see which companies asked this question

```
Hide Tags Tree (/tag/tree/) Depth-first Search (/tag/depth-first-search/)

Hide Similar Problems (M) Binary Tree Inorder Traversal (/problems/binary-tree-inorder-traversal/)
```

Have you met this question in a real interview? Yes No

Discuss (https://discuss.leetcode.com/category/106)

Top Solutions

Pick One (/problems/random-one-question/)

```
C++
                                </>
  1
  2
      * Definition for a binary tree node.
      * struct TreeNode {
  3
  4
            int val;
  5
            TreeNode *left;
            TreeNode *right;
  6
  7
            TreeNode(int x) : val(x), left(NULL), right(NULL) {}
  8
      */
  9
 10
     class Solution {
 11
     public:
 12
         bool isValidBST(TreeNode* root) {
 13
             return helper(root,NULL,NULL);
 14
         bool helper(TreeNode* root,TreeNode* minNode,TreeNode* maxNode){
 15
 16
             if(root==NULL) return true;
 17
             if(minNode&&root->val<=minNode->val||maxNode&&root->val>=maxNode->val) return false;
 18
             return helper(root->left,minNode,root)&&helper(root->right,root,maxNode);
 19
 20 };
```

Frequently Asked Questions (/faq/) | Terms of Service (/tos/)

Privacv

Copyright © 2017 LeetCode