

## 86. Partition List

[Add to List ▾](#)[Question](#)[Editorial Solution](#)[My Submissions \(/problems/partition-list/submissions/\)](/problems/partition-list/submissions/)

Total Accepted: **87439** Total Submissions: **276867** Difficulty: **Medium** Contributors: **Admin**

Given a linked list and a value  $x$ , partition it such that all nodes less than  $x$  come before nodes greater than or equal to  $x$ .

You should preserve the original relative order of the nodes in each of the two partitions.

For example,

Given  $1 \rightarrow 4 \rightarrow 3 \rightarrow 2 \rightarrow 5 \rightarrow 2$  and  $x = 3$ ,

return  $1 \rightarrow 2 \rightarrow 2 \rightarrow 4 \rightarrow 3 \rightarrow 5$ .

[Subscribe \(/subscribe/\)](/subscribe/) to see which companies asked this question

[Show Tags](#)

Have you met this question in a real interview?

[Discuss \(https://discuss.leetcode.com/category/94\)](https://discuss.leetcode.com/category/94)[Top Solutions](#)[Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)

C++ ▾





```
1 /**
2  * Definition for singly-linked list.
3  * struct ListNode {
4  *     int val;
5  *     ListNode *next;
6  *     ListNode(int x) : val(x), next(NULL) {}
7  * };
8  */
9 class Solution {
10 public:
11     ListNode* partition(ListNode* head, int x) {
12         if(head==NULL) return NULL;
13
14         ListNode* greater = new ListNode(0);
15         ListNode* dummy = new ListNode(0);
16         dummy->next = head;
17         ListNode* cur = dummy;
18         ListNode* gt = greater;
19         while(cur->next!=NULL){
20             if(cur->next->val < x) cur = cur->next;
21             else {
22                 gt->next = cur->next;
23                 cur->next = cur->next->next;
24                 gt = gt->next;
25             }
26         }
27         cur->next = greater->next;
28         gt->next = NULL;
29         return dummy->next;
30     }
31 };
```

Custom Testcase ☐

Contribute Testcase 

[Run Code](#)[Submit Solution](#)[Notes](#)